

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : ROTOSTAR UV 166 875 FLEXO INK  
Material number : 023655U10

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Acute toxicity, Category 4, Oral, H302  
Serious eye damage/eye irritation, Category 2A, H319  
Skin sensitisation, Category 1, H317

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ROTOSTAR UV 166 875 FLEXO INK

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

Reproductive toxicity, Category 2, H361d  
 Short-term (acute) aquatic hazard, Category 1, H400  
 Long-term (chronic) aquatic hazard, Category 1, H410

### GHS-Labelling

Symbol(s)



Signal word

: Warning

Hazard statements

: H302: Harmful if swallowed.  
 H317: May cause an allergic skin reaction.  
 H319: Causes serious eye irritation.  
 H361d: Suspected of damaging the unborn child.  
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
 P203 Obtain, read and follow all safety instructions before use.  
 P261 Avoid breathing mist or vapours.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
 P301 + P317 + P330 IF SWALLOWED: Get medical help. Rinse mouth.  
 P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P318 IF exposed or concerned, get medical advice.  
 P333 + P317 If skin irritation or rash occurs: Get medical

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

help.

P337 + P317 If eye irritation persists: Get medical help.

P391 Collect spillage.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Hazardous components which must be listed on the label**

Identification	CAS-No.
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)	28961-43-5
copper	7440-50-8
Bisphenol A epoxy acrylate	55818-57-0
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0
Glycerol, propoxylated, esters with acrylic acid	52408-84-1
2-Propenoic acid, ester with C12-16-alkyl glycidyl ether	68071-40-9

**SECTION 3: Composition/information on ingredients**

Substance No. :

**Hazardous components**

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propenyl)oxy]-, ether with 2-	28961-43-5	;2A;H319 Skin Sens.;1;H317 Aquatic	25 - 50

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)		Chronic;3;H412	
copper	7440-50-8 231-159-6	Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	25 - 50
Bisphenol A epoxy acrylate	55818-57-0	Skin Sens.;1;H317 Aquatic Chronic;2;H411	10 - 20
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9	Repr.;2;H361d Aquatic Chronic;3;H412	2,5 - 10
zinc	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	2,5 - 10
Glycerol, propoxylated, esters with acrylic acid	52408-84-1	;2A;H319 Skin Sens.;1;H317	1 - 10
2-Propenoic acid, ester with C12-16-alkyl glycidyl ether	68071-40-9	Skin Sens.;1A;H317	1 - 10
Epoxy acrylate	55818-57-0	Skin Sens.;1;H317	0,1 - 1
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	28961-43-5	;2A;H319 Skin Sens.;1;H317	0,1 - 1

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

--	--	--	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

General advice	: Move the victim to fresh air. Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Wash off immediately with soap and plenty of water.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Special powder against metal fire, Dry sand, ABC powder

Unsuitable extinguishing media : Water, High volume water jet, Carbon dioxide (CO<sub>2</sub>)**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Use personal protective equipment.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

**6.2 Environmental precautions**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

This information is not available.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Pick up and transfer to properly labelled containers.  
Do not flush with water.  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against : Keep away from heat and sources of ignition. No smoking.

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures

: General industrial hygiene practice.

When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**Requirements for storage  
areas and containers: Keep away from sources of ignition - No smoking. Do not  
store near combustible materials. Keep containers tightly  
closed in a cool, well-ventilated place. To maintain product  
quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated  
place. Containers which are opened must be carefully  
resealed and kept upright to prevent leakage. Observe label  
precautions. Electrical installations / working materials must  
comply with the technological safety standards.

Further information on  
storage conditions

: Protect from humidity and water.

Advice on common storage

: Keep away from oxidizing agents, strongly alkaline and  
strongly acid materials in order to avoid exothermic reactions.  
Do not store together with oxidizing and self-igniting products.

Dampness

: Keep in a dry, cool and well-ventilated place.

Other data

: No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

This information is not available.

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
copper	7440-50-8	AGW (inhalable fraction)	1 mg/m <sup>3</sup>		DE TRGS 900
Bisphenol A epoxy acrylate	55818-57-0	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2020-03-30	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Bisphenol A epoxy acrylate	55818-57-0	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2020-03-30	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
zinc	7440-66-6	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
zinc	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Epoxy acrylate	55818-57-0	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2020-03-30	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ROTOSTAR UV 166 875 FLEXO INK

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

Epoxy acrylate	55818-57-0	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2020-03-30	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			

### 8.2 Exposure controls

#### Personal protective equipment

- Eye protection : Safety glasses  
: Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
The exact break through time can be obtained from the protective glove producer and this has to be observed.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
Recommended preventive skin protection  
Skin should be washed after contact.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

Respiratory protection : Use suitable breathing protection if workplace concentration requires.  
Equipment should conform to EN 14387

**Environmental exposure controls**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
: Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: gold
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Melting point/range	: Not applicable
Boiling point/boiling range	: > 100 °C
Flash point	: > 100 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

Density	: 1,4 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow evaporation to dryness.

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

No data available

**10.5 Incompatible materials**

Materials to avoid : No data available

**10.6 Hazardous decomposition products**

Hazardous decomposition products :

Other information : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****copper :**

Acute oral toxicity : The component/mixture is moderately toxic after single ingestion.

**Skin corrosion/irritation****Product**

May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation****Product**

May cause irreversible eye damage.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

**Respiratory or skin sensitisation****Product**

Causes sensitisation.

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

No data available

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

**SECTION 12: Ecological information****12.1 Toxicity****Components:****Poly(oxy-1,2-ethanediyl), .alpha.-hydro.-omega.-[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) (28961-43-5) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

**copper (7440-50-8) :**

M-Factor : 10

**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

**Bisphenol A epoxy acrylate (55818-57-0) :****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Toxic to aquatic life.

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

**1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (6846-50-0) :**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 2,46 mg/l

**Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

**zinc (7440-66-6) :****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

Contaminated packaging : chemical or used container.  
Send to a licensed waste management company.  
: Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

**SECTION 14: Transport information****14.1 UN number****ADR** : 3082**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : 3082**IATA** : 3082**14.2 Proper shipping name**

**ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(Copper metal powder )

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(,Copper metal powder )

**IATA** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(Copper metal powder)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

**14.3 Transport hazard class****ADR** : 9**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : 9**IATA** : 9**14.4 Packing group****ADR**

Packaging group : III

Classification Code : M6

Hazard Identification Number : 90

Labels : 9

Tunnel restriction code : (-)

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Packaging group : III

Labels : 9

EmS Code : F-A, S-F

**IATA**Packing instruction (cargo  
aircraft) : 964

Packing instruction : 964

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

(passenger aircraft)

Packing instruction (LQ) : Y964

Packaging group : III

Labels : 9

**14.5 Environmental hazards****ADR** : Environmentally hazardous**IMDG** : Marine pollutant**14.6 Special precautions for user**

For single packagings ≤ 5L / 5 kg, or combination packagings containing inner packagings ≤ 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

---

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, :

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

mixtures and articles (Annex XVII)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

: Banned and/or restricted  
(Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1))  
(Bisphenol A epoxy acrylate)  
(1-isopropyl-2,2-dimethyltrimethylene diisobutyrate)  
(Glycerol, propoxylated, esters with acrylic acid)  
(Epoxy acrylate)  
(Propylidynetrimethanol, ethoxylated, esters with acrylic acid)

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

H302	: Harmful if swallowed.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H361d	: Suspected of damaging the unborn child.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**ROTOSTAR UV 166 875 FLEXO INK**

Version 4.0

Revision Date 30.01.2024

Print Date 01.02.2024

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.