according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ROTOSTAR Aqua FPG 74014 Silver

Product code : 025404HX0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Colorant; Printing ink related material; Printing ink, Colouring

Substance/Mixture agents, dyes

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person

responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a dangerous substance according to GHS.

Additional Labelling

EUH210 Safety data sheet available on request.

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-

isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an

allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name aluminium powder (stabilised)	CAS-No. EC-No. Index-No. Registration number 7429-90-5	ClassificationREGUL ATION (EC) No 1272/2008 Flam. Sol. 1; H228	Concentration (% w/w) >= 10 - < 20
	231-072-3 013-002-00-1 01-2119529243-45		
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	154518-38-4 (52933-07-0) 01-2119976356-25	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 1 - < 2.5
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 specific concentration limit Skin Sens. 1; H317 >= 0.05 % Skin Sens. 1; H317 >= 0.05 %	>= 0.0025 - < 0.025
reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2- methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 0.0002 - < 0.0015

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.08.2023 Date of first issue: 02.09.2019
7.0	15.08.2023	102000031931	
			Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1B; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Eye Irrit. 2; H319 0.06 - < 0.6 % Skin Sens. 1; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 % Skin Corr. 1C; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Stin Irrit. 3; H315 0.06 - < 0.6 % Stin Irrit. 4; H315 0.06 - < 0.6 % Stin Sens. 1A; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 % Skin Sens. 1A; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 %

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

Move the victim to fresh air.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water.

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

If on clothes, remove clothes.

Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand

ABC powder

Foam

Unsuitable extinguishing

Water

media

Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Evacuate personnel to safe areas.

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

The product should not be allowed to enter drains, water

courses or the soil.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

Do not flush with water.

Keep in suitable, closed containers for disposal.

Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use

explosion-proof equipment. Store in original container.

Advice on common storage : Do not store near acids.

Do not store together with oxidizing and self-igniting products. Keep away from oxidizing agents and strongly acid or alkaline

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

materials.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	inhalable dust when samplin MDHS14/4 Government on the substance has concentration inhalable dust any dust will be levels. Some must comply particles of a particular part response that distinguishes and 'respirable material that cavailable for to the fraction definitions and contain composhould be contain.	are those fractions of is undertaken in acceneral methods for some and inhalable accents are equal to or greater and in air equal to or greater are equal to or greater are equal to COSHI dusts have been asswith the appropriate wide range of sizes. Inhalable dust appeared to the equal to the equal to the equal to the explanatory materic onents that have the explicited with., Where retimes the long-term	ses of these limits, respirable of airborne dust which will be occordance with the methods ampling and gravimetric ana aerosols., The COSHH definitudes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to dustigned specific WELs and explimits., Most industrial dusts of the behaviour, deposition are human respiratory system the nature and size of the partimit-setting purposes termed proximates to the fraction of mouth during breathing and indiratory tract. Respirable dust are given in MDHS14/4., Voir own assigned WEL, all the no specific short-term exposure limit should be use	e collected described in lysis or ition of a present at a TWA of a means that at above these contain and fate of any and the body article. HSE ad 'inhalable' airborne a therefore approximates e lung. Fuller Where dusts relevant limits are limit is listed, d.
		TWA (Respirable dust)	4 mg/m3	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or			

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

 Version
 Revision Date:
 SDS Number:
 Print Date: 16.08.2023

 7.0
 15.08.2023
 102000031931
 Date of first issue: 02.09.2019

respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'.. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed. a figure three times the long-term exposure limit should be used. GB EH40 propane-1,2-diol 57-55-6 TWA (particles) 10 ma/m3 Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. TWA (Total 150 ppm GB EH40 vapour and 474 mg/m3 particles) Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
propane-1,2-diol	Workers	Inhalation	Long-term systemic effects	168 mg/m3
	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Inhalation	Long-term systemic effects	50 mg/m3
	Consumers	Inhalation	Long-term local effects	10 mg/m3
Phosphoric acid, C11- 14-isoalkyl esters, C13-rich	Workers	Inhalation	Long-term systemic effects	34.94 mg/m3
	Workers	Skin contact	Long-term systemic effects	100.13 mg/kg
	Consumers	Inhalation	Long-term systemic	10.43 mg/m3

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

			effects	
	Consumers	Skin contact	Long-term systemic effects	60.08 mg/kg
	Consumers	Ingestion	Long-term systemic effects	6.01 mg/kg
2,2',2"-nitrilotriethanol	Workers	Inhalation	Long-term local effects	1 mg/m3
	Workers	Skin contact	Long-term systemic effects	7.5 mg/kg
	Workers	Skin contact	Long-term local effects	0.14 mg/cm2
	Consumers	Inhalation	Long-term local effects	0.4 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3.3 mg/kg
	Consumers	Skin contact	Long-term systemic effects	2.66 mg/kg
	Consumers	Skin contact	Long-term local effects	0.07 mg/cm2
1,2-benzisothiazol- 3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.966 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0.345 mg/kg
reaction mass of 5- chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1)	Workers	Inhalation	Long-term local effects	0.02 mg/m3
-	Workers	Inhalation	Acute local effects	0.04 mg/m3
	Consumers	Inhalation	Long-term local effects	0.02 mg/m3
	Consumers	Inhalation	Acute local effects	0.04 mg/m3
	Consumers	Ingestion	Long-term local effects	0.090 mg/kg
	Consumers	Ingestion	Acute local effects	0.11 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
propane-1,2-diol	Fresh water	260 mg/l
	Marine water	26 mg/l
	Intermittent use/release	183 mg/l
	Fresh water sediment	572 mg/kg
	Marine sediment	57.2 mg/kg
	Soil	50 mg/kg
Phosphoric acid, C11-14-isoalkyl	Fresh water	0.00631 mg/l

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

esters, C13-rich		
	Fresh water sediment	0.113 mg/kg
	Intermittent water release	0.0631 mg/l
	Marine water	0.000631 mg/l
	Marine sediment	0.0113 mg/kg
	STP	10 mg/l
	Soil	0.0188 mg/kg
2,2',2"-nitrilotriethanol	Soil	0.151 mg/kg
	Fresh water	0.32 mg/l
	Fresh water sediment	1.7 mg/kg
	clarification plant	10 mg/l
	Marine water	0.032 mg/l
	Marine sediment	0.17 mg/kg
1,2-benzisothiazol-3(2H)-one	Fresh water	0.00403 mg/l
,	Marine water	0.000403 mg/l
	STP	0.00103 mg/l
	Intermittent water release	0.0011 mg/l
	Intermittent Release	0.00011 mg/l
	Fresh water sediment	0.0499 mg/kg
	Marine sediment	0.00499 mg/kg
	Soil	3 mg/kg
reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Fresh water	0.00339 mg/l
	Intermittent water release	0.00339 mg/l
	Marine water	0.00339 mg/l
	Intermittent Release	0.00339 mg/l
	STP	0.23 mg/l
	Soil	0.0471 mg/kg
	Fresh water sediment	0.027 mg/kg
	Marine sediment	0.027 mg/kg
·	Soil	0.01 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses

Goggles

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of

contact). Please observe the instructions regarding permeability and breakthrough time which are provided by

permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Melting point/range : Not applicable

Boiling point/boiling range : > 100 °C

Flammability : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : > 100 °C

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : 6-8

Concentration: 100 %

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : No data available

Relative density : No data available

Density : 1.1 - 1.2 g/cm3

Relative vapour density : No data available

Particle Size Distribution : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Contact with acids and alkalis may release hydrogen.

10.4 Conditions to avoid

Conditions to avoid : No data available

Do not allow evaporation to dryness.

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity : LC50 (Rat): 0.4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The component/mixture is highly toxic after short

term inhalation.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : Assessment: The component/mixture is toxic after single

ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short

term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is highly toxic after

single contact with skin.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Result : Skin irritation

1,2-benzisothiazol-3(2H)-one:

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

 Version
 Revision Date:
 SDS Number:
 Print Date: 16.08.2023

 7.0
 15.08.2023
 102000031931
 Date of first issue: 02.09.2019

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Result : Corrosive

1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 6.31 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (algae): 150 mg/l Exposure time: 72 h

1,2-benzisothiazol-3(2H)-one:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

M-Factor (Short-term (acute) : 100

aquatic hazard)

M-Factor (Long-term

100

(chronic) aquatic hazard)

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : UN 9999

Not permitted for transport

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not permitted for transport

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

IMDG : Not regulated as a dangerous good

IATA : Not permitted for transport

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not permitted for transport

IATA (Passenger) : Not permitted for transport

14.5 Environmental hazards

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport

regulations.

Due to the risk of hydrogen development we recommend to

refrain from airfreighting this/these product(s).

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be

considered:

aluminium powder (stabilised)

(Number on list 40)

Phosphoric acid, C11-14-isoalkyl esters, C13-rich (Number on list 3)

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Regulation (EC) No 1005/2009 on substances that

Not applicable

Not applicable

: Not applicable

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

deplete the ozone layer

UK REACH List of substances subject to authorisation : Not applicable

(Annex XIV)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid.
H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Flam. Sol. : Flammable solids Skin Corr. : Skin corrosion Skin Irrit. : Skin sensitisation : Skin sensitisation

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -

according to Regulation (EC) No. 1907/2006



ROTOSTAR Aqua FPG 74014 Silver

Version Revision Date: SDS Number: Print Date: 16.08.2023

7.0 15.08.2023 102000031931 Date of first issue: 02.09.2019

International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN