

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : Agent Zincludust 92 230 kgs 17-07009
Material number : 08135618V

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Flammable liquids, Category 2, H225
Skin corrosion/irritation, Category 2, H315
Serious eye damage/eye irritation, Category 2A, H319

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

Specific target organ toxicity - single exposure, Category 3, Respiratory system, H335
 Specific target organ toxicity - repeated exposure, Category 2, H373
 Aspiration hazard, Category 1, H304
 Short-term (acute) aquatic hazard, Category 1, H400
 Long-term (chronic) aquatic hazard, Category 1, H410

GHS-Labelling

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H335: May cause respiratory irritation.
 H373: May cause damage to organs through prolonged or repeated exposure.
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P260 Do not breathe mist or vapours.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P316 IF SWALLOWED: Get emergency medical help immediately.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water.

P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P317 If skin irritation occurs: Get medical help.

P337 + P317 If eye irritation persists: Get medical help.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
xylene	1330-20-7
Solvent naphtha (petroleum), light arom.	64742-95-6
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincdust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	50 - 100
xylene	1330-20-7 215-535-7	Flam. Liq.;3;H226 Acute Tox.;4;H332 ;2;H315 ;2A;H319 STOT SE;3;H335 STOT RE;2;H373 Asp. Tox.;1;H304	10 - 20
Solvent naphtha (petroleum), light arom.	64742-95-6 918-668-5	Flam. Liq.;3;H226 Acute Tox.;5;H303 Acute Tox.;5;H313 STOT SE;3;H335, H336 Asp. Tox.;1;H304 Aquatic Chronic;2;H411	2,5 - 10
zinc oxide	1314-13-2 215-222-5	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	2,5 - 10

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha	64742-82-1 265-185-4	Flam. Liq.;3;H226 STOT SE;3;H336 STOT RE;1;H372 Asp. Tox.;1;H304 Aquatic Chronic;2;H411	1 - 2,5
Fatty acids, tall-oil, reaction products with diethylenetriamine compds. with polyethylene glycol hydrogen maleate C9-11-alkyl ether	1262797-52-3	Skin Sens.;1;H317 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	0,25 - 1
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0 263-160-2	Acute Tox.;4;H302 ;1B;H314 STOT RE;2;H373 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	0,1 - 0,25

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

- If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media : Dry sand, ABC powder, Foam
- Unsuitable extinguishing media : High volume water jet

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
- Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

Germany:

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000-06-16	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skinIndicative				
xylene	1330-20-7	STEL	100 ppm 442 mg/m ³	2000-06-16	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skinIndicative				
xylene	1330-20-7	AGW	50 ppm 220 mg/m ³	2020-10-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Skin absorption				
Solvent naphtha (petroleum), light arom.	64742-95-6	AGW	100 mg/m ³	2009-02-16	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9				

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

	of the TRGS 900
--	-----------------

8.2 Exposure controls**Personal protective equipment**

- Eye protection : Goggles
- : Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Recommended preventive skin protection
Skin should be washed after contact.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

- General advice :
- : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Water : The product should not be allowed to enter drains, water courses or the soil.
- :

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance : liquid
- Colour : grey
- Odour : characteristic

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009


Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: 137 °C
Flash point	: > 23 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: ca. 2,2 g/cm ³
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: see user defined free text
Viscosity, kinematic	: No data available
Flow time	: 11 - 14 s at 20 °C Cross section: 4 mm Method: DIN 53211

9.2 Other information

Page 13 / 23	102000000099	A member of  ALTANA
--------------	--------------	---

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

Other information : No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****xylene :**

Acute inhalation toxicity : The component/mixture is moderately toxic after short term inhalation.

Solvent naphtha (petroleum), light arom. :

Acute oral toxicity : LD50 Rat: 3 492 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated**naphtha :**

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Fatty acids, tall-oil, reaction products with diethylenetriamine :

Acute oral toxicity : The component/mixture is moderately toxic after single ingestion.

Skin corrosion/irritation**Product**

May cause skin irritation in susceptible persons.

SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

Serious eye damage/eye irritation

Product

May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product

Page 16 / 23	102000000099	A member of ALTANA
--------------	--------------	---------------------

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincdust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

Solvents may degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity****Components:****zinc (7440-66-6) :****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Solvent naphtha (petroleum), light arom. (64742-95-6) :**Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

zinc oxide (1314-13-2) :

M-Factor : 1

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1) :**Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

Fatty acids, tall-oil, reaction products with diethylenetriamine compds. with polyethylene glycol hydrogen maleate C9-11-alkyl ether (1262797-52-3) :

M-Factor : 1

Ecotoxicology Assessment

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Fatty acids, tall-oil, reaction products with diethylenetriamine (61790-69-0) :

M-Factor : 1

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Zincdust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

- | | | |
|------------------------|---|--|
| Product | : | The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14: Transport information**14.1 UN number**

- | | | |
|------|---|------|
| ADR | : | 1263 |
| TDG | : | 1263 |
| CFR | : | 1263 |
| IMDG | : | 1263 |
| IATA | : | 1263 |

14.2 Proper shipping name

- | | | |
|------|---|-------|
| ADR | : | PAINT |
| TDG | : | PAINT |
| CFR | : | PAINT |
| IMDG | : | PAINT |
- (,Zinc powder, stabilized)

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Zincdust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

IATA : PAINT**14.3 Transport hazard class****ADR** : 3**TDG** : 3**CFR** : 3**IMDG** : 3**IATA** : 3**14.4 Packing group****ADR**

Packaging group : III

Classification Code : F1

Hazard Identification Number : 30

Labels : 3

Tunnel restriction code : (D/E)

TDG

Packaging group : III

Labels : 3

CFR

Packaging group : III

Labels : 3

IMDG

Packaging group : III

Labels : 3

EmS Number : F-E, S-E

IATA

Packing instruction (cargo) : 366

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincdust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

aircraft)

Packing instruction : 355

(passenger aircraft)

Packing instruction (LQ) : Y344

Packaging group : III

Labels : 3

14.5 Environmental hazards**IMDG** : Marine pollutant**ADR** : Environmentally hazardous**14.6 Special precautions for user****14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, :

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

preparations and articles (Annex XVII)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

: Banned and/or restricted
(xylene)
(Solvent naphtha (petroleum), light arom.)
(naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha)
(ethylbenzene)
(Fatty acids, tall-oil, reaction products with diethylenetriamine compds. with polyethylene glycol hydrogen maleate C9-11-alkyl ether)
(Castor oil, sulfated, sodium salt)
(manganese neodecanoate)
(Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha)
(2-methylpropan-1-ol)
(Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Zincludust 92 230 kgs 17-07009

Version 8.0

Revision Date 29.06.2022

Print Date 30.06.2022

H303	: May be harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H313	: May be harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.