according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
11.0	30.04.2024	102000022823	Date of first issue: 21.04.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	:	METALSTAR Supergloss 07 2007 Silver
Product code	:	050393RC0M1
1.2 Relevant identified uses of t Use of the Substance/Mixture		substance or mixture and uses advised against Colorant; Printing ink related material; Printing ink, Colouring agents, dyes
1.3 Details of the supplier of the	e saf	-
Company	:	ECKART GmbH

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects. Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version 11.0	Revision Date: 30.04.2024	-	SDS Number: 02000022823	Print Date: 03.05.2024 Date of first issue: 21.04.2015
Hazar	d pictograms	:	¥2	
Hazar	d statements	:	H411	Toxic to aquatic life with long lasting effects.
Precautionary statements		Prevention: P273 Response: P391 Disposal:		Avoid release to the environment. Collect spillage.
			P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components			
Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 10 - < 20
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Distillates (petroleum),	64742-46-7	Asp. Tox. 1; H304	>= 1 - < 10
hydrotreated middle; Gasoil —	927-632-8		
unspecified	649-221-00-X		
	01-2119457736-27-		
	000201-2119457736- 27		
Distillates (petroleum), solvent-	64741-91-9	Asp. Tox. 1; H304	>= 1 - < 10
refined middle; Gasoil —	919-029-3	7.5p. 10X. 1, 11004	
unspecified	010 020 0		
Petroleum resins	64742-16-1	Aquatic Chronic 4;	>= 2.5 - < 10
	265-116-8	H413	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version 11.0	Revision Date: 30.04.2024		8 Number: 000022823	 0ate: 03.05.2024 of first issue: 21.04.2015	5
dim	opropyl-2,2- ethyltrimethylene diisob adecylamine	outyrate	6846-50-0 229-934-9 01-2119451093 124-30-1 204-695-3 612-282-00-8 01-2119473804	Repr. 2; H361d Aquatic Chronic 3; H412 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373 (Liver, Gastrointestinal tract, Immune system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic	>= 0.25 - < 1
				aquatic toxicity): 10	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures				
General advice :	Move the victim to fresh air.			
	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.			
If inhaled :	Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.			
In case of skin contact :	Wash off immediately with soap and plenty of water.			
In case of eye contact :	Immediately flush eye(s) with plenty of water.			
	Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.			
If swallowed :	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.			

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
11.0	30.04.2024	102000022823	Date of first issue: 21.04.2015

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Dry sand ABC powder Foam
Unsuitable extinguishing media	:	High volume water jet Carbon dioxide (CO2)

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protect Personal precautions		equipment and emergency procedures Evacuate personnel to safe areas.
6.2 Environmental precautions General advice	:	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version 11.0	Revision Date: 30.04.2024	SDS Number: 102000022823	Print Date: 03.05.2024 Date of first issue: 21.04.2015			
		Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains info respective authorities.				
6.3 Methods and material for containment and cleaning up						
Methods for cleaning up		Soak up with in	: Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).			
		acid binder, uni	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.			
		Soak up with in acid binder, uni Soak up with in acid binder, uni	ert absorbent material (e.g. sand, silica gel, versal binder, sawdust). ert absorbent material (e.g. sand, silica gel, versal binder, sawdust).			

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1	Precautions for safe handling	g	
	Advice on safe handling	:	Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage , Requirements for storage areas and containers	incl :	uding any incompatibilities Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
	Further information on storage conditions	:	Protect from humidity and water.
	Advice on common storage	:	Do not store near acids.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version 11.0	Revision Date: 30.04.2024	SDS Numb 102000022	
		Never a storage Keep a	store together with oxidizing and self-igniting products. allow product to get in contact with water during e. way from oxidizing agents, strongly alkaline and y acid materials in order to avoid exothermic reactions.
	er information on age stability	: No dec	composition if stored and applied as directed.
7 2 Spaci	fic and use(a)		

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	inhalable dus when samplir MDHS14/4 G respirable, the substance ha concentration inhalable dus any dust will b levels. Some must comply particles of a particular par response that distinguishes and 'respirabl material that of available for of to the fraction definitions an contain comp should be con	t are those fractions on g is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or great t or 4 mg.m-3 8-hour be subject to COSHH dusts have been ass with the appropriate wide range of sizes. ticle after entry into the it elicits, depend on two size fractions for e'., Inhalable dust appenters the nose and deposition in the responter that penetrates to the d explanatory material onents that have the mplied with., Where r times the long-term TWA (Respirable	ses of these limits, respirable of airborne dust which will be ccordance with the methods ampling and gravimetric ana aerosols., The COSHH defir cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du signed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition a he human respiratory system the nature and size of the pa- r limit-setting purposes terms oproximates to the fraction of mouth during breathing and in- itratory tract. Respirable dusi- ne gas exchange region of the al are given in MDHS14/4., W in own assigned WEL, all the possure limit should be use (4 mg/m3	e collected described in lysis or nition of a present at a TWA of a means that ast above these contain nd fate of any n, and the body article. HSE ed 'inhalable' airborne as therefore t approximates he lung. Fuller Where dusts relevant limits ure limit is listed,
	Fourth on inf	dust)		
	Further inform	nation: For the purpo	ses of these limits, respirable	e dust and

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version	Revision Date: 30.04.2024	SDS Number:	Print Date: 03.05.2024
11.0		102000022823	Date of first issue: 21.04.2015
	when MDH respi subs conc inhala any c levels must partic partic respo distir and ' mate availa to the defin conta shou	sampling is undertake S14/4 General method rable, thoracic and inha- tance hazardous to hea- entration in air equal to able dust or 4 mg.m-3 lust will be subject to 0 s. Some dusts have be comply with the appro- cles of a wide range of cular particle after entry onse that it elicits, depen- guishes two size fraction respirable'., Inhalable of rial that enters the nos able for deposition in the e fraction that penetrate itions and explanatory ain components that ha Id be complied with., W	ctions of airborne dust which will be collected en in accordance with the methods described in ds for sampling and gravimetric analysis or alable aerosols., The COSHH definition of a alth includes dust of any kind when present at a o or greater than 10 mg.m-3 8-hour TWA of 8-hour TWA of respirable dust. This means that COSHH if people are exposed to dust above these een assigned specific WELs and exposure to these opriate limits., Most industrial dusts contain sizes. The behaviour, deposition and fate of any y into the human respiratory system, and the body end on the nature and size of the particle. HSE ions for limit-setting purposes termed 'inhalable' dust approximates to the fraction of airborne the respiratory tract. Respirable dust approximates es to the gas exchange region of the lung. Fuller material are given in MDHS14/4., Where dusts ave their own assigned WEL, all the relevant limits Where no specific short-term exposure limit is listed, g-term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
isooctadecanoic acid	Consumers	Oral	Long-term systemic effects	20 mg/kg
	Consumers	Dermal	Long-term systemic effects	100 mg/kg
	Consumers	Inhalation	Long-term systemic effects	69.565 mg/m3
1-isopropyl-2,2- dimethyltrimethylene diisobutyrate	Workers	Dermal	Long-term systemic effects	5.00 mg/kg
Ĩ	Workers	Inhalation	Long-term systemic effects	17.62 mg/m3
	Consumers	Oral	Long-term systemic effects	5.00 mg/kg
	Consumers	Dermal	Long-term systemic effects	5.00 mg/kg
	Consumers	Inhalation	Long-term systemic effects	4.35 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version	Revision Date: 30.04.2024	SDS Number:	Print Date: 03.05.2024
11.0		102000022823	Date of first issue: 21.04.2015

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
1-isopropyl-2,2-	Fresh water	0.014 mg/l
dimethyltrimethylene		
diisobutyrate		
	Marine water	0.0014 mg/l
	Fresh water sediment	5.29 mg/kg
	Soil	1.05 mg/kg
	STP	3 mg/l
	Marine sediment	0.529 mg/kg
	oral (secondary poisoning)	83.3 mg/kg

8.2 Exposure controls

Personal protective equipmen Eye/face protection Hand protection Material	nt :	Goggles Tightly fitting safety goggles Solvent-resistant gloves (butyl-rubber)
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and
Respiratory protection	:	concentration of the dangerous substance at the work place. Use suitable breathing protection if workplace concentration requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	:	liquid
Colour	:	silver

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Version 11.0	Revision Date: 30.04.2024	-	S Number: 2000022823	Print Date: 03.05.2024 Date of first issue: 21.04.2015
Odo	ur	:	characteristic	
Odo	ur Threshold	:	No data available)
Free	zing point	:	No data available	9
Boili	ng point/boiling range	:	> 100 °C	
Flam	mability	:	No data available	3
	er explosion limit / Upper mability limit	:	No data available	
	er explosion limit / Lower mability limit	:	No data available	
Flash	n point	:	> 100 °C	
Auto	-ignition temperature	:	No data available)
Deco	omposition temperature	:	No data available	9
рН		:	substance/mixtu	re is non-soluble (in water)
Visco Visco	osity osity, kinematic	:	> 21 mm2/s (40	°C)
Wate	bility(ies) er solubility bility in other solvents	:	insoluble No data available	9
	tion coefficient: n- nol/water	:	No data available	2
	our pressure	:	No data available	
Di hy	or Pressure for Compone stillates (petroleum), drotreated middle; asoil — unspecified	nts: :	4 hPa (40 °C)	
1-i dir	sopropyl-2,2- methyltrimethylene sobutyrate	:	1.5 Pa (25 °C)	
	tive density	:	No data available	9
Dens	sity	:	1 g/cm3	
Relat	tive vapour density	:	No data available	
	cle characteristics article Size Distribution	:	No data available	9

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
11.0	30.04.2024	102000022823	Date of first issue: 21.04.2015

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Cor	tact with acids and alkalis may release hydrogen.
---------------------------	---

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid

: Do not allow evaporation to dryness.

No data available

10.5 Incompatible materials

Materials to avoid	: Acids
	Bases
	Oxidizing agents

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

Distillates (petroleum), solvent-refined middle; Gasoil - unspecified:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
---------------------	-----------------------------

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



.0	Revision Date: 30.04.2024	SDS Number: 102000022823	Print Date: 03.05.2024 Date of first issue: 21.04.2015
Acute	e dermal toxicity	: LD50 (Rabbit)	: > 2,000 mg/kg
1-isoj	propyl-2,2-dimethylti	rimethylene diisobut	yrate:
-		-	, (Rabbit): > 2,000 mg/kg
	-	Method: OEC	D Test Guideline 402
Skin	corrosion/irritation		
Not c	lassified based on av	ailable information.	
<u>Com</u>	ponents:		
1-isoj	propyl-2,2-dimethylti	rimethylene diisobut	yrate:
Speci	ies	: Rabbit	
	sure time	: 4 h	
Metho		: OECD Test G	
Resul	t	: No skin irritatio	on
octad	lecylamine:		
Asses	ssment	: Irritating to ski	n.
Not cl	us eye damage/eye lassified based on av		
Not cl <u>Com</u> t	lassified based on av ponents:	ailable information.	
Not cl <u>Com</u> t 1-isoj	lassified based on av ponents: propyl-2,2-dimethylti	ailable information. rimethylene diisobut	yrate:
Not cl <u>Com</u> t 1-isol Speci	lassified based on av ponents: propyl-2,2-dimethyltr ies	ailable information. r imethylene diisobut : Rabbit	yrate:
Not cl <u>Com</u> t 1-isol Speci	lassified based on av <u>ponents:</u> propyl-2,2-dimethyltr ies sure time	ailable information. rimethylene diisobut	-
Not cl <u>Comp</u> 1-isoj Speci Expo	lassified based on av <u>ponents:</u> propyl-2,2-dimethyltr ies sure time pd	ailable information. r imethylene diisobut : Rabbit : 72 h	uideline 405
Not cl <u>Com</u> 1-iso Speci Expo Metho Resul	lassified based on av <u>ponents:</u> propyl-2,2-dimethyltr ies sure time od lt	ailable information. r imethylene diisobut : Rabbit : 72 h : OECD Test Gu	uideline 405
Not cl <u>Comp</u> 1-iso Speci Expo Metho Resul	lassified based on av <u>ponents:</u> propyl-2,2-dimethyltr ies sure time pd	ailable information. r imethylene diisobut : Rabbit : 72 h : OECD Test Gu	uideline 405
Not cl <u>Comp</u> Speci Expo Metho Resul octad Asses	lassified based on ave <u>ponents:</u> propyl-2,2-dimethyltr ies sure time od it lecylamine:	ailable information. rimethylene diisobut : Rabbit : 72 h : OECD Test Go : No eye irritatio : Corrosive	uideline 405
Not cl <u>Comp</u> Speci Expo Metho Resul Octad Asses Respi Skin	lassified based on ave <u>ponents:</u> propyl-2,2-dimethyltr ies sure time od it lecylamine: ssment iratory or skin sensi sensitisation	ailable information. rimethylene diisobut : Rabbit : 72 h : OECD Test Gu : No eye irritatio : Corrosive	uideline 405
Not cl <u>Comp</u> Speci Expo Metho Resul Octad Asses Respi Skin	lassified based on ave <u>ponents:</u> propyl-2,2-dimethyltr ies sure time od it lecylamine: ssment iratory or skin sensi	ailable information. rimethylene diisobut : Rabbit : 72 h : OECD Test Gu : No eye irritatio : Corrosive	uideline 405
Not cl <u>Comp</u> Speci Expo Metho Resul octad Asses Respi Skin Not cl	lassified based on ave <u>ponents:</u> propyl-2,2-dimethyltr ies sure time od it lecylamine: ssment iratory or skin sensi sensitisation	ailable information. rimethylene diisobut : Rabbit : 72 h : OECD Test Gi : No eye irritatio : Corrosive itisation ailable information.	uideline 405
Not cl Comp Speci Expo Metho Resul Octad Asses Respi Skin Not cl Respi	lassified based on ave <u>ponents:</u> propyl-2,2-dimethyltri ies sure time od it lecylamine: ssment iratory or skin sensi sensitisation lassified based on av	ailable information. rimethylene diisobut : Rabbit : 72 h : OECD Test Gu : No eye irritatio : Corrosive itisation ailable information.	uideline 405
Not cl Comp Speci Expo Metho Resul octad Asses Respi Skin Not cl Respi Not cl	lassified based on ave <u>ponents:</u> propyl-2,2-dimethyltri ies sure time od it lecylamine: ssment iratory or skin sensi sensitisation lassified based on ave iratory sensitisation	ailable information. rimethylene diisobut : Rabbit : 72 h : OECD Test Gu : No eye irritatio : Corrosive itisation ailable information.	uideline 405
Not cl Comp Speci Expo Metho Resul octad Asses Respi Skin Not cl Respi Not cl Germ	lassified based on aver ponents: propyl-2,2-dimethyltri ies sure time od it lecylamine: ssment iratory or skin sensi sensitisation lassified based on aver iratory sensitisation lassified based on aver	ailable information. rimethylene diisobut : Rabbit : 72 h : OECD Test Gu : No eye irritatio : Corrosive ailable information. ailable information.	uideline 405
Not cl Comp Speci Expo Metho Resul octad Asses Respi Skin Not cl Respi Not cl Carci	lassified based on aver propyl-2,2-dimethyltri ies sure time od it lecylamine: ssment iratory or skin sensit sensitisation lassified based on aver iratory sensitisation lassified based on aver i cell mutagenicity	ailable information. rimethylene diisobut : Rabbit : 72 h : OECD Test Gu : No eye irritatio : Corrosive itisation ailable information. ailable information.	uideline 405

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
11.0	30.04.2024	102000022823	Date of first issue: 21.04.2015

Components:

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

S 1	based on the conditions cited in Nota N (Regulation 2008, Annex VI, Part 3, Note N)
------------	--

Distillates (petroleum), solvent-refined middle; Gasoil - unspecified:

Carcinogenicity -	:	Classified based on the conditions cited in Nota N (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note N)

Reproductive toxicity

Not classified based on available information.

Components:

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Reproductive toxicity -	:	Some evidence of adverse effects on development, based on
Assessment		animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

octadecylamine:

Exposure routes	:	Ingestion
Target Organs	:	Liver, digestive system, Immune system
Assessment	:	May cause damage to organs through prolonged or repeated
		exposure.

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified: May be fatal if swallowed and enters airways.

Distillates (petroleum), solvent-refined middle; Gasoil - unspecified:

May be fatal if swallowed and enters airways.

octadecylamine:

May be fatal if swallowed and enters airways.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Version 11.0	Revision Date: 30.04.2024		OS Number: 2000022823	Print Date: 03.05.2024 Date of first issue: 21.04.2015
11.2 Info	rmation on other hazard	ds		
Furt	her information			
<u>Proc</u> Rem		:	No data available	
SECTIO	N 12: Ecological infor	rma	ation	
12.1 Tox	icity			
Com	ponents:			
Petr	oleum resins:			
	toxicology Assessment nic aquatic toxicity	:	May cause long la	asting harmful effects to aquatic life.
Toxi	ppropyl-2,2-dimethyltrim city to daphnia and other atic invertebrates		• •	
	toxicology Assessment	:	Harmful to aquati	c life with long lasting effects.
M-Fa aqua M-Fa	decylamine: actor (Short-term (acute) atic hazard) actor (Long-term onic) aquatic hazard)	:	10 10	
Eco	e aquatic toxicity		Very toxic to aqu	atic life
	nic aquatic toxicity	:		atic life with long lasting effects.
	sistence and degradabil lata available	ity		
	accumulative potential lata available			
	bility in soil lata available			
12.5 Res	ults of PBT and vPvB as	sse	ssment	
	luct: essment	:	This substance/m	nixture contains no components considered



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version 11.0	Revision Date: 30.04.2024	SDS Num 10200002	
		very p	either persistent, bioaccumulative and toxic (PBT), or persistent and very bioaccumulative (vPvB) at levels of or higher.
	ocrine disrupting pro ata available	perties	
12.7 Othe	r adverse effects		
Prod	uct:		
	tional ecological nation	unpro	vironmental hazard cannot be excluded in the event of fessional handling or disposal. to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

European Waste Catalogue	:	08 03 12* - waste ink containing dangerous substances
13.1 Waste treatment methods		
Product	:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	:	UN 3082
IMDG	:	UN 3082
ΙΑΤΑ	:	UN 3082
14.2 UN proper shipping name		
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (paint related material)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (paint related material)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Versior 11.0	n Revision Date: 30.04.2024		9S Number: 2000022823	Print Date: 03.05.2024 Date of first issue: 21.04.2015		
IA	ТА	: Environmental (paint related r		ly hazardous substance, liquid, n.o.s. material)		
14.3 Tr	ansport hazard class(es)					
			Class	Subsidiary risks		
A	DR	:	9			
IM	DG	:	9			
IA	ТА	:	9			
14.4 Pa	acking group					
A	DR					
	acking group	:				
	assification Code azard Identification Number	÷	M6 90			
	bels	:	90			
	nnel restriction code	:	(-)			
IM	DG					
	acking group	:	III			
	bels	:	9			
Er	nS Code	:	F-A, S-F			
	TA (Cargo)					
	acking instruction (cargo craft)	:	964			
	acking instruction (LQ)		Y964			
	acking group	:	III			
	bels	:	9			
IA	TA (Passenger)					
	acking instruction	:	964			
	assenger aircraft) acking instruction (LQ)		Y964			
	acking group	:	III			
	bels	:	9			
14.5 Ei	14.5 Environmental hazards					
A	DR					
	vironmentally hazardous	:	yes			
IM	DG					
Ma	arine pollutant	:	yes			
14.6 Sj	pecial precautions for user	r				
Re	emarks	:	packagings conta	ings <=5L / 5 kg, or combination ining inner packagings <= 5L / 5 kg net per SV375 ADR, 2.10.2.7 IMDG-Code, A197 be applied.		

Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
11.0	30.04.2024	102000022823	Date of first issue: 21.04.2015

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3 aluminium powder (stabilised) (Number on list 40) Distillates (petroleum), hydrotreated middle; Gasoil — unspecified (Number on list 3, 28) (Number on list 3) 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (Number on list 3)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements		
H228	:	Flammable solid.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version 11.0	Revision Date: 30.04.2024		DS Number: 2000022823	Print Date: 03.05.2024 Date of first issue: 21.04.2015	
H361d H373		:		naging the unborn child. ge to organs through prolonged or repeated	
H400 H410 H412 H413		::	Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.		
Full te	xt of other abbreviati	ons			
•		:	Short-term (acute Long-term (chroni Aspiration hazard Serious eye dama	c) aquatic hazard	
Flam. Repr. Skin Ir STOT GB EH	rit. RE 140		UK. EH40 WEL -	city gan toxicity - repeated exposure Workplace Exposure Limits	
GB EF	GB EH40 / TWA :			ure limit (8-hour TWA reference period)	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail: SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



METALSTAR Supergloss 07 2007 Silver

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
11.0	30.04.2024	102000022823	Date of first issue: 21.04.2015

Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information				
Classification of the mi	xture:	Classification procedure:		
Aquatic Chronic 2	H411	Calculation method		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN