according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030588	Date of first issue: 27.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Trade name	: STAPA METALLUX 2195 Aluminium Paste
Product code	: 051825G60

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	:	ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	:	+499152770
Telefax	:	+499152777008
E-mail address of person responsible for the SDS	:	msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008) Long-term (chronic) aquatic hazard, H412: Harmful to aquatic life with long lasting Category 3 effects. 2.2 Label elements Labelling (REGULATION (EC) No 1272/2008) Hazard statements : H412 Harmful to aquatic life with long lasting effects. Prevention: Precautionary statements : P273 Avoid release to the environment. Disposal:

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version	Revision Date: 12.02.2023	SDS Number:	Print Date: 16.04.2024
3.0		102000030588	Date of first issue: 27.09.2018

P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chamical name		Classification	Concentration
Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Naphtha (petroleum),	64742-48-9	Asp. Tox. 1; H304	>= 25 - < 50
hydrotreated heavy; Low boiling			
point ydrogen treated naphtha	918-481-9		
	01-2119457273-39		
Solvent naphtha (petroleum), light	64742-95-6	Flam. Liq. 3; H226	>= 2.5 - < 10
arom.		STOT SE 3; H336	
	918-668-5	(Central nervous	
	01-2119455851-35	system)	
		STOT SE 3; H335	
		(Respiratory system)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures				
General advice :	:	Move the victim to fresh air.		
		Do not leave the victim unattended.		
If inhaled :	:	Remove to fresh air. If unconscious, place in recovery position and seek medical		

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version 3.0	Revision Date: 12.02.2023		DS Number: 2000030588	Print Date: 16.04.2024 Date of first issue: 27.09.2018
			advice. If symptoms pers	ist, call a physician.
In case	e of skin contact	:	Wash off immedi	ately with soap and plenty of water.
In case	e of eye contact	:	Immediately flush	eye(s) with plenty of water.
			Remove contact I If eye irritation pe	enses. rsists, consult a specialist.
lf swall	owed	:	Never give anythi	tract clear. or alcoholic beverages. ng by mouth to an unconscious person. ist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	Water Foam ABC powder Carbon dioxide (CO2)
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
5.3 Advice for firefighters Special protective equipment for firefighters	:	Use personal protective equipment.
		Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030588	Date of first issue: 27.09.2018

SECTION 6: Accidental release measures

• •	e equipment and emergency procedures Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition. Avoid dust formation.
6.2 Environmental precautions	
Environmental precautions :	The product should not be allowed to enter drains, water courses or the soil.
	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Mothods and material for contai	nmont and cleaning up
6.3 Methods and material for contain Methods for cleaning up :	Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
Advice on protection against fire and explosion	:	Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.
		Provide appropriate exhaust ventilation at places where dust is formed.
Hygiene measures	:	General industrial hygiene practice.

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Versi 3.0	ion Revision Date: 12.02.2023	SDS Num 10200003		Print Date: 16.04.2024 Date of first issue: 27.09.2018
	Conditions for safe storage , Requirements for storage	-		atibilities ontainer. Keep containers tightly closed in a
areas and containers		cool,	well-ventilate	ad place. Keep container closed when not in rom sources of ignition - No smoking.
		kept u	pright to pre ng materials	are opened must be carefully resealed and vent leakage. Electrical installations / must comply with the technological safety
	Further information on storage conditions	: Protec	ct from humi	dity and water. Do not allow to dry.
	Advice on common storage	Never storaç Keep	allow produ ge. away from c	her with oxidizing and self-igniting products. In to get in contact with water during exidizing agents, strongly alkaline and erials in order to avoid exothermic reactions.
		No ma	aterials to be	especially mentioned.
	Further information on storage stability	: No de	composition	if stored and applied as directed.
7.3 S	specific end use(s)			

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis		
		of exposure)				
aluminium powder	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40		
(stabilised)						
		TWA (Respirable	4 mg/m3	GB EH40		
		fraction)				
		TWA (inhalable	10 mg/m3	GB EH40		
		dust)				
	Further inform	nation: For the purpo	ses of these limits, respirable	e dust and		
	inhalable dust	are those fractions	of airborne dust which will be	e collected		
	when samplin	g is undertaken in a	ccordance with the methods	described in		
			ampling and gravimetric ana			
			aerosols., The COSHH defir			
			ludes dust of any kind when			
			ater than 10 mg.m-3 8-hour			
	inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that					
	any dust will be subject to COSHH if people are exposed to dust above these					
	levels. Some dusts have been assigned specific WELs and exposure to these					
			limits., Most industrial dusts			
	particles of a	wide range of sizes.	The behaviour, deposition a	nd fate of any		

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version 3.0	Revision Date: 12.02.2023	SDS Number: 102000030588		nt Date: 16.04.2024 te of first issue: 27.09.2018	
	respo distir and ' mate availa to the defin conta shou	onse that it elicits, dep nguishes two size fract respirable'., Inhalable rial that enters the no able for deposition in a fraction that penetra itions and explanator ain components that h Id be complied with.,	bend on ctions fo dust ap se and the resp tes to the materia ave the Where r	he human respiratory system the nature and size of the part r limit-setting purposes terme proximates to the fraction of mouth during breathing and is iratory tract. Respirable dust he gas exchange region of the all are given in MDHS14/4., W ir own assigned WEL, all the ho specific short-term exposu- exposure limit should be use	article. HSE ad 'inhalable' airborne s therefore approximates e lung. Fuller Vhere dusts relevant limits ure limit is listed,
		TWA (Resp dust)		4 mg/m3	GB EH40
	inhala when MDH respi subs conc inhala any c levels must partic partic respo distir and ' mate avails to the defin conta shou	able dust are those fr sampling is undertak S14/4 General metho rable, thoracic and inl tance hazardous to he entration in air equal able dust or 4 mg.m-4 dust will be subject to so Some dusts have b comply with the appr cles of a wide range of cular particle after ent onse that it elicits, dep neguishes two size fract respirable'., Inhalable rial that enters the no able for deposition in e fraction that penetra itions and explanator ain components that h	actions actions and for s halable alth inc to or great 8 8-hour COSHHeen ass opriate f sizes. ry into the bend on thous for dust ap se and the resp tes to the y materia ave the Where r	ses of these limits, respirable of airborne dust which will be cordance with the methods of ampling and gravimetric anal aerosols., The COSHH defin dudes dust of any kind when atter than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du signed specific WELs and exp limits., Most industrial dusts of The behaviour, deposition are he human respiratory system the nature and size of the par r limit-setting purposes terme oproximates to the fraction of mouth during breathing and is iratory tract. Respirable dust a are given in MDHS14/4., W ir own assigned WEL, all the ho specific short-term exposu	collected described in ysis or ition of a present at a TWA of means that st above these cosure to these contain of fate of any , and the body inticle. HSE of 'inhalable' airborne s therefore approximates e lung. Fuller /here dusts relevant limits ure limit is listed,

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	()		() · · · · · · · · ·	
Substance name	End Use	Exposure routes	Potential health	Value
			effects	
aluminium powder	Workers	Inhalation	Long-term systemic	3.72 mg/m3
(stabilised)			effects	Ū
	Workers	Inhalation	Long-term local	3.72 mg/m3
			effects	-
	Consumers	Oral	Long-term systemic	3.95 mg/kg
			effects	
Naphtha (petroleum), hydrotreated heavy;	Workers	Inhalation	Acute systemic effects	1500 mg/m3
Low boiling point			enects	
ydrogen treated				
naphtha				
Парппа	M/a also as	Olda a sata at		000
	Workers	Skin contact	Long-term systemic	300 mg/kg

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Consumers

Ver 3.0	sion	Revision Date: 12.02.2023	SDS Nu 1020000		Print Date: 16. Date of first is:	04.2024 sue: 27.09.2018	
	I				effects	S	
			Consumers	Ingestion	Long-t effects	term systemic s	300 mg/kg
			Consumers	Skin cont	act Long-t effects	term systemic s	300 mg/kg
			Consumers	Inhalatior	Long-t effects	term systemic s	900 mg/m3
		nt naphtha leum), light	Workers	Inhalatior	Long-t effects	term systemic s	150 mg/m3
			Workers	Skin cont	act Long-t effects	term systemic s	25 mg/kg
			Consumers	Skin cont	act Long-t effects	term systemic s	11 mg/kg
			Consumers	Inhalatior	Long-t effects	term systemic s	32 mg/m3
			Consumers	Inhalatior	Long-t effects	term local s	11 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Ingestion

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

Long-term systemic

effects

11 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection Hand protection	:	Safety glasses
Material	:	Solvent-resistant gloves
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Long sleeved clothing Safety shoes
		Choose body protection according to the amount and
		concentration of the dangerous substance at the work place. Protective suit

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version	Revision Date: 12.02.2023	SDS Number:	Print Date: 16.04.2024
3.0		102000030588	Date of first issue: 27.09.2018
Respir	atory protection	: Use suitable br requires.	eathing protection if workplace concentration

SECTION 9: Physical and chemical properties

1	Information on basic physical Physical state	an :	d chemical properties Pasty solid
	Colour	:	silver
	Odour	:	characteristic
	Odour Threshold	:	No data available
	Freezing point	:	No data available
	Boiling point/boiling range	:	140 - 200 °C
	Flammability	:	Combustible Solids
	Upper explosion limit / Upper flammability limit	:	No data available
	Lower explosion limit / Lower flammability limit	:	No data available
	Flash point	:	No data available
	Auto-ignition temperature	:	Not relevant
	Decomposition temperature	:	No data available
	рН	:	substance/mixture is non-soluble (in water)
	Viscosity, kinematic	:	No data available
	Solubility(ies) Water solubility Solubility in other solvents		insoluble No data available
	Partition coefficient: n- octanol/water	:	No data available
	Vapour pressure	:	No data available
	Relative density	:	No data available
	Density	:	1.3 - 2.0 g/cm3
	Relative vapour density	:	No data available

9.1 Information on basic physical and chemical properties

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version Revision Date 3.0 12.02.2023	SDS Number: 102000030588	Print Date: 16.04.2024 Date of first issue: 27.09.2018	
Particle Size Distrib	ution :		
9.2 Other information Explosives Self-ignition Miscibility with water	: Not explosive : not auto-flam : immiscible		

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions. No hazards to be specially mentioned.
10.4 Conditions to avoid		
Conditions to avoid	:	Do not allow to dry.
		No data available
10.5 Incompatible materials		
Materials to avoid	:	Acids Bases Oxidizing agents Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

sion	Revision Date: 12.02.2023	SDS Number: 102000030588	Print Date: 16.04.2024 Date of first issue: 27.09.2018
<u>Com</u>	oonents:		
alumi	inium powder (stabil	ised):	
Acute	inhalation toxicity	: LC50 (Rat): Exposure tin Test atmosp	
Naph	tha (petroleum), hyd	rotreated heavy; L	ow boiling point ydrogen treated naphtha:
Acute	oral toxicity	: LD50 (Rat):	> 5,000 mg/kg
Acute	inhalation toxicity	Remarks: Ai because no	Test atmosphere: vapour n LC50/inhalation/4h/rat could not be determined mortality of rats was observed at the maximum oncentration.
Acute	dermal toxicity	: LD50 (Rabb	it): > 5,000 mg/kg
Solve	ent naphtha (petroleu	ım). light arom.:	
	oral toxicity	: LD50 (Rat):	3,492 mg/kg
Acute	dermal toxicity	: LD50 (Rabb	it): > 3,160 mg/kg
	corrosion/irritation assified based on ava	ailable information.	
	us eye damage/eye assified based on ava		
Resp	ratory or skin sensi	tisation	
	sensitisation assified based on ava	ailable information.	
-	ratory sensitisation assified based on ava	ailable information.	
	cell mutagenicity assified based on ava	ailable information.	
<u>Com</u>	oonents:		
Naph	tha (petroleum), hyd	rotreated heavy; L	ow boiling point ydrogen treated naphtha:
Germ	cell mutagenicity- ssment	: Classified ba	ased on benzene content < 0.1% (Regulation (E Annex VI, Part 3, Note P)
) liselet en ener	
Solve	ent naphtha (petroleu	im), light arom.:	

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version 3.0	Revision Date: 12.02.2023	SDS Number: 102000030588	Print Date: 16.04.2024 Date of first issue: 27.09.2018
	nogenicity lassified based on av	ailable information.	
<u>Com</u>	oonents:		
Carci	tha (petroleum), hyc nogenicity - ssment	: Classified bas	w boiling point ydrogen treated naphtha: ed on benzene content < 0.1% (Regulation (EC) nex VI, Part 3, Note P)
Solve	ent naphtha (petroleu	um), light arom.:	
	nogenicity - ssment		ed on benzene content < 0.1% (Regulation (EC) nex VI, Part 3, Note P)
-	oductive toxicity lassified based on avail	ailable information.	
	- single exposure lassified based on ava	ailable information.	
<u>Com</u>	oonents:		
	ent naphtha (petroleu ssment		piratory irritation., May cause drowsiness or
	- repeated exposur assified based on ava		
•	ation toxicity lassified based on ava	ailable information.	
<u>Com</u>	oonents:		
-	tha (petroleum), hyd oe fatal if swallowed a		w boiling point ydrogen treated naphtha:
	ent naphtha (petrole) be fatal if swallowed a		
11.2 Infor	mation on other haz	ards	
Furth	er information		
<u>Produ</u> Rema		: No data availa	ble

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030588	Date of first issue: 27.09.2018

SECTION 12: Ecological information

12.1 Toxicity

Components:

Solvent naphtha (petroleum), light arom .:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological	:	An environmental hazard cannot be excluded in the event of
information		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

Components:

Naphtha (petroleum),	hydrotreated	heavy; Low boiling point ydrogen treated naphtha:
Additional ecological	: No	o data available
information		

SECTION 13: Disposal considerations

European Waste Catalogue	:	12 01 04 - non-ferrous metal dust and particles
European Waste Catalogue	:	10 03 21 - other particulates and dust (including ball-mill dust)
		containing hazardous substances

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version 3.0	Revision Date: 12.02.2023		OS Number: 2000030588	Print Date: 16.04.2024 Date of first issue: 27.09.2018			
13.1 Wast	e treatment methods	5					
Produ	uct	:	: The product should not be allowed to enter drains, courses or the soil.				
SECTIO	N 14: Transport info	orma	tion				
14.1 UN n	umber or ID number						
ADR		:	Not regulated a	as a dangerous good			
IMDG	i	:	Not regulated a	as a dangerous good			
ΙΑΤΑ		:	Not regulated a	as a dangerous good			
14.2 UN p	roper shipping name	•					
ADR		:	Not regulated a	as a dangerous good			
IMDG	i	:	Not regulated a	as a dangerous good			
ΙΑΤΑ		:	Not regulated a	as a dangerous good			
14.3 Trans	sport hazard class(es	5)					
ADR		:	Not regulated a	as a dangerous good			
IMDG	i	:	Not regulated a	as a dangerous good			
ΙΑΤΑ		:	Not regulated a	as a dangerous good			
14.4 Pack	ing group						
ADR		:	Not regulated a	as a dangerous good			
IMDG	i	:	Not regulated a	as a dangerous good			
ΙΑΤΑ	(Cargo)	:	Not regulated a	as a dangerous good			
ΙΑΤΑ	(Passenger)	:	Not regulated a	as a dangerous good			
	r onmental hazards egulated as a dangero	us go	od				
-	ial precautions for u	ser					
Rema	ırks	:	Not classified a regulations.	as dangerous in the meaning of transport			

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 2195 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030588	Date of first issue: 27.09.2018

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha (Number on list 3) Solvent naphtha (petroleum), light arom. (Number on list 3)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H226 H228 H304 H335 H336 H411	:	Flammable liquid and vapour. Flammable solid. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.			
Full text of other abbreviations					
Aquatic Chronic Asp. Tox. Flam. Liq. Flam. Sol. STOT SE GB EH40		Long-term (chronic) aquatic hazard Aspiration hazard Flammable liquids Flammable solids Specific target organ toxicity - single exposure UK. EH40 WEL - Workplace Exposure Limits			
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)			

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -



STAPA METALLUX 2195 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030588	Date of first issue: 27.09.2018

Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information Classification of the mixture:

H412

Aquatic Chronic 3

Classification procedure:	
Calculation method	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN