according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.1	02.04.2024	10200000285	Date of first issue: 02.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	:	STANDART PCA 214 Aluminium Powder
Draduataada		049146EV0
Product code	•	049140EV0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1 H228: Flammable solid.

Information concerning particular hazards for human and environment: Please refer to our website for further important safety instructions for handling aluminium powder:

http://www.eckart.net/fileadmin/eckart/Service/GDA_Alupulver_Safety_engl.pdf

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

A member of **C ALTANA**

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Version 4.1	Revision Date: 02.04.2024	-	DS Number: 02000000285	Print Date: 16.04.2024 Date of first issue: 02.01.2014
Hazard pictograms		:		
Sig	nal word	:	Danger	
Haz	ard statements	:	H228	Flammable solid.
Pre	cautionary statements	:	Prevention: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
			P240	Ground and bond container and receiving equipment.
			P241	Use explosion-proof electrical/ventilating/ lighting equipment.
			P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
			Response: P370 + P378	In case of fire: Use for extinction: Special powder for metal fires.
			P370 + P378	In case of fire: Use for extinction: Dry sand.

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures


Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
monoalkyl or monoaryl or	2530-85-0	Skin Irrit. 2; H315	>= 1 - < 10
monoalkyaryl esters of	219-785-8	Eye Irrit. 2; H319	
methacrylic acid	607-134-00-4	STOT SE 3; H335	
-		(Respiratory system)	
	01-2119513216-50		

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder



For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures			
General advice	:	Move the victim to fresh air.	
		Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.	
If inhaled	:	Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.	
In case of skin contact	:	Wash off immediately with soap and plenty of water.	
		If skin irritation persists, call a physician. If on clothes, remove clothes.	
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.	

4.2 Most important symptoms and effects, both acute and delayed None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1	Exting	guishing	media
-----	--------	----------	-------

Suitable extinguishing media : Dry sand Special powder against metal fire

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Version 4.1	Revision Date: 02.04.2024		DS Number: 2000000285	Print Date: 16.04.2024 Date of first issue: 02.01.2014
	Unsuitable extinguishing media		ABC powder Carbon dioxide (0 Water Foam	CO2)
			High volume wate	er jet
5.2 Spec	5.2 Special hazards arising from the		e substance or mi	xture
	Specific hazards during : firefighting		Contact with water liberates extremely flammable gas (hydrogen).	
5.3 Advi	ce for firefighters			
•	Special protective equipment : for firefighters		Wear self-contained breathing apparatus for firefighting if necessary.	
Furt	Further information :		For safety reasons in case of fire, cans should be stored separately in closed containments. Use extinguishing measures that are appropriate to loca circumstances and the surrounding environment. Use a water spray to cool fully closed containers.	

SECTION 6: Accidental release measures

	e equipment and emergency procedures Use personal protective equipment. Evacuate personnel to safe areas. Avoid dust formation. Avoid breathing dust. Remove all sources of ignition.
6.2 Environmental precautions	
General advice :	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contain	inment and cleaning up
Methods for cleaning up :	Use mechanical handling equipment. Do not use a vacuum cleaner.
	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.1	02.04.2024	10200000285	Date of first issue: 02.01.2014

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling Avoid creating dust. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Store away from heat. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Use explosion-proof equipment. During processing, dust may Advice on protection against form explosive mixture in air. Take measures to prevent the fire and explosion build up of electrostatic charge. When transferring from one container to another apply earthing measures and use conductive hose material. Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from open flames, hot surfaces and sources of ignition. Hygiene measures When using do not eat or drink. When using do not smoke. : Wash hands before breaks and at the end of workday. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage : Earthing of containers and apparatuses is essential. Reaction areas and containers with water liberates extremely flammable gas (hydrogen) Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use. No smoking. Keep container tightly closed in a dry and wellventilated place. Electrical installations / working materials must comply with the technological safety standards. Further information on Protect from humidity and water. storage conditions Do not store together with oxidizing and self-igniting products. Advice on common storage Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.1	02.04.2024	102000000285	Date of first issue: 02.01.2014
	er information on	: Keep in a dry p	lace.
	ge stability	No decomposi	tion if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	of exposure) TWA (Inhalable)	10 mg/m3	GB EH40
(stabilised)		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	inhalable dust	hation: For the purpo tare those fractions	ses of these limits, respirable of airborne dust which will be ccordance with the methods	e collected
	MDHS14/4 Ge respirable, the	eneral methods for s pracic and inhalable	ampling and gravimetric ana aerosols., The COSHH defir	lysis or hition of a
	concentration	in air equal to or gre	eludes dust of any kind when eater than 10 mg.m-3 8-hour	TWA of
	any dust will b	e subject to COSHH	TWA of respirable dust. This I if people are exposed to du signed specific WELs and ex	ust above these
	must comply particles of a	with the appropriate wide range of sizes.	limits., Most industrial dusts The behaviour, deposition a	contain nd fate of any
	response that	it elicits, depend on	he human respiratory system the nature and size of the part r limit-setting purposes termo	article. HSE
	and 'respirabl	e'., Inhalable dust ap	proximates to the fraction of mouth during breathing and	airborne
	available for c	leposition in the resp	iratory tract. Respirable dus ne gas exchange region of the	t approximates
	contain comp	onents that have the	al are given in MDHS14/4., \ ir own assigned WEL, all the	relevant limits
		times the long-term	no specific short-term expos exposure limit should be use	ed.
		TWA (Respirable dust)	4 mg/m3	GB EH40
	inhalable dust	t are those fractions	ses of these limits, respirable of airborne dust which will be	e collected
	MDHS14/4 G	eneral methods for s	ccordance with the methods ampling and gravimetric ana	lysis or
	substance ha	zardous to health inc	aerosols., The COSHH defir cludes dust of any kind when	present at a
	concentration	in air equal to or gre	ater than 10 mg.m-3 8-hour	IVVA OT

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.1	02.04.2024	102000000285	Date of first issue: 02.01.2014
	any du levels must particl particl respo disting and 'ru materi availa to the definit contai should	ust will be subject to Cl . Some dusts have bee comply with the approp les of a wide range of s ular particle after entry nse that it elicits, depe guishes two size fraction espirable'., Inhalable d al that enters the nose ble for deposition in the fraction that penetrates tions and explanatory r in components that have d be complied with., W	B-hour TWA of respirable dust. This means that OSHH if people are exposed to dust above these en assigned specific WELs and exposure to these oriate limits., Most industrial dusts contain sizes. The behaviour, deposition and fate of any into the human respiratory system, and the body nd on the nature and size of the particle. HSE ons for limit-setting purposes termed 'inhalable' ust approximates to the fraction of airborne e and mouth during breathing and is therefore e respiratory tract. Respirable dust approximates s to the gas exchange region of the lung. Fuller naterial are given in MDHS14/4., Where dusts ve their own assigned WEL, all the relevant limits here no specific short-term exposure limit is listed, -term exposure limit should be used.

Derived No Effect Level	(DNEL)	according to Regulation	(EC) No. 1907/2006:
--------------------------------	--------	-------------------------	---------------------

Substance name	End Use	Exposure routes	Potential health	Value
			effects	
aluminium powder	Workers	Inhalation	Long-term systemic	3.72 mg/m3
(stabilised)			effects	
	Workers	Inhalation	Long-term local	3.72 mg/m3
			effects	_
	Consumers	Oral	Long-term systemic	3.95 mg/kg
			effects	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipm	ent	
Eye/face protection	:	Face-shield Tightly fitting safety goggles
Hand protection		
Material	:	Leather
Glove length	:	Long sleeve gloves
Remarks		Leather gloves The choice of an entropyiste glove does not
Remarks	•	Leather gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Anti-static and fire resistant protective clothing. DIN EN 11612; EN 533; EN 1149-1. Anti-static safety shoes. Dust impervious protective suit
		Choose body protection according to the amount and concentration of the dangerous substance at the work place.

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Version	Revision Date: 02.04.2024	SDS Number:	Print Date: 16.04.2024
4.1		102000000285	Date of first issue: 02.01.2014
Respi	ratory protection	requires.	reathing protection if workplace concentration aratus with filter.

SECTION 9: Physical and chemical properties

9.1	Information on basic physical Form	an :	d chemical properties powder
	Colour	:	silver
	Odour	:	characteristic
	Odour Threshold	:	No data available
	Melting point/range	:	> 600 °C
	Boiling point/boiling range	:	No data available
	Flammability	:	Combustible Solids
	Upper explosion limit / Upper flammability limit	:	No data available
	Lower explosion limit / Lower flammability limit	:	30 g/m3
	Flash point	:	No data available
	Auto-ignition temperature	:	340 °C
	Decomposition temperature	:	No data available
	рН	:	substance/mixture is non-soluble (in water)
	Viscosity, kinematic	:	No data available
	Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
	Partition coefficient: n- octanol/water	:	No data available
	Vapour pressure	:	No data available
	Relative density	:	No data available
	Density	:	2.5 g/cm3

A member of **C ALTANA**

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Version 4.1	Revision Date: 02.04.2024	SDS Number: 102000000285	Print Date: 16.04.2024 Date of first issue: 02.01.2014
Relat	ive vapour density	: No data avai	lable
	cle characteristics article Size Distribution	: No data avai	lable
	information ata available		
SECTIO	N 10: Stability and re	activity	
10.1 Reac No de	tivity ecomposition if stored a	nd applied as direc	ted.
	nical stability ecomposition if stored a	nd applied as direc	ted.
10.3 Poss	sibility of hazardous re	actions	
Hazai	rdous reactions	: Contact with	acids and alkalis may release hydrogen.
		No decompo	osition if stored and applied as directed.
		Dust may fo	rm explosive mixture in air.
10.4 Conc	ditions to avoid		
Cond	litions to avoid	: Heat, flames	and sparks.
10.5 Inco	mpatible materials		
	rials to avoid	: Acids Bases Oxidizing ag Water	ents
	rdous decomposition mation is not available.	products	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

A member of **C ALTANA**

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

rsion	Revision Date: 02.04.2024		DS Number: 2000000285	Print Date: 16.04.2024 Date of first issue: 02.01.2014
mono	oalkyl or monoaryl o	or mon	oalkyaryl ester	s of methacrylic acid:
Acute	oral toxicity	:	LD50 (Rat): >	2,000 mg/kg
Acute	dermal toxicity	:	(Rat): > 2,000	mg/kg
	corrosion/irritation assified based on av	ailable	information.	
<u>Produ</u> Rema		:	May cause ski	in irritation and/or dermatitis.
<u>Com</u>	oonents:			
monc Resul		or mon :	oalkyaryl ester Skin irritation	s of methacrylic acid:
	us eye damage/eye assified based on av			
<u>Produ</u> Rema		:	Product dust r system.	nay be irritating to eyes, skin and respiratory
<u>Com</u> p	oonents:			
monc Resul		or mon :		s of methacrylic acid:
Resp	ratory or skin sensi	itisatio	n	
	sensitisation assified based on av	ailable	information.	
-	ratory sensitisation assified based on av		information.	
	cell mutagenicity assified based on av	ailable	information.	
	n ogenicity assified based on av	ailable	information.	
-	oductive toxicity assified based on av	ailable	information.	
STOT	- single exposure			

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

/ersion 4.1	Revision Date: 02.04.2024	SDS Number: 102000000285	Print Date: 16.04.2024 Date of first issue: 02.01.2014
<u>Com</u>	oonents:		
	oalkyl or monoaryl o ssment		s of methacrylic acid: piratory irritation.
	- repeated exposur lassified based on av		
-	r ation toxicity lassified based on av	ailable information.	
11.2 Infor	mation on other haz	zards	
Furth	er information		
<u>Prod</u> Rema		: No data availa	ble
SECTIO	N 12: Ecological in	formation	
	•		
No da 12.2 Pers i	city ata available i stence and degrada ata available	ability	
No da 12.2 Persi No da 12.3 Bioa	ata available istence and degrada	-	
No da 12.2 Persi No da 12.3 Bioa No da 12.4 Mobi	ata available istence and degrada ata available ccumulative potentia	-	
No da 12.2 Persi No da 12.3 Bioa No da 12.4 Mobi No da	ata available istence and degrada ata available ccumulative potentia ata available ility in soil	al	
12.2 Persi No da 12.3 Bioa No da 12.4 Mobi No da 12.5 Resu <u>Prod</u>	ata available istence and degrada ata available ccumulative potentia ata available ility in soil ata available ilts of PBT and vPvE	al 3 assessment : This substance to be either pe	e/mixture contains no components considered rsistent, bioaccumulative and toxic (PBT), or and very bioaccumulative (vPvB) at levels of
No da 12.2 Persi No da 12.3 Bioa No da 12.4 Mobi No da 12.5 Resu Produ Asses 12.6 Endo	ata available istence and degrada ata available ccumulative potentia ata available lity in soil ata available lits of PBT and vPvE uct:	al 3 assessment : This substance to be either pe very persistent 0.1% or higher	rsistent, bioaccumulative and toxic (PBT), or and very bioaccumulative (vPvB) at levels of
No da 12.2 Persi No da 12.3 Bioa No da 12.4 Mobi No da 12.5 Resu Produ Asses 12.6 Endo No da	ata available istence and degrada ata available ccumulative potentia ata available lity in soil ata available lits of PBT and vPvE uct: ssment	al 3 assessment : This substance to be either pe very persistent 0.1% or higher	rsistent, bioaccumulative and toxic (PBT), or and very bioaccumulative (vPvB) at levels of

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Version 4.1	Revision Date: 02.04.2024		S Number: 2000000285	Print Date: 16.04.2024 Date of first issue: 02.01.2014		
SECTI	ON 13: Disposal consi	idera	ations			
	ropean Waste Catalogue ropean Waste Catalogue	:		rrous metal dust and particles particulates and dust (including ball-mill dust) ous substances		
13.1 Wa	aste treatment methods					
Product		:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.			
Contaminated packaging		:	Dispose of as un Do not re-use em	emaining contents. of as unused product. e-use empty containers. urn, or use a cutting torch on, the empty drum.		

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	UN 1309	
	IMDG	:	UN 1309	
	ΙΑΤΑ	:	UN 1309	
14.2	UN proper shipping name			
	ADR	:	ALUMINIUM	POWDER, COATED
	IMDG	:	ALUMINIUM	POWDER, COATED
	ΙΑΤΑ	:	Aluminium p	owder, coated
14.3	Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	4.1	
	IMDG	:	4.1	
	ΙΑΤΑ	:	4.1	
14.4	Packing group			
	ADR			
	Packing group	:	II	
	Classification Code	:	F3	
	Hazard Identification Number	:	40	
	Labels	:	4.1	
	Tunnel restriction code	:	(E)	

according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Versic 4.1	on	Revision Date: 02.04.2024		DS Number: 2000000285	Print Date: 16.04.2024 Date of first issue: 02.01.2014
P L E	MDG Packing Labels EmS C Remark		:	ll 4.1 F-G, S-G IMDG Code segre	egation group 15 - Powdered metals
P a P P	Packing aircraft Packing	Cargo) g instruction (cargo) g instruction (LQ) g group	:	448 Y441 II 4.1	
P ((P P	Packing passe Packing	Passenger) g instruction nger aircraft) g instruction (LQ) g group	:	445 Y441 II 4.1	
14.5 Environmental hazards					
E	ADR Enviror MDG	nmentally hazardous	:	no	
		pollutant	:	no	

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 40 aluminium powder (stabilised) (Number on list 40)

monoalkyl or monoaryl or monoalkyaryl esters of methacrylic according to Regulation (EC) No. 1907/2006



STANDART PCA 214 Aluminium Powder

Versi 4.1	on	Revision Date: 02.04.2024	SDS Number: 10200000285			ate: 16.04.2024 first issue: 02.01.2014
						acid (Number on list 3)
		ACH Candidate list of n (SVHC) for Authoris	substances of very hig ation	h	:	Not applicable
- 	The Pe	ersistent Organic Pollu ition (EU) 2019/1021 a	tants Regulations (retai	ined	:	Not applicable
F	Regula		9 on substances that		:	Not applicable
F	Regula	5	on the marketing and us	se of	:	aluminium powder (stabilised)
ι	•	ACH List of substance	es subject to authorisati	ion	:	Not applicable
F	Regula	,	on the marketing and us	se of		
5	suspic	ious transactions, and	Regulation (EU) 2019/1 significant disappearar evant national contact p	nces ar		aluminium powder (stabilised) thefts (ANNEX II)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H228	:	Flammable solid.			
H315	:	Causes skin irritation.			
H319	:	Causes serious eye irritation.			
H335	:	May cause respiratory irritation.			
Full text of other abbreviations					
Eye Irrit.	:	Eye irritation			
Flam. Sol.	:	Flammable solids			
Skin Irrit.	:	Skin irritation			
STOT SE	:	Specific target organ toxicity - single exposure			
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits			
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)			

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System;



STANDART PCA 214 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.1	02.04.2024	102000000285	Date of first issue: 02.01.2014

GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN