according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version	Revision Date:	SDS Number:	Print Date: 15.04.2024
4.0	30.01.2024	102000021561	Date of first issue: 16.06.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	: Rotovario UV 900 114 Silver
Product code	: 053498G60
1.2 Relevant identified uses o	f the substance or mixture and uses advised against
Use of the Substance/Mixture	: Colouring agents, pigments
1.3 Details of the supplier of t	he safety data sheet
Company	: ECKART Suisse SA Route de la Brasserie 2 1963 Vétroz
Telephone	: +410273454800
Telefax	: +410273454859

E-mail address of person : <u>msds.eckart@altana.com</u> responsible for the SDS

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 Long-term (chronic) aquatic hazard, Category 3 H317: May cause an allergic skin reaction. H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version 4.0	Revision Date: 30.01.2024		DS Number: 02000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014
Hazar	d pictograms	:	(!)	
Signa	l word	:	Warning	
Hazar	d statements	:	H317 H412	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Preca	utionary statements	:	Prevention: P261 P273 P280 Response: P333 + P313 P362 + P364 Disposal:	Avoid breathing dust. Avoid release to the environment. Wear protective gloves. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.
			P501	Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) Glycerol, propoxylated, esters with acrylic acid

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

oomponenta			
Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 25 - < 50
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Poly(oxy-1,2-ethanediyl), .alpha	28961-43-5	Eye Irrit. 2; H319	>= 25 - < 50

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version 4.0	Revision Date: 30.01.2024		8 Number: 000021561		Date: 15.04.2024 of first issue: 16.06.2014	4
prope 2-(hyd	oomega[(1-oxo-2- enyl)oxy]-, ether with 2 droxymethyl)-1,3- anediol (3:1)	-ethyl-	500-066-5 01-2119489900)-30	Skin Sens. 1; H317 Aquatic Chronic 3; H412	
	erol, propoxylated, est acrylic acid	ers	52408-84-1 500-114-5 01-2119487948	8-12	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 10
dode	cylphosphonic acid		5137-70-2 225-897-8		Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT RE 2; H373 (Kidney)	>= 5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measur General advice		Move the victim to fresh air.
		Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	Wash off immediately with soap and plenty of water.
In case of eye contact	:	Immediately flush eye(s) with plenty of water.
		Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Risks
- : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed This information is not available.

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Versio 4.0		evision Date: 0.01.2024		9S Number: 2000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014
SEC	TION 5:	Firefighting meas	sure	es	
5.1 E	xtinguisł	ning media			
S	Suitable e	extinguishing media	:	Dry sand Special powder a	gainst metal fire
	Unsuitable media	e extinguishing	:	Water Foam ABC powder Carbon dioxide (C	CO2)
S	-	azards arising from nazards during g	the :		xture off from fire fighting to enter drains or water
5		r firefighters rotective equipment hters	:	Use personal prot	tective equipment.
				Wear self-contain necessary.	ed breathing apparatus for firefighting if
F	Further in	formation	:	must not be disch Fire residues and be disposed of in Use extinguishing	ted fire extinguishing water separately. This arged into drains. contaminated fire extinguishing water must accordance with local regulations. measures that are appropriate to local d the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition. Use personal protective equipment. Avoid dust formation. Avoid breathing dust.
----------------------	---	--

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version 4.0	Revision Date: 30.01.2024	SDS Number: 102000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014
6.3 Metho	ds and material for	containment and clea	aning up
Metho	ods for cleaning up	Soak up with in	al handling equipment. nert absorbent material (e.g. sand, silica gel, niversal binder, sawdust).
		Keep in suitab	le, closed containers for disposal.
6 4 Refere	nce to other section	15	

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling Keep away from heat and sources of ignition. : Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Advice on protection against Keep away from open flames, hot surfaces and sources of : fire and explosion ignition. Earthing of containers and apparatuses is essential. Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Hygiene measures Wash hands before breaks and at the end of workday. : 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage Store in original container. Keep containers tightly closed in a : areas and containers cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on Protect from humidity and water. Do not allow to dry.

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version 4.0	Revision Date: 30.01.2024	SDS Number: 102000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014
stora	ge conditions		
Advid	ce on common storage	Never allow p storage. Keep away fro	ogether with oxidizing and self-igniting products. roduct to get in contact with water during om oxidizing agents, strongly alkaline and materials in order to avoid exothermic reactions.
	er information on ge stability	: No decompos	sition if stored and applied as directed.
7.3 Specif	fic end use(s)		

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

aluminium powder (stabilised) 7429-90-5 TWA (Inhalable) 10 mg/m3 GB EH40 (stabilised) TWA (Respirable fraction) 4 mg/m3 GB EH40 TWA (inhalable dust) 10 mg/m3 GB EH40 Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4,. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with	Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
fraction TWA (inhalable dust) 10 mg/m3 GB EH40 Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
dust)Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			· ·	4 mg/m3	GB EH40
inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable', Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			``	10 mg/m3	GB EH40
TWA (Respirable 4 mg/m3 GB EH40		inhalable dus when samplir MDHS14/4 G respirable, the substance ha concentration inhalable dus any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that e available for o to the fraction definitions an contain comp should be con	t are those fractions of is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or great tor 4 mg.m-3 8-hour be subject to COSHH dusts have been ass with the appropriate wide range of sizes. ticle after entry into the it elicits, depend on two size fractions for e'., Inhalable dust appendent that penetrates to the deposition in the respondent that penetrates to the decision of the the in that penetrates to the decision of the the molied with., Where response	of airborne dust which will be coordance with the methods sampling and gravimetric and aerosols., The COSHH defin- cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du- signed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition a he human respiratory system the nature and size of the p r limit-setting purposes term oproximates to the fraction or mouth during breathing and irratory tract. Respirable dus he gas exchange region of the all are given in MDHS14/4., V ir own assigned WEL, all the no specific short-term exposed	e collected described in alysis or nition of a present at a TWA of s means that ust above these posure to these contain and fate of any n, and the body article. HSE ed 'inhalable' f airborne is therefore t approximates ne lung. Fuller Where dusts e relevant limits ure limit is listed,

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version	Revision Date: 30.01.2024	SDS Number:	Print Date: 15.04.2024
4.0		102000021561	Date of first issue: 16.06.2014
	inhala when MDHS respir subst conce inhala any d levels must partic partic respon distin and 'r mater availa to the defini conta shoul	able dust are those fra sampling is undertak S14/4 General metho rable, thoracic and inh ance hazardous to he entration in air equal t able dust or 4 mg.m-3 ust will be subject to comply with the appro- les of a wide range of ular particle after entr inse that it elicits, dep guishes two size fract respirable'., Inhalable ial that enters the nos able for deposition in t fraction that penetrat tions and explanatory in components that ha	e purposes of these limits, respirable dust and actions of airborne dust which will be collected en in accordance with the methods described in ds for sampling and gravimetric analysis or halable aerosols., The COSHH definition of a eath includes dust of any kind when present at a o or greater than 10 mg.m-3 8-hour TWA of 8-hour TWA of respirable dust. This means that COSHH if people are exposed to dust above these een assigned specific WELs and exposure to these opriate limits., Most industrial dusts contain f sizes. The behaviour, deposition and fate of any y into the human respiratory system, and the body rend on the nature and size of the particle. HSE tions for limit-setting purposes termed 'inhalable' dust approximates to the fraction of airborne se and mouth during breathing and is therefore the respiratory tract. Respirable dust approximates es to the gas exchange region of the lung. Fuller material are given in MDHS14/4., Where dusts ave their own assigned WEL, all the relevant limits Where no specific short-term exposure limit is listed, g-term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Glycerol, propoxylated, esters with acrylic acid	Workers	Inhalation	Long-term systemic effects	16.22 mg/m3
	Workers	Dermal	Long-term systemic effects	1.92 mg/kg
	Consumers	Inhalation	Long-term systemic effects	4.87 mg/m3
	Consumers	Dermal	Long-term systemic effects	1.15 mg/kg
	Consumers	Oral	Long-term systemic effects	1.39 mg/kg
Rosin, hydrogenated	Workers	Skin contact	Long-term systemic effects	17 mg/kg
	Workers	Inhalation	Long-term systemic effects	117 mg/m3
	Consumers	Ingestion	Long-term systemic effects	10 mg/kg
	Consumers	Skin contact	Long-term systemic	10 mg/kg

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version Revision Date: 4.0 30.01.2024			S Numb 000021	-	Print Date: 15.04.2024 Date of first issue: 16.06.2014		
ļ		Consume	re	Inhalation	effects Long-term s	vetomia	35 mg/m3
		Consume	15	Innalation	effects	ystemic	35 mg/m3
-		oncentratio			ng to Regulation (E	·	
	tance name			onmental Cor	npartment		alue
alumi	nium powder (stab	ilised)	Fresh water		0.	0.0749 mg/l	
			clarifi	arification plant		20	0 mg/l
	Glycerol, propoxylated, esters with acrylic acid		Fresh	water			.0057 mg/l
			Marine water			0.	.00057 mg/l
			Fresh	Fresh water sediment			.0168 mg/kg
			Marin	e sediment			00168 mg/kg

	Fresh water sediment	0.0168 mg/kg
	Marine sediment	0.00168 mg/kg
	STP	10 mg/l
	Soil	0.0011 mg/kg
Rosin, hydrogenated	Soil	0.00045 mg/kg
	Fresh water	0.0016 mg/l
	Fresh water sediment	0.007 mg/kg
	Intermittent Release	0.016 mg/l
	Marine water	0.00016 mg/l
	Marine sediment	0.0007 mg/kg
	STP	1000 mg/l

8.2 Exposure controls

Personal protective equipme Eye/face protection Hand protection Material	ent : :	Tightly fitting safety goggles Solvent-resistant gloves
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Long sleeved clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version	Revision Date: 30.01.2024	SDS Number:	Print Date: 15.04.2024
4.0		102000021561	Date of first issue: 16.06.2014
Respir	ratory protection	: Use suitable bi requires.	reathing protection if workplace concentration

SECTION 9: Physical and chemical properties

1	Form		Pasty solid
	Colour	:	silver
	Odour	:	characteristic
	Odour Threshold	:	No data available
	Melting point/range	:	> 600 °C
	Boiling point/boiling range	:	No data available
	Flammability	:	Combustible Solids
	Upper explosion limit / Upper flammability limit	:	No data available
	Lower explosion limit / Lower flammability limit	:	No data available
	Flash point	:	> 100 °C
	Auto-ignition temperature	:	No data available
	Decomposition temperature	:	No data available
	рН	:	substance/mixture is non-soluble (in water)
	Viscosity, kinematic	:	No data available
	Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
	Partition coefficient: n- octanol/water	:	No data available
	Vapour pressure	:	No data available
	Relative density	:	No data available
	Density	:	1.3 - 2.0 g/cm3 (20 °C)
	Relative vapour density	:	No data available

9.1 Information on basic physical and chemical properties

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version 4.0	Revision Date: 30.01.2024	SDS Number: 102000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014	
	ticle characteristics Particle Size Distribution	: No data ava	ailable	
	r information	: Not explosiv	ve	
Self	f-ignition	: not auto-fla	mmable	
Mis	cibility with water	: immiscible		

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. No decomposition if stored and applied as directed.
10.4 Conditions to avoid		
Conditions to avoid	:	Do not allow to dry.
		No data available
10.5 Incompatible materials		
Materials to avoid	:	Acids Bases Oxidizing agents
		Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

rsion)	Revision Date: 30.01.2024	SDS Number: 102000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014
<u>Comp</u>	onents:		
alumi	nium powder (stabili	ised):	
	inhalation toxicity	: LC50 (Rat): : Exposure tim	
	corrosion/irritation assified based on ava	ilable information.	
Produ	ict:		
Result Remai	t	: No skin irritat : Based on da	ion ta from similar materials
Remai	rks	: May cause s	kin irritation and/or dermatitis.
<u>Comp</u>	onents:		
	cylphosphonic acid:	: Corrosive aft	er 3 minutes to 1 hour of exposure
Result			
Serio	u s eye damage/eye i assified based on ava	rritation	
Serio	u s eye damage/eye i assified based on ava	rritation	
Serior Not cla	u s eye damage/eye i assified based on ava <u>ıct:</u>	rritation ilable information. : No eye irritat	
Serio Not cla <u>Produ</u> Result	u s eye damage/eye i assified based on ava <u>ict:</u> rks	rritation ilable information. : No eye irritat : Based on da	ion
Seriou Not cla Produ Result Remai	u s eye damage/eye i assified based on ava <u>ict:</u> rks	rritation ilable information. : No eye irritat : Based on da : Product dust	ion ta from similar materials
Seriou Not cla Produ Result Remai Remai	us eye damage/eye i assified based on ava <u>ict:</u> rks rks	rritation ilable information. : No eye irritat : Based on da : Product dust system. .alphahydroome	ion ta from similar materials may be irritating to eyes, skin and respiratory ga[(1-oxo-2-propenyl)oxy]-, ether with 2-
Seriou Not cla Produ Result Remai Remai	us eye damage/eye i assified based on ava <u>ict:</u> rks rks <u>ponents:</u> pxy-1,2-ethanediyl), 2-(hydroxymethyl)-1,	rritation ilable information. : No eye irritat : Based on da : Product dust system. .alphahydroome	ion ta from similar materials may be irritating to eyes, skin and respiratory ga[(1-oxo-2-propenyl)oxy]-, ether with 2-):
Seriou Not cla Produ Result Remai Remai Remai Remai Remai Remai Remai	us eye damage/eye i assified based on ava i <u>t</u> rks rks <u>ponents:</u> pxy-1,2-ethanediyl), 2-(hydroxymethyl)-1,	 rritation ilable information. No eye irritat Based on dat Product dust system. .alphahydroome 3-propanediol (3:1 Irritating to eye 	ion ta from similar materials may be irritating to eyes, skin and respiratory ga[(1-oxo-2-propenyl)oxy]-, ether with 2-): yes.
Seriou Not cla Produ Result Remai Remai Remai Remai Remai Remai Remai	us eye damage/eye i assified based on ava <u>ict:</u> rks rks <u>ponents:</u> poxy-1,2-ethanediyl), 2-(hydroxymethyl)-1,	 rritation ilable information. No eye irritat Based on dat Product dust system. .alphahydroome 3-propanediol (3:1 Irritating to eye 	ion ta from similar materials may be irritating to eyes, skin and respiratory ga[(1-oxo-2-propenyl)oxy]-, ether with 2-): yes.
Seriou Not cla Produ Result Remain Remain Remain Remain Remain Remain Comp Poly(o ethyl-2 Result Glyce Result	us eye damage/eye i assified based on ava <u>ict:</u> rks rks <u>ponents:</u> poxy-1,2-ethanediyl), 2-(hydroxymethyl)-1,	 rritation ilable information. No eye irritat Based on da Product dust system. alphahydroome alphahydroome propanediol (3:1) Irritating to eye sters with acrylic are Eye irritation	ion ta from similar materials may be irritating to eyes, skin and respiratory ga[(1-oxo-2-propenyl)oxy]-, ether with 2-): yes.
Seriou Not cla Produ Result Remain Remain Remain Comp Poly(o ethyl-2 Result Glyce Result Result Result	us eye damage/eye i assified based on ava <u>ict:</u> rks rks <u>conents:</u> poxy-1,2-ethanediyl), 2-(hydroxymethyl)-1, t rol, propoxylated, es ratory or skin sensit	rritation ilable information. : No eye irritat : Based on da : Product dust system. .alphahydroome 3-propanediol (3:1 : Irritating to ey sters with acrylic ac : Eye irritation isation	ion ta from similar materials may be irritating to eyes, skin and respiratory ga[(1-oxo-2-propenyl)oxy]-, ether with 2-): yes.
Seriou Not cla Produ Result Remain Remain Remain Remain Poly(o ethyl-2 Result Result Result Result Result Skin s May c	us eye damage/eye i assified based on ava <u>ict:</u> rks rks <u>ponents:</u> pxy-1,2-ethanediyl), 2-(hydroxymethyl)-1, t rol, propoxylated, es t	rritation ilable information. : No eye irritat : Based on da : Product dust system. .alphahydroome 3-propanediol (3:1 : Irritating to ey sters with acrylic ac : Eye irritation isation	ion ta from similar materials may be irritating to eyes, skin and respiratory ga[(1-oxo-2-propenyl)oxy]-, ether with 2-): yes.

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version 4.0	Revision Date: 30.01.2024	SDS Number: 102000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014
<u>Proc</u> Rem		: Causes ser	isitisation.
<u>Com</u>	ponents:		
-			ega[(1-oxo-2-propenyl)oxy]-, ether with 2-
etny Resu	I-2-(hydroxymethyl)-1, ^{Ilt}	• • •	:1): sensitisation by skin contact.
Glvc	erol, propoxylated, e	sters with acrylic	acid:
Resu		-	sensitisation by skin contact.
	n cell mutagenicity classified based on ava	ilable information.	
	inogenicity classified based on ava	ilable information.	
-	oductive toxicity classified based on ava	ilable information.	
	T - single exposure classified based on ava	ilable information.	
	T - repeated exposure		
<u>Com</u>	ponents:		
Targ	ecylphosphonic acid: et Organs essment		nce or mixture is classified as specific target organ beated exposure, category 2.
•	ration toxicity classified based on ava	ilable information.	
11.2 Info	rmation on other haza	ards	
Furt	her information		
<u>Proc</u> Rem		: No data ava	ailable
Com	ponents:		
dod e Rem	ecylphosphonic acid: arks	: No data ava	ailable

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version 4.0	Revision Date: 30.01.2024		DS Number:)2000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014
4.0	30.01.2024		12000021561	Date of first issue. 10.00.2014
SECTIC	N 12: Ecological info	orma	ation	
12.1 Tox	icity			
Com	<u>iponents:</u>			
•	/(oxy-1,2-ethanediyl), .a/ l-2-(hydroxymethyl)-1,3	-		a[(1-oxo-2-propenyl)oxy]-, ether with 2-
	toxicology Assessment onic aquatic toxicity		Harmful to aqu	atic life with long lasting effects.
dod	ecylphosphonic acid:			
	toxicology Assessment te aquatic toxicity		Harmful to aqu	atic life.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Glycerol, propoxylated, esters with acrylic acid:Partition coefficient: n-
octanol/water:log Pow: 2.52 (23 °C)Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological	:	An environmental hazard cannot be excluded in the event of
information		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version 4.0	Revision Date: 30.01.2024	SDS Number: 102000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014
<u>Com</u>	oonents:		
Glyce	erol, propoxylated, e	sters with acrylic a	sid:
	ional ecological nation	: No data avail	able
dode	cylphosphonic acid:	:	
	ional ecological nation	unprofession	ental hazard cannot be excluded in the event of al handling or disposal. uatic life with long lasting effects.
SECTIO	N 13: Disposal con	aiderationa	

SECTION 13: Disposal considerations

European Waste Catalogue	:	08 03 12 - waste ink containing dangerous substances
13.1 Waste treatment methods		
Product	:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper ship	ping name	
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version 4.0	Revision Date: 30.01.2024	SDS Number: 102000021561	Print Date: 15.04.2024 Date of first issue: 16.06.2014
ADR		: Not regulated as	a dangerous good
IMDG		0	a dangerous good
IATA (Cargo)		: Not regulated as	a dangerous good
IATA (Passenger)		: Not regulated as	a dangerous good
14.5 Environmental hazards Not regulated as a dangerous go		is good	
14.6 Spe	cial precautions for us	er	
Rem	arks	: Not classified as regulations.	dangerous in the meaning of transport

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) Poly(oxy-1,2-ethanediyl), .alpha hydroomega[(1-oxo-2- propenyl)oxy]-, ether with 2-ethyl-2- (hydroxymethyl)-1,3-propanediol (3:1) (Number on list 3) Glycerol, propoxylated, esters with acrylic acid (Number on list 3)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version	Revision Date:	SDS Number:	Print Date: 15.04.2024
4.0	30.01.2024	102000021561	Date of first issue: 16.06.2014

SECTION 16: Other information

Full text of H-Statements		
H228	:	Flammable solid.
H314	:	Causes severe skin burns and eye damage.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	าร	
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Sol.	:	Flammable solids
Skin Corr.	:	Skin corrosion
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -

according to Regulation (EC) No. 1907/2006



Rotovario UV 900 114 Silver

Version	Revision Date:	SDS Number:	Print Date: 15.04.2024
4.0	30.01.2024	102000021561	Date of first issue: 16.06.2014

Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the m	ixture:	Classification procedure:
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN