according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SHINEDECOR 3500 NEU

Product code : 023844HD0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Colorant; Printing ink related material; Printing ink, Colouring

Substance/Mixture agents, dyes

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person

responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a dangerous substance according to GHS.

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components	040 11	O	
Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 25 - < 50
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Phosphoric acid, C11-14-isoalkyl	154518-38-4	Skin Irrit. 2; H315	>= 3 - < 10
esters, C13-rich	(52933-07-0)	Eye Dam. 1; H318	
,	,	Aquatic Chronic 2;	
	01-2119976356-25	H411	
2-dimethylaminoethanol	108-01-0	Flam. Liq. 3; H226	>= 0.1 - < 1
,		Acute Tox. 4; H302	
	203-542-8	Acute Tox. 3; H331	
	603-047-00-0	Acute Tox. 4; H312	
		Skin Corr. 1B; H314	
		Eye Dam. 1; H318	
		STOT SE 3; H335	
		(Respiratory system)	
		(Respiratory system)	
		specific concentration	
		limit	
		STOT SE 3; H335	
		>= 5 %	
		STOT SE 3; H335 >= 5 %	
		<i>>=</i> 5 %	
Alcohols, C11-14-iso-, C13-rich	68526-86-3	Aquatic Acute 1;	>= 0.25 - < 1
Alconois, C11-14-150-, C13-11011	00020-00-3	H400)= 0.20 · < 1
	271-235-6	1 1400	
		M Factor (A outo	
	01-2119454259-32	M-Factor (Acute	
		aquatic toxicity): 1	
		M-Factor (Chronic	
		aquatic toxicity): 1	

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

 Version
 Revision Date:
 SDS Number:
 Print Date: 26.04.2023

 6.0
 12.02.2023
 102000029533
 Date of first issue: 08.05.2018

1,2-benzisothiazol-3(2H)-one	2634-33-5	Acute Tox. 4; H302	>= 0.0025 - <
	220-120-9 613-088-00-6	Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 ——————————————————————————————————	0.025
		Skin Sens. 1; H317 >= 0.05 %	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1B; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Skin Sens. 1; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 % Skin Corr. 1C; H314 >= 0.6 % Skin Corr. 1C; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Skin Irrit. 2; H315	>= 0.0002 - < 0.0015

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

 Version
 Revision Date:
 SDS Number:
 Print Date: 26.04.2023

 6.0
 12.02.2023
 102000029533
 Date of first issue: 08.05.2018

Skin Sens. 1A; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 %

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Do not leave the victim unattended.

If inhaled : Remove to fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand

ABC powder

Foam

Unsuitable extinguishing

Water

media

Carbon dioxide (CO2)

according to Regulation (EC) No. 1907/2006

C ECKART

SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water

courses or the soil.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use

explosion-proof equipment. Store in original container.

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

Electrical installations / working materials must comply with

the technological safety standards.

Advice on common storage : Do not store near acids.

Do not store together with oxidizing and self-igniting products. Keep away from oxidizing agents and strongly acid or alkaline

materials.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

No materials to be especially mentioned.

Further information on storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
aluminium powder	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
(stabilised)				
		TWA (Respirable	4 mg/m3	GB EH40
		fraction)		
		TWA (inhalable	10 mg/m3	GB EH40
		dust)		
	Further information: For the purposes of these limits, respirable dust and			
	inhalable dust are those fractions of airborne dust which will be collected			
	when sampling is undertaken in accordance with the methods described in			
	MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a			
	substance hazardous to health includes dust of any kind when present at a			
	concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of			
	inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that			
	any dust will be subject to COSHH if people are exposed to dust above these			
	levels. Some dusts have been assigned specific WELs and exposure to these			

any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

	contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
	a rigule tillee	TWA (Respirable dust)	4 mg/m3	GB EH40
2-	inhalable dust when samplin MDHS14/4 Ge respirable, the substance has concentration inhalable dust any dust will be levels. Some must comply particles of a particular part response that distinguishes and 'respirable material that e available for ot the fraction definitions and contain comply should be corresponded.	ration: For the purpo a are those fractions ag is undertaken in a general methods for so pracic and inhalable a gracic and inhalable as in air equal to or great for 4 mg.m-3 8-hour be subject to COSHH dusts have been ass with the appropriate a wide range of sizes. icle after entry into the it elicits, depend on two size fractions for et., Inhalable dust appendents the nose and deposition in the respondents that penetrates to the dexplanatory material onents that have the mplied with., Where respondents	ses of these limits, respirable of airborne dust which will be coordance with the methods ampling and gravimetric analyserosols., The COSHH definitudes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to dustigned specific WELs and explimits., Most industrial dusts and the human respiratory system the nature and size of the partimit-setting purposes termes approximates to the fraction of mouth during breathing and in iratory tract. Respirable dust he gas exchange region of the later given in MDHS14/4., Wir own assigned WEL, all the mospecific short-term exposure limit should be use 2 ppm	e collected described in lysis or ition of a present at a TWA of means that is tabove these contain and fate of any and the body article. HSE is d'inhalable airborne is therefore approximates e lung. Fuller Where dusts are limit is listed,
dimethylaminoetha	108-01-0	IVVA	2 ppm 7.4 mg/m3	GB EH40
1101		STEL	6 ppm 22 mg/m3	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health	Value
			effects	
aluminium powder	Workers	Inhalation	Long-term systemic	3.72 mg/m3
(stabilised)			effects	
	Workers	Inhalation	Long-term local	3.72 mg/m3
			effects	
	Consumers	Oral	Long-term systemic	3.95 mg/kg
			effects	
Phosphoric acid, C11-	Workers	Inhalation	Long-term systemic	34.94 mg/m3
14-isoalkyl esters,			effects	
C13-rich				
	Workers	Skin contact	Long-term systemic	100.13 mg/kg
			effects	
	Consumers	Inhalation	Long-term systemic	10.43 mg/m3
			effects	
	Consumers	Skin contact	Long-term systemic	60.08 mg/kg

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

	1		effects	
	Consumers	Ingestion	Long-term systemic effects	6.01 mg/kg
2,2',2"-nitrilotriethanol	Workers	Inhalation	Long-term local effects	1 mg/m3
	Workers	Skin contact	Long-term systemic effects	7.5 mg/kg
	Workers	Skin contact	Long-term local effects	0.14 mg/cm2
	Consumers	Inhalation	Long-term local effects	0.4 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3.3 mg/kg
	Consumers	Skin contact	Long-term systemic effects	2.66 mg/kg
	Consumers	Skin contact	Long-term local effects	0.07 mg/cm2
2- dimethylaminoethanol	Workers	Inhalation	long term – systemic and local effects	1.76 mg/m3
	Workers	Inhalation	Acute systemic effects	5.28 mg/m3
	Workers	Inhalation	Acute local effects	13.53 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.25 mg/kg
	Workers	Skin contact	Acute systemic effects	1.2 mg/kg
	Workers	Skin contact	Acute local effects	0.080 mg/cm2
	Consumers	Inhalation	Long-term systemic effects	0.43 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0.126 mg/kg
Alcohols, C11-14-iso-, C13-rich	Workers	Skin contact	Long-term systemic effects	416.67 mg/kg
	Workers	Inhalation	Long-term systemic effects	293.86 mg/m3
	Consumers	Skin contact	Long-term systemic effects	250 mg/kg
	Consumers	Inhalation	Long-term systemic effects	89.96 mg/m3
	Consumers	Ingestion	Long-term systemic effects	25 mg/kg
1,2-benzisothiazol- 3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.966 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0.345 mg/kg
reaction mass of 5- chloro-2-methyl-2H-	Workers	Inhalation	Long-term local effects	0.02 mg/m3

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1)				
	Workers	Inhalation	Acute local effects	0.04 mg/m3
	Consumers	Inhalation	Long-term local effects	0.02 mg/m3
	Consumers	Inhalation	Acute local effects	0.04 mg/m3
	Consumers	Ingestion	Long-term local effects	0.090 mg/kg
	Consumers	Ingestion	Acute local effects	0.11 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	Fresh water	0.00631 mg/l
	Fresh water sediment	0.113 mg/kg
	Intermittent water release	0.0631 mg/l
	Marine water	0.000631 mg/l
	Marine sediment	0.0113 mg/kg
	STP	10 mg/l
	Soil	0.0188 mg/kg
2,2',2''-nitrilotriethanol	Soil	0.151 mg/kg
	Fresh water	0.32 mg/l
	Fresh water sediment	1.7 mg/kg
	clarification plant	10 mg/l
	Marine water	0.032 mg/l
	Marine sediment	0.17 mg/kg
2-dimethylaminoethanol	Fresh water	0.0661 mg/l
	Marine water	0.004 mg/l
	Intermittent Release	661 µg/l
	STP	10 mg/l
	Fresh water sediment	0.246 mg/kg dry
		weight (d.w.)
	Soil	0.0177 mg/kg
	Marine sediment	0.015 mg/kg dry
		weight (d.w.)
Alcohols, C11-14-iso-, C13-rich	STP	105.3 mg/l
	Fresh water sediment	115.6 mg/kg
	Soil	93.7 mg/kg
1,2-benzisothiazol-3(2H)-one	Fresh water	0.00403 mg/l
	Marine water	0.000403 mg/l
	STP	0.00103 mg/l
	Intermittent water release	0.0011 mg/l
	Intermittent Release	0.00011 mg/l
	Fresh water sediment	0.0499 mg/kg
	Marine sediment	0.00499 mg/kg
	Soil	3 mg/kg
reaction mass of 5-chloro-2-	Fresh water	0.00339 mg/l

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)		
	Intermittent water release	0.00339 mg/l
	Marine water	0.00339 mg/l
	Intermittent Release	0.00339 mg/l
	STP	0.23 mg/l
	Soil	0.0471 mg/kg
	Fresh water sediment	0.027 mg/kg
	Marine sediment	0.027 mg/kg
	Soil	0.01 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Goggles

Safety glasses

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of

contact). Please observe the instructions regarding

permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace

should be discussed with the producers of the protective

gloves.

Skin and body protection

Protective suit

Respiratory protection

Use suitable breathing protection if workplace concentration

requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : No data available

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

102000029533 Date of first issue: 08.05.2018 6.0 12.02.2023

Flammability No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

flammability limit

Flash point : > 100 °C

Auto-ignition temperature : Not relevant

Decomposition temperature No data available

μq 6 - 8

Concentration: 100 %

: No data available Viscosity, kinematic

No data available Water solubility

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : No data available

Relative density : No data available

Density No data available

Relative vapour density No data available

Particle Size Distribution : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

No hazards to be specially mentioned.

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

2-dimethylaminoethanol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term

inhalation

Acute dermal toxicity : Assessment: The component/mixture is minimally toxic after

single contact with skin.

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity : LC50 (Rat): 0.4 mg/l

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The component/mixture is highly toxic after short

term inhalation.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : Assessment: The component/mixture is toxic after single

ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short

term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is highly toxic after

single contact with skin.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : No skin irritation

Remarks : Based on available data, the classification criteria are not met.

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Result : Skin irritation

2-dimethylaminoethanol:

Result : Corrosive after 3 minutes to 1 hour of exposure

1,2-benzisothiazol-3(2H)-one:

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

Remarks : Based on available data, the classification criteria are not met.

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Result : Corrosive

2-dimethylaminoethanol:

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

Result : Corrosive

1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

2-dimethylaminoethanol:

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with respiratory tract

irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

11.2 Information on other hazards

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 6.31 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (algae): 150 mg/l Exposure time: 72 h

2-dimethylaminoethanol:

Toxicity to daphnia and other :

aquatic invertebrates

(Daphnia (water flea)): 98.77 mg/l

Toxicity to algae/aquatic : (Chlorella pyrenoidosa (algae)): 35 mg/l

plants Exposure time: 72 h

Alcohols, C11-14-iso-, C13-rich:

M-Factor (Short-term (acute) : 1

aquatic hazard)

M-Factor (Long-term : 1

(chronic) aquatic hazard)

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

1,2-benzisothiazol-3(2H)-one:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

M-Factor (Short-term (acute) : 100

aquatic hazard)

M-Factor (Long-term : 100

(chronic) aquatic hazard)

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological :

information

: No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents

16 / 20

or other dangerous substances

according to Regulation (EC) No. 1907/2006

C ECKART

SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

13.1 Waste treatment methods

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : UN 9999

Not permitted for transport

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not permitted for transport

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good : Not regulated as a dangerous good

IATA : Not permitted for transport

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not permitted for transport

IATA (Passenger) : Not permitted for transport

14.5 Environmental hazards

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Due to the risk of hydrogen development we recommend to

refrain from airfreighting this/these product(s).

Not classified as dangerous in the meaning of transport

regulations.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

according to Regulation (EC) No. 1907/2006

C ECKART

SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be

considered:

aluminium powder (stabilised)

(Number on list 40)

Phosphoric acid, C11-14-isoalkyl esters, C13-rich (Number on list 3) 2-dimethylaminoethanol (Number on

list 3)

Alcohols, C11-14-iso-, C13-rich

(Number on list 3)

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

Not applicable

Not applicable

Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H228 : Flammable solid.
H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

 Version
 Revision Date:
 SDS Number:
 Print Date: 26.04.2023

 6.0
 12.02.2023
 102000029533
 Date of first issue: 08.05.2018

H331 : Toxic if inhaled.

H335 : May cause respiratory irritation. H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam.

Serious eye damage
Flam. Liq.

Flammable liquids
Flam. Sol.

Skin Corr.

Skin corrosion
Skin Irrit.

Skin Sens.

Serious eye damage
Flammable solids
Skin corrosion
Skin irritation
Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail: SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern: TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals

according to Regulation (EC) No. 1907/2006



SHINEDECOR 3500 NEU

Version Revision Date: SDS Number: Print Date: 26.04.2023

6.0 12.02.2023 102000029533 Date of first issue: 08.05.2018

Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN