

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SHINEDECOR 9161  
Product code : 052655HD0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address of person responsible for the SDS : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3      H226: Flammable liquid and vapour.  
Eye irritation, Category 2      H319: Causes serious eye irritation.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

Signal word	:	Warning	
Hazard statements	:	H226 H319	Flammable liquid and vapour. Causes serious eye irritation.
Precautionary statements	:	<b>Prevention:</b> P210  P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
		<b>Response:</b> P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
		P337 + P313	If eye irritation persists: Get medical advice/ attention.
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
		<b>Storage:</b> P403 + P235	Store in a well-ventilated place. Keep cool.

### Additional Labelling

EUH208      Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGULATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5  231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 20 - < 25
propan-2-ol	67-63-0	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 10 - < 20

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version  
9.0

Revision Date:  
17.08.2023

SDS Number:  
102000005644

Print Date: 16.04.2024  
Date of first issue: 02.10.2015

	200-661-7 603-117-00-0 01-2119457558-25	STOT SE 3; H336 (Central nervous system)	
ethanol	64-17-5  200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	$\geq 1 - < 10$
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9  918-481-9 01-2119457273-39	Asp. Tox. 1; H304 EUH066	$\geq 1 - < 10$
1,2-benzisothiazol-3(2H)-one	2634-33-5  220-120-9 613-088-00-6	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411  specific concentration limit Skin Sens. 1; H317 $\geq 0.05$ % Skin Sens. 1; H317 $\geq 0.05$ %	$\geq 0.0025 - < 0.025$
reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2- methyl-2H-isothiazol-3-one (3:1)	55965-84-9  613-167-00-5	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1B; H314 $\geq 0.6$ % Skin Irrit. 2; H315 0.06 - < 0.6 %	$\geq 0.0002 - < 0.0015$

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version  
9.0

Revision Date:  
17.08.2023

SDS Number:  
102000005644

Print Date: 16.04.2024  
Date of first issue: 02.10.2015

			Eye Irrit. 2; H319 0.06 - < 0.6 % Skin Sens. 1; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 % Skin Corr. 1C; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % STOT RE 2; H319 0.06 - < 0.6 % Skin Sens. 1A; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 %	
--	--	--	--	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
9.0	17.08.2023	102000005644	Date of first issue: 02.10.2015

---

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
ABC powder  
Foam

Unsuitable extinguishing media : Water  
Carbon dioxide (CO<sub>2</sub>)  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
9.0	17.08.2023	102000005644	Date of first issue: 02.10.2015

---

### 6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

explosion-proof equipment. Store in original container.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Advice on common storage : Do not store near acids.  
Do not store together with oxidizing and self-igniting products. Keep away from oxidizing agents and strongly acid or alkaline materials.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable fraction)	4 mg/m <sup>3</sup>	GB EH40
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version  
9.0

Revision Date:  
17.08.2023

SDS Number:  
102000005644

Print Date: 16.04.2024  
Date of first issue: 02.10.2015

		available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m <sup>3</sup>	GB EH40
		STEL	500 ppm 1,250 mg/m <sup>3</sup>	GB EH40
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m <sup>3</sup>	GB EH40
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
silicon dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m <sup>3</sup> (Silica)	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these			



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version  
9.0

Revision Date:  
17.08.2023

SDS Number:  
102000005644

Print Date: 16.04.2024  
Date of first issue: 02.10.2015

<p>must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
	TWA (Respirable dust)	2.4 mg/m <sup>3</sup> (Silica)	GB EH40
<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
propan-2-ol	Workers	Skin contact	Long-term systemic effects	888 mg/kg
	Workers	Inhalation	Long-term systemic effects	500 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version  
9.0

Revision Date:  
17.08.2023

SDS Number:  
102000005644

Print Date: 16.04.2024  
Date of first issue: 02.10.2015

	Consumers	Ingestion	Long-term systemic effects	26 mg/kg
	Consumers	Skin contact	Long-term systemic effects	319 mg/kg
	Consumers	Inhalation	Long-term systemic effects	89 mg/m3
ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m3
	Workers	Inhalation	Long-term local effects	1900 mg/m3
	Workers	Skin contact	Long-term systemic effects	343 mg/kg
	Consumers	Inhalation	Long-term systemic effects	114 mg/m3
	Consumers	Skin contact	Long-term systemic effects	206 mg/kg
	Consumers	Ingestion	Long-term systemic effects	87 mg/kg
silicon dioxide	Workers	Inhalation	Long-term systemic effects	4 mg/m3
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	Workers	Inhalation	Acute systemic effects	1500 mg/m3
	Workers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Ingestion	Long-term systemic effects	300 mg/kg
	Consumers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
1,2-benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.966 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0.345 mg/kg
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Workers	Inhalation	Long-term local effects	0.02 mg/m3
	Workers	Inhalation	Acute local effects	0.04 mg/m3
	Consumers	Inhalation	Long-term local effects	0.02 mg/m3
	Consumers	Inhalation	Acute local effects	0.04 mg/m3
	Consumers	Ingestion	Long-term local	0.090 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version  
9.0

Revision Date:  
17.08.2023

SDS Number:  
102000005644

Print Date: 16.04.2024  
Date of first issue: 02.10.2015

			effects	
	Consumers	Ingestion	Acute local effects	0.11 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
propan-2-ol	Soil	28 mg/kg
	Fresh water	140.9 mg/l
	Fresh water sediment	552 mg/kg
	Marine water	140.9 mg/l
	Marine sediment	552 mg/kg
	STP	2251 mg/l
ethanol	Fresh water	0.96 mg/l
	Marine water	0.79 mg/l
	Intermittent water release	2.75 mg/l
	STP	580 mg/l
	Fresh water sediment	3.6 mg/kg
	Marine sediment	2.9 mg/kg
1,2-benzisothiazol-3(2H)-one	Soil	0.63 mg/kg
	Secondary Poisoning	380 mg/kg
	Fresh water	0.00403 mg/l
	Marine water	0.000403 mg/l
	STP	0.00103 mg/l
	Intermittent water release	0.0011 mg/l
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Intermittent Release	0.00011 mg/l
	Fresh water sediment	0.0499 mg/kg
	Marine sediment	0.00499 mg/kg
	Soil	3 mg/kg
	Fresh water	0.00339 mg/l
	Intermittent water release	0.00339 mg/l
	Marine water	0.00339 mg/l
	Intermittent Release	0.00339 mg/l
	STP	0.23 mg/l
	Soil	0.0471 mg/kg
	Fresh water sediment	0.027 mg/kg
	Marine sediment	0.027 mg/kg
	Soil	0.01 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Goggles  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
9.0	17.08.2023	102000005644	Date of first issue: 02.10.2015

---

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : 82 - 83 °C (1,013 hPa)

Flammability : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 31 °C

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

---

pH : 6 - 8  
Concentration: 100 %

Viscosity  
Viscosity, kinematic : No data available

Flow time : 20 - 60 s  
Cross section: 4 mm

Solubility(ies)  
Water solubility : insoluble  
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available  
Vapour pressure : No data available

Relative density : No data available

Density : 1.2 g/cm<sup>3</sup>

Relative vapour density : No data available

Particle Size Distribution : No data available

### 9.2 Other information

Flammability (liquids) : Flammable liquids

Self-ignition : No data available

Miscibility with water : immiscible

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
9.0	17.08.2023	102000005644	Date of first issue: 02.10.2015

---

Conditions to avoid : Do not allow evaporation to dryness.  
Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents

### 10.6 Hazardous decomposition products

This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **aluminium powder (stabilised):**

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **propan-2-ol:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

##### **ethanol:**

Acute oral toxicity : LD50 (Rat, male and female): 10,470 mg/kg  
Method: OECD Test Guideline 401  
Acute inhalation toxicity : LC50 (Rat, male and female): 124.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

##### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): Test atmosphere: vapour  
Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

---

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### **1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 0.4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The component/mixture is highly toxic after short term inhalation.

### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is highly toxic after single contact with skin.

### **Skin corrosion/irritation**

Not classified based on available information.

### **Product:**

Remarks : May cause skin irritation in susceptible persons.

### **Components:**

#### **ethanol:**

Result : No skin irritation

Remarks : Based on available data, the classification criteria are not met.

### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Result : Repeated exposure may cause skin dryness or cracking.

### **1,2-benzisothiazol-3(2H)-one:**

Result : Skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Product:**

Remarks : May cause irreversible eye damage.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

---

### Components:

#### **propan-2-ol:**

Result : Eye irritation

#### **ethanol:**

Result : Eye irritation  
Remarks : Based on available data, the classification criteria are not met.

#### **1,2-benzisothiazol-3(2H)-one:**

Result : Corrosive

#### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Result : Corrosive

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### Components:

#### **1,2-benzisothiazol-3(2H)-one:**

Result : May cause sensitisation by skin contact.

### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Germ cell mutagenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Carcinogenicity**

Not classified based on available information.

### Components:

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

---



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

---

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

Not classified based on available information.

### **Components:**

#### **propan-2-ol:**

Assessment : May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### **Further information**

#### **Product:**

Remarks : Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

#### **1,2-benzisothiazol-3(2H)-one:**

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

#### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

M-Factor (Short-term (acute) aquatic hazard) : 100

M-Factor (Long-term (chronic) aquatic hazard) : 100

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

---

### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.  
Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

#### Product:

Additional ecological information : No data available

#### Components:

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles  
European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
Contaminated packaging : Empty remaining contents.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

---

Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADR** : Not regulated as a dangerous good  
**IMDG** : UN 1263  
**IATA** : UN 1263

#### 14.2 UN proper shipping name

**ADR** : Not regulated as a dangerous good  
**IMDG** : PAINT  
**IATA** : Paint

#### 14.3 Transport hazard class(es)

**ADR** : Not regulated as a dangerous good  
Class                                  Subsidiary risks  
**IMDG** : 3  
**IATA** : 3

#### 14.4 Packing group

**ADR** : Not regulated as a dangerous good  
**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : Transport in accordance with 2.3.2.5 of the IMDG Code.

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : 3

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : 3

#### 14.5 Environmental hazards

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

---

**ADR** : Not regulated as a dangerous good

**IMDG**

Marine pollutant : no

### 14.6 Special precautions for user

Remarks : IMDG: Classified in accordance with Chapter 2.3.2.5 IMDG-Code  
ADR: Classified in accordance with Chapter 2.2.3.1.5.1 and 2.2.3.1.5.2 ADR  
Due to the risk of hydrogen development we recommend to refrain from airfreighting this/these product(s).

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3  
aluminium powder (stabilised)  
(Number on list 40)  
propan-2-ol (Number on list 3)  
ethanol (Number on list 3)  
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha (Number on list 3)  
Solvent naphtha (petroleum), light arom. (Number on list 3)

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version 9.0      Revision Date: 17.08.2023      SDS Number: 102000005644      Print Date: 16.04.2024  
Date of first issue: 02.10.2015

---

### 15.2 Chemical safety assessment

No data available

---

### SECTION 16: Other information

#### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H228 : Flammable solid.  
H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H310 : Fatal in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H336 : May cause drowsiness or dizziness.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Flam. Sol. : Flammable solids  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT SE : Specific target organ toxicity - single exposure  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9161

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
9.0	17.08.2023	102000005644	Date of first issue: 02.10.2015

Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Eye Irrit. 2	H319

#### Classification procedure:

Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN