according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version	Revision Date:	SDS Number:	Print Date: 16.02.2023
2.0	14.02.2023	102000035985	Date of first issue: 07.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Trade name : SILVERSHINE Platinum Grey

Product code : 027433QQ0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	
Substance/Mixture	

: Colouring agents, pigments

1.3 Details of the supplier of the safety data sheet

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein	
Telephone	: +499152770	
Telefax	: +499152777008	
E-mail address of person responsible for the SDS	: msds.eckart@altana.com	<u>n</u>

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version 2.0	Revision Date: 14.02.2023		DS Number: 02000035985	Print Date: 16.02.2023 Date of first issue: 07.11.2022
Hazard pictograms		:		!
Signa	al word	:	Danger	
Hazard statements		:	H225 H319 H336	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements		:	Prevention: P210 P233 P261 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Avoid breathing mist or vapours. Wear protective gloves/ protective clothing/
			F200	eye protection/ face protection/ hearing protection.
			Response: P303 + P361 + P	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
			P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

propan-2-ol 1-methoxy-2-propanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components			
Chemical name	CAS-No. EC-No.	ClassificationREGUL ATION (EC) No	Concentration (% w/w)
	Index-No.	1272/2008	· · · ·
	Registration number		
propan-2-ol	67-63-0	Flam. Liq. 2; H225	>= 50 - <= 100
		Eye Irrit. 2; H319	
	200-661-7	STOT SE 3; H336	
	603-117-00-0	(Central nervous	
	01-2119457558-25	system)	

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version 2.0	Revision Date: 14.02.2023	SDS Number: 102000035985	Print Date: 16.02.2023 Date of first issue: 07.11.2022	2
alumi	nium powder (stabilised)	231-072-3 013-002-00-1	Flam. Sol. 1; H228	>= 20 - < 25
1-me	thoxy-2-propanol	01-2119529243 107-98-2 203-539-1 603-064-00-3 01-2119457435	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
	f phosphoric acid I3/00/2008.0040, Germa	Not Assigned	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move the victim to fresh air.
		Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	Remove to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	:	Wash off immediately with soap and plenty of water.
		If skin irritation persists, call a physician. If on clothes, remove clothes.
In case of eye contact	:	Immediately flush eye(s) with plenty of water.
		Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks	:	Causes serious eye irritation.
		May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version	Revision Date:	SDS Number:	Print Date: 16.02.2023
2.0	14.02.2023	102000035985	Date of first issue: 07.11.2022

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media :	Dry sand Special powder against metal fire
Unsuitable extinguishing : media	Water Foam Carbon dioxide (CO2) ABC powder
	High volume water jet
5.2 Special hazards arising from the	e substance or mixture
Specific hazards during : firefighting	Contact with water liberates extremely flammable gas (hydrogen).
5.3 Advice for firefighters	
Special protective equipment : for firefighters	Use personal protective equipment.
	Wear self-contained breathing apparatus for firefighting if necessary.
Further information :	For safety reasons in case of fire, cans should be stored separately in closed containments. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Evacuate personnel to safe areas.
	Use personal protective equipment.
	Use personal protective equipment.
	Avoid dust formation.
	Avoid breathing dust.
	Remove all sources of ignition.

6.2 Environmental precautions

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version 2.0	Revision Date: 14.02.2023		DS Number: 02000035985	Print Date: 16.02.2023 Date of first issue: 07.11.2022			
Environmental precautions		:	The product should not be allowed to enter drains, water courses or the soil.				
			Prevent further le	rom entering drains. akage or spillage if safe to do so. taminates rivers and lakes or drains inform ities.			
6.3 Method	Is and material for co	ntai	inment and cleani	ng up			
Metho	ds for cleaning up	:	Soak up with iner	nandling equipment. t absorbent material (e.g. sand, silica gel, ersal binder, sawdust).			
			vacuum cleaner o disposal accordin	and then collect with an electrically protected or by wet-brushing and place in container for g to local regulations (see section 13). closed containers for disposal.			

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling Keep away from heat and sources of ignition. 1 Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Advice on protection against : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use fire and explosion explosion-proof equipment. Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from open flames, hot surfaces and sources of ignition.

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version 2.0	Revision Date: 14.02.2023		DS Number: 2000035985	Print Date: 16.02.2023 Date of first issue: 07.11.2022
Hyg	Hygiene measures		•	not eat or drink. When using do not smoke. efore breaks and at the end of workday.
7.2 Cond	litions for safe storage,	inc	luding any inco	mpatibilities
	uirements for storage as and containers	:	cool, well-vent	al container. Keep containers tightly closed in a lated place. Keep container closed when not in y from sources of ignition - No smoking.
			ventilated plac installations / v	eep container tightly closed in a dry and well- e. Observe label precautions. Electrical vorking materials must comply with the afety standards.
	Further information on storage conditions		Protect from h	umidity and water. Do not allow to dry.
Adv	ice on common storage	:	Never allow pr storage. Keep away fro	gether with oxidizing and self-igniting products. oduct to get in contact with water during m oxidizing agents, strongly alkaline and naterials in order to avoid exothermic reactions.
	her information on age stability	:	No decomposi	ion if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis			
		of exposure)					
propan-2-ol	67-63-0	TWA	400 ppm	GB EH40			
propari 2 or	0.000		999 mg/m3	00 2000			
		STEL	500 ppm	GB EH40			
		SIEL		GD EI140			
			1,250 mg/m3				
aluminium powder	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40			
(stabilised)		. ,	-				
		TWA (Respirable	4 mg/m3	GB EH40			
		fraction)	3.				
		TWA (inhalable	10 mg/m3	GB EH40			
		dust)					
	Further inform	nation: For the purpo	ses of these limits, respirable	e dust and			
	inhalable dust are those fractions of airborne dust which will be collected						
	when sampling is undertaken in accordance with the methods described in						
		MDHS14/4 General methods for sampling and gravimetric analysis or					
	respirable, the	pracic and inhalable	aerosols., The COSHH defir	ition of a			

according to Regulation (EC) No. 1907/2006



ersion 0	Revision Date: 14.02.2023	SDS Number: 102000035985	Print Date: 16.02.2023 Date of first issue: 07.11.2	2022
	conce inhala any c levels must partic partic respondistin and 'n mate availa to the definit conta shoul	entration in air equal to able dust or 4 mg.m-3 & ust will be subject to C . Some dusts have be comply with the approp les of a wide range of ular particle after entry nse that it elicits, deper guishes two size fraction espirable'., Inhalable of ial that enters the nose able for deposition in the fraction that penetrate tions and explanatory is in components that ha d be complied with., W	alth includes dust of any kind or greater than 10 mg.m-3 8 8-hour TWA of respirable dus OSHH if people are exposed en assigned specific WELs a priate limits., Most industrial of sizes. The behaviour, deposit into the human respiratory s end on the nature and size of ons for limit-setting purposes lust approximates to the fract e and mouth during breathing the respiratory tract. Respirable es to the gas exchange regior material are given in MDHS14 ve their own assigned WEL, a /here no specific short-term e	-hour TWA of to dust above thes nd exposure to the dusts contain tion and fate of any ystem, and the bod the particle. HSE termed 'inhalable' ion of airborne and is therefore e dust approximate n of the lung. Fuller 4/4., Where dusts all the relevant limit xposure limit is liste
	a figu	re three times the long TWA (Respir dust)	I-term exposure limit should b rable 4 mg/m3	GB EH40
	MDH respin subst conce inhala any c levels must partic partic respon distin and 'n mate availa to the defini conta shoul	S14/4 General method able, thoracic and inha ance hazardous to hea entration in air equal to able dust or 4 mg.m-3 a ust will be subject to C . Some dusts have be comply with the approp les of a wide range of ular particle after entry nse that it elicits, depe guishes two size fraction espirable'., Inhalable of ial that enters the nose able for deposition in the fraction that penetrate tions and explanatory in components that ha d be complied with., W	in in accordance with the met s for sampling and gravimetri alable aerosols., The COSHH alth includes dust of any kind or greater than 10 mg.m-3 8 8-hour TWA of respirable dus COSHH if people are exposed en assigned specific WELs a priate limits., Most industrial of sizes. The behaviour, deposit into the human respiratory s and on the nature and size of ons for limit-setting purposes lust approximates to the fract e and mouth during breathing the respiratory tract. Respirable so to the gas exchange region material are given in MDHS1 ve their own assigned WEL, a there no specific short-term e pterm exposure limit should b	c analysis or definition of a when present at a -hour TWA of t. This means that to dust above thes nd exposure to the dusts contain tion and fate of any ystem, and the bod the particle. HSE termed 'inhalable' ion of airborne and is therefore e dust approximate n of the lung. Fuller 4/4., Where dusts all the relevant limit xposure limit is liste
1-meth propan	107-9 ioxy-2-		150 ppm 568 mg/m3	2000/39/EC
	Furth	er information: Identifie	es the possibility of significant	uptake through the
		TWA	100 ppm 375 mg/m3	2000/39/EC
		er information: Identifie	es the possibility of significant	uptake through the

according to Regulation (EC) No. 1907/2006



	14.02.2023	102000	035985 E	Date of	f first issue: 07.11.2022	
		T	WA) ppm 5 mg/m3	GB EH40
	1	Further informati	on: Can be abso		through the skin. The a	ssigned
				here a	are concerns that derma	al absorption
		ead to systemic				
		5	TEL) ppm) mg/m3	GB EH40
		Further informati	on: Can be abso		through the skin. The a	ssianed
	5		hose for which t		are concerns that derma	
Derive	ed No Effect Le	vel (DNEL) acco	ording to Regu	lation	(EC) No. 1907/2006:	
Subst	ance name	End Use	Exposure ro	outes	Potential health effects	Value
propa	n-2-ol	Workers	Skin contac	t	Long-term systemic effects	888 mg/kg
		Workers	Inhalation		Long-term systemic effects	500 mg/m
		Consumers	Ingestion		Long-term systemic effects	26 mg/kg
		Consumers	Skin contac	t	Long-term systemic effects	319 mg/kg
		Consumers	Inhalation		Long-term systemic effects	89 mg/m3
alumir (stabil	nium powder ised)	Workers	Inhalation		Long-term systemic effects	3.72 mg/m
		Workers	Inhalation		Long-term local effects	3.72 mg/m
		Consumers	Oral		Long-term systemic effects	3.95 mg/k
1-met	hoxy-2-propanol	Workers	Inhalation		Long-term systemic effects	369 mg/m
		Workers	Inhalation		Acute local effects	553.5 mg/
		Workers	Skin contac	t	Long-term systemic effects	50.6 mg/kg
		Consumers	Inhalation		Long-term systemic effects	43.9 mg/m
		Consumers	Skin contac	t	Long-term systemic effects	18.1 mg/kg
		Consumers	Ingestion		Long-term systemic effects	3.3 mg/kg

Substance name	Environmental Compartment	Value
propan-2-ol	Soil	28 mg/kg
	Fresh water	140.9 mg/l
	Fresh water sediment	552 mg/kg
	Marine water	140.9 mg/l
	Marine sediment	552 mg/kg
	STP	2251 mg/l
aluminium powder (stabilised)	Fresh water	0.0749 mg/l

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

ersion .0	Revision Date: 14.02.2023			Print Date: 16.02. Date of first issue	
Ì			clarification plant		20 mg/l
1-me	thoxy-2-propanol		Fresh water		10 mg/l
	, , , , , , , , , , , , , , , , , , , ,		Marine water		1 mg/l
			STP		100 mg/l
			Fresh water sedim	nent	41.6 mg/kg
			Marine sediment		4.17 mg/kg
			Soil		2.47 mg/kg
			periodical release		100 mg/l
2 Expos	sure controls				
Perso	onal protective equip	ment			
Eye/fa	ace protection	:	Tightly fitting safety Wear face-shield ar problems.		for abnormal processing
	protection aterial	:	Solvent-resistant gl	oves (butyl-rubbe	ər)
Re	emarks	:	special workplace of contact). The exact the protective glove Please observe the breakthrough time v gloves. Also take in conditions under wh danger of cuts, abra Recommended pre- washed after contact	bility and break the onditions (mecha break through tir producer and the instructions regative vhich are provide to consideration the or consideration the sion, and the con- ventive skin protect. The suitability	hrough times, and of anical strain, duration of me can be obtained from is has to be observed. arding permeability and ed by the supplier of the the specific local s used, such as the
Skin a	and body protection	:	Long sleeved clothi Safety shoes Choose body protec	ction according to	o the amount and stance at the work place.
Resp	iratory protection	:		-	workplace concentration

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

according to Regulation (EC) No. 1907/2006



	Revision Date: 14.02.2023		S Number: 2000035985	Print Date: 16.02.2023 Date of first issue: 07.11.2022
Colour		:	silver	
Odour		:	characteristic	
Odour T	hreshold	:	No data available	9
Freezing) point	:	No data available	9
Boiling p	oint/boiling range	:	82 °C	
Flamma	bility	:	The substance of category 1.	r mixture is a flammable solid with the
Upper ex flammab	xplosion limit / Upper illity limit	:	No data available)
Lower ex flammab	xplosion limit / Lower ility limit	:	No data available	2
Flash po	vint	:	12 °C	
Auto-ign	ition temperature	:	Not relevant	
Decomp	osition temperature	:	No data available	9
рН		:	substance/mixtur	e is non-soluble (in water)
Visco	osity, kinematic	:	No data available	9
Solubility Wate	y(ies) r solubility	:	insoluble	
Solut	bility in other solvents	:	No data available	9
Partition octanol/\	coefficient: n- water	:	No data available)
Vapour p	oressure	:	No data available	9
Relative	density	:	No data available	9
Density		:	No data available	9
Relative	vapour density	:	No data available	9
Partic	cle Size Distribution	:	No data available	

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version 2.0	Revision Date: 14.02.2023	SDS Nu 102000	umber: 035985	Print Date: 16.02.2023 Date of first issue: 07.11.2022
9.2 Oth	er information			
Ex	plosives		t explosive pours may for	m explosive mixture with air.
			t explosive pours may for	m explosive mixture with air.
Se	lf-ignition	: not	auto-flammal	ble
Mis	scibility with water	: imr	niscible	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
10.4 Conditions to avoid		
Conditions to avoid	:	Do not allow to dry.
		Heat, flames and sparks.
10.5 Incompatible materials		
Materials to avoid	:	Acids Bases

Oxidizing agents

Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version	Revision Date:	SDS Number:	Print Date: 16.02.2023
2.0	14.02.2023	102000035985	Date of first issue: 07.11.2022

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Not classified based on available information.	
Components:	
propan-2-ol: Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg	
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg	
aluminium powder (stabilised):Acute inhalation toxicity:LC50 (Rat): > 5 mg/lExposure time: 4 hTest atmosphere: dust/mist	
1-methoxy-2-propanol: Acute oral toxicity : LD50 (Rat): 4,016 mg/kg	
Acute inhalation toxicity : LC50 (Rat): > 25.8 mg/l Exposure time: 4 h Test atmosphere: vapour	
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg	
Skin corrosion/irritation Not classified based on available information.	
Product:Remarks: May cause skin irritation and/or dermatitis.	
Components:	
salt of phosphoric acid (72243/00/2008.0040, Germany):	
Result : Skin irritation	
Serious eye damage/eye irritation Causes serious eye irritation. <u>Product:</u>	
Remarks : May cause irreversible eye damage.	
Components:	
propan-2-ol:	

according to Regulation (EC) No. 1907/2006



Version 2.0	Revision Date: 14.02.2023	SDS Number: 102000035985	Print Date: 16.02.2023 Date of first issue: 07.11.2022		
Resu	ılt	: Eye irritatior	1		
salt	of phosphoric acid (7	2243/00/2008.0040), Germany):		
Resu	llt	: Eye irritatior	1		
Resp	piratory or skin sensi	tisation			
	sensitisation	ailable information.			
-	biratory sensitisation classified based on ava				
	n cell mutagenicity classified based on ava	ailable information.			
	inogenicity classified based on ava	ailable information.			
-	Reproductive toxicity Not classified based on available information.				
	STOT - single exposure				
	cause drowsiness or c ponents:	1122111855.			
prop	an-2-ol: ssment	: May cause o	drowsiness or dizziness.		
	T - repeated exposur				
-	ration toxicity classified based on ava	ailable information.			
11.2 Info	mation on other haz	ards			
Furtl	ner information				
<u>Prod</u> Rem		tiredness, na Concentratio narcotic effe	of overexposure may be headache, dizziness, ausea and vomiting. ons substantially above the TLV value may cause ects. ay degrease the skin.		

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version	Revision Date:	SDS Number:	Print Date: 16.02.2023
2.0	14.02.2023	102000035985	Date of first issue: 07.11.2022

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological	:	No data available
information		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version 2.0	Revision Date: 14.02.2023	SDS Number: 102000035985	Print Date: 16.02.2023 Date of first issue: 07.11.2022
SECTION	N 14: Transport inform	mation	
14.1 UN n	umber or ID number		
ADR		: UN 1263	
IMDG	ì	: UN 1263	
ΙΑΤΑ		: UN 1263	
14.2 UN p	roper shipping name		
ADR		: PAINT	
IMDG	ì	: PAINT	
ΙΑΤΑ		: Paint	
14.3 Trans	sport hazard class(es)		
		Class	Subsidiary risks
ADR		: 3	
IMDG	ì	: 3	
ΙΑΤΑ		: 3	
14.4 Pack	ing group		
Class Haza Label	el restriction code	: II : F1 : 33 : 3 : (D/E)	
Packi Label	ng group	: II : 3 : F-E, <u>S-E</u>	
	(Cargo) ng instruction (cargo ft)	: 364	
Packi	ng instruction (LQ)	: Y341 : II : 3	
Packi (pass Packi Packi Label	(Passenger) ng instruction enger aircraft) ing instruction (LQ) ing group s ronmental hazards	: 353 : Y341 : II : 3	
14.3 ENVI	uninental nazalus		

ADR



according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version 2.0	Revision Date: 14.02.2023	SDS Number: 102000035985	Print Date: 16.02.2023 Date of first issue: 07.11.2022
Enviro	onmentally hazardous	: no	
IMDG Marin	e pollutant	: no	
1/ 6 Spec	ial procautions for us	ər	

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3propan-2-ol (Number on list 3) aluminium powder (stabilised) (Number on list 40) 1-methoxy-2-propanol (Number on list 40, 3) salt of phosphoric acid (72243/00/2008.0040, Germany) (Number on list 3)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version	Revision Date:	SDS Number:	Print Date: 16.02.2023
2.0	14.02.2023	102000035985	Date of first issue: 07.11.2022

SECTION 16: Other information

Full text of H-Statements		
H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H228	:	Flammable solid.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
Full text of other abbreviation	ons	
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Flam. Sol.	:	Flammable solids
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008: CMR - Carcinogen, Mutagen or Reproductive Toxicant: DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council according to Regulation (EC) No. 1907/2006



SILVERSHINE Platinum Grey

Version	Revision Date:	SDS Number:	Print Date: 16.02.2023
2.0	14.02.2023	102000035985	Date of first issue: 07.11.2022

concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of th	e mixture:	Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN