according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ROTOVARIO UV FPG 950 214 Silver

Product code : 053610N20

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Colouring agents, pigments

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person

responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

 Version
 Revision Date:
 SDS Number:
 Print Date: 12.07.2023

 6.0
 11.07.2023
 102000021558
 Date of first issue: 04.11.2015

Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Precautionary statements : Prevention:

P261 Avoid breathing dust.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Hazardous components which must be listed on the label:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid Glycerol, propoxylated, esters with acrylic acid

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. | ClassificationREGUL | Concentration |
|----------------------------------|---------------------|---------------------|---------------|
| | EC-No. | ATION (EC) No | (% w/w) |
| | Index-No. | 1272/2008 | |
| | Registration number | | |
| Propylidynetrimethanol, | 28961-43-5 | Eye Irrit. 2; H319 | >= 25 - < 50 |
| ethoxylated, esters with acrylic | | Skin Sens. 1; H317 | |
| acid | 500-066-5 | | |
| | 01-2119489900-30 | | |
| aluminium powder (stabilised) | 7429-90-5 | Flam. Sol. 1; H228 | >= 25 - < 50 |
| | | | |
| | 231-072-3 | | |
| | 013-002-00-1 | | |
| | 01-2119529243-45 | | |
| Glycerol, propoxylated, esters | 52408-84-1 | Eye Irrit. 2; H319 | >= 1 - < 10 |
| with acrylic acid | | Skin Sens. 1; H317 | |
| | 500-114-5 | | |

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023 6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

| | 01-2119487948-12 | | |
|------------------------|------------------|---|------------|
| dodecylphosphonic acid | 5137-70-2 | Skin Corr. 1B; H314 Eye Dam. 1; H318 | >= 3 - < 5 |
| | 225-897-8 | STOT RE 2; H373 (Kidney) Aquatic Chronic 3; H412 | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

Date of first issue: 04.11.2015 6.0 11.07.2023 102000021558

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand

Special powder against metal fire

Unsuitable extinguishing

media

Water Foam

ABC powder

Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

for firefighters

Special protective equipment : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas.

> Use personal protective equipment. Remove all sources of ignition. Use personal protective equipment.

Avoid dust formation.

6.2 Environmental precautions

Environmental precautions The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

acid binder, universal binder, sawdust).

Do not flush with water.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.

Avoid dust formation.

Ensure adequate ventilation.

Avoid formation of respirable particles.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Advice on protection against

fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Avoid dust formation.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in

use. Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on storage conditions

Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-------------------------------|--|--|---|---|
| aluminium powder (stabilised) | 7429-90-5 | TWA (Inhalable) | 10 mg/m3 | GB EH40 |
| | | TWA (Respirable fraction) | 4 mg/m3 | GB EH40 |
| | | TWA (inhalable dust) | 10 mg/m3 | GB EH40 |
| | inhalable dust when samplin MDHS14/4 Go respirable, the substance has concentration inhalable dust any dust will be levels. Some must comply particles of a particular particula | are those fractions g is undertaken in acceneral methods for so pracic and inhalable acardous to health incoming are equal to or greater of a management of the subject to COSH-dusts have been asswith the appropriate wide range of sizes. In the interest of the subject to the s | ses of these limits, respirable of airborne dust which will be cordance with the methods ampling and gravimetric ana aerosols., The COSHH definitudes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to dustigned specific WELs and explimits., Most industrial dusts of the behaviour, deposition are human respiratory system the nature and size of the partimit-setting purposes terme proximates to the fraction of mouth during breathing and initiatory tract. Respirable dust he gas exchange region of the last are given in MDHS14/4., Vir own assigned WEL, all the no specific short-term exposure sexposure limit should be used a mg/m3 ses of these limits, respirable of airborne dust which will be coordance with the methods ampling and gravimetric ana aerosols., The COSHH defin | described in lysis or ition of a present at a TWA of a means that st above these contain and fate of any and the body article. HSE d'inhalable' airborne approximates e lung. Fuller Where dusts relevant limits are limit is listed, d. GB EH40 e dust and a collected described in lysis or |
| | substance na | zardous to nealth ind | cludes dust of any kind when | present at a |

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|--|-----------|-----------------|----------------------------|-------------|
| Propylidynetrimethan ol, ethoxylated, esters with acrylic acid | Workers | Inhalation | Long-term systemic effects | 16.2 mg/m3 |
| | Workers | Skin contact | Long-term systemic effects | 0.8 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 4.9 mg/m3 |
| | Consumers | Skin contact | Long-term systemic effects | 0.48 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 1.39 mg/kg |
| aluminium powder (stabilised) | Workers | Inhalation | Long-term systemic effects | 3.72 mg/m3 |
| | Workers | Inhalation | Long-term local effects | 3.72 mg/m3 |
| | Consumers | Oral | Long-term systemic effects | 3.95 mg/kg |
| Glycerol, propoxylated, esters with acrylic acid | Workers | Inhalation | Long-term systemic effects | 16.22 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 1.92 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 4.87 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 1.15 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 1.39 mg/kg |
| Fatty acids, C16-18 | Workers | Skin contact | Long-term systemic effects | 10 mg/kg |

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

| , | Workers | Inhalation | Long-term systemic effects | 17.632 mg/m3 |
|---|-----------|--------------|----------------------------|--------------|
| | Consumers | Ingestion | Long-term systemic effects | 2.5 mg/kg |
| | Consumers | Skin contact | Long-term systemic effects | 5 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 4.348 mg/m3 |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment Value | |
|--|---------------------------------|---------------|
| Propylidynetrimethanol, | Soil | 0.00644 mg/kg |
| ethoxylated, esters with acrylic | | |
| acid | | |
| | Fresh water | 0.00195 mg/l |
| | Fresh water sediment | 0.038 mg/kg |
| | STP | 10 mg/l |
| | Marine water | 0.000195 mg/l |
| | Marine sediment | 0.0038 mg/kg |
| | Intermittent Release | 0.00195 mg/l |
| | Intermittent water release | 0.0195 mg/l |
| aluminium powder (stabilised) | Fresh water | 0.0749 mg/l |
| | clarification plant | 20 mg/l |
| Glycerol, propoxylated, esters with acrylic acid | Fresh water | 0.0057 mg/l |
| | Marine water | 0.0005 mg/l |
| | Fresh water sediment | 0.0169 mg/kg |
| | Marine sediment | 0.0017 mg/kg |
| | STP | 10 mg/l |
| | Soil | 0.0011 mg/kg |

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Pasty solid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Melting point/range : > 600 °C

Boiling point/boiling range : No data available

Flammability : Combustible Solids

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : $> 100 \, ^{\circ}\text{C}$

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : No data available

Relative density : No data available

Density : 1.3 - 2.0 g/cm3

Relative vapour density : No data available

Particle Size Distribution :

9.2 Other information

Explosives : Not explosive

Flammable solids

Burning number : 1

Self-ignition : not auto-flammable

Miscibility with water : immiscible

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

No data available

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Result : Eye irritation

Remarks : Eye irritation

Components:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Result : Irritating to eyes.

Glycerol, propoxylated, esters with acrylic acid:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

Product:

Remarks : Causes sensitisation.

May cause sensitisation of susceptible persons by skin

contact.

Components:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Result : May cause sensitisation by skin contact.

Remarks : Causes sensitisation.

May cause sensitisation of susceptible persons by skin

contact.

Glycerol, propoxylated, esters with acrylic acid:

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

dodecylphosphonic acid:

Target Organs : Kidney

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : No data available

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

Components:

dodecylphosphonic acid:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

dodecylphosphonic acid:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Glycerol, propoxylated, esters with acrylic acid:

Partition coefficient: n- : log Pow: 2.52 (23 °C)

octanol/water Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological

: No data available

information

Components:

Glycerol, propoxylated, esters with acrylic acid:

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

Additional ecological

information

No data available

dodecylphosphonic acid:

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

IMDG : Not regulated as a dangerous good
 IATA (Cargo) : Not regulated as a dangerous good
 IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport

regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be

considered:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid (Number on

list 3)

aluminium powder (stabilised)

(Number on list 40)

Glycerol, propoxylated, esters with acrylic acid (Number on list 3)

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

15.2 Chemical safety assessment

No data available

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid.

H314 : Causes severe skin burns and eye damage.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Sol. : Flammable solids
Skin Corr. : Skin corrosion
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -

according to Regulation (EC) No. 1907/2006



ROTOVARIO UV FPG 950 214 Silver

Version Revision Date: SDS Number: Print Date: 12.07.2023

6.0 11.07.2023 102000021558 Date of first issue: 04.11.2015

Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method

Eye Irrit. 2 H319 Based on product data or assessment

Skin Sens. 1 H317 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN