Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0

Revision Date 30.01.2024

Print Date 01.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	ROTOSTAR	UV FP	66-40501	Silver
Material number	:	053354U20			

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company	: ECKART GmbH
	Guentersthal 4
	91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address	: msds.eckart@altana.com
Responsible/issuing person	

1.4 Emergency telephone number

NCEC: (contract no.: ECKART29003-NCEC) +44 1235 239671 (Middle East/Africa, call and response in your language) +1 215 207 0061 (Americas, call and response in your language) +65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Serious eye damage/eye irritation, Category 2A, H319 Skin sensitisation, Category 1, H317 Reproductive toxicity, Category 2, H361d


Page 1 / 20	10200000366	A member of C ALTANA
-------------	-------------	-----------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

ersion 12.0		Revision Date 30.01.2024	Print Date 01.02.202
		Long-term (chronic) aquatic haza	ard, Category 2, H411
GHS-Labelling			
Symbol(s)	:		
Signal word	:	Warning	
Hazard statements	:	H317: May cause an allergic skir H319: Causes serious eye irritati H361d: Suspected of damaging H411: Toxic to aquatic life with lo	on. the unborn child.
Precautionary statements	:	use. P261 Avoid breathing mist or v P264 Wash skin thoroughly af P272 Contaminated work cloth of the workplace. P273 Avoid release to the env P280 Wear protective gloves/ protection/ face protection/ heari Response: P302 + P352 IF ON SKIN: Wa P305 + P351 + P338 IF IN EY water for several minutes. Remo and easy to do. Continue rinsing P318 IF exposed or concerned P333 + P317 If skin irritation of help.	ter handling. hing should not be allowed out ironment. protective clothing/ eye ng protection. ash with plenty of water. /ES: Rinse cautiously with ve contact lenses, if present
age 2 / 20		10200000366	A member of C ALTANA



CECKART

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification Poly(oxy-1,2-ethanediyl), .alphahydro- .omega[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3- propanediol (3:1)	CAS-No. 28961-43-5
Bisphenol A epoxy acrylate	55818-57-0
ethyl phenyl(2,4,6-	84434-11-7
trimethylbenzoyl)phosphinate	
1-isopropyl-2,2-dimethyltrimethylene	6846-50-0
diisobutyrate	
Propoxylated neopentyl glycol diacrylate	84170-74-1
esters	
2-Propenoic acid, ester with C12-16-alkyl	68071-40-9
glycidyl ether	
Glycerol, propoxylated, esters with acrylic	52408-84-1
acid	

SECTION 3: Composition/information on ingredients

:

Substance No.

Hazardous components

Chemical name	CAS-No.	Classification and	Concentration[%]
	EINECS-No.	labelling	
Poly(oxy-1,2-ethanediyl), .alpha	28961-43-5	;2A;H319	25 - 50
hydroomega[(1-oxo-2-		Skin Sens.;1;H317	
propenyl)oxy]-, ether with 2-		Aquatic	
ethyl-2-(hydroxymethyl)-1,3-		Chronic;3;H412	
propanediol (3:1)			

Page 3 / 20	10200000366	A member of C ALTANA





Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0

Revision Date 30.01.2024

Print Date 01.02.2024

Bisphenol A epoxy acrylate	55818-57-0	Skin Sens.;1;H317 Aquatic Chronic;2;H411	10 - 20
ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate	84434-11-7 282-810-6	Skin Sens.;1;H317 Aquatic Chronic;2;H411	10 - 20
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	1 - 10
1-isopropyl-2,2- dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9	Repr.;2;H361d Aquatic Chronic;3;H412	2,5 - 10
Propoxylated neopentyl glycol diacrylate esters	84170-74-1	Skin Sens.;1;H317 Aquatic Chronic;2;H411	2,5 - 10
2-Propenoic acid, ester with C12-16-alkyl glycidyl ether	68071-40-9	Skin Sens.;1A;H317	1 - 10
Glycerol, propoxylated, esters with acrylic acid	52408-84-1	;2A;H319 Skin Sens.;1;H317	1 - 10

For the full text of the H-Statements mentioned in this Section, see Section 16.


SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

: Move the victim to fresh air.

Page 4 / 20	10200000366	A member of C ALTANA





ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024
If inhaled	Move out of dangerous area. Show this safety data sheet to the do Do not leave the victim unattended. Remove to fresh air. If unconscious, place in recovery pos	
In case of skin contact In case of eye contact	advice. If symptoms persist, call a physician : Wash off immediately with soap and : Immediately flush eye(s) with plenty Immediately flush eye(s) with plenty	plenty of water. of water.
If swallowed	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a sport Keep respiratory tract clear.	ecialist.
	Do not give milk or alcoholic beverage Never give anything by mouth to an If symptoms persist, call a physician Take victim immediately to hospital.	unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Dry sand, ABC powder, Foam
Unsuitable extinguishing media	: High volume water jet, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	: Do not allow ru courses.	Do not allow run-off from fire fighting to enter drains or water courses.	
Page 5 / 20	1020000	00366	A member of C ALTANA

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024	

5.3 Advice for firefighters

Special protective equipment for firefighters	Wear self-contained breathing apparatus for firefig necessary.	hting if
Further information	Collect contaminated fire extinguishing water separ must not be discharged into drains. Fire residues a contaminated fire extinguishing water must be disp accordance with local regulations. Use extinguishin measures that are appropriate to local circumstance surrounding environment.	nd osed of in g

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Evacuate personnel to safe are Use personal protective equipn	
6.2 Environmental precautions		
General advice	 The product should not be allow courses or the soil. Prevent product from entering of Prevent further leakage or spill. If the product contaminates rive respective authorities. 	drains. age if safe to do so.
This information is not availabl	•	
6.3 Methods and materials for co	ntainment and cleaning up	
Methods for cleaning up	: Use mechanical handling equip Soak up with inert absorbent m acid binder, universal binder, sa Soak up with inert absorbent m acid binder, universal binder, sa Keep in suitable, closed contain	aterial (e.g. sand, silica gel, awdust). aterial (e.g. sand, silica gel, awdust).
6.4 Reference to other sections	-	-
Page 6 / 20	10200000366	A member of O ALTANA

000000366 A member of **C ALTANA**



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0

Revision Date 30.01.2024

Print Date 01.02.2024

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	: Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.
	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Further information on	: Protect from humidity and water.

Page 7 / 20	10200000366	A member of C ALTANA





Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024
storage conditions		
Advice on common storage	: Do not store near acids. Do not store and self-igniting products. Never allo contact with water during storage. Ke agents, strongly alkaline and strongl avoid exothermic reactions.	w product to get in eep away from oxidizing
Other data	: No decomposition if stored and appl	ied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
Bisphenol A	55818-57-	AGW (Inhalable	10 mg/m3	2020-03-30	DE TRGS 900
ероху	0	fraction)			
acrylate					
Peak-limit: exc	ursion	2;(II)			
factor (categor	y)				
Bisphenol A	55818-57-	AGW (Alveolate	1,25 mg/m3	2020-03-30	DE TRGS 900
ероху	0	fraction)			
acrylate					
Peak-limit: excursion		2;(II)			
factor (categor	у)				
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m3	2021-07-02	DE TRGS 900
Peak-limit: exc	ursion	2;(II)			
factor (categor	у)				

Page 8 / 20 10200000366	A member of C ALTANA
-------------------------	----------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Version	12.0
--------------	---------	------

Revision Date 30.01.2024


Print Date 01.02.2024

Further informa	ation	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m3	2021-07-02	DE TRGS 900
Peak-limit: exc factor (categor		2;(II)			
Further information	ation	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

8.2 Exposure controls

Personal protective equipment

Eye protection	:	Goggles		
	:	Tightly fitting safety goggles		
		Wear face-shield and protective problems.	e suit for abnormal processing	
Hand protection				
Material	:	Solvent-resistant gloves (butyl-	rubber)	
Remarks	:	Take note of the information giv permeability and break through workplace conditions (mechanic The exact break through time c protective glove producer and t	times, and of special cal strain, duration of contact). an be obtained from the	
		Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection		
		Skin should be washed after contact.		
		The suitability for a specific workplace should be discussed with the producers of the protective gloves.		
	:	The suitability for a specific wo	rkplace should be discussed	
Page 9 / 20		10200000366	A member of C ALTANA	





ROTOSTAR UV FP 66-40501 Silver

Version 12.0		Revision Date 30.01.2024	Print Date 01.02.2024
		with the producers of the protective gloves.	
Skin and body protection	:	Impervious clothing	

Skin and body protection	•	Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use suitable breathing protection if workplace concentration requires.
Environmental exposure co	ntro	bls
General advice	:	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: silver
Odour	: characteristic
рН	: substance/mixture is non-soluble (in water)
Melting point/range	: Not applicable
Boiling point/boiling range	: >100 °C
Flash point	: >100 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available

Page 10 / 20	10200000366	A member of 🜔 ALTANA

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024

Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Density	:	1,1 g/cm3
Solubility(ies)		
Water solubility	:	insoluble
Miscibility with water	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	No data available
Thermal decomposition	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 21 mm2/s (40 °C)
Flow time	:	No data available
Other information		

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

No decomposition if stored and applied as directed.


10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Page 11 / 20 10200000366 A	A member of C ALTANA
----------------------------	-----------------------------







ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024
Hazardous reactions	: Contact with acids and alkalis may re	lease hydrogen.
	No decomposition if stored and appli	ed as directed.
10.4 Conditions to avoid		
Conditions to avoid	: Do not allow evaporation to dryness. No data available	
10.5 Incompatible materials		
Materials to avoid	: Acids Bases Oxidizing agents	
10.6 Hazardous decomposition	n products	
Other information	: No data available	
SECTION 11: Toxicological	information	
11.1 Information on toxicologi	cal effects	
Acute toxicity		
Components:		
ethyl phenyl(2,4,6-trimethylben		
Acute oral toxicity	: Rat: >5 000 mg/kg	
	Method: OECD Test Guideline 401	
Acute dermal toxicity	∶ Rat: > 2 000 mg/kg	
	Method: OECD Test Guideline 402	
Skin corrosion/irritation		

Page 12 / 20	10200000366	A member of C ALTANA



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0

Revision Date 30.01.2024

Print Date 01.02.2024

Product

May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product

May cause irreversible eye damage.

Respiratory or skin sensitisation

Product

Causes sensitisation.

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available


STOT - single exposure

No data available

STOT - repeated exposure

No data available

Page 13 / 20	10200000366	A member of C ALTANA





ROTOSTAR UV FP 66-40501 Silver

Version	12.0		

Revision Date 30.01.2024

Print Date 01.02.2024

Aspiration toxicity

No data available

Further information

Product

No data available

SECTION 12: Ecological information

12.1 Toxicity

<u>Components:</u> Poly(oxy-1,2-ethanediyl), .alphahydroomega[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2- (hydroxymethyl)-1,3-propanediol (3:1) (28961-43-5) : Ecotoxicology Assessment
Long-term (chronic) aquatic : Harmful to aquatic life with long lasting effects. hazard Bisphenol A epoxy acrylate (55818-57-0) :
Ecotoxicology Assessment
Short-term (acute) aquatic : Toxic to aquatic life.
Long-term (chronic) aquatic : Toxic to aquatic life with long lasting effects.
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate (84434-11-7):
Ecotoxicology Assessment
Long-term (chronic) aquatic : Toxic to aquatic life with long lasting effects.
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (6846-50-0) :
Toxicity to daphnia and other : (Daphnia (water flea)): 2,46 mg/l aquatic invertebrates

Page 14 / 20	10200000366	A member of 🜔 ALTANA

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024

Ecotoxicology Assessment

Long-term (chronic) aquatic : Harmful to aquatic life with long lasting effects. hazard

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

Product:

Additional ecological : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations


13.1 Waste treatment methods

Product

: The product should not be allowed to enter drains, water courses or the soil.

Page 15 / 20 10200000366	A member of C ALTANA
--------------------------	----------------------







ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024
	Do not contaminate ponds, waterway chemical or used container. Send to a licensed waste manageme	
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.	

SECTION 14: Transport information

14.1 UN number		
ADR	: 3082	
TDG		
Not dangerous goods		
CFR		
Not dangerous goods		
IMDG	: 3082	
ΙΑΤΑ	: 3082	
14.2 Proper shipping name		
ADR	: ENVIRONMENTALLY HAZAR N.O.S.	DOUS SUBSTANCE, LIQUID,
	(Bisphenol A Epoxy resin)	
TDG		
Not dangerous goods		
CFR		
Not dangerous goods		
IMDG	: ENVIRONMENTALLY HAZAR N.O.S.	DOUS SUBSTANCE, LIQUID,
	(,Bisphenol A Epoxy resin)	
ΙΑΤΑ	: ENVIRONMENTALLY HAZAR N.O.S.	DOUS SUBSTANCE, LIQUID,
Page 16 / 20	10200000366	A member of C ALTANA

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024

14.3 Transport hazard class		
ADR	:	9
TDG		
Not dangerous goods		
CFR		
Not dangerous goods		
IMDG	:	9
ΙΑΤΑ	:	9
14.4 Packing group		
ADR		
Packaging group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9
Tunnel restriction code	:	(-)
TDG		
Not dangerous goods		
CFR		
Not dangerous goods		
IMDG		
Packaging group	:	III
Labels	:	9
EmS Code	:	F-A, S-F
ΙΑΤΑ		
Packing instruction (cargo aircraft)	:	964
Page 17 / 20		10200000366

Page 17 / 20	10200000366	A member of 🜔 ALTANA

(Bisphenol A Epoxy resin)





Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2024	Print Date 01.02.2024

Packing instruction (passenger aircraft)	: 964
Packing instruction (LQ)	: Y964
Packaging group	: 111
Labels	: 9
14.5 Environmental hazards	
ADR	: Environmentally hazardous
IMDG	: Marine pollutant

14.6 Special precautions for user

For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environm	ental regulations/legislation	spe	cific for the substance or mixture
REACH - Candidate List of Su	bstances of Very High	Not	applicable
Concern for Authorisation (Arti	icle 59).		
REACH - List of substances s	ubject to authorisation	Not	applicable
(Annex XIV)			
Regulation (EC) No 1005/2009	on substances that	Not	applicable
deplete the ozone layer			
Regulation (EU) 2019/1021 or	n persistent organic	Not	applicable
pollutants (recast)			
REACH - Restrictions on the n	nanufacture, placing on		
Page 18 / 20	10200000366		A member of C ALTANA
			A MEMber OF C ALIANA

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0	Revision Date 30.01.2	2024 Print Date 01.02.2024
mixtures and articles (Ar REACH - Restrictions or	h the manufacture, placing on ertain dangerous substances,	: Banned and/or restricted (Poly(oxy-1,2-ethanediyl), .alpha hydroomega[(1-oxo-2- propenyl)oxy]-, ether with 2-ethyl-2- (hydroxymethyl)-1,3-propanediol (3:1)) (Bisphenol A epoxy acrylate) (ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate) (aluminium powder (stabilised)) (1-isopropyl-2,2- dimethyltrimethylene diisobutyrate)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements	
H228	: Flammable solid.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H361d	: Suspected of damaging the unborn child.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

Page 19 / 20	10200000366	A member of C ALTANA
--------------	-------------	-----------------------------



Version 12.0

Revision Date 30.01.2024

Print Date 01.02.2024

(Propoxylated neopentyl glycol

(Glycerol, propoxylated, esters with

diacrylate esters)

acrylic acid)



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV FP 66-40501 Silver

Version 12.0

Revision Date 30.01.2024

Print Date 01.02.2024

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Page 20 / 20	10200000366	A member of C ALTANA
--------------	-------------	-----------------------------