

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ROTOSTAR UV/LED FPG 730 877 FLEXO INK  
Product code : 024757HW0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
  
Telephone : +499152770  
  
Telefax : +499152777008  
  
E-mail address of person responsible for the SDS : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H317      May cause an allergic skin reaction. H319      Causes serious eye irritation. H411      Toxic to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b> P261      Avoid breathing mist or vapours. P273      Avoid release to the environment. P280      Wear protective gloves/ eye protection/ face protection. <b>Response:</b> P333 + P313      If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313      If eye irritation persists: Get medical advice/ attention. P391      Collect spillage.

### Hazardous components which must be listed on the label:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid  
Glycerol, propoxylated, esters with acrylic acid  
2-Propenoic acid, reaction products with dipentaerythritol  
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide  
2-Propenoic acid, reaction products with pentaerythritol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGULATION (EC) No 1272/2008	Concentration (% w/w)
2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane	144086-02-2 604-394-0	Eye Irrit. 2; H319 Aquatic Chronic 2; H411	>= 25 - < 50
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	28961-43-5 500-066-5	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 20 - < 25

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

	01-2119489900-30		
Glycerol, propoxylated, esters with acrylic acid	52408-84-1 500-114-5 01-2119487948-12	Eye Irrit. 2; H319 Skin Sens. 1; H317	$\geq 10 - < 20$
2-Propenoic acid, reaction products with dipentaerythritol	1384855-91-7 01-2119980666-22	Eye Irrit. 2; H319 Skin Sens. 1A; H317 Aquatic Chronic 3; H412	$\geq 2.5 - < 10$
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	$\geq 1 - < 10$
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	162881-26-7 423-340-5 015-189-00-5 01-2119489401-38	Skin Sens. 1; H317 Aquatic Chronic 4; H413	$\geq 2.5 - < 10$
2-Propenoic acid, reaction products with pentaerythritol	1245638-61-2	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411	$\geq 0.1 - < 0.25$

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version	Revision Date:	SDS Number:	Print Date: 11.10.2023
6.0	10.10.2023	102000031580	Date of first issue: 05.06.2019

---

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
ABC powder  
Foam

Unsuitable extinguishing media : High volume water jet  
Carbon dioxide (CO<sub>2</sub>)

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.

### 6.2 Environmental precautions

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version	Revision Date:	SDS Number:	Print Date: 11.10.2023
6.0	10.10.2023	102000031580	Date of first issue: 05.06.2019

---

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

away from sources of ignition - No smoking. Keep container closed when not in use.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids.  
Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable fraction)	4 mg/m <sup>3</sup>	GB EH40
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
 Date of first issue: 05.06.2019

	distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane	Workers	Inhalation	Long-term systemic effects	5.87 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	3.33 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1.45 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1.67 mg/kg
	Consumers	Ingestion	Long-term systemic effects	0.83 mg/kg



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version  
6.0

Revision Date:  
10.10.2023

SDS Number:  
102000031580

Print Date: 11.10.2023  
Date of first issue: 05.06.2019

Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Workers	Inhalation	Long-term systemic effects	16.2 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	0.8 mg/kg
	Consumers	Inhalation	Long-term systemic effects	4.9 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	0.48 mg/kg
	Consumers	Oral	Long-term systemic effects	1.39 mg/kg
Glycerol, propoxylated, esters with acrylic acid	Workers	Inhalation	Long-term systemic effects	16.22 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	1.92 mg/kg
	Consumers	Inhalation	Long-term systemic effects	4.87 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	1.15 mg/kg
	Consumers	Oral	Long-term systemic effects	1.39 mg/kg
2-Propenoic acid, reaction products with dipentaerythritol	Workers	Inhalation	Long-term systemic effects	1.76 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	0.5 mg/m <sup>3</sup>
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	Workers	Inhalation	Long-term systemic effects	7.84 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	3.0 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1.93 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	1.5 mg/kg
	Consumers	Oral	Long-term systemic effects	1.5 mg/kg
	Workers	Inhalation	Acute systemic effects	7.84 mg/m <sup>3</sup>
	Workers	Dermal	Acute systemic effects	3.3 mg/kg
	Consumers	Inhalation	Acute systemic effects	1.93 mg/m <sup>3</sup>
	Consumers	Dermal	Acute systemic effects	1.67 mg/kg



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version  
6.0

Revision Date:  
10.10.2023

SDS Number:  
102000031580

Print Date: 11.10.2023  
Date of first issue: 05.06.2019

			effects	
	Consumers	Oral	Acute systemic effects	0.00167 ppm

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane	Fresh water	0.0079 mg/l
	Marine water	0.00079 mg/l
	Fresh water sediment	0.119 mg/kg
	Marine sediment	0.0119 mg/kg
	Soil	0.0192 mg/kg
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Soil	0.00644 mg/kg
	Fresh water	0.00195 mg/l
	Fresh water sediment	0.038 mg/kg
	STP	10 mg/l
	Marine water	0.000195 mg/l
	Marine sediment	0.0038 mg/kg
	Intermittent Release	0.00195 mg/l
Glycerol, propoxylated, esters with acrylic acid	Intermittent water release	0.0195 mg/l
	Fresh water	0.0057 mg/l
	Marine water	0.0005 mg/l
	Fresh water sediment	0.0169 mg/kg
	Marine sediment	0.0017 mg/kg
	STP	10 mg/l
	Soil	0.0011 mg/kg
2-Propenoic acid, reaction products with dipentaerythritol	Fresh water	0.013 mg/l
	STP	10 mg/l
	Marine sediment	0.28 mg/kg
	Fresh water sediment	2.8 mg/kg
	Marine water	0.0013 mg/l
	Soil	0.22 mg/kg
	Intermittent water release	0.13 mg/l
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	Fresh water	0.8 µg/l
	Marine water	0.8 µg/l
	STP	1 mg/l
	Fresh water sediment	0.712 mg/kg
	Marine sediment	0.712 mg/kg
	Soil	20 mg/kg
Intermittent water release	0.8 µg/l	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

2-Propenoic acid, reaction products with pentaerythritol	Fresh water	0.0032 mg/l
	Fresh water sediment	1.73 mg/kg
	Marine sediment	0.173 mg/kg
	STP	10 mg/l
	Soil	0.240 mg/kg
	Intermittent water release	0.032 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : silver  
Odour : characteristic  
Odour Threshold : No data available  
Melting point/range : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

Boiling point/boiling range : > 100 °C

Flammability : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 100 °C

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Relative density : No data available

Density : 1.1 g/cm<sup>3</sup>

Relative vapour density : No data available

Particle Size Distribution : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents

### 10.6 Hazardous decomposition products

This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

#### Skin corrosion/irritation

Not classified based on available information.

#### Product:

Remarks : May cause skin irritation and/or dermatitis.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

**Product:**

Remarks : Eye irritation

**Components:**

**2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane:**

Result : Eye irritation

**Propylidynetrimethanol, ethoxylated, esters with acrylic acid:**

Result : Irritating to eyes.

**Glycerol, propoxylated, esters with acrylic acid:**

Result : Eye irritation

**2-Propenoic acid, reaction products with dipentaerythritol:**

Result : Eye irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Product:**

Remarks : Causes sensitisation.  
May cause sensitisation of susceptible persons by skin contact.

**Components:**

**Propylidynetrimethanol, ethoxylated, esters with acrylic acid:**

Result : May cause sensitisation by skin contact.

Remarks : Causes sensitisation.  
May cause sensitisation of susceptible persons by skin contact.

**Glycerol, propoxylated, esters with acrylic acid:**

Result : May cause sensitisation by skin contact.

**2-Propenoic acid, reaction products with dipentaerythritol:**

Result : The product is a skin sensitiser, sub-category 1A.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

### phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

Result : May cause sensitisation by skin contact.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

## 11.2 Information on other hazards

### Further information

#### Product:

Remarks : No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

**2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane:**

#### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**2-Propenoic acid, reaction products with dipentaerythritol:**

#### Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:**

#### Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

#### **Glycerol, propoxylated, esters with acrylic acid:**

Partition coefficient: n-octanol/water : log Pow: 2.52 (23 °C)  
Method: OECD Test Guideline 107

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

#### Components:

#### **2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

#### **Glycerol, propoxylated, esters with acrylic acid:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

### 13.1 Waste treatment methods

---



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

- Product** : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.
- Contaminated packaging** : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
In accordance with local and national regulations.
- 

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR** : UN 3082  
**IMDG** : UN 3082  
**IATA** : UN 3082

#### 14.2 UN proper shipping name

- ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Alkoxylated Pentaerythritol Tetraacrylate)
- IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Alkoxylated Pentaerythritol Tetraacrylate)
- IATA** : Environmentally hazardous substance, liquid, n.o.s.  
(Alkoxylated Pentaerythritol Tetraacrylate)

#### 14.3 Transport hazard class(es)

- |             | Class | Subsidiary risks |
|-------------|-------|------------------|
| <b>ADR</b>  | : 9   |                  |
| <b>IMDG</b> | : 9   |                  |
| <b>IATA</b> | : 9   |                  |

#### 14.4 Packing group

- ADR**  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Tunnel restriction code : (-)
- IMDG**  
Packing group : III
-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

Labels : 9  
EmS Code : F-A, S-F

### IATA (Cargo)

Packing instruction (cargo aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : 9

### IATA (Passenger)

Packing instruction (passenger aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : 9

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

Remarks : For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3  
2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane (Number on list 3)

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

Propylidynetrimethanol, ethoxylated, esters with acrylic acid (Number on list 3)  
Glycerol, propoxylated, esters with acrylic acid (Number on list 3)  
2-Propenoic acid, reaction products with dipentaerythritol (Number on list 3)  
aluminium powder (stabilised) (Number on list 40)

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable  
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable  
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable  
UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

### 15.2 Chemical safety assessment

No data available

---

## SECTION 16: Other information

### Full text of H-Statements

H228 : Flammable solid.  
H302 : Harmful if swallowed.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.  
H413 : May cause long lasting harmful effects to aquatic life.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Sol. : Flammable solids  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOSTAR UV/LED FPG 730 877 FLEXO INK

Version 6.0      Revision Date: 10.10.2023      SDS Number: 102000031580      Print Date: 11.10.2023  
Date of first issue: 05.06.2019

---

Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

#### Classification procedure:

Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN