according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 11.02.2023
5.0	10.02.2023	10200000255	Date of first issue: 03.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	:	STAPA METALLIC 401 Aluminium Paste
Product code	:	057302G60M1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	
Substance/Mixture	

: Colouring agents, pigments

1.3 Details of the supplier of the safety data sheet

Company	ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008) Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects. 2.2 Label elements Long-terms

Labelling (REGULATION (EC)	No 1272/2008)	
Hazard statements	:	H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P273	Avoid release to the environment.



STAPA METALLIC 401 Aluminium Paste

5.0	10.02.2023	10200000255	Date of first issue: 03.01.2014	
Version	Revision Date:	SDS Number:	Print Date: 11.02.2023	

Disposal: P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components			
Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1	Flam. Sol. 1; H228	>= 50 - <= 100
Naphtha (petroleum), hydrotreated heavy; Low boiling	01-2119529243-45 64742-48-9	Asp. Tox. 1; H304	>= 10 - < 20
point ydrogen treated naphtha	918-481-9 01-2119457273-39		
Solvent naphtha (petroleum), light arom.	64742-95-6 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move the victim to fresh air.
		No hazards which require special first aid measures.
If inhaled	:	If unconscious, place in recovery position and seek medical



STAPA METALLIC 401 Aluminium Paste

Version 5.0	Revision Date: 10.02.2023		OS Number: 2000000255	Print Date: 11.02.2023 Date of first issue: 03.01.2014		
			advice. If symptoms pers	ist, call a physician.		
In case of skin contact		:	: Wash off immediately with soap and plenty of water.			
In case of eye contact		:	Immediately flush	eye(s) with plenty of water.		
			Remove contact	enses.		
If swallowed		:	Never give anythi	tract clear. or alcoholic beverages. ing by mouth to an unconscious person. ist, call a physician.		

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

	Suitable extinguishing media	:	Dry sand Special powder against metal fire
	Unsuitable extinguishing media	:	Water Foam ABC powder Carbon dioxide (CO2)
5.2	Special hazards arising from	the	substance or mixture
	Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	Use personal protective equipment.
			Wear self-contained breathing apparatus for firefighting if necessary.
	Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 11.02.2023
5.0	10.02.2023	10200000255	Date of first issue: 03.01.2014

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures			
Personal precautions :	Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition. Avoid dust formation.		
6.2 Environmental precautions			
Environmental precautions :	The product should not be allowed to enter drains, water courses or the soil.		
	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.		

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	: Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
	Sweep up and shovel. Do not flush with water. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation.
		For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
Advice on protection against fire and explosion	:	Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.
		Normal measures for preventive fire protection.
Hygiene measures	:	General industrial hygiene practice.

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

Version 5.0	Revision Date: 10.02.2023		DS Number: 2000000255	Print Date: 11.02.2023 Date of first issue: 03.01.2014	
7.2 Con	ditions for safe storage,	inc	luding any incom	patibilities	
Requirements for storage areas and containers		:	Store in original container. Keep containers tightly closed in cool, well-ventilated place. Keep container closed when not use. Keep away from sources of ignition - No smoking.		
		Electrical installations / working materials mus the technological safety standards.			
	ther information on rage conditions	:	Protect from hun	nidity and water. Do not allow to dry.	
Adv	<i>v</i> ice on common storage	:	Never allow proc storage. Keep away from	ether with oxidizing and self-igniting products. luct to get in contact with water during oxidizing agents, strongly alkaline and terials in order to avoid exothermic reactions.	
	ther information on rage stability	:	No decompositio	n if stored and applied as directed.	

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	when samplin MDHS14/4 G respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply particles of a particular part response that	g is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or great or 4 mg.m-3 8-hour be subject to COSHF dusts have been ass with the appropriate wide range of sizes. ticle after entry into the it elicits, depend on	of airborne dust which will b ccordance with the methods ampling and gravimetric an aerosols., The COSHH define cludes dust of any kind where eater than 10 mg.m-3 8-hour TWA of respirable dust. The dif people are exposed to du- signed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition a ne human respiratory system the nature and size of the p r limit-setting purposes term	a described in alysis or nition of a n present at a r TWA of is means that ust above these contain and fate of any n, and the body particle. HSE

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

Version 5.0	Revision Date: 10.02.2023	SDS Number: 102000000255	Print Date: 11.02.2023 Date of first issue: 03.0	
	materi availal to the definiti contai should	al that enters the nos ole for deposition in the fraction that penetrate ions and explanatory n components that hat I be complied with., W	dust approximates to the fr e and mouth during breath he respiratory tract. Respira es to the gas exchange reg material are given in MDH ve their own assigned WE /here no specific short-terr g-term exposure limit shoul rable 4 mg/m3	ing and is therefore able dust approximates gion of the lung. Fuller S14/4., Where dusts L, all the relevant limits n exposure limit is listed,
	inhala when a MDHS respira substa concer inhala any du levels. must o particle particle particle particle respor disting and 're materi availal to the definiti contai should	ble dust are those fractions and explanation in the appro- some dusts are those fractions and in the appro- ble dust or 4 mg.m-3 ast will be subject to C some dusts have be comply with the appro- es of a wide range of a vide range of a start it elicits, deper- uishes two size fractions and explanatory in the appro- phanet of the appro- sole for deposition in the fraction that penetrate of the approximation in the approximation of the approximation in the approximation of the approximation in the approximation in the approximation and explanatory in components that had be complied with., We approximate the approximation in the approximation in the approximation and explanatory in components that had be complied with., We approximate the approximation approximation in the approximation and explanatory in components that had be complied with., We approximate the approximation approximatio	purposes of these limits, r ctions of airborne dust which an in accordance with the r ls for sampling and gravim alable aerosols., The COS alth includes dust of any ki or greater than 10 mg.m-3 8-hour TWA of respirable of COSHH if people are expose en assigned specific WEL priate limits., Most industri sizes. The behaviour, dep- v into the human respirator end on the nature and size ons for limit-setting purpos dust approximates to the fr e and mouth during breath he respiratory tract. Respira es to the gas exchange reg- material are given in MDH ve their own assigned WE /here no specific short-terr g-term exposure limit shoul	ch will be collected nethods described in etric analysis or HH definition of a nd when present at a 3 8-hour TWA of dust. This means that sed to dust above these s and exposure to these al dusts contain osition and fate of any y system, and the body of the particle. HSE test termed 'inhalable' action of airborne ing and is therefore able dust approximates gion of the lung. Fuller S14/4., Where dusts L, all the relevant limits n exposure limit is listed,

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	Workers	Inhalation	Acute systemic effects	1500 mg/m3
	Workers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Ingestion	Long-term systemic	300 mg/kg

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

Version 5.0	Revision Date: 10.02.2023	SDS Nu 1020000		Date: 11.02.2023 of first issue: 03.01.2014	
		0		effects	
		Consumers	Skin contact	Long-term systemic effects	300 mg/kg
		Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	ent naphtha oleum), light 1.	Workers	Inhalation	Long-term systemic effects	150 mg/m3
		Workers	Skin contact	Long-term systemic effects	25 mg/kg
		Consumers	Skin contact	Long-term systemic effects	11 mg/kg
		Consumers	Inhalation	Long-term systemic effects	32 mg/m3
		Consumers	Inhalation	Long-term local effects	11 mg/kg
		Consumers	Ingestion	Long-term systemic effects	11 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Safety glasses	
Hand protection Material	:	Solvent-resistant gloves	
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.	
Skin and body protection	:	Long sleeved clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place.	

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

Version	Revision Date: 10.02.2023	SDS Number:	Print Date: 11.02.2023
5.0		102000000255	Date of first issue: 03.01.2014
Resp	iratory protection	: Use suitable bro requires.	eathing protection if workplace concentration

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state		Pasty solid
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Freezing point	:	No data available
Boiling point/boiling range	:	140 - 200 °C
Flammability	:	Combustible Solids
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	Not relevant
Decomposition temperature	:	No data available
рН	:	substance/mixture is non-soluble (in water)
Viscosity, kinematic	:	No data available
Solubility(ies) Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	No data available



STAPA METALLIC 401 Aluminium Paste

Versio 5.0	on	Revision Date: 10.02.2023		S Number: 2000000255	Print Date: 11.02.2023 Date of first issue: 03.01.2014	
F	Relative	e density	:	No data available	e	
Γ	Density		:	: 1.3 - 2.0 g/cm3		
F	Relative	e vapour density	:	No data available	e	
	Particle Size Distribution		:			
9.2 Other information						
Explosives		:	Not explosive			
F		able solids ning number	:	1		
5	Self-ign	ition	:	not auto-flamma	ble	
Ν	Miscibil	ity with water	:	immiscible		

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions :	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.
10.4 Conditions to avoid	
Conditions to avoid :	Do not allow to dry.
	No data available
10.5 Incompatible materials	
Materials to avoid :	Acids Bases Oxidizing agents

Highly halogenated compounds

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 11.02.2023
5.0	10.02.2023	10200000255	Date of first issue: 03.01.2014

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): Test atmosphere: vapour Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.
		D_{FO} (Dobbit) $= F_{OOO} m \pi / (\pi$

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Solvent naphtha (petroleum), light arom .:

Acute oral toxicity	:	LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity	: LD50 (Rabbit): > 3,160 mg/kg
-----------------------	--------------------------------

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

ersion)	Revision Date: 10.02.2023	SDS Number: 102000000255	Print Date: 11.02.2023 Date of first issue: 03.01.2014		
<u>Comp</u>	oonents:				
Naph	tha (petroleum), hyd	Irotreated heavy;	Low boiling point ydrogen treated naphtha:		
	cell mutagenicity- ssment		based on benzene content < 0.1% (Regulation (EC Annex VI, Part 3, Note P)		
Solve	ent naphtha (petrole	um), light arom.:			
	cell mutagenicity- ssment		based on benzene content < 0.1% (Regulation (EC Annex VI, Part 3, Note P)		
	nogenicity assified based on av	ailable information.			
<u>Comp</u>	oonents:				
Naph	tha (petroleum), hyd	Irotreated heavy;	Low boiling point ydrogen treated naphtha:		
Carcir	nogenicity - ssment	: Classified b	based on benzene content < 0.1% (Regulation (EC Annex VI, Part 3, Note P)		
Solve	ent naphtha (petrole	um), light arom.:			
	nogenicity - ssment		based on benzene content < 0.1% (Regulation (EC Annex VI, Part 3, Note P)		
Reproductive toxicity Not classified based on available information.					
	• single exposure assified based on av	ailable information.			
<u>Comp</u>	oonents:				
Solve	ent naphtha (petrole	um), light arom.:			
Asses	ssment	: May cause dizziness.	respiratory irritation., May cause drowsiness or		
	- repeated exposur assified based on av				
Aspir	ation toxicity assified based on av				
Comp	oonents:	-			
-	tha (petroleum), hyd be fatal if swallowed a	•	Low boiling point ydrogen treated naphtha:		
	ent naphtha (petrole				
May b	e fatal if swallowed a	nd enters airways.			

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

Version 5.0	Revision Date: 10.02.2023	SDS Number: 102000000255	Print Date: 11.02.2023 Date of first issue: 03.01.2014
11.2 Infor	mation on other haz	ards	
Furth	er information		
<u>Prod</u> Rema		: No data avai	lable
SECTION	12: Ecological inf	formation	
12.1 Toxic	city		
Com	oonents:		
Solve	ent naphtha (petrole	um), light arom.:	
	oxicology Assessme		atic life with long lasting effects.
	i stence and degrada ata available	bility	
	ccumulative potentia ata available	al	
	lity in soil ata available		
12.5 Resu	lts of PBT and vPvB	assessment	
<u>Prod</u> Asse	uct: ssment	to be either p	ce/mixture contains no components considered persistent, bioaccumulative and toxic (PBT), or nt and very bioaccumulative (vPvB) at levels of er.
	ocrine disrupting pro ata available	perties	
12.7 Othe	r adverse effects		
	uct: onal ecological nation	unprofession	ental hazard cannot be excluded in the event of al handling or disposal. quatic life with long lasting effects.
Com	oonents:		
-		-	ow boiling point ydrogen treated naphtha:
	onal ecological	: No data avai	lable

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

	ite: 11.02.2023 first issue: 03.01.2014
--	--

SECTION 13: Disposal considerations

European Waste Catalogue European Waste Catalogue	:	12 01 04 - non-ferrous metal dust and particles 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances
13.1 Waste treatment methods		
Product	:	The product should not be allowed to enter drains, water courses or the soil. In accordance with local and national regulations.
Contaminated packaging	:	In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good	
IMDG	:	Not regulated as a dangerous good	
ΙΑΤΑ	:	Not regulated as a dangerous good	
14.2 UN proper shipping name			
ADR	:	Not regulated as a dangerous good	
IMDG	:	Not regulated as a dangerous good	
ΙΑΤΑ	:	Not regulated as a dangerous good	
14.3 Transport hazard class(es)			
ADR	:	Not regulated as a dangerous good	
IMDG	:	Not regulated as a dangerous good	
ΙΑΤΑ	:	Not regulated as a dangerous good	
14.4 Packing group			
ADR	:	Not regulated as a dangerous good	
IMDG	:	Not regulated as a dangerous good	
IATA (Cargo)	:	Not regulated as a dangerous good	
IATA (Passenger)	:	Not regulated as a dangerous good	
14.5 Environmental hazards			

Not regulated as a dangerous good

14.6 Special precautions for user



STAPA METALLIC 401 Aluminium Paste

Version	Revision Date: 10.02.2023	SDS Number:	Print Date: 11.02.2023	
5.0		102000000255	Date of first issue: 03.01.2014	
Remarks		: Not classified as dangerous in the meaning of transport regulations.		

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha (Number on list 3) Solvent naphtha (petroleum), light arom. (Number on list 3)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H226 :	Flammable liquid and vapour.			
H228 :	Flammable solid.			
H304 :	May be fatal if swallowed and enters airways.			
H335 :	May cause respiratory irritation.			
H336 :	May cause drowsiness or dizziness.			
H411 :	Toxic to aquatic life with long lasting effects.			
Full text of other abbreviations				

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Flam. Liq.	:	Flammable liquids
Flam. Sol.	:	Flammable solids

GB EH40 / TWA



STAPA METALLIC 401 Aluminium Paste

Version	Revision Date: 10.02.2023	SDS Number:	Print Date: 11.02.2023
5.0		102000000255	Date of first issue: 03.01.2014
STOT SE GB EH40			t organ toxicity - single exposure L - Workplace Exposure Limits

: Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information Classification of the mixture: H412

Classification procedure:

Aquatic Chronic 3

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

according to Regulation (EC) No. 1907/2006



STAPA METALLIC 401 Aluminium Paste

Version 5.0 10.02.2023

Revision Date:

SDS Number: 10200000255 Print Date: 11.02.2023 Date of first issue: 03.01.2014