

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : METALSTAR UV/LED FPG 726 500 N.L. LITHO INK  
Material number : 026618N20

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guntersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

---

**SECTION 2: Hazards identification****GHS Classification**

: Serious eye damage/eye irritation, Category 2A, H319  
Skin sensitisation, Category 1, H317

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

**GHS-Labeling**

Symbol(s)

:



Signal word

: Warning

Hazard statements

: H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.

Precautionary statements

:
 

**Prevention:**  
 P261 Avoid breathing mist or vapours.  
 P264 Wash skin thoroughly after handling.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/ eye protection/ face protection.

**Response:**  
 P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333 + P317 If skin irritation or rash occurs: Get medical help.  
 P337 + P317 If eye irritation persists: Get medical help.

**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Hazardous components which must be listed on the label**

Identification	CAS-No.
Glycerol, propoxylated, esters with acrylic acid	52408-84-1
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	28961-43-5
2-Propenoic acid, reaction products with	1384855-91-7

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## METALSTAR UV/LED FPG 726 500 N.L. LITHO INK

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

dipentaerythritol

### SECTION 3: Composition/information on ingredients

Substance No. :

#### Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
Glycerol, propoxylated, esters with acrylic acid	52408-84-1	;2A;H319 Skin Sens.;1;H317	20 - 25
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	28961-43-5	;2A;H319 Skin Sens.;1;H317	10 - 20
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	10 - 20
2-Propenoic acid, reaction products with dipentaerythritol	1384855-91-7	;2A;H319 Skin Sens.;1A;H317 Aquatic Chronic;3;H412	2,5 - 10
2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-	7078-98-0	Skin Sens.;1;H317 Aquatic Chronic;4;H413	0,25 - 1
2-Propenoic acid, reaction products with pentaerythritol	1245638-61-2	Acute Tox.;4;H302 Skin Irrit.;2;H315 Eye Dam.;1;H318 Skin Sens.;1;H317 Aquatic Acute;2;H401	0,1 - 0,25

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

		Aquatic Chronic;2;H411	
--	--	---------------------------	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

General advice	: Move the victim to fresh air. Move out of dangerous area. Show this safety data sheet to the doctor in attendance.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Wash off immediately with soap and plenty of water. If on skin, rinse well with water.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, ABC powder, Foam

Unsuitable extinguishing media : High volume water jet, Carbon dioxide (CO<sub>2</sub>)**5.2 Special hazards arising from the substance or mixture**

This information is not available.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.**6.2 Environmental precautions**

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

**6.3 Methods and materials for containment and cleaning up**

- Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

- Advice on safe handling : Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## METALSTAR UV/LED FPG 726 500 N.L. LITHO INK

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

away from sources of ignition - No smoking. Keep container closed when not in use.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

## 8.2 Exposure controls

### Personal protective equipment

- Eye protection : Goggles  
: Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
The exact break through time can be obtained from the protective glove producer and this has to be observed.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
Recommended preventive skin protection  
Skin should be washed after contact.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
: Choose body protection according to the amount and concentration of the dangerous substance at the work place.



**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

**Environmental exposure controls**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
: Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance : liquid  
Colour : silver  
Odour : characteristic  
pH : substance/mixture is non-soluble (in water)  
Melting point/range : Not applicable  
Boiling point/boiling range : > 100 °C  
Flash point : > 100 °C  
  
Bulk density : No data available  
Flammability (solid, gas) : No data available  
Auto-flammability : No data available  
Upper explosion limit : No data available  
Lower explosion limit : No data available  
Vapour pressure : No data available  
Density : 1,1 g/cm<sup>3</sup>  
Solubility(ies)  
Water solubility : insoluble

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 22 mm <sup>2</sup> /s (40 °C)
Flow time	: No data available

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

**10.4 Conditions to avoid**Conditions to avoid : Do not allow evaporation to dryness.  
No data available

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

---

**10.5 Incompatible materials**

Materials to avoid : Acids  
Bases  
Oxidizing agents

**10.6 Hazardous decomposition products**

Other information : No data available

---

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

No data available

**Skin corrosion/irritation****Product**

May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation****Product**

Eye irritation

**Respiratory or skin sensitisation****Product**

Causes sensitisation.

May cause sensitisation of susceptible persons by skin contact.

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

---

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

No data available

---

**SECTION 12: Ecological information****12.1 Toxicity****Components:**

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

---

**2-Propenoic acid, reaction products with dipentaerythritol (1384855-91-7) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological information : No data available

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

Contaminated packaging : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.  
: Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
In accordance with local and national regulations.

**SECTION 14: Transport information****14.1 UN number****ADR**

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

**14.2 Proper shipping name****ADR**

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

Not dangerous goods

**IATA**

Not dangerous goods

**14.3 Transport hazard class**

**ADR**

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

**14.4 Packing group**

**ADR**

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

**14.5 Environmental hazards**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## METALSTAR UV/LED FPG 726 500 N.L. LITHO INK

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

### 14.6 Special precautions for user

Not classified as dangerous in the meaning of transport regulations.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Banned and/or restricted (Glycerol, propoxylated, esters with acrylic acid) (Propylidynetrimethanol, ethoxylated, esters with acrylic acid) (aluminium powder (stabilised)) (2-Propenoic acid, reaction products with dipentaerythritol) (2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one)



Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALSTAR UV/LED FPG 726 500 N.L. LITHO INK**

Version 3.0

Revision Date 10.10.2023

Print Date 11.10.2023

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

H228	: Flammable solid.
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H401	: Toxic to aquatic life.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.