

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : METALSTAR PANTONE 875 Supergloss 07 4875  
Material number : 070353RN0

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Acute toxicity, Category 4, Oral, H302  
Serious eye damage/eye irritation, Category 2A, H319  
Reproductive toxicity, Category 2, H361d

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## METALSTAR PANTONE 875 Supergloss 07 4875

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Short-term (acute) aquatic hazard, Category 1, H400  
Long-term (chronic) aquatic hazard, Category 1, H410

### GHS-Labelling

Symbol(s)



Signal word

: Warning

Hazard statements

: H302: Harmful if swallowed.  
H319: Causes serious eye irritation.  
H361d: Suspected of damaging the unborn child.  
H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
P203 Obtain, read and follow all safety instructions before use.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
P301 + P317 + P330 IF SWALLOWED: Get medical help. Rinse mouth.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P318 IF exposed or concerned, get medical advice.  
P337 + P317 If eye irritation persists: Get medical help.  
P391 Collect spillage.  
**Storage:**  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

**Hazardous components which must be listed on the label**

Identification	CAS-No.
copper	7440-50-8
1-isopropyl-2,2-dimethyltrimethylene	6846-50-0
diisobutyrate	

**SECTION 3: Composition/information on ingredients**

Substance No. :

**Hazardous components**

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
copper	7440-50-8 231-159-6	Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	25 - 50
Distillates (petroleum), hydrotreated middle	64742-46-7 265-148-2	Asp. Tox.;1;H304	20 - 25
zinc	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	2,5 - 10
Petroleum resins	64742-16-1 265-116-8	Aquatic Chronic;4;H413	2,5 - 10
1-isopropyl-2,2-	6846-50-0	Repr.;2;H361d	1 - 2,5

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

dimethyltrimethylene diisobutyrate	229-934-9	Aquatic Chronic;3;H412	
octadecylamine	124-30-1 204-695-3	;2;H315 ;1;H318 STOT RE;2;H373 Asp. Tox.;1;H304 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	0,25 - 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Special powder against metal fire, Dry sand, ABC powder

Unsuitable extinguishing media : Water, High volume water jet, Carbon dioxide (CO<sub>2</sub>)

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

measures that are appropriate to local circumstances and the surrounding environment.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Use personal protective equipment.

**6.2 Environmental precautions**

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.

Pick up and transfer to properly labelled containers.  
Do not flush with water.  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

- Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.
- Dampness : Keep in a dry, cool and well-ventilated place.
- Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

This information is not available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
copper	7440-50-8	AGW (inhalable fraction)	1 mg/m <sup>3</sup>		DE TRGS 900
Distillates (petroleum), hydrotreated middle	64742-46-7	AGW	600 mg/m <sup>3</sup>	2009-02-16	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures Commission for dangerous substances See also No. 2.9 of the TRGS 900				
zinc	7440-66-6	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## METALSTAR PANTONE 875 Supergloss 07 4875

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
zinc	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m3	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
copper	7440-50-8	TWA	1 mg/m3	2008-01-01	
copper	7440-50-8	TWA (dust and mists)	1 mg/m3	2005-09-01	
copper	7440-50-8	TWA	1 mg/m3	1989-01-19	
copper	7440-50-8	TWA	0,2 mg/m3	2008-01-01	
copper	7440-50-8	TWA	0,1 mg/m3	1989-01-19	
copper	7440-50-8	TWA (Dust and mist)	1 mg/m3	2010-03-01	
copper	7440-50-8	TWA (Fumes)	0,2 mg/m3	2010-03-01	
copper	7440-50-8	TWA (Dust)	1 mg/m3	2013-10-08	
copper	7440-50-8	TWA (Mist)	1 mg/m3	2013-10-08	
copper	7440-50-8	TWA (dusts and mists)	1 mg/m3	2011-07-01	
copper	7440-50-8	TWA (Fumes)	0,1 mg/m3	2011-07-01	
copper	7440-50-8	PEL (Fumes)	0,1 mg/m3	2014-11-26	
copper	7440-50-8	TWA (Fumes)	0,1 mg/m3	1989-01-19	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

copper	7440-50-8	TWA (Dust and mist)	1 mg/m <sup>3</sup>	1989-01-19	
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA	500 ppm 2 000 mg/m <sup>3</sup>	2007-01-01	
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA	400 ppm 1 600 mg/m <sup>3</sup>	1989-01-19	
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA	5 mg/m <sup>3</sup>	1989-01-19	
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m <sup>3</sup>	2018-03-15	
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m <sup>3</sup>	1989-01-19	
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m <sup>3</sup>	2019-10-04	
Distillates (petroleum), hydrotreated middle	64742-46-7	ST (Mist)	10 mg/m <sup>3</sup>	2019-10-04	
Distillates (petroleum), hydrotreated middle	64742-46-7	PEL (particulate)	5 mg/m <sup>3</sup>	2017-12-05	
zinc	7440-66-6	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
zinc	7440-66-6	TWA (total dust)	15 mg/m <sup>3</sup>	2012-07-01	
zinc	7440-66-6	TWA (respirable)	5 mg/m <sup>3</sup>	2012-07-01	

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

		fraction)			
zinc	7440-66-6	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
zinc	7440-66-6	PEL (Total dust)	10 mg/m3	2014-11-26	
zinc	7440-66-6	PEL (respirable dust fraction)	5 mg/m3	2014-11-26	
Safflower oil	8001-23-8	TWA (mist - total)	10 mg/m3	2013-10-08	
Safflower oil	8001-23-8	TWA (mist - respirable)	5 mg/m3	2013-10-08	
Safflower oil	8001-23-8	PEL (Total dust)	10 mg/m3	2014-11-26	
Safflower oil	8001-23-8	PEL (respirable dust fraction)	5 mg/m3	2014-11-26	

**8.2 Exposure controls****Personal protective equipment**

Eye protection : Safety glasses

: Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.  
Equipment should conform to EN 14387

**Environmental exposure controls**

- General advice :
- The product should not be allowed to enter drains, water courses or the soil.
  - Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Appearance	: liquid
Colour	: gold
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: > 100 °C
Flash point	: > 100 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 21 mm <sup>2</sup> /s (40 °C)

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Flow time : No data available

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow evaporation to dryness.

No data available

**10.5 Incompatible materials**

Materials to avoid : No data available

**10.6 Hazardous decomposition products**

Hazardous decomposition  
products :

Other information : Carbon monoxide, carbon dioxide and unburned  
hydrocarbons (smoke).

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****copper :**

Acute oral toxicity

: The component/mixture is moderately toxic after single  
ingestion.**Skin corrosion/irritation****Product**

May cause skin irritation in susceptible persons.

**Serious eye damage/eye irritation****Product**

May cause irreversible eye damage.

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

No data available

---

**SECTION 12: Ecological information****12.1 Toxicity****Components:****copper (7440-50-8) :**

M-Factor : 10

**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

**zinc (7440-66-6) :**



**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

**Petroleum resins (64742-16-1) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : May cause long lasting harmful effects to aquatic life.

**1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (6846-50-0) :**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 2,46 mg/l

**Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

**octadecylamine (124-30-1) :**

M-Factor : 10

**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

---

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**Additional ecological  
information: An environmental hazard cannot be excluded in the event of  
unprofessional handling or disposal., Very toxic to aquatic life  
with long lasting effects.

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product

: The product should not be allowed to enter drains, water  
courses or the soil.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging

: Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

**SECTION 14: Transport information****14.1 UN number****ADR**

: 3082

**TDG**

Not dangerous goods

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

**CFR**

Not dangerous goods

**IMDG** : 3082**IATA** : 3082**14.2 Proper shipping name**

**ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(Copper metal powder )

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(,Copper metal powder )

**IATA** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(Copper metal powder)

**14.3 Transport hazard class****ADR** : 9**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : 9**IATA** : 9**14.4 Packing group**

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

**ADR**

Packaging group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Tunnel restriction code : (-)

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Packaging group : III  
Labels : 9

**IATA**

Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964  
Packing instruction (LQ) : Y964  
Packaging group : III  
Labels : 9

**14.5 Environmental hazards**

**ADR** : Environmentally hazardous

**IMDG** : Marine pollutant

**14.6 Special precautions for user**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Banned and/or restricted (Distillates (petroleum), hydrotreated middle; Gasoil — unspecified) (1-isopropyl-2,2-dimethyltrimethylene diisobutyrate) (manganese neodecanoate)

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALSTAR PANTONE 875 Supergloss 07 4875**

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H361d	: Suspected of damaging the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.