

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Product code : 005787GK0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colouring agents, pigments

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)
Call and response in your language is possible.
Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Hazardous components which must be listed on the label:

2-butoxyethanol

Additional Labelling

EUH208 Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version
5.0

Revision Date:
01.12.2023

SDS Number:
102000000201

Print Date: 02.12.2023
Date of first issue: 02.01.2014

aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 50 - <= 100
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1,200 mg/kg 1,200 mg/kg 1,200 mg/kg Acute inhalation toxicity (vapour): 3 mg/l 3 mg/l	>= 25 - < 50
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3 217-164-6 01-2119970215-39	Acute Tox. 4; H332 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 0.1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.
Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.
Causes serious eye irritation.
Harmful if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand
Special powder against metal fire

Unsuitable extinguishing media : Water
Foam
ABC powder
Carbon dioxide (CO₂)

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Remove all sources of ignition.
Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Ensure adequate ventilation.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.
Avoid dust formation.
Ensure adequate ventilation.
Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m ³	GB EH40
		TWA (Respirable fraction)	4 mg/m ³	GB EH40
		TWA (inhalable dust)	10 mg/m ³	GB EH40
Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version
5.0

Revision Date:
01.12.2023

SDS Number:
102000000201

Print Date: 02.12.2023
Date of first issue: 02.01.2014

	<p>particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
		TWA (Respirable dust)	4 mg/m ³	GB EH40
	<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m ³	2000/39/EC
	<p>Further information: Identifies the possibility of significant uptake through the skin, Indicative</p>			
		STEL	50 ppm 246 mg/m ³	2000/39/EC
	<p>Further information: Identifies the possibility of significant uptake through the skin, Indicative</p>			
		TWA	25 ppm 123 mg/m ³	GB EH40
	<p>Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.</p>			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version
5.0

Revision Date:
01.12.2023

SDS Number:
102000000201

Print Date: 02.12.2023
Date of first issue: 02.01.2014

		STEL	50 ppm 246 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
silicon dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m ³ (Silica)	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	2.4 mg/m ³ (Silica)	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version
5.0

Revision Date:
01.12.2023

SDS Number:
102000000201

Print Date: 02.12.2023
Date of first issue: 02.01.2014

to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m3
	Workers	Inhalation	Acute systemic effects	1091 mg/m3
	Workers	Inhalation	Acute local effects	246 mg/m3
	Workers	Skin contact	Long-term systemic effects	75 mg/kg
	Workers	Skin contact	Acute systemic effects	89 mg/kg
	Consumers	Inhalation	Long-term systemic effects	59 mg/m3
	Consumers	Inhalation	Acute systemic effects	426 mg/m3
	Consumers	Inhalation	Acute local effects	147 mg/m3
	Consumers	Skin contact	Long-term systemic effects	75 mg/kg
silicon dioxide	Consumers	Skin contact	Acute systemic effects	89 mg/kg
	Consumers	Ingestion	Long-term systemic effects	6.3 mg/kg
	Consumers	Ingestion	Acute systemic effects	26.7 mg/kg
	Workers	Inhalation	Long-term systemic effects	4 mg/m3
	Workers	Inhalation	Long-term systemic effects	35.3 mg/m3
	Workers	Dermal	Long-term systemic effects	5 mg/kg
	Workers	Inhalation	Long-term systemic effects	35.3 mg/m3
	Workers	Inhalation	Long-term systemic effects	35.3 mg/m3
	Workers	Dermal	Long-term systemic effects	5 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version
5.0

Revision Date:
01.12.2023

SDS Number:
102000000201

Print Date: 02.12.2023
Date of first issue: 02.01.2014

			effects	
	Workers	Dermal	Acute systemic effects	5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	8.7 mg/m3
	Consumers	Dermal	Long-term systemic effects	2.5 mg/kg
	Consumers	Dermal	Acute systemic effects	17 mg/kg
	Consumers	Oral	Long-term systemic effects	2.5 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
2-butoxyethanol	Fresh water	8.8 mg/l
	Marine water	0.88 mg/l
	STP	463 mg/l
	Fresh water sediment	34.6 mg/kg
	Marine sediment	3.46 mg/kg
	Soil	2.33 mg/kg
	Sporadic Release	9.1 mg/l
N-(3-(trimethoxysilyl)propyl)ethylenedi amine	Secondary Poisoning	20 mg/kg
	Fresh water	0.062 mg/l
	Marine water	0.0062 mg/l
	STP	25 mg/l
	Fresh water sediment	0.048 mg/kg
	Marine sediment	0.0048 mg/kg
	Soil	0.0075 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection	:	Long sleeved clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place. Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use suitable breathing protection if workplace concentration requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	:	Pasty solid
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/range	:	Not applicable
Boiling point/boiling range	:	168 - 172 °C
Flammability	:	Combustible Solids
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	65 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	substance/mixture is non-soluble (in water)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Vapor Pressure for Components:

2-butoxyethanol : 0.8 hPa (20 °C)

N-(3-(trimethoxysilyl)propyl)ethylenediamine : 1.5 hPa (20 °C)

Relative density : No data available

Density : 1.3 - 2.0 g/cm³

Relative vapour density : No data available

Particle characteristics

Particle Size Distribution : No data available

9.2 Other information

Explosives : Not explosive

Self-ignition : not auto-flammable

Miscibility with water : partly miscible

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.
No data available

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents
Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 1.43 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

2-butoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1,200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute toxicity estimate: 1,200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute toxicity estimate: 1,200 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Test atmosphere: vapour
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute toxicity estimate: 3 mg/l
Test atmosphere: vapour
Method: Expert judgement

N-(3-(trimethoxysilyl)propyl)ethylenediamine:

Acute oral toxicity : LD50 (Rat): ca. 2,995 mg/kg

Acute inhalation toxicity : LC50: 1.49 - 2.44 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

2-butoxyethanol:

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

2-butoxyethanol:

Result : Eye irritation

N-(3-(trimethoxysilyl)propyl)ethylenediamine:

Result : Corrosive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

N-(3-(trimethoxysilyl)propyl)ethylenediamine:

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles
European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version 5.0	Revision Date: 01.12.2023	SDS Number: 102000000201	Print Date: 02.12.2023 Date of first issue: 02.01.2014
----------------	------------------------------	-----------------------------	---

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
aluminium powder (stabilised)
(Number on list 40)
2-butoxyethanol (Number on list 3)
N-(3-(trimethoxysilyl)propyl)ethylenediamine (Number on list 3)

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

Britain)
Regulation (EC) No 1005/2009 on substances that : Not applicable
deplete the ozone layer
UK REACH List of substances subject to authorisation : Not applicable
(Annex XIV)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H228	: Flammable solid.
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H332	: Harmful if inhaled.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Sol.	: Flammable solids
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STAPA BG HYDROLAN 2156 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 02.12.2023
5.0	01.12.2023	102000000201	Date of first issue: 02.01.2014

Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319

Classification procedure:

Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN