

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : PRISMASTAR SX-5321

Product code : 052283LS0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)
Call and response in your language is possible.
Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 3	H331: Toxic if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)


SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version 4.0 Revision Date: 02.01.2024 SDS Number: 102000000752 Print Date: 03.01.2024
Date of first issue: 05.02.2014

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H302 Harmful if swallowed. H315 Causes skin irritation. H319 Causes serious eye irritation. H331 Toxic if inhaled.
Precautionary statements	:	Prevention: P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ eye protection/ face protection. Response: P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor. P337 + P313 If eye irritation persists: Get medical advice/ attention. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous components which must be listed on the label:

2-butoxyethanol

Additional Labelling

EUH208 Contains Aziridine, homopolymer. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315	>= 50 - <= 100

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version 4.0 Revision Date: 02.01.2024 SDS Number: 102000000752 Print Date: 03.01.2024
Date of first issue: 05.02.2014

	01-2119475108-36	Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1,200 mg/kg 1,200 mg/kg 1,200 mg/kg Acute inhalation toxicity (vapour): 3 mg/l 3 mg/l	
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	$\geq 1 - < 10$
Aziridine, homopolymer	9002-98-6	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	$\geq 0.25 - < 1$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
- Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.
Remove to fresh air.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
Toxic if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand
Special powder against metal fire

Carbon dioxide (CO₂)

Unsuitable extinguishing media : ABC powder
Carbon dioxide (CO₂)
Water
Foam

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

separately in closed containments.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

Advice on protection against fire and explosion : regulations.
Do not spray on a naked flame or any incandescent material.
Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids.
Do not store together with oxidizing and self-igniting products.
Keep away from oxidizing agents and strongly acid or alkaline materials.
Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m ³	2000/39/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version
4.0

Revision Date:
02.01.2024

SDS Number:
102000000752

Print Date: 03.01.2024
Date of first issue: 05.02.2014

	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	25 ppm 123 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 246 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
propane-1,2-diol	57-55-6	TWA (particles)	10 mg/m ³	GB EH40
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Total vapour and particles)	150 ppm 474 mg/m ³	GB EH40
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m ³	GB EH40
		TWA (Respirable fraction)	4 mg/m ³	GB EH40
		TWA (inhalable dust)	10 mg/m ³	GB EH40
	<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits</p>			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version
4.0

Revision Date:
02.01.2024

SDS Number:
102000000752

Print Date: 03.01.2024
Date of first issue: 05.02.2014

	should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (Respirable dust)	4 mg/m ³	GB EH40
	<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>		

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m ³
	Workers	Inhalation	Acute systemic effects	1091 mg/m ³
	Workers	Inhalation	Acute local effects	246 mg/m ³
	Workers	Skin contact	Long-term systemic effects	75 mg/kg
	Workers	Skin contact	Acute systemic effects	89 mg/kg
	Consumers	Inhalation	Long-term systemic effects	59 mg/m ³
	Consumers	Inhalation	Acute systemic effects	426 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version
4.0

Revision Date:
02.01.2024

SDS Number:
102000000752

Print Date: 03.01.2024
Date of first issue: 05.02.2014

	Consumers	Inhalation	Acute local effects	147 mg/m3
	Consumers	Skin contact	Long-term systemic effects	75 mg/kg
	Consumers	Skin contact	Acute systemic effects	89 mg/kg
	Consumers	Ingestion	Long-term systemic effects	6.3 mg/kg
	Consumers	Ingestion	Acute systemic effects	26.7 mg/kg
propane-1,2-diol	Workers	Inhalation	Long-term systemic effects	168 mg/m3
	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Inhalation	Long-term systemic effects	50 mg/m3
	Consumers	Inhalation	Long-term local effects	10 mg/m3
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-butoxyethanol	Fresh water	8.8 mg/l
	Marine water	0.88 mg/l
	STP	463 mg/l
	Fresh water sediment	34.6 mg/kg
	Marine sediment	3.46 mg/kg
	Soil	2.33 mg/kg
	Sporadic Release	9.1 mg/l
propane-1,2-diol	Secondary Poisoning	20 mg/kg
	Fresh water	260 mg/l
	Marine water	26 mg/l
	Intermittent use/release	183 mg/l
	Fresh water sediment	572 mg/kg
	Marine sediment	57.2 mg/kg
	Soil	50 mg/kg
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Goggles
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use suitable breathing protection if workplace concentration requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	:	liquid
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/range	:	Not applicable
Boiling point/boiling range	:	171 °C
Flammability	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	65 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	6 - 8 Concentration: 100 %
Viscosity, kinematic	:	No data available
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

Vapour pressure : No data available

Vapor Pressure for Components:
2-butoxyethanol : 0.8 hPa (20 °C)

Relative density : No data available

Density : 0.9 - 1.0 g/cm³

Relative vapour density : No data available

Particle characteristics
Particle Size Distribution : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

Toxic if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,707 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4.27 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1,200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute toxicity estimate: 1,200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute toxicity estimate: 1,200 mg/kg
Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Test atmosphere: vapour
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute toxicity estimate: 3 mg/l
Test atmosphere: vapour
Method: Expert judgement

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Aziridine, homopolymer:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after
single ingestion.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

2-butoxyethanol:

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

2-butoxyethanol:

Result : Eye irritation

Aziridine, homopolymer:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Aziridine, homopolymer:

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Aziridine, homopolymer:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 2810
IMDG : UN 2810
IATA : UN 2810

14.2 UN proper shipping name

ADR : TOXIC LIQUID, ORGANIC, N.O.S.
(2-Butoxy-ethanol)
IMDG : TOXIC LIQUID, ORGANIC, N.O.S.
(2-Butoxy-ethanol)
IATA : Toxic liquid, organic, n.o.s.
(2-Butoxy-ethanol)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 6.1	
IMDG	: 6.1	
IATA	: 6.1	

14.4 Packing group

ADR
Packing group : III
Classification Code : T1
Hazard Identification Number : 60
Labels : 6.1
Tunnel restriction code : (E)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

IMDG

Packing group : III
Labels : 6.1
EmS Code : F-A, S-A

IATA (Cargo)

Packing instruction (cargo aircraft) : 663
Packing instruction (LQ) : Y642
Packing group : III
Labels : 6.1

IATA (Passenger)

Packing instruction (passenger aircraft) : 655
Packing instruction (LQ) : Y642
Packing group : III
Labels : 6.1

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 3 2-butoxyethanol (Number on list 3) aluminium powder (stabilised) (Number on list 40) Aziridine, homopolymer (Number on list 3)
--------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	: Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H228	: Flammable solid.
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Flam. Sol.	: Flammable solids
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PRISMASTAR SX-5321

Version	Revision Date:	SDS Number:	Print Date: 03.01.2024
4.0	02.01.2024	102000000752	Date of first issue: 05.02.2014

GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4	H302
Acute Tox. 3	H331
Skin Irrit. 2	H315
Eye Irrit. 2	H319

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN