

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SILVERDREAM Starlight 70 IL
Material number : 007302FX0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cosmetic products

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guntersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Flammable solids, Category 1, H228
Serious eye damage/eye irritation, Category 2A, H319

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

Specific target organ toxicity - single exposure, Category 3,
 Central nervous system, H336

GHS-Labeling

Symbol(s)



Signal word

: Danger

Hazard statements

: H228: Flammable solid.
 H319: Causes serious eye irritation.
 H336: May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P261 Avoid breathing dust.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
 P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P317 If eye irritation persists: Get medical help.
 P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.
 P370 + P378 In case of fire: Use for extinction: Dry sand.
Storage:

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
propan-2-ol	67-63-0

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100
propan-2-ol	67-63-0 200-661-7	Flam. Liq.;2;H225 Acute Tox.;5;H303 Acute Tox.;5;H313 ;2A;H319 STOT SE;3;H336	25 - 50

For the full text of the H-Statements mentioned in this Section, see Section 16.

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

SECTION 4: First aid measures**4.1 Description of first aid measures**

General advice	: Move the victim to fresh air. Move out of dangerous area. Show this safety data sheet to the doctor in attendance.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: Wash off immediately with soap and plenty of water. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

Unsuitable extinguishing media : Carbon dioxide (CO₂), ABC powder, Water, Foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures
6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
 Use personal protective equipment.
 Use personal protective equipment.
 Avoid dust formation.
 Remove all sources of ignition.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.
 Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

This information is not available.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
 Soak up with inert absorbent material (e.g. sand, silica gel,
 acid binder, universal binder, sawdust).
 Do not flush with water.
 Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust
 formation. Ensure adequate ventilation.


Avoid formation of respirable particles. Do not breathe
 vapours/dust. Avoid exposure - obtain special instructions
 before use. Avoid contact with skin and eyes. For personal
 protection see section 8. Smoking, eating and drinking should
 be prohibited in the application area. Provide sufficient air
 exchange and/or exhaust in work rooms. Dispose of rinse
 water in accordance with local and national regulations.

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. Take
 measures to prevent the build up of electrostatic charge. Use
 explosion-proof equipment.

Avoid dust formation. Keep away from open flames, hot
 surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
 Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Page 6 / 19	102000021521	A member of 
-------------	--------------	---

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

- Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from humidity and water. Do not allow to dry.
- Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance			

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

		values, there is no risk of harming the unborn child			
aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
propan-2-ol	67-63-0	AGW	200 ppm 500 mg/m ³	2006-01-01	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	TWA (Respirable)	5 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (total dust)	15 mg/m ³	2012-07-01	
aluminium	7429-90-5	TWA (total)	10 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m ³	2012-07-01	
aluminium	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	PEL (Total dust)	10 mg/m ³	2014-11-26	
aluminium	7429-90-5	PEL (respirable dust fraction)	5 mg/m ³	2014-11-26	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m ³	2008-01-01	
aluminium	7429-90-5	TWA	5 mg/m ³	2005-09-01	
aluminium	7429-90-5	TWA (Total)	15 mg/m ³	1989-01-19	

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

aluminium	7429-90-5	TWA (Respirable fraction)	5 mg/m ³	1989-01-19	
aluminium	7429-90-5	TWA (total dust)	15 mg/m ³	2011-07-01	
aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m ³	2011-07-01	
aluminium	7429-90-5	TWA (Total dust)	15 mg/m ³	1989-01-19	
aluminium	7429-90-5	TWA (respirable dust fraction)	5 mg/m ³	1989-01-19	
aluminium	7429-90-5	TWA (welding fumes)	5 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (pyro powders)	5 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m ³	2013-03-01	
aluminium	7429-90-5	TWA (Fumes)	5 mg/m ³	1989-01-19	
aluminium	7429-90-5	PEL (Welding fumes)	5 mg/m ³	2017-10-02	
aluminium	7429-90-5	PEL (Pyro powders)	5 mg/m ³	2017-10-02	
aluminium	7429-90-5	TWA (powder)	5 mg/m ³	1989-01-19	
propan-2-ol	67-63-0	TWA	200 ppm	2013-03-01	
propan-2-ol	67-63-0	STEL	400 ppm	2013-03-01	
propan-2-ol	67-63-0	TWA	400 ppm 980 mg/m ³	2013-10-08	
propan-2-ol	67-63-0	ST	500 ppm 1 225 mg/m ³	2013-10-08	
propan-2-ol	67-63-0	TWA	400 ppm 980 mg/m ³	1997-08-04	
propan-2-ol	67-63-0	TWA	400 ppm 980 mg/m ³	1989-01-19	
propan-2-ol	67-63-0	STEL	500 ppm 1 225 mg/m ³	1989-01-19	
propan-2-ol	67-63-0	PEL	400 ppm 980 mg/m ³	2014-11-26	
propan-2-ol	67-63-0	STEL	500 ppm 1 225 mg/m ³	2014-11-26	

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

8.2 Exposure controls
Personal protective equipment

- Eye protection : Eye wash bottle with pure water
 : Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
 The exact break through time can be obtained from the protective glove producer and this has to be observed.
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
 Recommended preventive skin protection
 Skin should be washed after contact.
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.
 : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Long sleeved clothing
 Safety shoes
 : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
 : In the case of dust or aerosol formation use respirator with an approved filter.

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

Environmental exposure controls

General advice : The product should not be allowed to enter drains, water courses or the soil.
: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance : Pasty solid

Colour : silver

Odour : characteristic

pH : substance/mixture is non-soluble (in water)

Freezing point : No data available

Boiling point/boiling range : 82 °C

Flash point : No data available

Bulk density : No data available

Flammability (solid, gas) : The substance or mixture is a flammable solid with the category 1.

Auto-flammability : not auto-flammable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Density : 1,3 - 2,0 g/cm³

Solubility(ies)

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive Vapours may form explosive mixture with air.

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.
Contact with acids and alkalis may release hydrogen.
Mixture reacts slowly with water resulting in evolution of hydrogen.
Vapours may form explosive mixture with air.

Stable under recommended storage conditions.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents
Highly halogenated compounds

10.6 Hazardous decomposition products

Other information : No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

propan-2-ol :

Acute oral toxicity : LD50 Rat: > 2 000 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

Skin corrosion/irritation

Product

May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

Product

Eye irritation

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : No data available

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

SECTION 13: Disposal considerations
13.1 Waste treatment methods

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. In accordance with local and national regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum. In accordance with local and national regulations.

SECTION 14: Transport information
14.1 UN number

ADR	: 1325
TDG	: 1325
CFR	: 1325
IMDG	: 1325
IATA	: 1325

14.2 Proper shipping name

ADR	: FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste)
TDG	: FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste)
CFR	: FLAMMABLE SOLIDS, ORGANIC, N.O.S. (Aluminum pigment paste)

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

IMDG : FLAMMABLE SOLID, ORGANIC, N.O.S.
(,Aluminium pigment paste)

IATA : Flammable solid, organic, n.o.s.
Not permitted for transport

14.3 Transport hazard class

ADR : 4.1

TDG : 4.1

CFR : 4.1

IMDG : 4.1

IATA : 4.1

14.4 Packing group**ADR**

Packaging group : II

Classification Code : F1

Hazard Identification Number : 40

Labels : 4.1

Tunnel restriction code : (E)

TDG

Packaging group : II

Labels : 4.1

CFR

Packaging group : II

Labels : 4.1

IMDG

Packaging group : II

Labels : 4.1

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

EmS Number : F-G, S-G

IATA

(Cargo) : Flammable solid, organic, n.o.s. Not permitted for transport

(Passenger) : Flammable solid, organic, n.o.s. Not permitted for transport

Packaging group : II

Labels : 4.1

14.5 Environmental hazards

IMDG :

14.6 Special precautions for user

IMDG Code- segregation group:

: IMDG Code segregation group 15 - Powdered metals

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - Restrictions on the manufacture, placing on : Banned and/or restricted

SILVERDREAM Starlight 70 IL

Version 3.1

Revision Date 04.12.2023

Print Date 10.04.2024

the market and use of certain dangerous substances, (aluminium powder (stabilised))
 mixtures and articles (Annex XVII) (propan-2-ol)
 Regulation (EU) 2019/1148 on the marketing and use of : Listed
 explosives precursors (aluminium powder (stabilised))

15.2 Chemical safety assessment

No data available

SECTION 16: Other information
Full text of H-Statements

H225 : Highly flammable liquid and vapour.
 H228 : Flammable solid.
 H303 : May be harmful if swallowed.
 H313 : May be harmful in contact with skin.
 H319 : Causes serious eye irritation.
 H336 : May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.