

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : Agent Acrylic Brass 180 kgs 14-01013
Material number : 08090125V

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Flammable liquids, Category 2, H225
Acute toxicity, Category 5, Oral, H303
Serious eye damage/eye irritation, Category 2A, H319

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

Specific target organ toxicity - single exposure, Category 3,
Central nervous system, H336
Aspiration hazard, Category 1, H304
Short-term (acute) aquatic hazard, Category 1, H400
Long-term (chronic) aquatic hazard, Category 1, H410

GHS-Labelling

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.
H303: May be harmful if swallowed.
H304: May be fatal if swallowed and enters airways.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
P301 + P316 IF SWALLOWED: Get emergency medical

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

help immediately.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water.

P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P337 + P317 If eye irritation persists: Get medical help.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
acetone	67-64-1
ethyl acetate	141-78-6
Solvent naphtha (petroleum), light arom.	64742-95-6
copper	7440-50-8

SECTION 3: Composition/information on ingredients

Substance No. :

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
acetone	67-64-1 200-662-2	Flam. Liq.;2;H225 Acute Tox.;5;H303 Acute Tox.;5;H313 ;2A;H319 STOT SE;3;H336	25 - 50
ethyl acetate	141-78-6 205-500-4	Flam. Liq.;2;H225 ;2A;H319 STOT SE;3;H336	25 - 50
Solvent naphtha (petroleum), light arom.	64742-95-6 918-668-5	Flam. Liq.;3;H226 Acute Tox.;5;H303 Acute Tox.;5;H313 STOT SE;3;H335, H336 Asp. Tox.;1;H304 Aquatic Chronic;2;H411	10 - 20
Copper	7440-50-8 231-159-6	Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	10 - 20
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	1 - 2,5
Fatty acids, C14-18 and C16-18-	85711-46-2	Skin Irrit.;2;H315	0,1 - 1

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

unsatd., maleated	288-306-2	Skin Sens.;1;H317	
amines, hydrogenated tallow alkyl	61788-45-2 (90640-32-7) 262-976-6	Acute Tox.;5;H303 ;2;H315 ;1;H318 STOT RE;2;H373 Asp. Tox.;1;H304 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	0,0025 - 0,025

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Special powder against metal fire, Dry sand, ABC powder

Unsuitable extinguishing media : Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Standard procedure for chemical fires. Use extinguishing

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

measures that are appropriate to local circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Pick up and transfer to properly labelled containers.
Do not flush with water.

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : General industrial hygiene practice.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities


- Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.
- Dampness : Keep in a dry, cool and well-ventilated place.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

Germany:

Components	CAS-No.	Value type	Control	Update	Basis
Page 9 / 24		102000000036		A member of  ALTANA	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

		(Form of exposure)	parameters		
acetone	67-64-1	TWA	500 ppm 1 210 mg/m ³	2000-06-16	2000/39/EC
Further information		Indicative			
acetone	67-64-1	AGW	500 ppm 1 200 mg/m ³	2015-03-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(I)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	AGW	200 ppm 730 mg/m ³	2017-06-08	DE TRGS 900
Peak-limit: excursion factor (category)		2;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	STEL	400 ppm 1 468 mg/m ³	2017-02-01	2017/164/EU
Further information		Indicative			
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m ³	2017-02-01	2017/164/EU
Further information		Indicative			
Solvent	64742-95-	AGW	100 mg/m ³	2009-02-16	DE TRGS 900

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

naphtha (petroleum), light arom.	6				
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures Commission for dangerous substances See also No. 2.9 of the TRGS 900				
Copper	7440-50-8	AGW (inhalable fraction)	1 mg/m ³		DE TRGS 900
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
maleic anhydride	108-31-6	AGW (Vapour and aerosols)	0,02 ppm 0,081 mg/m ³	2018-06-07	DE TRGS 900
Peak-limit: excursion factor (category)	1; =2.5=(I)				
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). Sum of vapor and aerosols. When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child. Substance sensitizing through the skin and respiratory system				

8.2 Exposure controls

Personal protective equipment

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

- Eye protection : Safety glasses
- : Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Recommended preventive skin protection
Skin should be washed after contact.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
Equipment should conform to EN 14387

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

: In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice

: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Water

: The product should not be allowed to enter drains, water courses or the soil.

:

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: gold
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: 55 °C
Flash point	: -19 °C
Bulk density	: No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: ca. 0,96 g/cm ³
Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: see user defined free text
Viscosity, kinematic	: No data available
Flow time	: 10 - 13 s at 20 °C Cross section: 4 mm Method: DIN 53211

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products :

Other information : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****acetone :**

Acute oral toxicity : LD50 Rabbit: 4 700 - 5 800 mg/kg

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

Mouse: 3 000 mg/kg

Rat: 9 800 mg/kg

Acute inhalation toxicity : LC50 Rat: 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

ethyl acetate :

Acute oral toxicity : Rat: 5 620 mg/kg

Acute inhalation toxicity : LC50 Rat: 56 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 18 000 mg/kg

Solvent naphtha (petroleum), light arom. :

Acute oral toxicity : LD50 Rat: 3 492 mg/kg

SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

Copper :

Acute oral toxicity : The component/mixture is moderately toxic after single ingestion.

amines, hydrogenated tallow alkyl :

Acute oral toxicity : LD50 Rat: > 2 000 - 5 000 mg/kg

Method: OECD Test Guideline 401

Skin corrosion/irritation

Product

May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product

Eye irritation

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity****Components:****acetone (67-64-1) :**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21 600 mg/l

ethyl acetate (141-78-6) :

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

Toxicity to daphnia and other : (Daphnia (water flea)): 717 mg/l
aquatic invertebrates

Solvent naphtha (petroleum), light arom. (64742-95-6) :

Ecotoxicology Assessment

Long-term (chronic) aquatic : Toxic to aquatic life with long lasting effects.
hazard

copper (7440-50-8) :

M-Factor : 10

Ecotoxicology Assessment

Short-term (acute) aquatic : Very toxic to aquatic life.
hazard

Long-term (chronic) aquatic : Very toxic to aquatic life with long lasting effects.
hazard

zinc (7440-66-6) :

Ecotoxicology Assessment

Short-term (acute) aquatic : Very toxic to aquatic life.
hazard

Long-term (chronic) aquatic : Very toxic to aquatic life with long lasting effects.
hazard

Amines, hydrogenated tallow alkyl (61788-45-2) :

Ecotoxicology Assessment

Short-term (acute) aquatic : Very toxic to aquatic life.
hazard

Long-term (chronic) aquatic : Very toxic to aquatic life with long lasting effects.
hazard

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological
information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

- Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

SECTION 14: Transport information**14.1 UN number**

ADR	: 1263
TDG	: 1263
CFR	: 1263
IMDG	: 1263
IATA	: 1263

14.2 Proper shipping name

ADR	: PAINT (,Copper metal powder)
TDG	: PAINT
CFR	: PAINT
IMDG	: PAINT (,Copper metal powder)
IATA	: PAINT

14.3 Transport hazard class

ADR	: 3
TDG	: 3
CFR	: 3
IMDG	: 3
IATA	: 3

14.4 Packing group

ADR	
Packaging group	: II
Classification Code	: F1

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

TDG

Packaging group : II
Labels : 3

CFR

Packaging group : II
Labels : 3

IMDG

Packaging group : II
Labels : 3
EmS Number : F-E, S-E

IATA

Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packaging group : II
Labels : 3

14.5 Environmental hazards

IMDG : Marine pollutant

ADR : Environmentally hazardous

14.6 Special precautions for user

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	: Banned and/or restricted (acetone) (ethyl acetate) (Solvent naphtha (petroleum), light arom.) (xylene)

15.2 Chemical safety assessment

No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Acrylic Brass 180 kgs 14-01013

Version 4.1

Revision Date 03.08.2022

Print Date 07.03.2023

SECTION 16: Other information**Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H303	: May be harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H313	: May be harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.