according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
9.0	27.02.2023	102000023597	Date of first issue: 07.09.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	: METALSTAR PANTONE 877 07 2877 Silver	
Product code	: 056281RC0	

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colorant; Printing ink related material; Printing ink, Colouring
Substance/Mixture		agents, dyes

1.3 Details of the supplier of the safety data sheet

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects. Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

:

Hazard pictograms

Hazard statements



Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version	Revision Date: 27.02.2023	SDS Number:	Print Date: 16.04.2024
9.0		102000023597	Date of first issue: 07.09.2015
Preca	utionary statements	Prevention: P273 Response: P391 Disposal: P501	Avoid release to the environment. Collect spillage. Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	Registration number	1212/2000	
Distillates (petroleum),	64742-46-7	Asp. Tox. 1; H304	>= 10 - < 20
hydrotreated middle; Gasoil —		EUH066	
unspecified	265-148-2		
•	649-221-00-X		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 10 - < 20
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Petroleum resins	64742-16-1	Aquatic Chronic 4; H413	>= 10 - < 20
	265-116-8		
1-isopropyl-2,2-	6846-50-0	Repr. 2; H361d	>= 0.25 - < 1
dimethyltrimethylene diisobutyrate		Aquatic Chronic 3;	
	229-934-9	H412	
	01-2119451093-47		
octadecylamine	124-30-1	Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 0.25 - < 1
	204-695-3	STOT RE 2; H373	
	612-282-00-8	(Liver,	
	01-2119473804-32	Gastrointestinal tract,	
	012113473004 32	Immune system)	
		Asp. Tox. 1; H304	
		Aquatic Acute 1;	
		H400	
		11100	

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version	Revision Date: 27.02.2023	SDS Number:	Print Date: 16.04.2024
9.0		102000023597	Date of first issue: 07.09.2015
			Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures			
General advice :	Move the victim to fresh air.		
	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.		
If inhaled :	Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.		
In case of skin contact :	Wash off immediately with soap and plenty of water.		
In case of eye contact :	Immediately flush eye(s) with plenty of water.		
If swallowed :	Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.		

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand ABC powder

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version 9.0	Revision Date: 27.02.2023	-	DS Number: 2000023597	Print Date: 16.04.2024 Date of first issue: 07.09.2015
			Foam	
Unsuit media	able extinguishing	:	High volume wate Carbon dioxide (C	
			High volume wate	er jet
5.2 Special	hazards arising from	the	e substance or mi	xture
Specif firefigh	ic hazards during nting	:	Do not allow run-o courses.	off from fire fighting to enter drains or water
5.3 Advice for firefighters				
Specia	al protective equipment fighters	:	Wear self-contair necessary.	ed breathing apparatus for firefighting if
Furthe	r information	:	must not be disch Fire residues and be disposed of in Use extinguishing	ted fire extinguishing water separately. This larged into drains. contaminated fire extinguishing water must accordance with local regulations. measures that are appropriate to local d the surrounding environment.

SECTION 6: Accidental release measures

• •	equipment and emergency procedures Evacuate personnel to safe areas.
6.2 Environmental precautions	
Environmental precautions :	The product should not be allowed to enter drains, water courses or the soil.
	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contain	nment and cleaning up
	Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

9.0 27.02.2023 10200023597 Date of first issue: 07.09.2015	Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
	9.0	27.02.2023	102000023597	Date of first issue: 07.09.2015

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage			
7.1 Precautions for safe handling	g		
Advice on safe handling	:	Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.	
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Wash hands before breaks and at the end of workday.	
7.2 Conditions for safe storage,	incl	uding any incompatibilities	
Requirements for storage areas and containers	:	Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.	
		Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.	
Further information on storage conditions	:	Protect from humidity and water.	
Advice on common storage	:	Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.	
Further information on storage stability	:	No decomposition if stored and applied as directed.	

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version	Revision Date:
9.0	27.02.2023

SDS Number: 102000023597

Print Date: 16.04.2024 Date of first issue: 07.09.2015

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		dust)		GB EH40
	inhalable dust when samplin MDHS14/4 G respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that e available for o to the fraction definitions and contain comp should be cor	, S		
	inhalable dust when samplin MDHS14/4 G respirable, the substance has concentration inhalable dust any dust will b levels. Some	t are those fractions of is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or great t or 4 mg.m-3 8-hour be subject to COSHH dusts have been as	bees of these limits, respirable of airborne dust which will be ccordance with the methods sampling and gravimetric ana aerosols., The COSHH defir cludes dust of any kind when beater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du signed specific WELs and explimits., Most industrial dusts	e collected described in lysis or hition of a present at a TWA of s means that ust above these posure to these

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version	Revision Date: 27.02.2023	SDS Number:	Print Date: 16.04.2024
9.0		102000023597	Date of first issue: 07.09.2015
	partic respo distin and 'n mater availa to the	ular particle after entry onse that it elicits, depe- guishes two size fraction respirable'., Inhalable de rial that enters the nose able for deposition in the fraction that penetrate	sizes. The behaviour, deposition and fate of any into the human respiratory system, and the body and on the nature and size of the particle. HSE ons for limit-setting purposes termed 'inhalable' lust approximates to the fraction of airborne e and mouth during breathing and is therefore he respiratory tract. Respirable dust approximates s to the gas exchange region of the lung. Fuller material are given in MDHS14/4., Where dusts

should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

contain components that have their own assigned WEL, all the relevant limits

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health	Value
Substance name	End Use	Exposure routes		value
			effects	
aluminium powder	Workers	Inhalation	Long-term systemic	3.72 mg/m3
(stabilised)			effects	J
	Workers	Inhalation	Long-term local	3.72 mg/m3
			effects	ege
	Consumers	Oral	Long-term systemic	3.95 mg/kg
			effects	0 0
1-isopropyl-2,2-	Workers	Skin contact	Long-term systemic	5.00 mg/kg
dimethyltrimethylene			effects	
diisobutyrate				
	Workers	Inhalation	Long-term systemic	17.62 mg/m3
			effects	11.02 mg/me
	Consumers	Ingestion	Long-term systemic	5.00 mg/kg
		Ŭ	effects	0 0
	Consumers	Skin contact	Long-term systemic	5.00 mg/kg
			effects	
	Consumers	Inhalation	Long-term systemic	4.35 mg/m3
			effects	J J

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value	
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
1-isopropyl-2,2-	Fresh water	0.014 mg/l
dimethyltrimethylene		
diisobutyrate		
	Marine water	0.0014 mg/l
	Fresh water sediment	5.29 mg/kg
	Soil	1.05 mg/kg
	STP	3 mg/l
	Marine sediment	0.529 mg/kg
	oral (secondary poisoning)	83.3 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection Goggles :

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version 9.0	Revision Date: 27.02.2023	SDS Nur 10200002		Print Date: 16.04.2024 Date of first issue: 07.09.2015
	protection	-	ly fitting safe	ety goggles gloves (butyl-rubber)
Rer	narks	conc spec conta the p Pleas break glove cond dang Reco wash shou	Take note of the information given by the producer concerning permeability and break through times, and o special workplace conditions (mechanical strain, duratio contact). The exact break through time can be obtained the protective glove producer and this has to be observe Please observe the instructions regarding permeability a breakthrough time which are provided by the supplier of gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should b washed after contact. The suitability for a specific workp should be discussed with the producers of the protective gloves.	
	nd body protection atory protection	Choo	entration of t suitable brea	ng tection according to the amount and he dangerous substance at the work place. thing protection if workplace concentration

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 100 °C

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Vers 9.0	sion	Revision Date: 27.02.2023		S Number: 2000023597	Print Date: 16.04.2024 Date of first issue: 07.09.2015
	Auto-ig	nition temperature	:	Not relevant	
	Decom	position temperature	:	No data available	9
	рН		:	substance/mixtu	re is non-soluble (in water)
	Viscos Visc	ity cosity, kinematic	:	>21 mm2/s (40	°C)
		ity(ies) er solubility ubility in other solvents		insoluble No data available	e
		n coefficient: n-	:	No data available	9
	octanol/water Vapour pressure		:	No data available	9
	Relativ	e density	:	: No data available	
	Density	/	: No data available		9
	Relativ	e vapour density	: No data available		9
	Par	ticle Size Distribution	:	No data available	e
9.2		n formation a available			

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions Hazardous reactions : Contact with acids and alkalis may release hydrogen. No decomposition if stored and applied as directed. 10.4 Conditions to avoid Conditions to avoid : Do not allow evaporation to dryness. No data available 10.5 Incompatible materials Materials to avoid : Acids Bases

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version 9.0	Revision Date: 27.02.2023	SDS Number: 102000023597	Print Date: 16.04.2024 Date of first issue: 07.09.2015	

Oxidizing agents

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2,000 mg/kg
		Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

:	Rabbit
:	4 h
:	OECD Test Guideline 404
:	No skin irritation
	:

octadecylamine:

Assessment	: Irritating to skin.
//0000011011	. initiating to okin.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species	:	Rabbit
Exposure time	:	72 h
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

/ersion).0	Revision Date: 27.02.2023	SDS Number: 102000023597	Print Date: 16.04.2024 Date of first issue: 07.09.2015
	lecylamine: ssment	: Corrosive	
Resp	iratory or skin sensi	tisation	
-	sensitisation lassified based on ava	ailable information.	
-	iratory sensitisation lassified based on ava	ailable information.	
	n cell mutagenicity lassified based on ava	ailable information.	
	nogenicity lassified based on ava	ailable information.	
<u>Com</u>	ponents:		
Carci	l lates (petroleum), h nogenicity - ssment	: Classified bas	Gasoil — unspecified: sed on the conditions cited in Nota N (Regulation 08, Annex VI, Part 3, Note N)
-	oductive toxicity lassified based on ava	ailable information.	
<u>Com</u>	ponents:		
Repro	propyl-2,2-dimethyltr oductive toxicity - ssment	•	ce of adverse effects on development, based on
	F - single exposure lassified based on ava	ailable information.	
	F - repeated exposur lassified based on ava		
<u>Com</u>	ponents:		
Expo Targe	lecylamine: sure routes et Organs ssment		ve system, Immune system amage to organs through prolonged or repeated

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version	Revision Date: 27.02.2023	SDS Number:	Print Date: 16.04.2024
9.0		102000023597	Date of first issue: 07.09.2015

Components:

octadecylamine:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Further information

Product:

Remarks

: No data available

SECTION 12: Ecological information

12

12.1 Toxicity	
Components:	
Petroleum resins:	
Ecotoxicology Assessment Chronic aquatic toxicity	: May cause long lasting harmful effects to aquatic life.
1-isopropyl-2,2-dimethyltrim	• •
Toxicity to daphnia and other aquatic invertebrates	: (Daphnia (water flea)): 2.46 mg/l
Ecotoxicology Assessment Chronic aquatic toxicity	: Harmful to aquatic life with long lasting effects.
octadecylamine:	
M-Factor (Short-term (acute) aquatic hazard)	: 10
M-Factor (Long-term (chronic) aquatic hazard)	: 10
Ecotoxicology Assessment	
Acute aquatic toxicity	: Very toxic to aquatic life.
Chronic aquatic toxicity	: Very toxic to aquatic life with long lasting effects.
12.2 Persistence and degradabil No data available	lity
12.3 Bioaccumulative potential No data available	
12.4 Mobility in soil No data available	

No data available

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version 9.0	Revision Date: 27.02.2023	•••	DS Number: 02000023597	Print Date: 16.04.2024 Date of first issue: 07.09.2015
12.5 Res	ults of PBT and vPvB a	asse	ssment	
Proc	luct:			
Asse	essment	:	to be either persis	nixture contains no components considered stent, bioaccumulative and toxic (PBT), or not very bioaccumulative (vPvB) at levels of
	ocrine disrupting prop	oertie	25	
12.7 Othe	er adverse effects			
Proc	luct:			
	itional ecological mation	:	unprofessional ha	hazard cannot be excluded in the event of andling or disposal. ife with long lasting effects.

SECTION 13: Disposal considerations

European Waste Catalogue European Waste Catalogue	:	12 01 04 - non-ferrous metal dust and particles 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances
13.1 Waste treatment methods		
Product	:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	:	UN 3082
IMDG	:	UN 3082
ΙΑΤΑ	:	UN 3082
14.2 UN proper shipping name		
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version 9.0	Revision Date: 27.02.2023		S Number: 2000023597	Print Date: 16.04.2024 Date of first issue: 07.09.2015
			(paint related mat	terial)
IMDG		:	ENVIRONMENTA N.O.S. (paint related mat	LLY HAZARDOUS SUBSTANCE, LIQUID
ΙΑΤΑ		:	Environmentally I (paint related mat	nazardous substance, liquid, n.o.s. terial)
14.3 Trans	port hazard class(es)			
			Class	Subsidiary risks
ADR		:	9	
IMDG		:	9	
ΙΑΤΑ		:	9	
14.4 Packi	ng group			
Classi Hazaro Labels Tunnel IMDG Packir Labels EmS O IATA Packir aircraf Packir Packir Labels	I restriction code ng group Code (Cargo) ng instruction (cargo t) ng instruction (LQ) ng group (Passenger)		III M6 90 9 (-) III 9 F-A, S-F 964 Y964 III 9	
(passe Packir	ng instruction enger aircraft) ng instruction (LQ) ng group	:	964 Y964 III 9	
14.5 Envir	onmental hazards			
ADR				
	nmentally hazardous	:	yes	
IMDG Marine	e pollutant		Ves	
	•		yes	
14.6 Speci Remai	al precautions for use	:		gings <=5L / 5 kg, or combination aining inner packagings <= 5L / 5 kg net pe

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
9.0	27.02.2023	102000023597	Date of first issue: 07.09.2015

inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3 Distillates (petroleum), hydrotreated middle; Gasoil — unspecified (Number on list 3) aluminium powder (stabilised) (Number on list 40) 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (Number on list 3) Distillates (petroleum), hydro- treated light; Kerosine — unspecified (Number on list 3)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
2 Chemical actaty, according to		

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H228

Flammable solid.

:

according to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version 9.0	Revision Date: 27.02.2023		DS Number: 2000023597	Print Date: 16.04.2024 Date of first issue: 07.09.2015
H304 H315 H318 H361d H373 H400 H410 H410 H412 H413 EUH06			 May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repea exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life. Repeated exposure may cause skin dryness or cracking. 	
Full te	ext of other abbreviati	ons		
Aquati Asp. T Eye D Flam. Repr. Skin Ir STOT GB EH	am. Sol. rit. RE		UK. EH40 WEL -	c) aquatic hazard age

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Selfaccording to Regulation (EC) No. 1907/2006



METALSTAR PANTONE 877 07 2877 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
9.0	27.02.2023	102000023597	Date of first issue: 07.09.2015

Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture	e:	Classification procedure:
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN