

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STANDART RESIST LT Copper Powder
Material number : 069527C20

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART Suisse SA
Route de la Brasserie 2
1963 Vétroz
Telephone : +410273454800
Telefax : +410273454859
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Acute toxicity, Category 4, Oral, H302
Serious eye damage/eye irritation, Category 2A, H319
Short-term (acute) aquatic hazard, Category 1, H400

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

Long-term (chronic) aquatic hazard, Category 1, H410

GHS-Labeling

Symbol(s)



Signal word

: Warning

Hazard statements

: H302: Harmful if swallowed.
H319: Causes serious eye irritation.
H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear eye protection/ face protection.
Response:
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P391 Collect spillage.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

| | |
|-----------------|-----------|
| Identification | CAS-No. |
| copper | 7440-50-8 |
| silicon dioxide | 7631-86-9 |

Other hazards which do not result in classification

Combustible Solids

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

SECTION 3: Composition/information on ingredients

Substance No. : EINECS-No. : 231-159-6

Hazardous components

| Chemical name | CAS-No. EINECS-No. | Classification and labelling | Concentration[%] |
|-----------------|------------------------|------------------------------------------------------------------------------------|------------------|
| Copper | 7440-50-8 231-159-6 | Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410 | 50 - 100 |
| silicon dioxide | 7631-86-9 231-545-4 | Acute Tox.;5;H303 | 1 - 10 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.
Do not leave the victim unattended.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

If swallowed

If eye irritation persists, consult a specialist.
: Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Special powder against metal fire, Dry sand, ABC powder

Unsuitable extinguishing media : Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Evacuate personnel to safe areas.
Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Pick up and transfer to properly labelled containers.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid creating dust. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Avoid dust formation.

Hygiene measures : General industrial hygiene practice. Do not smoke. Wash hands before breaks and at the end of workday. Keep away from food and drink. Keep away from tobacco products.

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards.

Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

Dampness : Keep in a dry, cool and well-ventilated place.

Other data : Keep in a dry place. No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Update | Basis |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|---------------------|------------|-------------|
| Copper | 7440-50-8 | AGW (inhalable fraction) | 1 mg/m ³ | | DE TRGS 900 |
| silicon dioxide | 7631-86-9 | AGW (Inhalable fraction) | 4 mg/m ³ | 2013-09-19 | DE TRGS 900 |
| Further information | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, silicagel). When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | | |

United States of America (USA):

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Update | Basis |
|------------|-----------|----------------------------------|---------------------|------------|-------|
| Copper | 7440-50-8 | TWA | 1 mg/m ³ | 2008-01-01 | |
| Copper | 7440-50-8 | TWA (dust and mists) | 1 mg/m ³ | 2005-09-01 | |
| Copper | 7440-50-8 | TWA | 1 mg/m ³ | 1989-01-19 | |

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

| | | | | | |
|-----------------|-----------|-----------------------|------------------------------------------|------------|--|
| Copper | 7440-50-8 | TWA | 0,2 mg/m ³ | 2008-01-01 | |
| Copper | 7440-50-8 | TWA | 0,1 mg/m ³ | 1989-01-19 | |
| Copper | 7440-50-8 | TWA (Dust and mist) | 1 mg/m ³ | 2010-03-01 | |
| Copper | 7440-50-8 | TWA (Fumes) | 0,2 mg/m ³ | 2010-03-01 | |
| Copper | 7440-50-8 | TWA (Dust) | 1 mg/m ³ | 2013-10-08 | |
| Copper | 7440-50-8 | TWA (Mist) | 1 mg/m ³ | 2013-10-08 | |
| Copper | 7440-50-8 | TWA (dusts and mists) | 1 mg/m ³ | 2011-07-01 | |
| Copper | 7440-50-8 | TWA (Fumes) | 0,1 mg/m ³ | 2011-07-01 | |
| Copper | 7440-50-8 | TWA (Fumes) | 0,1 mg/m ³ | 1989-01-19 | |
| Copper | 7440-50-8 | TWA (Dust and mist) | 1 mg/m ³ | 1989-01-19 | |
| Copper | 7440-50-8 | PEL (Fumes) | 0,1 mg/m ³ | 2014-11-26 | |
| silicon dioxide | 7631-86-9 | TWA (Dust) | 20 Million particles per cubic foot | 2012-07-01 | |
| silicon dioxide | 7631-86-9 | TWA (Dust) | 80 mg/m ³ / %SiO ₂ | 2012-07-01 | |
| silicon dioxide | 7631-86-9 | TWA | 6 mg/m ³ | 2013-10-08 | |
| silicon dioxide | 7631-86-9 | PEL | 6 mg/m ³ | 2014-11-26 | |

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses
 : Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Leather
 Remarks : Leather gloves

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

- The exact break through time can be obtained from the protective glove producer and this has to be observed.
- Recommended preventive skin protection
- Skin and body protection :
- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
 - : Long sleeved clothing
 - : Safety shoes
 - : Dust impervious protective suit
- Respiratory protection :
- : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 - : Use suitable breathing protection if workplace concentration requires.
 - : Respirator with a dust filter
 - : P1 filter

Environmental exposure controls

- General advice :
- : Prevent product from entering drains.
 - : Prevent further leakage or spillage if safe to do so.
 - : If the product contaminates rivers and lakes or drains inform respective authorities.
- Water :
- : The product should not be allowed to enter drains, water courses or the soil.
 - :

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

- Appearance : powder
- Colour : copper
- Odour : odourless
- pH : substance/mixture is non-soluble (in water)

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

| | |
|----------------------------------------|-----------------------------|
| Freezing point | : No data available |
| Boiling point/boiling range | : 2 597 °C |
| Flash point | : No data available |
| Bulk density | : No data available |
| Flammability (solid, gas) | : Combustible Solids |
| Auto-flammability | : No data available |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapour pressure | : No data available |
| Density | : ca. 8,7 g/cm ³ |
| Solubility(ies) | |
| Water solubility | : immiscible |
| Miscibility with water | : immiscible |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Ignition temperature | : No data available |
| Thermal decomposition | : No data available |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : No data available |
| Flow time | : No data available |

9.2 Other information

No data available

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

No decomposition if stored and applied as directed.**10.2 Chemical stability**

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactionsHazardous reactions : Stable under recommended storage conditions., No hazards
to be specially mentioned.

No decomposition if stored and applied as directed.

Dust may form explosive mixture in air.

10.4 Conditions to avoidConditions to avoid : No data available
No data available**10.5 Incompatible materials**

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : No data available

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

Acute toxicity**Components:****Copper :**Acute oral toxicity : The component/mixture is moderately toxic after single
ingestion.**silicon dioxide :**

Acute oral toxicity : LD50 Rat: 5 000 mg/kg

Mouse: 15 000 mg/kg

Acute inhalation toxicity : Rat: 0,139 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5 000 mg/kg

Skin corrosion/irritation**Product**

May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation**Product**

Eye irritation

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product

No data available

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

SECTION 12: Ecological information**12.1 Toxicity****Components:****copper (7440-50-8) :**

M-Factor : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

silicon dioxide (7631-86-9) :

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 7 600 mg/l

Toxicity to algae : (Chlorella pyrenoidosa (aglae)): 440 mg/l
Exposure time: 72 h**12.2 Persistence and degradability**

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

12.6 Other adverse effects
Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations
13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.
 In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.
 In accordance with local and national regulations.

SECTION 14: Transport information
14.1 UN number
ADR : 3077

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG : 3077

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

IATA : 3077**14.2 Proper shipping name****ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Copper metal powder)**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(,Copper metal powder)**IATA** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Copper metal powder)**14.3 Transport hazard class****ADR** : 9**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : 9**IATA** : 9**14.4 Packing group****ADR**

Packaging group : III

Classification Code : M7

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

Hazard Identification Number : 90

Labels : 9

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Packaging group : III

Labels : 9

EmS Number : F-A, S-F

IATAPacking instruction (cargo
aircraft) : 956Packing instruction
(passenger aircraft) : 956

Packing instruction (LQ) : Y956

Packaging group : III

Labels : 9

14.5 Environmental hazards**IMDG** : Marine pollutant**ADR** : Environmentally hazardous**14.6 Special precautions for user****IMDG Code- segregation group:**

: IMDG Code segregation group 7 - Heavy metals and their salts

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H303 : May be harmful if swallowed.
H319 : Causes serious eye irritation.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

STANDART RESIST LT Copper Powder

Version 6.0

Revision Date 20.01.2021

Print Date 15.04.2024

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.