

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : HK9224 RP UNIPAK 450 PALE LITHO INK
Material number : 014233RN0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guntersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Acute toxicity, Category 4, Oral, H302
Skin corrosion/irritation, Category 3, H316
Serious eye damage/eye irritation, Category 2A, H319

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Reproductive toxicity, Category 2, H361d
 Short-term (acute) aquatic hazard, Category 1, H400
 Long-term (chronic) aquatic hazard, Category 1, H410

GHS-Labeling

Symbol(s)



Signal word

: Warning

Hazard statements

: H302: Harmful if swallowed.
 H316: Causes mild skin irritation.
 H319: Causes serious eye irritation.
 H361d: Suspected of damaging the unborn child.
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
 P203 Obtain, read and follow all safety instructions before use.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
 P301 + P317 + P330 IF SWALLOWED: Get medical help. Rinse mouth.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P318 IF exposed or concerned, get medical advice.
 P332 + P317 If skin irritation occurs: Get medical help.
 P337 + P317 If eye irritation persists: Get medical help.
 P391 Collect spillage.
Storage:
 P405 Store locked up.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
copper	7440-50-8
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
copper	7440-50-8 231-159-6	Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	25 - 50
Distillates (petroleum), hydrotreated middle	64742-46-7 265-148-2	Asp. Tox.;1;H304	10 - 20
Petroleum resins	64742-16-1 265-116-8	Aquatic Chronic;4;H413	2,5 - 10
zinc	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	2,5 - 10

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9	Repr.;2;H361d Aquatic Chronic;3;H412	1 - 2,5
manganese neodecanoate	27253-32-3 248-374-6	;2;H315	1 - 10
octadecylamine	124-30-1 204-695-3	;2;H315 ;1;H318 STOT RE;2;H373 Asp. Tox.;1;H304 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	0,25 - 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

	<p>If skin irritation persists, call a physician. If on clothes, remove clothes.</p>
In case of eye contact	<p>: Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.</p>
If swallowed	<p>: Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.</p>

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.


SECTION 5: Firefighting measures
5.1 Extinguishing media

Suitable extinguishing media	: Special powder against metal fire, Dry sand, ABC powder
Unsuitable extinguishing media	: Water, High volume water jet, Carbon dioxide (CO ₂)

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
--------------------------------------	---

5.3 Advice for firefighters

Page 5 / 21	102000000158	A member of 
-------------	--------------	---

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Pick up and transfer to properly labelled containers.
Do not flush with water.

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.
- Dampness : Keep in a dry, cool and well-ventilated place.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
copper	7440-50-8	AGW (inhalable fraction)	1 mg/m ³		DE TRGS 900
Distillates (petroleum), hydrotreated middle	64742-46-7	AGW	600 mg/m ³	2009-02-16	DE TRGS 900
Peak-limit: excursion		2;(II)			

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

factor (category)					
Further information		Group exposure limit for hydrocarbon solvent mixtures Commission for dangerous substances See also No. 2.9 of the TRGS 900			
zinc	7440-66-6	AGW (Inhalable fraction)	10 mg/m ³	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
zinc	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m ³	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Soybean oil	8001-22-7	AGW (Alveolar fraction)	5 mg/m ³	2022-05-31	DE TRGS 900
Peak-limit: excursion factor (category)		4;(II)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Polyethylene	9002-88-4	AGW (Inhalable fraction)	10 mg/m ³	2020-03-30	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Polyethylene	9002-88-4	AGW (Alveolate fraction)	1,25 mg/m ³	2020-03-30	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			

8.2 Exposure controls

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Personal protective equipment

- Eye protection : Safety glasses
- : Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Recommended preventive skin protection
Skin should be washed after contact.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Respiratory protection : Use suitable breathing protection if workplace concentration requires.
Equipment should conform to EN 14387

Environmental exposure controls

General advice : The product should not be allowed to enter drains, water courses or the soil.

: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance : liquid

Colour : gold

Odour : characteristic

pH : substance/mixture is non-soluble (in water)

Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 100 °C

Bulk density : No data available

Flammability (solid, gas) : No data available

Auto-flammability : No data available

Upper explosion limit : No data available

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 21 mm ² /s (40 °C)
Flow time	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition productsHazardous decomposition
products :Other information : Carbon monoxide, carbon dioxide and unburned
hydrocarbons (smoke).

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****copper :**Acute oral toxicity : The component/mixture is moderately toxic after single
ingestion.**Skin corrosion/irritation****Product**

May cause skin irritation and/or dermatitis.

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Serious eye damage/eye irritation

Product

May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

No data available

SECTION 12: Ecological information
12.1 Toxicity
Components:
copper (7440-50-8) :

M-Factor : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Petroleum resins (64742-16-1) :
Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : May cause long lasting harmful effects to aquatic life.

zinc (7440-66-6) :
Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (6846-50-0) :

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 2,46 mg/l

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

octadecylamine (124-30-1) :

M-Factor : 10

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information**14.1 UN number****ADR** : 3082**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : 3082**IATA** : 3082**14.2 Proper shipping name****ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Copper metal powder)**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

IATA : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
 N.O.S.
 (Copper metal powder)
 (Copper metal powder)

14.3 Transport hazard class**ADR** : 9**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : 9**IATA** : 9**14.4 Packing group****ADR**

Packaging group : III

Classification Code : M6

Hazard Identification Number : 90

Labels : 9

Tunnel restriction code : (-)

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Packaging group : III

Labels : 9

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

IATA

Packing instruction (cargo aircraft) : 964

Packing instruction (passenger aircraft) : 964

Packing instruction (LQ) : Y964

Packaging group : III

Labels : 9

14.5 Environmental hazards**ADR** : Environmentally hazardous**IMDG** : Marine pollutant**14.6 Special precautions for user**

For single packagings ≤5L / 5 kg, or combination packagings containing inner packagings ≤ 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Banned and/or restricted (Distillates (petroleum), hydrotreated middle; Gasoil — unspecified) (1-isopropyl-2,2-dimethyltrimethylene diisobutyrate) (manganese neodecanoate) (Distillates (petroleum), hydro-treated light; Kerosine — unspecified)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information
Full text of H-Statements

H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H316	: Causes mild skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H361d	: Suspected of damaging the unborn child.

HK9224 RP UNIPAK 450 PALE LITHO INK

Version 7.0

Revision Date 27.02.2023

Print Date 28.02.2023

H373	: May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.