according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 31.05.2023
3.1	30.05.2023	102000030620	Date of first issue: 19.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Trade name	: STAPA 22 n.l. Aluminium Paste

Product code : 054602G60

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	
Substance/Mixture	

: Colouring agents, pigments

1.3 Details of the supplier of the safety data sheet

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein	
Telephone	: +499152770	
Telefax	: +499152777008	
E-mail address of person responsible for the SDS	: msds.eckart@altana.com	<u>m</u>

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)					
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.				
2.2 Label elements					
Labelling (REGULATION (EC) No 1272/2	2008)				
Hazard statements : H412	Harmful to aquatic life with long lasting effects.				
Precautionary statements : Preventionary Statements : P273 Disposa	Avoid release to the environment.				

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 31.05.2023	
3.1	30.05.2023	102000030620	Date of first issue: 19.03.2019	

P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Naphtha (petroleum),	64742-48-9	Asp. Tox. 1; H304	>= 10 - < 20
hydrotreated heavy; Low boiling		EUH066	
point ydrogen treated naphtha	918-481-9		
	01-2119457273-39		
Solvent naphtha (petroleum), light	64742-95-6	Flam. Liq. 3; H226	>= 10 - < 20
arom.		STOT SE 3; H336	
	918-668-5	(Central nervous	
	01-2119455851-35	system)	
		STOT SE 3; H335	
		(Respiratory system)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	
		EUH066	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

: Move the victim to fresh air.

Do not leave the victim unattended.

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version 3.1	Revision Date: 30.05.2023	SDS Number: 102000030620		Print Date: 31.05.2023 Date of first issue: 19.03.2019	
If inhaled		l a	dvice.	air. ace in recovery position and seek medical ist, call a physician.	
In case of skin contact		: \	Vash off immedia	ately with soap and plenty of water.	
In case of eye contact		: Immediately flush eye(s) with plenty of water.			
			Remove contact I f eye irritation pe	enses. rsists, consult a specialist.	
lf swa	allowed	D N	lever give anythi	tract clear. or alcoholic beverages. ng by mouth to an unconscious person. ist, call a physician.	

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	Water Foam ABC powder Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during : firefighting		Do not allow run-off from fire fighting to enter drains or water courses.
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Use personal protective equipment.
		Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version 3.1	Revision Date: 30.05.2023		DS Number: 2000030620	Print Date: 31.05.2023 Date of first issue: 19.03.2019
			circumstances	and the surrounding environment.
SECTION	N 6: Accidental rele	ease i	neasures	
6.1 Perso	nal precautions, prot	tectiv	e equipment an	d emergency procedures
Personal precautions :		Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition. Avoid dust formation.		
6.2 Enviro	onmental precaution	s		
		:	The product sh courses or the	ould not be allowed to enter drains, water soil.
				ct from entering drains. contaminates rivers and lakes or drains inform norities.
6 3 Mothe	ods and material for o	contai	nment and clea	ining un
	ods for cleaning up			al handling equipment.

Methods for cleaning up	: Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
	Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling Keep away from heat and sources of ignition. : Avoid dust formation. Ensure adequate ventilation. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Advice on protection against Keep away from open flames, hot surfaces and sources of 1 fire and explosion ignition. Earthing of containers and apparatuses is essential. Provide appropriate exhaust ventilation at places where dust is formed.

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version 3.1	Revision Date: 30.05.2023	SDS Number: 102000030620	Print Date: 31.05.2023 Date of first issue: 19.03.2019
Hygie	ene measures	: General inc	dustrial hygiene practice.
7.2 Condi	tions for safe storage,	including any i	ncompatibilities
	Requirements for storage areas and containers		ginal container. Keep containers tightly closed in a rentilated place. Keep container closed when not in away from sources of ignition - No smoking.
		kept uprigh	which are opened must be carefully resealed and t to prevent leakage. Electrical installations / aterials must comply with the technological safety
	er information on ge conditions	: Protect from	n humidity and water. Do not allow to dry.
Advic	e on common storage	Never allov storage. Keep away strongly ac	e together with oxidizing and self-igniting products. v product to get in contact with water during from oxidizing agents, strongly alkaline and id materials in order to avoid exothermic reactions. Is to be especially mentioned.
stora	er information on ge stability fic end use(s)		position if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis			
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40			
		TWA (Respirable fraction)	4 mg/m3	GB EH40			
		TWA (inhalable dust)	10 mg/m3	GB EH40			
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these						

according to Regulation (EC) No. 1907/2006



STAPA 22 n.I. Aluminium Paste

Version 3.1	Revision Date: 30.05.2023	SDS Number: 102000030620	Print Date: 31.05.2023 Date of first issue: 19.0			
	mus part part resp dist and mat ava to tl defi con sho	st comply with the approp icles of a wide range of s icular particle after entry ponse that it elicits, depending inguishes two size fraction 'respirable'., Inhalable du erial that enters the nose ilable for deposition in the ne fraction that penetrates nitions and explanatory in tain components that have uld be complied with., Wil- gure three times the long-		al dusts contain osition and fate of any y system, and the body of the particle. HSE es termed 'inhalable' action of airborne ing and is therefore able dust approximates ion of the lung. Fuller S14/4., Where dusts L, all the relevant limits n exposure limit is listed d be used.		
	inha whe MD res sub con inha any leve mus part part res dist and mat ava to tt defi con	a figure three times the long-term exposure limit should be used. TWA (Respirable dust) 4 mg/m3 GB EH40 Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed.				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Naphtha (petroleum), hydrotreated heavy; Low boiling point	Workers	Inhalation	Acute systemic effects	1500 mg/m3

according to Regulation (EC) No. 1907/2006



STAPA 22 n.I. Aluminium Paste

Version 3.1	Revision Date: 30.05.2023	SDS Nui 1020000		Date: 31.05.2023 of first issue: 19.03.2019	
ydrog naph	gen treated tha				
		Workers	Skin contact	Long-term systemic effects	300 mg/kg
		Consumers	Ingestion	Long-term systemic effects	300 mg/kg
		Consumers	Skin contact	Long-term systemic effects	300 mg/kg
		Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	ent naphtha oleum), light	Workers	Inhalation	Long-term systemic effects	150 mg/m3
		Workers	Skin contact	Long-term systemic effects	25 mg/kg
		Consumers	Skin contact	Long-term systemic effects	11 mg/kg
		Consumers	Inhalation	Long-term systemic effects	32 mg/m3
		Consumers	Inhalation	Long-term local effects	11 mg/kg
		Consumers	Ingestion	Long-term systemic effects	11 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

-									
Personal protective equip	Personal protective equipment								
Eye/face protection Hand protection	: Safety glasses								
Material	: Solvent-resistant gloves								
Remarks	 Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves. 								
Skin and body protection	: Long sleeved clothing Safety shoes								

according to Regulation (EC) No. 1907/2006



STAPA 22 n.I. Aluminium Paste

Version	Revision Date: 30.05.2023	SDS Number:	Print Date: 31.05.2023
3.1		102000030620	Date of first issue: 19.03.2019
Resp	iratory protection	concentration of Protective suit	rotection according to the amount and of the dangerous substance at the work place. eathing protection if workplace concentration

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state		:	Pasty solid
Colour		:	silver
Odour		:	characteristic
Odour Thresh	nold	:	No data available
Freezing poir	nt	:	No data available
Boiling point/	boiling range	:	140 - 200 °C
Flammability		:	Combustible Solids
Upper explos flammability l	ion limit / Upper imit	:	No data available
Lower explos flammability I	ion limit / Lower imit	:	No data available
Flash point		:	No data available
Auto-ignition	temperature	:	Not relevant
Decompositio	on temperature	:	No data available
рН		:	substance/mixture is non-soluble (in water)
Viscosity,	kinematic	:	No data available
Solubility(ies) Water solu Solubility i		:	insoluble No data available
Partition coef		:	No data available
Vapour press		:	No data available
Relative dens	sity	:	No data available
Density		:	1.3 - 2.0 g/cm3

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version 3.1	Revision Date: 30.05.2023	SDS Number: 102000030620	Print Date: 31.05.2023 Date of first issue: 19.03.2019	
	ive vapour density article Size Distribution	: No data av	ailable	
9.2 Other information Explosives		: Not explos	ive	
Self-i	gnition	: not auto-fla	ammable	
Misci	bility with water	: immiscible		

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	 Reacts with alkalis, acids, halogenes and oxidizing age Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution o hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions. No hazards to be specially mentioned. 	
10.4 Conditions to avoid			
Conditions to avoid		Do not allow to dry.	
		No data available	
10.5 Incompatible materials			
Materials to avoid	:	Acids Bases Oxidizing agents Highly halogenated compounds	

10.6 Hazardous decomposition products

This information is not available.

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 31.05.2023
3.1	30.05.2023	102000030620	Date of first issue: 19.03.2019

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Acute oral toxicity

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha: : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity	:	LC50 (Rat): Test atmosphere: vapour Remarks: An LC50/inhalation/4h/rat could not be determined
		because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg
-----------------------	--------------------------------

Solvent naphtha (petroleum), light arom .:

Acute oral toxicity	:	LD50 (Rat): 3,492 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 3,160 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha: Result : Repeated exposure may cause skin dryness or cracking.

Solvent naphtha (petroleum), light arom .:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 31.05.2023
3.1	30.05.2023	102000030620	Date of first issue: 19.03.2019

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Germ cell mutagenicity-	:	Classified based on benzene content < 0.1% (Regulation (EC)
Assessment		1272/2008, Annex VI, Part 3, Note P)

Solvent naphtha (petroleum), light arom .:

Germ cell mutagenicity-
Assessment: Classified based on benzene content < 0.1% (Regulation (EC)
1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Carcinogenicity -	:	Classified based on benzene content < 0.1% (Regulation (EC)
Assessment		1272/2008, Annex VI, Part 3, Note P)

Solvent naphtha (petroleum), light arom.:

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.:

Assessment

: May cause respiratory irritation., May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 31.05.2023
3.1	30.05.2023	102000030620	Date of first issue: 19.03.2019

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha: May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum), light arom.: May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Further information

Product:

Remarks

: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Solvent naphtha (petroleum), light arom .:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

A member of **C ALTANA**

according to Regulation (EC) No. 1907/2006



STAPA 22 n.I. Aluminium Paste

Vers 3.1	ion	Revision Date: 30.05.2023		DS Number:)2000030620	Print Date: 31.05.2023 Date of first issue: 19.03.2019	
	Additio informa	nal ecological ation	:	unprofessional ha	I hazard cannot be excluded in the event of andling or disposal. c life with long lasting effects.	
	Comp	onents:				
	Napht	na (petroleum), hydro	otrea	ated heavy; Low b	oiling point ydrogen treated naphtha:	
	Additio informa	nal ecological ation	:	No data available		
SEC	TION	13: Disposal consid	der	ations		
		ean Waste Catalogue ean Waste Catalogue	:		rrous metal dust and particles particulates and dust (including ball-mill dust) dous substances	
13.1	Waste	treatment methods				
	Produc	t	:	The product should not be allowed to enter drains, water courses or the soil.		
SEC	TION	14: Transport infor	ma	tion		
14.1	UN nu	mber or ID number				
	ADR		:	Not regulated as	a dangerous good	
	IMDG		:	: Not regulated as a dangerous good		
	ΙΑΤΑ		:	Not regulated as a dangerous good		

14.2 UN proper shipping name

	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.3	3 Transport hazard class(es)		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.4	4 Packing group		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version 3.1	Revision Date: 30.05.2023	SDS Number: 102000030620	Print Date: 31.05.2023 Date of first issue: 19.03.2019		
ΙΑΤΑ	(Passenger)	: Not regulate	ed as a dangerous good		
	14.5 Environmental hazards Not regulated as a dangerous good				
14.6 Spec	ial precautions for u	ser			
Rema	arks	: Not classifie regulations.	ed as dangerous in the meaning of transport		
14.7 Maritime transport in bulk according to IMO instruments Not applicable for product as supplied.					

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha (Number on list 3) Solvent naphtha (petroleum), light arom. (Number on list 3)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H228	:	Flammable solid.
H304	:	May be fatal if swallowed and enters airways.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 31.05.2023
3.1	30.05.2023	102000030620	Date of first issue: 19.03.2019

Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Flam. Liq.	:	Flammable liquids
Flam. Sol.	:	Flammable solids
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response: GHS - Globally Harmonized System; GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory: TRGS - Technical Rule for Hazardous Substances: TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification procedure:

Classification of the mixture: Aquatic Chronic 3 H412

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

according to Regulation (EC) No. 1907/2006



STAPA 22 n.l. Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 31.05.2023
3.1	30.05.2023	102000030620	Date of first issue: 19.03.2019

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN