according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version | Revision Date: | SDS Number: | Print Date: 28.02.2023 |
|---------|----------------|--------------|---------------------------------|
| 6.0 | 27.02.2023 | 102000000707 | Date of first issue: 02.01.2014 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

| 1.1 Product identifier | | |
|------------------------|---|-----------------------------------|
| Trade name | : | METALSTAR SuperEco 10 2004 Silver |
| Product code | : | 053152RC0M1 |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Referant identified uses of the substance of mixture and uses advised against | | | |
|---|---|--|--|
| Use of the | : | Colorant; Printing ink related material; Printing ink, Colouring | |
| Substance/Mixture | | agents, dyes | |

1.3 Details of the supplier of the safety data sheet

| Company | : | ECKART GmbH Guentersthal 4 91235 Hartenstein |
|--|---|--|
| Telephone | : | +499152770 |
| Telefax | : | +499152777008 |
| E-mail address of person responsible for the SDS | : | msds.eckart@altana.com |

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

| Classification (REGULATION (EC) No 1272/2008) | |
|---|--|
|---|--|

Eye irritation, Category 2 H319: Causes serious eye irritation.

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects. Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version 6.0 | Revision Date: 27.02.2023 | - | SDS Number: 02000000707 | Print Date: 28.02.2023 Date of first issue: 02.01.2014 |
|----------------|------------------------------|---|---|--|
| Haza | rd pictograms | : | | ¥2 |
| Signa | l word | : | Warning | |
| Haza | rd statements | : | H319 H411 | Causes serious eye irritation. Toxic to aquatic life with long lasting effects. |
| Preca | autionary statements | : | Prevention: P264 P273 P280 Response: P337 + P313 P391 Disposal: P501 | Wash skin thoroughly after handling. Avoid release to the environment. Wear eye protection/ face protection. If eye irritation persists: Get medical advice/ attention. Collect spillage. Dispose of contents/ container to an approved waste disposal plant. |

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

| Components | | | |
|-------------------------------|--------------------------------|---|--------------------------|
| Chemical name | CAS-No. EC-No. Index-No. | ClassificationREGUL ATION (EC) No 1272/2008 | Concentration (% w/w) |
| | Registration number | | |
| aluminium powder (stabilised) | 7429-90-5 | Flam. Sol. 1; H228 | >= 10 - < 20 |
| | 231-072-3 | | |
| | 013-002-00-1 | | |
| | 01-2119529243-45 | | |
| manganese neodecanoate | 27253-32-3 | Acute Tox. 4; H302 Skin Irrit. 2; H315 | >= 1 - < 10 |
| | 248-374-6 | | |
| octadecylamine | 124-30-1 | Skin Irrit. 2; H315 Eye Dam. 1; H318 | >= 1 - < 2.5 |
| | 204-695-3 | STOT RE 2; H373 | |
| | 612-282-00-8 | (Liver, | |
| | 01-2119473804-32 | Gastrointestinal tract, | |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Number: 102000000707 | Print Date: 28.02.2023 Date of first issue: 02.01.2014 | |
|----------------|---------------------------|-----------------------------|---|--|
| | | | Immune system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10 | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

| 4.1 Description of first aid measures | | | | | |
|---------------------------------------|---|---|--|--|--|
| General advice | : | Move the victim to fresh air. | | | |
| | | Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. | | | |
| If inhaled | : | Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. | | | |
| In case of skin contact | : | Wash off immediately with soap and plenty of water. | | | |
| | | If skin irritation persists, call a physician. If on clothes, remove clothes. | | | |
| In case of eye contact | : | Immediately flush eye(s) with plenty of water. | | | |
| | | Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. | | | |
| If swallowed | : | Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. | | | |

4.2 Most important symptoms and effects, both acute and delayed

| Risks | : Causes serious eye irritation. |
|-------|----------------------------------|
|-------|----------------------------------|

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version | Revision Date: | SDS Number: | Print Date: 28.02.2023 |
|---------|----------------|--------------|---------------------------------|
| 6.0 | 27.02.2023 | 102000000707 | Date of first issue: 02.01.2014 |

4.3 Indication of any immediate medical attention and special treatment needed This information is not available.

SECTION 5: Firefighting measures

| 5.1 Extinguishing media | | | | |
|--|-----|---|--|--|
| Suitable extinguishing media | : | Dry sand ABC powder Foam | | |
| Unsuitable extinguishing media | : | High volume water jet Carbon dioxide (CO2) | | |
| | | High volume water jet | | |
| 5.2 Special hazards arising from | the | e substance or mixture | | |
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. | | |
| 5.3 Advice for firefighters | | | | |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. | | |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. | | |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, protect | ive | e equipment and emergency procedures |
|-----------------------------------|-----|--|
| Personal precautions | : | Evacuate personnel to safe areas. Use personal protective equipment. |
| 6.2 Environmental precautions | | |
| Environmental precautions : | : | The product should not be allowed to enter drains, water courses or the soil. |
| | | Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version | Revision Date: | SDS Number: | Print Date: 28.02.2023 |
|---------|----------------|-------------|---------------------------------|
| 6.0 | 27.02.2023 | 10200000707 | Date of first issue: 02.01.2014 |

6.3 Methods and material for containment and cleaning up

| Methods for cleaning up | : Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). |
|-------------------------|--|
| | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. |

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Advice on safe handling | : | Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. |
|---|---|--|
| Advice on protection against fire and explosion | : | Normal measures for preventive fire protection. |
| Hygiene measures | : | When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. |

7.2 Conditions for safe storage, including any incompatibilities

| U , | | |
|---|---|---|
| Requirements for storage areas and containers | : | Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use. |
| | | Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards. |
| Further information on storage conditions | : | Protect from humidity and water. |
| Advice on common storage | : | Do not store near acids. |
| | | |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version 6.0 | Revision Date: 27.02.2023 | | DS Number:)2000000707 | Print Date: 28.02.2023 Date of first issue: 02.01.2014 |
|----------------|-----------------------------------|---|--|--|
| | | | Never allow proc storage. Keep away from | ether with oxidizing and self-igniting products. luct to get in contact with water during oxidizing agents, strongly alkaline and terials in order to avoid exothermic reactions. |
| | ther information on age stability | : | No decompositio | n if stored and applied as directed. |

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|----------------------------------|---|---|---|--|
| aluminium powder (stabilised) | 7429-90-5 | TWA (Inhalable) | 10 mg/m3 | GB EH40 |
| | | TWA (Respirable fraction) | 4 mg/m3 | GB EH40 |
| | | TWA (inhalable dust) | 10 mg/m3 | GB EH40 |
| | inhalable dus when samplin MDHS14/4 G respirable, the substance ha concentration inhalable dus any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that of available for of to the fraction definitions an contain comp should be cor | t are those fractions of ig is undertaken in ac- eneral methods for s- bracic and inhalable zardous to health ind- in air equal to or grea- t or 4 mg.m-3 8-hour be subject to COSHF dusts have been ass- with the appropriate wide range of sizes. ticle after entry into the it elicits, depend on two size fractions for e'., Inhalable dust ap- enters the nose and deposition in the resp that penetrates to the d explanatory material onents that have the nplied with., Where r times the long-term TWA (Respirable | ses of these limits, respirable of airborne dust which will be ccordance with the methods ampling and gravimetric ana aerosols., The COSHH defin cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du signed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition and he human respiratory system the nature and size of the par- r limit-setting purposes termed proximates to the fraction of mouth during breathing and in piratory tract. Respirable dust he gas exchange region of the al are given in MDHS14/4., V ir own assigned WEL, all the ho specific short-term exposu- exposure limit should be use 4 mg/m3 | e collected described in lysis or ition of a present at a TWA of s means that st above these posure to these contain nd fate of any and the body article. HSE ed 'inhalable' airborne s therefore approximates e lung. Fuller Vhere dusts relevant limits ure limit is listed, |
| | Further inform | dust) | ses of these limits, respirable | e dust and |
| <u> </u> | | | | |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version | Revision Date: 27.02.2023 | SDS Number: | Print Date: 28.02.2023 |
|---------|---|--|--|
| 6.0 | | 102000000707 | Date of first issue: 02.01.2014 |
| | when MDH3 respir subst conce inhala any d levels must partic partic respo distin and 'r mater availa to the defini conta shoul | sampling is undertake S14/4 General method able, thoracic and inhat ance hazardous to heat entration in air equal to able dust or 4 mg.m-3 8 ust will be subject to C s. Some dusts have beat comply with the approp les of a wide range of sular particle after entry inse that it elicits, depe guishes two size fraction espirable'., Inhalable d rial that enters the nose able for deposition in the fraction that penetrate tions and explanatory r in components that have d be complied with., W | ctions of airborne dust which will be collected n in accordance with the methods described in s for sampling and gravimetric analysis or alable aerosols., The COSHH definition of a alth includes dust of any kind when present at a or greater than 10 mg.m-3 8-hour TWA of 8-hour TWA of respirable dust. This means that OSHH if people are exposed to dust above these en assigned specific WELs and exposure to these oriate limits., Most industrial dusts contain sizes. The behaviour, deposition and fate of any into the human respiratory system, and the body nd on the nature and size of the particle. HSE ons for limit-setting purposes termed 'inhalable' lust approximates to the fraction of airborne e and mouth during breathing and is therefore e respiratory tract. Respirable dust approximates as to the gas exchange region of the lung. Fuller material are given in MDHS14/4., Where dusts we their own assigned WEL, all the relevant limits 'here no specific short-term exposure limit is listed, -term exposure limit should be used. |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health | Value |
|------------------|-----------|-----------------|--------------------|------------|
| | | | effects | |
| aluminium powder | Workers | Inhalation | Long-term systemic | 3.72 mg/m3 |
| (stabilised) | | | effects | _ |
| | Workers | Inhalation | Long-term local | 3.72 mg/m3 |
| | | | effects | - |
| | Consumers | Oral | Long-term systemic | 3.95 mg/kg |
| | | | effects | 0.0 |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|-------------------------------|---------------------------|-------------|
| aluminium powder (stabilised) | Fresh water | 0.0749 mg/l |
| | clarification plant | 20 mg/l |

8.2 Exposure controls

Personal protective equipment

| Eye/face protection | : Goggles |
|-----------------------------|---|
| | Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems. |
| Hand protection Material | : Solvent-resistant gloves (butyl-rubber) |
| Remarks | : Take note of the information given by the producer |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Number: 10200000070 | |
|----------------|---------------------------|--|---|
| | | concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration contact). The exact break through time can be obtained the protective glove producer and this has to be observe Please observe the instructions regarding permeability a breakthrough time which are provided by the supplier of gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workp should be discussed with the producers of the protective gloves. | |
| Skii | n and body protection | | s clothing ody protection according to the amount and ion of the dangerous substance at the work place. |
| Res | spiratory protection | : Use suitab requires. | le breathing protection if workplace concentration |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Physical state | : | liquid |
|---|---|-------------------|
| Colour | : | silver |
| Odour | : | characteristic |
| Odour Threshold | : | No data available |
| Freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flammability | : | No data available |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Flash point | : | > 100 °C |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Vers 6.0 | sion | Revision Date: 27.02.2023 | | S Number: 2000000707 | Print Date: 28.02.2023 Date of first issue: 02.01.2014 | | |
|-------------|--|------------------------------|---|-------------------------|---|--|--|
| | | | | | | | |
| | Auto-ig | nition temperature | : | Not relevant | | | |
| | Decom | position temperature | : | No data available | 9 | | |
| | рН | | : | substance/mixtu | re is non-soluble (in water) | | |
| | Viscosi [.] Visc | ty osity, kinematic | : | > 21 mm2/s (40 ° | °C) | | |
| | Water solubility | | : | No data available | | | |
| | Solu | bility in other solvents | : | No data available | 9 | | |
| | Partition coefficient: n- octanol/water | | : | No data available | 9 | | |
| | Vapour pressure | | : | No data available | 9 | | |
| | Relative density | | : | No data available | 9 | | |
| | Density | , | : | No data available | 9 | | |
| | Relative | e vapour density | : | No data available | 9 | | |
| | Part | icle Size Distribution | : | No data available | 9 | | |

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions Hazardous reactions Contact with acids and alkalis may release hydrogen. No decomposition if stored and applied as directed. 10.4 Conditions to avoid Contact with acids and alkalis may release hydrogen. No decomposition if stored and applied as directed. 10.4 Conditions to avoid Conditions to avoid Do not allow evaporation to dryness.

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version 6.0 | Revision Date: 27.02.2023 | - | 0S Number: 2000000707 | Print Date: 28.02.2023 Date of first issue: 02.01.2014 |
|----------------|--|-------|---|---|
| | npatible materials ials to avoid | : | Acids Bases Oxidizing agents | |
| | rdous decomposition nation is not available. | pro | lucts | |
| SECTION | I 11: Toxicological in | nfor | mation | |
| 11.1 Infor | mation on hazard clas | ses | as defined in Reg | ulation (EC) No 1272/2008 |
| | e toxicity lassified based on availa | able | information. | |
| Prod | uct: | | | |
| Acute | oral toxicity | : | Acute toxicity esti Method: Calculati | mate: > 2,000 mg/kg on method |
| Com | oonents: | | | |
| alum | inium powder (stabilis | ed): | | |
| Acute | inhalation toxicity | : | LC50 (Rat): > 5 m Exposure time: 4 Test atmosphere: | ĥ |
| mang | anese neodecanoate: | | | |
| - | oral toxicity | : | Assessment: The single ingestion. | component/mixture is moderately toxic after |
| - | corrosion/irritation | able | information. | |
| Prod | uct: | | | |
| Rema | arks | : | May cause skin ir | ritation and/or dermatitis. |
| <u>Com</u> | oonents: | | | |
| mang | janese neodecanoate: | | | |
| Resu | t | : | Skin irritation | |
| | lecylamine: | | | |
| Asses | ssment | : | Irritating to skin. | |
| Serio | us eye damage/eye irr | itati | on | |
| Caus | es serious eye irritation. | | | |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Number: 102000000707 | Print Date: 28.02.2023 Date of first issue: 02.01.2014 | | | | | |
|----------------|---|-----------------------------|---|--|--|--|--|--|
| | <u>duct:</u> narks | : May cause in | rreversible eye damage. | | | | | |
| <u>Cor</u> | nponents: | | | | | | | |
| octa | adecylamine: | | | | | | | |
| Ass | essment | : Corrosive | | | | | | |
| Res | piratory or skin sensit | tisation | | | | | | |
| - | n sensitisation classified based on ava | ilable information. | | | | | | |
| | piratory sensitisation classified based on ava | ilable information. | | | | | | |
| | m cell mutagenicity classified based on ava | ilable information. | | | | | | |
| | cinogenicity classified based on ava | ilable information. | | | | | | |
| - | roductive toxicity classified based on ava | ilable information. | | | | | | |
| | STOT - single exposure Not classified based on available information. | | | | | | | |
| | STOT - repeated exposure Not classified based on available information. | | | | | | | |
| <u>Cor</u> | nponents: | | | | | | | |
| octa | adecylamine: | | | | | | | |
| Targ | osure routes get Organs essment | | ive system, Immune system lamage to organs through prolonged or repeated | | | | | |
| - | iration toxicity classified based on ava | ilable information. | | | | | | |
| <u>Cor</u> | nponents: | | | | | | | |
| | adecylamine: be fatal if swallowed a | nd enters airways. | | | | | | |
| 11.2 Info | ormation on other haza | ards | | | | | | |

Further information

Product:

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version 6.0 | Revision Date: 27.02.2023 | - | DS Number: 2000000707 | Print Date: 28.02.2023 Date of first issue: 02.01.2014 |
|----------------|---|------|--------------------------|--|
| Remarks | | : | No data available | 9 |
| SECTION | N 12: Ecological infor | ma | tion | |
| 12.1 Toxic | city | | | |
| Com | ponents: | | | |
| M-Fa | decylamine: ctor (Short-term (acute) tic hazard) | : | 10 | |
| | ctor (Long-term nic) aquatic hazard) | : | 10 | |
| Ecot | oxicology Assessment | | | |
| Acute | e aquatic toxicity | : | Very toxic to aqu | atic life. |
| Chroi | nic aquatic toxicity | : | Very toxic to aqu | atic life with long lasting effects. |
| | istence and degradabil ata available | ity | | |
| | ccumulative potential ata available | | | |
| | i lity in soil ata available | | | |
| 12.5 Resu | llts of PBT and vPvB as | se | ssment | |
| Prod Asse | <u>uct:</u> ssment | : | to be either persi | nixture contains no components considered stent, bioaccumulative and toxic (PBT), or nd very bioaccumulative (vPvB) at levels of |
| | ocrine disrupting prope ata available | rtie | S | |
| 12.7 Othe | r adverse effects | | | |
| | uct: ional ecological nation | : | unprofessional h | Il hazard cannot be excluded in the event of andling or disposal. ic life with long lasting effects. |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Number: 102000000707 | Print Date: 28.02.2023 Date of first issue: 02.01.2014 | | | |
|-------------------------------------|---------------------------|-----------------------------|---|--|--|--|
| SECTION 13: Disposal considerations | | | | | | |
| | | | | | | |

| European Waste Catalogue | : | 08 03 12 - waste ink containing dangerous substances |
|------------------------------|---|--|
| 13.1 Waste treatment methods | | |
| Product | : | The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. |

SECTION 14: Transport information

14.1 UN number or ID number

| ADR | | : | UN 3082 | | | |
|--------------|-----------------------|---|---|--------------------------------|--|--|
| IMDG | | : | UN 3082 | | | |
| ΙΑΤΑ | | : | UN 3082 | | | |
| 14.2 UN pro | per shipping name | | | | | |
| ADR | | : | ENVIRONMENTALLY N.O.S. (Stearyl amine) | Y HAZARDOUS SUBSTANCE, LIQUID, | | |
| IMDG | | : | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Stearyl amine) | | | |
| ΙΑΤΑ | | : | Environmentally hazardous substance, liquid, n.o.s. (Stearyl amine) | | | |
| 14.3 Transp | ort hazard class(es) | | | | | |
| | | | Class | Subsidiary risks | | |
| ADR | | : | 9 | | | |
| IMDG | | : | 9 | | | |
| ΙΑΤΑ | | : | 9 | | | |
| 14.4 Packing | g group | | | | | |
| ADR | | | | | | |
| Packing | | : | III | | | |
| Classific | cation Code | : | M6 | | | |
| Hazard | Identification Number | : | 90 | | | |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Versio 6.0 | on | Revision Date: 27.02.2023 | | OS Number: 2000000707 | Print Date: 28.02.2023 Date of first issue: 02.01.2014 |
|---------------|-----------------------------------|--|----|--------------------------|--|
| | _abels Funnel | restriction code | : | 9 (-) | |
| F | MDG Packing Labels EmS C | g group ode | : | III 9 F-A, S-F | |
| F | Packing aircraft) | | : | 964 | |
| F | | g instruction (LQ) g group | : | Y964 III 9 | |
| F (F | Packing passer Packing | Passenger) g instruction nger aircraft) g instruction (LQ) g group | : | 964 Y964 III 9 | |
| | | nmental hazards | • | 5 | |
| - | ADR Enviror | mentally hazardous | : | yes | |
| | MDG Marine | pollutant | : | yes | |
| 14.6 \$ | Specia | I precautions for use | er | | |
| F | Remarl | <s< td=""><td>:</td><td>packagings conta</td><td>jings <=5L / 5 kg, or combination ining inner packagings <= 5L / 5 kg net per SV375 ADR, 2.10.2.7 IMDG-Code, A197 be applied.</td></s<> | : | packagings conta | jings <=5L / 5 kg, or combination ining inner packagings <= 5L / 5 kg net per SV375 ADR, 2.10.2.7 IMDG-Code, A197 be applied. |

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

| REACH - Restrictions on the manufacture, placing on | : | Conditions of restriction for the |
|---|---|-----------------------------------|
| the market and use of certain dangerous substances, | | following entries should be |
| mixtures and articles (Annex XVII) | | considered: |
| | | |

according to Regulation (EC) No. 1907/2006



METALSTAR SuperEco 10 2004 Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Number: 102000000707 | | | ate: 28.02.2023 f first issue: 02.01.2014 |
|----------------|--|-----------------------------|----|----------------|--|
| | | | | | Number on list 3 aluminium powder (stabilised) (Number on list 40) |
| | EACH Candidate list of rn (SVHC) for Authoris | h | : | Not applicable | |
| | ersistent Organic Pollu ation (EU) 2019/1021 a) | ined | : | Not applicable | |
| • | ation (EC) No 1005/200 te the ozone layer | | : | Not applicable | |
| | EACH List of substance x XIV) | s subject to authorisati | on | : | Not applicable |

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

| H228 | : | Flammable solid. |
|---------------------------|----------|--|
| H302 | : | Harmful if swallowed. |
| H304 | : | May be fatal if swallowed and enters airways. |
| H315 | : | Causes skin irritation. |
| H318 | : | Causes serious eye damage. |
| H373 | : | May cause damage to organs through prolonged or repeated exposure. |
| H400 | : | Very toxic to aquatic life. |
| H410 | : | Very toxic to aquatic life with long lasting effects. |
| Full text of other abbrev | viations | |
| Acute Tox. | : | Acute toxicity |
| Aquatic Acute | : | Short-term (acute) aquatic hazard |

| Acute I ox. | : | Acute toxicity |
|-----------------|---|--|
| Aquatic Acute | : | Short-term (acute) aquatic hazard |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard |
| Asp. Tox. | : | Aspiration hazard |
| Eye Dam. | : | Serious eye damage |
| Flam. Sol. | : | Flammable solids |
| Skin Irrit. | : | Skin irritation |
| STOT RE | : | Specific target organ toxicity - repeated exposure |
| GB EH40 | : | UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 / TWA | : | Long-term exposure limit (8-hour TWA reference period) |
| | | |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation;



METALSTAR SuperEco 10 2004 Silver

| Version | Revision Date: | SDS Number: | Print Date: 28.02.2023 |
|---------|----------------|--------------|---------------------------------|
| 6.0 | 27.02.2023 | 102000000707 | Date of first issue: 02.01.2014 |

Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

| Classification of the mixtur | Classification procedure: | |
|------------------------------|---------------------------|--------------------|
| Eye Irrit. 2 | H319 | Calculation method |
| Aquatic Chronic 2 | H411 | Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN