

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version	Revision Date:	SDS Number:	Print Date: 23.04.2024
7.0	22.04.2024	102000029535	Date of first issue: 08.05.2018

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SHINEDECOR 5000  
Product code : 023845HD0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address of person responsible for the SDS : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Not a dangerous substance according to GHS.

##### Additional Labelling

EUH210 Safety data sheet available on request.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

EUH208      Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1  01-2119529243-45	Flam. Sol. 1; H228	>= 25 - < 50
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	154518-38-4(52933-07-0)  01-2119976356-25	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 3 - < 10
2-dimethylaminoethanol	108-01-0 203-542-8 603-047-00-0  01-2119492298-24	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)  specific concentration limit STOT SE 3; H335 >= 5 % STOT SE 3; H335 >= 5 %	>= 0.1 - < 1
Alcohols, C11-14-iso-, C13-rich	68526-86-3 271-235-6  01-2119454259-32	Skin Irrit. 2; H315 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0.1 - < 0.25
1,2-benzisothiazol-3(2H)-one	2634-33-5	Acute Tox. 4; H302	>= 0.0025 - <

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version  
7.0

Revision Date:  
22.04.2024

SDS Number:  
102000029535

Print Date: 23.04.2024  
Date of first issue: 08.05.2018

	220-120-9 613-088-00-6  01-2120761540-60	Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411  specific concentration limit Skin Sens. 1; H317 >= 0.05 % Skin Sens. 1; H317 >= 0.05 %	0.025
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5  01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1B; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Eye Irrit. 2; H319 0.06 - < 0.6 % Skin Sens. 1; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 % Skin Corr. 1C; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % STOT RE 2; H319 0.06 - < 0.6 % Skin Sens. 1A; H317	>= 0.0002 - < 0.0015

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

		>= 0.0015 % Eye Dam. 1; H318 >= 0.6 %	
--	--	---	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.  
No hazards which require special first aid measures.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Dry sand  
ABC powder  
Foam
- Unsuitable extinguishing media : Water  
Carbon dioxide (CO<sub>2</sub>)

#### 5.2 Special hazards arising from the substance or mixture

This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version	Revision Date:	SDS Number:	Print Date: 23.04.2024
7.0	22.04.2024	102000029535	Date of first issue: 08.05.2018

---

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- 

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Evacuate personnel to safe areas.

### 6.2 Environmental precautions

- General advice : The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
- Wipe up with absorbent material (e.g. cloth, fleece).  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : General industrial hygiene practice.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container.
-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

Electrical installations / working materials must comply with the technological safety standards.

Advice on common storage : Do not store near acids.  
Do not store together with oxidizing and self-igniting products.  
Keep away from oxidizing agents and strongly acid or alkaline materials.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable fraction)	4 mg/m <sup>3</sup>	GB EH40
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed,				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
 Date of first issue: 08.05.2018

	a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
	<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
2-dimethylaminoethanol	108-01-0	TWA	2 ppm 7.4 mg/m <sup>3</sup>	GB EH40
		STEL	6 ppm 22 mg/m <sup>3</sup>	GB EH40

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	Workers	Inhalation	Long-term systemic effects	34.94 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	100.13 mg/kg
	Consumers	Inhalation	Long-term systemic effects	10.43 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	60.08 mg/kg
	Consumers	Oral	Long-term systemic effects	6.01 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version  
7.0

Revision Date:  
22.04.2024

SDS Number:  
102000029535

Print Date: 23.04.2024  
Date of first issue: 08.05.2018

			effects	
2,2',2''-nitrilotriethanol	Workers	Inhalation	Long-term local effects	1 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	7.5 mg/kg
	Workers	Dermal	Long-term local effects	0.14 mg/cm <sup>2</sup>
	Consumers	Inhalation	Long-term local effects	0.4 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.3 mg/kg
	Consumers	Dermal	Long-term systemic effects	2.66 mg/kg
	Consumers	Dermal	Long-term local effects	0.07 mg/cm <sup>2</sup>
2-dimethylaminoethanol	Workers	Inhalation	Long-term systemic effects	1.76 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	5.28 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	1.76 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	13.53 mg/m <sup>3</sup>
	Workers	Dermal	Acute systemic effects	1.2 mg/kg
	Workers	Dermal	Long-term systemic effects	0.250 mg/kg
	Workers	Dermal	Acute local effects	0.100 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.438 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	0.148 mg/kg
1,2-benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	0.966 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	0.345 mg/kg
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Workers	Inhalation	Long-term local effects	0.02 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0.04 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	0.02 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	0.04 mg/m <sup>3</sup>
	Consumers	Oral	Long-term local effects	0.090 mg/kg
	Consumers	Oral	Acute local effects	0.11 mg/kg



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version  
7.0

Revision Date:  
22.04.2024

SDS Number:  
102000029535

Print Date: 23.04.2024  
Date of first issue: 08.05.2018

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	Fresh water	0.00631 mg/l
	Fresh water sediment	0.113 mg/kg
	Intermittent water release	0.0631 mg/l
	Marine water	0.000631 mg/l
	Marine sediment	0.0113 mg/kg
	STP	10 mg/l
2,2',2''-nitrilotriethanol	Soil	0.0188 mg/kg
	Fresh water	0.32 mg/l
	Marine water	0.032 mg/l
	Fresh water sediment	1.7 mg/kg
	Marine sediment	0.17 mg/kg
2-dimethylaminoethanol	clarification plant	10 mg/l
	Soil	0.151 mg/kg
	Fresh water	0.0661 mg/l
	Marine water	0.004 mg/l
	Fresh water sediment	0.246 mg/kg
	Marine sediment	0.015 mg/kg
1,2-benzisothiazol-3(2H)-one	STP	10 mg/l
	Soil	0.01 mg/kg
	Intermittent Release	661 µg/l
	oral (secondary poisoning)	20 mg/kg
	Fresh water	0.00403 mg/l
	Marine water	0.000403 mg/l
	STP	1.03 mg/l
	Intermittent water release	0.0011 mg/l
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Intermittent Release	0.00011 mg/l
	Fresh water sediment	0.0499 mg/kg
	Marine sediment	0.00499 mg/kg
	Soil	3 mg/kg
	Fresh water	0.00339 mg/l
	Intermittent water release	0.00339 mg/l
	Marine water	0.00339 mg/l
Personal protective equipment	Intermittent Release	0.00339 mg/l
	STP	0.23 mg/l
	Soil	0.0471 mg/kg
	Fresh water sediment	0.027 mg/kg
	Marine sediment	0.027 mg/kg
	Soil	0.01 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

Eye/face protection : Goggles  
Safety glasses

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Form : liquid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : 100 °C

Flammability : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 100 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 6 - 8

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

Concentration: 100 %

Viscosity, kinematic : No data available

### Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

### Vapor Pressure for Components:

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) : 2.2 Pa (20 °C)

Relative density : No data available

Density : 1.2 g/cm<sup>3</sup>

Relative vapour density : No data available

### Particle characteristics

Particle Size Distribution : No data available

## 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

### 10.5 Incompatible materials

Materials to avoid : Acids

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

Bases  
Oxidizing agents

### 10.6 Hazardous decomposition products

This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

#### Components:

##### **aluminium powder (stabilised):**

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **2-dimethylaminoethanol:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after a single skin contact.

##### **1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 0.4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The component/mixture is highly toxic after short term inhalation.

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

- Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.
- Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.
- Acute dermal toxicity : Assessment: The component/mixture is highly toxic after single contact with skin.

### **Skin corrosion/irritation**

Not classified based on available information.

#### **Product:**

- Result : No skin irritation
- Remarks : Based on available data, the classification criteria are not met.

#### **Components:**

##### **Phosphoric acid, C11-14-isoalkyl esters, C13-rich:**

- Result : Skin irritation

##### **2-dimethylaminoethanol:**

- Result : Corrosive after 3 minutes to 1 hour of exposure

##### **Alcohols, C11-14-iso-, C13-rich:**

- Result : Skin irritation

##### **1,2-benzisothiazol-3(2H)-one:**

- Result : Skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Product:**

- Result : No eye irritation
- Remarks : Based on available data, the classification criteria are not met.

#### **Components:**

##### **Phosphoric acid, C11-14-isoalkyl esters, C13-rich:**

- Result : Irreversible effects on the eye

##### **2-dimethylaminoethanol:**

- Result : Corrosive

##### **1,2-benzisothiazol-3(2H)-one:**

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

Result : Corrosive

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Result : Corrosive

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### **1,2-benzisothiazol-3(2H)-one:**

Result : May cause sensitisation by skin contact.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

#### Components:

##### **2-dimethylaminoethanol:**

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

### 11.2 Information on other hazards

#### Further information

#### Product:

Remarks : No data available

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Product:

##### **Ecotoxicology Assessment**

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

##### Components:

##### **Phosphoric acid, C11-14-isoalkyl esters, C13-rich:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 6.31 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 150 mg/l  
Exposure time: 72 h

##### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

##### **2-dimethylaminoethanol:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 98.77 mg/l

Toxicity to algae/aquatic plants : (Chlorella pyrenoidosa (algae)): 35 mg/l  
Exposure time: 72 h

##### **Alcohols, C11-14-iso-, C13-rich:**

##### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

##### **1,2-benzisothiazol-3(2H)-one:**

##### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

M-Factor (Short-term (acute) aquatic hazard) : 100

M-Factor (Long-term (chronic) aquatic hazard) : 100

**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Endocrine disrupting properties**

No data available

**12.7 Other adverse effects**

**Product:**

Additional ecological information : No data available

---

### SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11\* - waste paint and varnish containing organic solvents or other dangerous substances

**13.1 Waste treatment methods**

Product : In accordance with local and national regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
In accordance with local and national regulations.

---



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA** : UN 9999  
Not permitted for transport

#### 14.2 UN proper shipping name

**ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA** : Not permitted for transport

#### 14.3 Transport hazard class(es)

**ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA** : Not permitted for transport

#### 14.4 Packing group

**ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA (Cargo)** : Not permitted for transport  
**IATA (Passenger)** : Not permitted for transport

#### 14.5 Environmental hazards

**ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good

#### 14.6 Special precautions for user

**Remarks** : Due to the risk of hydrogen development we recommend to refrain from airfreighting this/these product(s).  
Not classified as dangerous in the meaning of transport regulations.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) Phosphoric acid, C11-14-isoalkyl esters, C13-rich (Number on list 3) 2-dimethylaminoethanol (Number on list 3) Alcohols, C11-14-iso-, C13-rich (Number on list 3)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

#### 15.2 Chemical safety assessment

No data available

---

### SECTION 16: Other information

#### Full text of H-Statements

H226	:	Flammable liquid and vapour.
H228	:	Flammable solid.
H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H310	:	Fatal in contact with skin.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H330	:	Fatal if inhaled.
H331	:	Toxic if inhaled.
H335	:	May cause respiratory irritation.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version 7.0      Revision Date: 22.04.2024      SDS Number: 102000029535      Print Date: 23.04.2024  
Date of first issue: 08.05.2018

---

H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Flam. Liq. : Flammable liquids  
Flam. Sol. : Flammable solids  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT SE : Specific target organ toxicity - single exposure  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 5000

Version	Revision Date:	SDS Number:	Print Date: 23.04.2024
7.0	22.04.2024	102000029535	Date of first issue: 08.05.2018

---

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN