according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030577	Date of first issue: 27.09.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	:	STAPA METALLUX 8154 Aluminium Paste
Product code	:	057615G60M1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

#### 1.3 Details of the supplier of the safety data sheet

Company	:	ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	:	+499152770
Telefax	:	+499152777008
E-mail address of person responsible for the SDS	:	msds.eckart@altana.com

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008) Long-term (chronic) aquatic hazard, H412: Harmful to aquatic life with long lasting Category 3 effects. 2.2 Label elements Labelling (REGULATION (EC) No 1272/2008) Hazard statements : H412 Harmful to aquatic life with long lasting effects. Prevention: Precautionary statements : P273 Avoid release to the environment. Disposal:

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version	Revision Date: 12.02.2023	SDS Number:	Print Date: 16.04.2024
3.0		102000030577	Date of first issue: 27.09.2018

P501

Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

### Components

Observiced a service			O a ma a m t m a t i a m
Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Naphtha (petroleum),	64742-48-9	Asp. Tox. 1; H304	>= 25 - < 50
hydrotreated heavy; Low boiling		-	
point ydrogen treated naphtha	918-481-9		
	01-2119457273-39		
Solvent naphtha (petroleum), light	64742-95-6	Flam. Liq. 3; H226	>= 2.5 - < 10
arom.		STOT SE 3; H336	
	918-668-5	(Central nervous	
	01-2119455851-35	system)	
		STOT SE 3; H335	
		(Respiratory system)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	
		4	

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

4.1 Description of first aid measures				
General advice	:	Move the victim to fresh air.		
		Do not leave the victim unattended.		
If inhaled	:	Remove to fresh air. If unconscious, place in recovery position and seek medical		

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version 3.0	Revision Date: 12.02.2023		DS Number: 2000030577	Print Date: 16.04.2024 Date of first issue: 27.09.2018
			advice. If symptoms pers	ist, call a physician.
In case	e of skin contact	:	Wash off immedi	ately with soap and plenty of water.
In case	e of eye contact	:	Immediately flush	eye(s) with plenty of water.
			Remove contact I If eye irritation pe	enses. rsists, consult a specialist.
lf swall	owed	:	Never give anythi	tract clear. or alcoholic beverages. ng by mouth to an unconscious person. ist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed** None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing media	:	Dry sand
		Special powder against metal fire
Unsuitable extinguishing media	:	Water Foam ABC powder Carbon dioxide (CO2)
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Use personal protective equipment.
		Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030577	Date of first issue: 27.09.2018

### **SECTION 6: Accidental release measures**

	e equipment and emergency procedures Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition. Avoid dust formation.
6.2 Environmental precautions	
Environmental precautions :	The product should not be allowed to enter drains, water courses or the soil.
	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contain	nment and cleaning up
	Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling	:	Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
Advice on protection against fire and explosion	:	Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.
		Provide appropriate exhaust ventilation at places where dust is formed.
Hygiene measures	:	General industrial hygiene practice.

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Versior 3.0	Revision Date: 12.02.2023	SDS Number: 102000030577	Print Date: 16.04.2024 Date of first issue: 27.09.2018
Re	nditions for safe storage, quirements for storage eas and containers	: Store in origi cool, well-vel use. Keep av Containers w	compatibilities nal container. Keep containers tightly closed in a ntilated place. Keep container closed when not in vay from sources of ignition - No smoking. which are opened must be carefully resealed and to prevent leakage. Electrical installations /
	rther information on prage conditions	standards.	erials must comply with the technological safety humidity and water. Do not allow to dry.
Ac	lvice on common storage	Never allow   storage. Keep away f	together with oxidizing and self-igniting products. broduct to get in contact with water during rom oxidizing agents, strongly alkaline and materials in order to avoid exothermic reactions.
		No materials	to be especially mentioned.
	rther information on prage stability	: No decompo	sition if stored and applied as directed.
7.3 Spe	ecific end use(s)		

### SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis		
		of exposure)				
aluminium powder	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40		
(stabilised)						
		TWA (Respirable	4 mg/m3	GB EH40		
		fraction)				
		TWA (inhalable	10 mg/m3	GB EH40		
		dust)				
	Further inform	nation: For the purpo	ses of these limits, respirable	e dust and		
	inhalable dust	are those fractions	of airborne dust which will be	e collected		
	when samplin	g is undertaken in a	ccordance with the methods	described in		
			ampling and gravimetric ana			
			aerosols., The COSHH defir			
			ludes dust of any kind when			
			ater than 10 mg.m-3 8-hour			
			TWA of respirable dust. This			
			l if people are exposed to du			
		levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain				
	particles of a	wide range of sizes.	The behaviour, deposition a	nd fate of any		

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version 3.0	Revision Date: 12.02.2023	SDS Nu 1020000		int Date: 16.04.2024 ate of first issue: 27.09.2018	
	resp distin and mate avail to th defin cont shou	onse that it end respirable'., rial that enter able for dep fraction that itions and ex ain component Id be compl	elicits, depend on size fractions fo Inhalable dust ap ers the nose and osition in the resp at penetrates to the collanatory materia ents that have the ied with., Where r	he human respiratory system the nature and size of the pa r limit-setting purposes terme proximates to the fraction of mouth during breathing and is iratory tract. Respirable dust he gas exchange region of the al are given in MDHS14/4., W ir own assigned WEL, all the ho specific short-term exposu- exposure limit should be used	rticle. HSE d 'inhalable' airborne s therefore approximates e lung. Fuller /here dusts relevant limits ure limit is listed,
		dı	NA (Respirable ust)	4 mg/m3	GB EH40
	inhal wher MDF resp subs cond inhal any o level must parti parti resp distin and mate avail to th defir cont shou	able dust are sampling is S14/4 Gene rable, thorac tance hazarc entration in a able dust or dust will be s s. Some dus comply with cles of a wid cular particle onse that it en guishes two respirable'., rial that ente able for dep e fraction that itions and ex ain component	e those fractions s undertaken in a ral methods for s cic and inhalable dous to health inc air equal to or gre 4 mg.m-3 8-hour subject to COSH- the appropriate e range of sizes. after entry into the elicits, depend on o size fractions fo Inhalable dust ap ers the nose and osition in the resp at penetrates to the colling that have the ied with., Where r	ses of these limits, respirable of airborne dust which will be ccordance with the methods of ampling and gravimetric anal aerosols., The COSHH defin cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This I if people are exposed to du signed specific WELs and exp limits., Most industrial dusts of The behaviour, deposition ar he human respiratory system the nature and size of the par r limit-setting purposes terme oproximates to the fraction of mouth during breathing and is iratory tract. Respirable dust he gas exchange region of the al are given in MDHS14/4., W ir own assigned WEL, all the ho specific short-term exposu	collected described in ysis or ition of a present at a TWA of means that st above these oosure to these contain nd fate of any , and the body inticle. HSE d 'inhalable' airborne s therefore approximates e lung. Fuller /here dusts relevant limits ure limit is listed,

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	Workers	Inhalation	Acute systemic effects	1500 mg/m3
	Workers	Skin contact	Long-term systemic	300 mg/kg

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Vers 3.0	sion Revision Date: 12.02.2023	SDS Nu 1020000		Print Date: 16.04.2024 Date of first issue: 27.09.2018	
1				effects	
		Consumers	Ingestion	Long-term systemic effects	300 mg/kg
		Consumers	Skin contac	t Long-term systemic effects	300 mg/kg
		Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	Solvent naphtha (petroleum), light arom.	Workers	Inhalation	Long-term systemic effects	150 mg/m3
		Workers	Skin contac	t Long-term systemic effects	25 mg/kg
		Consumers	Skin contac	t Long-term systemic effects	11 mg/kg
		Consumers	Inhalation	Long-term systemic effects	32 mg/m3
		Consumers	Inhalation	Long-term local effects	11 mg/kg
		Consumers	Ingestion	Long-term systemic effects	11 mg/kg

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

#### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection Hand protection	:	Safety glasses
Material	:	Solvent-resistant gloves
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Long sleeved clothing Safety shoes
		Choose body protection according to the amount and concentration of the dangerous substance at the work place. Protective suit

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version	Revision Date: 12.02.2023	SDS Number:	Print Date: 16.04.2024
3.0		102000030577	Date of first issue: 27.09.2018
Respiratory protection		: Use suitable br requires.	eathing protection if workplace concentration

### **SECTION 9: Physical and chemical properties**

#### Physical state Pasty solid : Colour silver : Odour characteristic : Odour Threshold No data available : Freezing point : No data available Boiling point/boiling range 140 - 200 °C : Flammability Combustible Solids : Upper explosion limit / Upper No data available : flammability limit Lower explosion limit / Lower No data available : flammability limit Flash point No data available : Auto-ignition temperature Not relevant : Decomposition temperature No data available : pН : substance/mixture is non-soluble (in water) Viscosity, kinematic : No data available Solubility(ies) insoluble Water solubility : Solubility in other solvents : No data available Partition coefficient: n-No data available : octanol/water Vapour pressure No data available : Relative density No data available : Density 1.3 - 2.0 g/cm3 : Relative vapour density No data available :

#### 9.1 Information on basic physical and chemical properties

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version 3.0	Revision Date: 12.02.2023	SDS Number: 102000030577	Print Date: 16.04.2024 Date of first issue: 27.09.2018	
	Particle Size Distribution	:		
Exp Sel	er information blosives f-ignition cibility with water	: Not explosive : not auto-flami : immiscible		

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions :	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.	
10.4 Conditions to avoid		
Conditions to avoid :	Do not allow to dry.	
	No data available	
10.5 Incompatible materials		
Materials to avoid :	Acids Bases Oxidizing agents Highly halogenated compounds	

#### **10.6 Hazardous decomposition products**

This information is not available.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

rsion	Revision Date: 12.02.2023	SDS Number: 102000030577	Print Date: 16.04.2024 Date of first issue: 27.09.2018
<u>Com</u>	oonents:		
alumi	inium powder (stabi	lised):	
Acute	inhalation toxicity	: LC50 (Rat): > Exposure time Test atmosph	:: 4 h
-	<b>tha (petroleum), hyc</b> e oral toxicity	drotreated heavy; Lo : LD50 (Rat): >	w boiling point ydrogen treated naphtha: 5,000 mg/kg
Acute	inhalation toxicity	Remarks: An I	est atmosphere: vapour LC50/inhalation/4h/rat could not be determined ortality of rats was observed at the maximum ncentration.
Acute	e dermal toxicity	: LD50 (Rabbit)	: > 5,000 mg/kg
Solve	ent naphtha (petroleu	um), light arom.:	
	oral toxicity	: LD50 (Rat): 3,	492 mg/kg
Acute	e dermal toxicity	: LD50 (Rabbit)	: > 3,160 mg/kg
	<b>corrosion/irritation</b> lassified based on ava	ailable information.	
	us eye damage/eye lassified based on ava		
Respi	iratory or skin sensi	tisation	
	sensitisation lassified based on ava	ailable information.	
-	iratory sensitisation lassified based on ava		
	cell mutagenicity	ailable information.	
<u>Com</u> p	oonents:		
Germ	tha (petroleum), hyd cell mutagenicity- ssment	: Classified bas	w boiling point ydrogen treated naphtha: ed on benzene content < 0.1% (Regulation (Ed nnex VI, Part 3, Note P)
Solve	ent naphtha (petroleu	um), light arom.:	
	cell mutagenicity-		ed on benzene content < 0.1% (Regulation (E0

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version 3.0	Revision Date: 12.02.2023	SDS Number: 102000030577	Print Date: 16.04.2024 Date of first issue: 27.09.2018
	<b>nogenicity</b> lassified based on av	ailable information.	
<u>Com</u>	oonents:		
Carci	<b>tha (petroleum), hyd</b> nogenicity - ssment	: Classified bas	w boiling point ydrogen treated naphtha: ed on benzene content < 0.1% (Regulation (EC nex VI, Part 3, Note P)
Solve	ent naphtha (petrole	um), light arom.:	
	nogenicity - ssment		ed on benzene content < 0.1% (Regulation (EC nex VI, Part 3, Note P)
-	oductive toxicity lassified based on av	ailable information.	
	<b>- single exposure</b> lassified based on av	ailable information.	
<u>Comp</u>	oonents:		
	e <b>nt naphtha (petrole</b> ssment		piratory irritation., May cause drowsiness or
	- repeated exposur lassified based on av		
	ation toxicity lassified based on av	ailable information.	
<u>Com</u>	oonents:		
-	<b>tha (petroleum)</b> , hyd oe fatal if swallowed a		w boiling point ydrogen treated naphtha:
	ent naphtha (petrole be fatal if swallowed a		
11.2 Infor	mation on other haz	ards	
Furth	er information		
<u>Produ</u> Rema		: No data availa	ble

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030577	Date of first issue: 27.09.2018

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

#### Solvent naphtha (petroleum), light arom .:

#### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

**12.4 Mobility in soil** No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

#### Product:

Additional ecological	:	An environmental hazard cannot be excluded in the event of
information		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

#### **Components:**

Naphtha (petroleum),	hydrotreated	heavy; Low boiling point ydrogen treated naphtha:
Additional ecological	: No	o data available
information		

#### **SECTION 13: Disposal considerations**

European Waste Catalogue	:	12 01 04 - non-ferrous metal dust and particles
European Waste Catalogue	:	10 03 21 - other particulates and dust (including ball-mill dust)
		containing hazardous substances

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version 3.0	Revision Date: 12.02.2023	-	0S Number: 2000030577	Print Date: 16.04.2024 Date of first issue: 27.09.2018
13.1 Wast	e treatment methods	5		
Produ	uct	:	The product sl courses or the	nould not be allowed to enter drains, wate soil.
SECTIO	N 14: Transport inf	orma	tion	
14.1 UN n	umber or ID number			
ADR		:	Not regulated	as a dangerous good
IMDG	ì	:	Not regulated	as a dangerous good
ΙΑΤΑ		:	Not regulated	as a dangerous good
14.2 UN p	roper shipping name	9		
ADR		:	Not regulated	as a dangerous good
IMDG	i	:	Not regulated	as a dangerous good
ΙΑΤΑ		:	Not regulated	as a dangerous good
14.3 Trans	sport hazard class(es	5)		
ADR		:	Not regulated	as a dangerous good
IMDG	ì	:	Not regulated	as a dangerous good
ΙΑΤΑ		:	Not regulated	as a dangerous good
14.4 Pack	ing group			
ADR		:	Not regulated	as a dangerous good
IMDG	ì	:	Not regulated	as a dangerous good
ΙΑΤΑ	(Cargo)	:	Not regulated	as a dangerous good
ΙΑΤΑ	(Passenger)	:	Not regulated	as a dangerous good
	r <b>onmental hazards</b> egulated as a dangero	us go	od	
14.6 Spec Rema	ial precautions for u	ser	Not classified	as dangerous in the meaning of transport
Reille	шлэ	•	regulations.	as cangerous in the meaning of transport

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006



# STAPA METALLUX 8154 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030577	Date of first issue: 27.09.2018

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha (Number on list 3) Solvent naphtha (petroleum), light arom. (Number on list 3)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

#### 15.2 Chemical safety assessment

No data available

### **SECTION 16: Other information**

Full text of H-Statements		
H226	:	Flammable liquid and vapour.
H228	:	Flammable solid.
H304	:	May be fatal if swallowed and enters airways.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	IS	
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Flam. Liq.	:	Flammable liquids
Flam. Sol.	:	Flammable solids
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)



# STAPA METALLUX 8154 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	12.02.2023	102000030577	Date of first issue: 27.09.2018

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Further information Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure: Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN