

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ROTOVARIO 501 023  
Product code : 026596G60

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colouring agents, pigments

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART Suisse SA  
Route de la Brasserie 2  
1963 Vétroz  
Telephone : +410273454800  
Telefax : +410273454859  
E-mail address of person responsible for the SDS : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1	H228: Flammable solid.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

---



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H228      Flammable solid. H319      Causes serious eye irritation. H336      May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066      Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261      Avoid breathing dust. P280      Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. <b>Response:</b> P304 + P340 + P312      IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P370 + P378      In case of fire: Use for extinction: Special powder for metal fires. P370 + P378      In case of fire: Use for extinction: Dry sand.

### Hazardous components which must be listed on the label:

ethyl acetate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGULATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1	Flam. Sol. 1; H228	>= 50 - <= 100

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

	01-2119529243-45		
ethyl acetate	141-78-6 205-500-4 607-022-00-5  01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 25 - < 50

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.  
  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.  
Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
Special powder against metal fire

Unsuitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
ABC powder  
Water  
Foam

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.  
Remove all sources of ignition.

#### 6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.  
Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.0	28.02.2024	102000034173	Date of first issue: 20.04.2021

---

respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.  
Avoid formation of respirable particles.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable fraction)	4 mg/m <sup>3</sup>	GB EH40
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

	should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m <sup>3</sup>	GB EH40
		STEL	400 ppm 1,468 mg/m <sup>3</sup>	GB EH40
		STEL	400 ppm 1,468 mg/m <sup>3</sup>	2017/164/EU
	Further information: Indicative			
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
	Further information: Indicative			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	734 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version  
4.0

Revision Date:  
28.02.2024

SDS Number:  
102000034173

Print Date: 16.04.2024  
Date of first issue: 20.04.2021

	Workers	Inhalation	Acute systemic effects	1468 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	63 mg/kg
	Workers	Inhalation	Acute local effects	1468 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	367 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	367 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	734 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	37 mg/kg
	Workers	Dermal	Long-term local effects	63 mg/kg
	Consumers	Oral	Long-term systemic effects	4.5 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
ethyl acetate	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	STP	650 mg/l
	Fresh water sediment	1.15 mg/kg
	Marine sediment	0.115 mg/kg
	Soil	0.148 mg/kg
	periodical release	1.65 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
Recommended preventive skin protection Skin should be



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.0	28.02.2024	102000034173	Date of first issue: 20.04.2021

---

washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection	:	Long sleeved clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use suitable breathing protection if workplace concentration requires.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Form	:	Pasty solid
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/range	:	Not applicable
Boiling point/boiling range	:	77 °C
Flammability	:	The substance or mixture is a flammable solid with the category 1.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Viscosity, kinematic	:	No data available
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	No data available

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.0	28.02.2024	102000034173	Date of first issue: 20.04.2021

---

Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	No data available
Relative density	:	No data available
Density	:	1.3 - 2.0 g/cm <sup>3</sup>
Relative vapour density	:	No data available
Particle characteristics	:	
Particle Size Distribution	:	No data available

### 9.2 Other information

Explosives	:	Not explosive Vapours may form explosive mixture with air.
Flammable solids	:	
Burning number	:	5
Self-ignition	:	not auto-flammable
Miscibility with water	:	partly miscible

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
---------------------	---	--

### 10.4 Conditions to avoid

Conditions to avoid	:	Do not allow to dry.  Heat, flames and sparks.
---------------------	---	--

### 10.5 Incompatible materials

Materials to avoid	:	Acids Bases
--------------------	---	----------------

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.0	28.02.2024	102000034173	Date of first issue: 20.04.2021

---

Oxidizing agents  
Highly halogenated compounds

### 10.6 Hazardous decomposition products

This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### ethyl acetate:

Acute oral toxicity : (Rat): 5,620 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 56 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

#### Product:

Remarks : May cause skin irritation in susceptible persons.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Product:

Remarks : May cause irreversible eye damage.

#### Components:

##### ethyl acetate:

Result : Eye irritation

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

---

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

May cause drowsiness or dizziness.

#### **Components:**

##### **ethyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

### **11.2 Information on other hazards**

#### **Further information**

##### **Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

#### **Components:**

##### **ethyl acetate:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

---

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

**Product:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles  
European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1325

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

---

**IMDG** : UN 1325

**IATA** : UN 1325

### 14.2 UN proper shipping name

**ADR** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)

**IMDG** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)

**IATA** : Flammable solid, organic, n.o.s.  
(Aluminium pigment paste)

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADR</b>	: 4.1	
<b>IMDG</b>	: 4.1	
<b>IATA</b>	: 4.1	

### 14.4 Packing group

**ADR**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 40  
Labels : 4.1  
Tunnel restriction code : (E)

**IMDG**  
Packing group : II  
Labels : 4.1  
EmS Code : F-G, S-G  
Remarks : IMDG Code segregation group 15 - Powdered metals

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 448  
Packing instruction (LQ) : Y441  
Packing group : II  
Labels : 4.1

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 445  
Packing instruction (LQ) : Y441  
Packing group : II  
Labels : 4.1

### 14.5 Environmental hazards

**ADR**

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

---

Environmentally hazardous : no

### IMDG

Marine pollutant : no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
aluminium powder (stabilised) (Number on list 40)  
ethyl acetate (Number on list 3)  
Poly(oxy-1,2-ethanediyl), alphasotridecyl-omega-hydroxy-, phosphate (Number on list 3)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

#### 15.2 Chemical safety assessment

No data available

---

### SECTION 16: Other information

#### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H228 : Flammable solid.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version 4.0      Revision Date: 28.02.2024      SDS Number: 102000034173      Print Date: 16.04.2024  
Date of first issue: 20.04.2021

Flam. Sol. : Flammable solids  
STOT SE : Specific target organ toxicity - single exposure  
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
2017/164/EU / STEL : Short term exposure limit  
2017/164/EU / TWA : Limit Value - eight hours  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Sol. 1      H228  
Eye Irrit. 2      H319  
STOT SE 3      H336

#### Classification procedure:

Based on product data or assessment  
Calculation method  
Calculation method



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ROTOVARIO 501 023

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
4.0	28.02.2024	102000034173	Date of first issue: 20.04.2021

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN