

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : UNIPAK WB 2287 Flexo Silver  
Product code : 024077HX0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address of person responsible for the SDS : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1      H318: Causes serious eye damage.  
Long-term (chronic) aquatic hazard, Category 3      H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Danger

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

Hazard statements : H318 Causes serious eye damage.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P273 Avoid release to the environment.  
P280 Wear eye protection/ face protection.  
**Response:**  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Hazardous components which must be listed on the label:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich  
2-(dimethylamino)-2-methylpropan-1-ol

### Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5  231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 10 - < 20
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	154518-38-4 (52933-07-0)  01-2119976356-25	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 2.5 - < 3

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**UNIPAK WB 2287 Flexo Silver**Version  
10.0Revision Date:  
12.02.2023SDS Number:  
102000029903Print Date: 16.04.2024  
Date of first issue: 07.08.2018

2-(dimethylamino)-2-methylpropan-1-ol	7005-47-2 230-279-6 01-2119963368-25	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318	$\geq 1 - < 3$
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411  specific concentration limit Skin Sens. 1; H317 $\geq 0.05$ % Skin Sens. 1; H317 $\geq 0.05$ %	$\geq 0.0025 - < 0.025$
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1B; H314 $\geq 0.6$ % Skin Irrit. 2; H315 0.06 - < 0.6 % Eye Irrit. 2; H319 0.06 - < 0.6 % Skin Sens. 1; H317 $\geq 0.0015$ % Eye Dam. 1; H318 $\geq 0.6$ % Skin Corr. 1C; H314 $\geq 0.6$ %	$\geq 0.0002 - < 0.0015$

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

			Skin Irrit. 2; H315 0.06 - < 0.6 % STOT RE 2; H319 0.06 - < 0.6 % Skin Sens. 1A; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 %	
--	--	--	--	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
- Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
10.0	12.02.2023	102000029903	Date of first issue: 07.08.2018

---

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye damage.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
ABC powder  
Foam

Unsuitable extinguishing media : Water  
Carbon dioxide (CO<sub>2</sub>)  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.

### 6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
10.0	12.02.2023	102000029903	Date of first issue: 07.08.2018

---

Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Advice on common storage : Do not store near acids.  
Do not store together with oxidizing and self-igniting products.  
Keep away from oxidizing agents and strongly acid or alkaline materials.  
Keep away from oxidizing agents, strongly alkaline and

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable fraction)	4 mg/m <sup>3</sup>	GB EH40
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version  
10.0

Revision Date:  
12.02.2023

SDS Number:  
102000029903

Print Date: 16.04.2024  
Date of first issue: 07.08.2018

concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	Workers	Inhalation	Long-term systemic effects	34.94 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	100.13 mg/kg
	Consumers	Inhalation	Long-term systemic effects	10.43 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	60.08 mg/kg
	Consumers	Ingestion	Long-term systemic effects	6.01 mg/kg
	2,2',2''-nitrilotriethanol	Workers	Inhalation	Long-term local effects
	Workers	Skin contact	Long-term systemic effects	7.5 mg/kg
	Workers	Skin contact	Long-term local effects	0.14 mg/cm <sup>2</sup>
	Consumers	Inhalation	Long-term local effects	0.4 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	3.3 mg/kg
	Consumers	Skin contact	Long-term systemic effects	2.66 mg/kg
	Consumers	Skin contact	Long-term local	0.07 mg/cm <sup>2</sup>



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version  
10.0

Revision Date:  
12.02.2023

SDS Number:  
102000029903

Print Date: 16.04.2024  
Date of first issue: 07.08.2018

			effects	
1,2-benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	0.966 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	0.345 mg/kg
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Workers	Inhalation	Long-term local effects	0.02 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0.04 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	0.02 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	0.04 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term local effects	0.090 mg/kg
	Consumers	Ingestion	Acute local effects	0.11 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value	
aluminium powder (stabilised)	Fresh water	0.0749 mg/l	
	clarification plant	20 mg/l	
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	Fresh water	0.00631 mg/l	
	Fresh water sediment	0.113 mg/kg	
	Intermittent water release	0.0631 mg/l	
	Marine water	0.000631 mg/l	
	Marine sediment	0.0113 mg/kg	
	STP	10 mg/l	
2,2',2''-nitrilotriethanol	Soil	0.0188 mg/kg	
	Soil	0.151 mg/kg	
1,2-benzisothiazol-3(2H)-one	Fresh water	0.32 mg/l	
	Fresh water sediment	1.7 mg/kg	
	clarification plant	10 mg/l	
	Marine water	0.032 mg/l	
	Marine sediment	0.17 mg/kg	
	STP	0.00103 mg/l	
1,2-benzisothiazol-3(2H)-one	Intermittent water release	0.0011 mg/l	
	Intermittent Release	0.00011 mg/l	
	Fresh water sediment	0.0499 mg/kg	
	Marine sediment	0.00499 mg/kg	
	Soil	3 mg/kg	
	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	Fresh water	0.00339 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

2-methyl-2H-isothiazol-3-one (3:1)		
	Intermittent water release	0.00339 mg/l
	Marine water	0.00339 mg/l
	Intermittent Release	0.00339 mg/l
	STP	0.23 mg/l
	Soil	0.0471 mg/kg
	Fresh water sediment	0.027 mg/kg
	Marine sediment	0.027 mg/kg
	Soil	0.01 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Goggles  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : silver  
Odour : characteristic  
Odour Threshold : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

---

Freezing point : No data available

Boiling point/boiling range : > 100 °C

Flammability : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 100 °C

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : 6 - 8  
Concentration: 100 %

Viscosity, kinematic : No data available

Solubility(ies)  
Water solubility : insoluble  
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Relative density : No data available

Density : No data available

Relative vapour density : No data available

Particle Size Distribution : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
10.0	12.02.2023	102000029903	Date of first issue: 07.08.2018

---

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.  
No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.  
No data available

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents

### 10.6 Hazardous decomposition products

This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

#### Components:

##### aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### 2-(dimethylamino)-2-methylpropan-1-ol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

##### 1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 0.4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

---

Assessment: The component/mixture is highly toxic after short term inhalation.

### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

- Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.
- Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.
- Acute dermal toxicity : Assessment: The component/mixture is highly toxic after single contact with skin.

### **Skin corrosion/irritation**

Not classified based on available information.

### **Product:**

Remarks : Extremely corrosive and destructive to tissue.

### **Components:**

#### **Phosphoric acid, C11-14-isoalkyl esters, C13-rich:**

Result : Skin irritation

#### **2-(dimethylamino)-2-methylpropan-1-ol:**

Result : Skin irritation

#### **1,2-benzisothiazol-3(2H)-one:**

Result : Skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Product:**

Remarks : May cause irreversible eye damage.

### **Components:**

#### **Phosphoric acid, C11-14-isoalkyl esters, C13-rich:**

Result : Corrosive

#### **2-(dimethylamino)-2-methylpropan-1-ol:**

Result : Corrosive

#### **1,2-benzisothiazol-3(2H)-one:**

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

---

Result : Corrosive

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Result : Corrosive

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### **1,2-benzisothiazol-3(2H)-one:**

Result : May cause sensitisation by skin contact.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

### 11.2 Information on other hazards

#### Further information

##### Product:

Remarks : No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

**Phosphoric acid, C11-14-isoalkyl esters, C13-rich:**

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

---

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 6.31 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 150 mg/l  
Exposure time: 72 h

### 1,2-benzisothiazol-3(2H)-one:

#### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Short-term (acute) aquatic hazard) : 100

M-Factor (Long-term (chronic) aquatic hazard) : 100

#### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

#### Product:

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

---

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

### SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : UN 9999  
Not permitted for transport

#### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not permitted for transport

#### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not permitted for transport

#### 14.4 Packing group

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not permitted for transport

---



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version 10.0      Revision Date: 12.02.2023      SDS Number: 102000029903      Print Date: 16.04.2024  
Date of first issue: 07.08.2018

---

**IATA (Passenger)** : Not permitted for transport

### 14.5 Environmental hazards

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

### 14.6 Special precautions for user

**Remarks** : Not classified as dangerous in the meaning of transport regulations.  
Due to the risk of hydrogen development we recommend to refrain from airfreighting this/these product(s).

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

**REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)** : Conditions of restriction for the following entries should be considered:  
Number on list 3  
aluminium powder (stabilised)  
(Number on list 40)  
Phosphoric acid, C11-14-isoalkyl esters, C13-rich (Number on list 3)  
2-(dimethylamino)-2-methylpropan-1-ol (Number on list 40, 3)  
Alcohols, C16-18, ethoxylated (Number on list 3)

**UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation** : Not applicable

**The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)** : Not applicable

**Regulation (EC) No 1005/2009 on substances that deplete the ozone layer** : Not applicable

**UK REACH List of substances subject to authorisation (Annex XIV)** : Not applicable

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
10.0	12.02.2023	102000029903	Date of first issue: 07.08.2018

### 15.2 Chemical safety assessment

No data available

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H228	: Flammable solid.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Flam. Liq.	: Flammable liquids
Flam. Sol.	: Flammable solids
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## UNIPAK WB 2287 Flexo Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
10.0	12.02.2023	102000029903	Date of first issue: 07.08.2018

---

- Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Eye Dam. 1	H318
Aquatic Chronic 3	H412

#### Classification procedure:

Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN