

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : STAPA BG HYDROLAN 2192 55900/G Aluminium Paste
Material number : 005350GK0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Acute toxicity, Category 5, Oral, H303
Acute toxicity, Category 4, Inhalation, H332
Skin corrosion/irritation, Category 2, H315

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

Serious eye damage/eye irritation, Category 2A, H319

GHS-Labelling

Symbol(s)

:



Signal word

:

Warning

Hazard statements

:

H303: May be harmful if swallowed.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.

Precautionary statements

:

Prevention:

P261 Avoid breathing dust.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P332 + P317 IF SWALLOWED or if skin irritation occurs: Get medical help.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P317 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P317 If eye irritation persists: Get medical help.

Hazardous components which must be listed on the label

Identification
2-butoxyethanol

CAS-No.
111-76-2

Other hazards which do not result in classification

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

Combustible Solids

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

| Chemical name | CAS-No. EINECS-No. | Classification and labelling | Concentration[%] |
|--|------------------------|--|------------------|
| aluminium | 7429-90-5 231-072-3 | Flam. Sol.;1;H228 | 50 - 100 |
| 2-butoxyethanol | 111-76-2 203-905-0 | Flam. Liq.;4;H227 Acute Tox.;4;H302 Acute Tox.;3;H331 ;2;H315 ;2A;H319 | 25 - 50 |
| N-(3-(trimethoxysilyl)propyl)ethylenediamine | 1760-24-3 217-164-6 | Acute Tox.;5;H303 Acute Tox.;4;H332 ;1;H318 Skin Sens.;1;H317 | 0,1 - 1 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

General advice : Move the victim to fresh air.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

- | | |
|-------------------------|--|
| If inhaled | : Remove to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. |
| In case of skin contact | : Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician. If on clothes, remove clothes. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water. Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |
| If swallowed | : Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.


SECTION 5: Firefighting measures**5.1 Extinguishing media**

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Dry sand, Special powder against metal fire |
| Unsuitable extinguishing media | : Water, Foam, ABC powder, Carbon dioxide (CO ₂) |

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

| | | |
|-------------|--------------|---|
| Page 4 / 20 | 102000020087 | A member of  ALTANA |
|-------------|--------------|---|

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

Special protective equipment : Use personal protective equipment.
for firefighters

Wear self-contained breathing apparatus for firefighting if
necessary.

Further information : Use extinguishing measures that are appropriate to local
circumstances and the surrounding environment.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Remove all sources of ignition.
Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Ensure adequate ventilation.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water
courses or the soil.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

This information is not available.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation.
- Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.
- Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.
- Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from humidity and water. Do not allow to dry.
- Advice on common storage : Do not store together with oxidizing and self-igniting products.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Germany:

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Update | Basis |
|---|-----------|---|--------------------------------|------------|-------------|
| aluminium | 7429-90-5 | AGW (Inhalable fraction) | 10 mg/m ³ | 2021-07-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category) | | 2;(II) | | | |
| Further information | | When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| aluminium | 7429-90-5 | AGW (Alveolate fraction) | 1,25 mg/m ³ | 2021-07-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category) | | 2;(II) | | | |
| Further information | | When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| 2-butoxyethanol | 111-76-2 | TWA | 20 ppm 98 mg/m ³ | 2000-06-16 | 2000/39/EC |
| Further information | | Identifies the possibility of significant uptake through the | | | |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

| | | | | | |
|---|-----------|--|---------------------------------|------------|-------------|
| | | skinIndicative | | | |
| 2-butoxyethanol | 111-76-2 | STEL | 50 ppm 246 mg/m ³ | 2000-06-16 | 2000/39/EC |
| Further information | | Identifies the possibility of significant uptake through the skinIndicative | | | |
| 2-butoxyethanol | 111-76-2 | AGW | 10 ppm 49 mg/m ³ | 2019-03-29 | DE TRGS 900 |
| Peak-limit: excursion factor (category) | | 2;(I) | | | |
| Further information | | Skin absorptionWhen there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| silicon dioxide | 7631-86-9 | AGW (Inhalable fraction) | 4 mg/m ³ | 2013-09-19 | DE TRGS 900 |
| Further information | | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, silicagel).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |

United States of America (USA):

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Update | Basis |
|------------|-----------|-------------------------------|-------------------------------------|------------|-------|
| aluminium | 7429-90-5 | TWA (total dust) | 50 Million particles per cubic foot | 2012-07-01 | |
| aluminium | 7429-90-5 | TWA (Respirable) | 5 mg/m ³ | 2013-10-08 | |
| aluminium | 7429-90-5 | TWA (total dust) | 15 mg/m ³ | 2012-07-01 | |
| aluminium | 7429-90-5 | TWA (total) | 10 mg/m ³ | 2013-10-08 | |
| aluminium | 7429-90-5 | TWA (respirable fraction) | 5 mg/m ³ | 2012-07-01 | |
| aluminium | 7429-90-5 | TWA (respirable fraction) | 15 Million particles per cubic foot | 2012-07-01 | |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

| | | | | | |
|-----------------|-----------|-------------------------------------|---------------------|------------|--|
| aluminium | 7429-90-5 | PEL (Total dust) | 10 mg/m3 | 2014-11-26 | |
| aluminium | 7429-90-5 | PEL (respirable dust fraction) | 5 mg/m3 | 2014-11-26 | |
| aluminium | 7429-90-5 | TWA (Respirable particulate matter) | 1 mg/m3 | 2008-01-01 | |
| aluminium | 7429-90-5 | TWA | 5 mg/m3 | 2005-09-01 | |
| aluminium | 7429-90-5 | TWA (Total) | 15 mg/m3 | 1989-01-19 | |
| aluminium | 7429-90-5 | TWA (Respirable fraction) | 5 mg/m3 | 1989-01-19 | |
| aluminium | 7429-90-5 | TWA (total dust) | 15 mg/m3 | 2011-07-01 | |
| aluminium | 7429-90-5 | TWA (respirable fraction) | 5 mg/m3 | 2011-07-01 | |
| aluminium | 7429-90-5 | TWA (Total dust) | 15 mg/m3 | 1989-01-19 | |
| aluminium | 7429-90-5 | TWA (respirable dust fraction) | 5 mg/m3 | 1989-01-19 | |
| aluminium | 7429-90-5 | TWA (welding fumes) | 5 mg/m3 | 2013-10-08 | |
| aluminium | 7429-90-5 | TWA (pyro powders) | 5 mg/m3 | 2013-10-08 | |
| aluminium | 7429-90-5 | TWA (Respirable particulate matter) | 1 mg/m3 | 2013-03-01 | |
| aluminium | 7429-90-5 | TWA (Fumes) | 5 mg/m3 | 1989-01-19 | |
| aluminium | 7429-90-5 | PEL (Welding fumes) | 5 mg/m3 | 2017-10-02 | |
| aluminium | 7429-90-5 | PEL (Pyro powders) | 5 mg/m3 | 2017-10-02 | |
| aluminium | 7429-90-5 | TWA (powder) | 5 mg/m3 | 1989-01-19 | |
| 2-butoxyethanol | 111-76-2 | TWA | 20 ppm | 2013-03-01 | |
| 2-butoxyethanol | 111-76-2 | TWA | 5 ppm 24 mg/m3 | 2013-10-08 | |
| 2-butoxyethanol | 111-76-2 | TWA | 50 ppm 240 mg/m3 | 1997-08-04 | |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

| | | | | | |
|-----------------|-----------|------------|---|------------|--|
| I | | | | | |
| 2-butoxyethano | 111-76-2 | TWA | 25 ppm 120 mg/m ³ | 1989-01-19 | |
| I | | | | | |
| 2-butoxyethano | 111-76-2 | PEL | 20 ppm 97 mg/m ³ | 2014-11-26 | |
| I | | | | | |
| silicon dioxide | 7631-86-9 | TWA (Dust) | 20 Million particles per cubic foot | 2012-07-01 | |
| silicon dioxide | 7631-86-9 | TWA (Dust) | 80 mg/m ³ / %SiO ₂ | 2012-07-01 | |
| silicon dioxide | 7631-86-9 | TWA | 6 mg/m ³ | 2013-10-08 | |
| silicon dioxide | 7631-86-9 | PEL | 6 mg/m ³ | 2014-11-26 | |

8.2 Exposure controls

Personal protective equipment

- Eye protection : Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection : Solvent-resistant gloves
- Material : Solvent-resistant gloves
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

- Recommended preventive skin protection
Skin should be washed after contact.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
: Long sleeved clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
: Use suitable breathing protection if workplace concentration requires.
: In the case of dust or aerosol formation use respirator with an approved filter.
Dust safety masks are recommended when the dust concentration is more than 10 mg/m³.

Environmental exposure controls

- General advice : The product should not be allowed to enter drains, water courses or the soil.
: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance : Pasty solid
- Colour : silver

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

| | |
|--|---|
| Odour | : characteristic |
| pH | : substance/mixture is non-soluble (in water) |
| Melting point/range | : Not applicable |
| Boiling point/boiling range | : 168 - 172 °C |
| Flash point | : No data available |
| Bulk density | : No data available |
| Flammability (solid, gas) | : Combustible Solids |
| Auto-flammability | : not auto-flammable |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapour pressure | : No data available |
| Density | : 1,3 - 2,0 g/cm ³ |
| Solubility(ies) | |
| Water solubility | : insoluble |
| Miscibility with water | : partly miscible |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Ignition temperature | : No data available |
| Thermal decomposition | : No data available |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : No data available |
| Flow time | : No data available |
| Explosive properties | : Not explosive |

9.2 Other information

No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.
Contact with acids and alkalis may release hydrogen.
Mixture reacts slowly with water resulting in evolution of hydrogen.
Vapour/air-mixtures are explosive at intense warming.

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.
No data available

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents
Highly halogenated compounds

10.6 Hazardous decomposition products

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

Components:**2-butoxyethanol :**

Acute oral toxicity : Acute toxicity estimate : 1 200 mg/kg

Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate : 3 mg/l

Test atmosphere: vapour

Method: Expert judgement

N-(3-(trimethoxysilyl)propyl)ethylenediamine :

Acute oral toxicity : LD50 Rat: ca. 2 995 mg/kg

Acute inhalation toxicity : LC50 : 1,49 - 2,44 mg/l

Exposure time: 4 h

Test atmosphere: vapour

The component/mixture is moderately toxic after short term
inhalation.

Skin corrosion/irritation**Product**

May cause skin irritation in susceptible persons.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

Serious eye damage/eye irritation**Product**

May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

No data available

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological : No data available
information

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

- | | | |
|------------------------|---|--|
| Product | : | Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. |

SECTION 14: Transport information**14.1 UN number****ADR**

Not dangerous goods

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.2 Proper shipping name**ADR**

Not dangerous goods

TDG

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

Not dangerous goods

CFR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.3 Transport hazard class**ADR**

Not dangerous goods

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.4 Packing group**ADR**

Not dangerous goods

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

Not dangerous goods

IATA

Not dangerous goods

14.5 Environmental hazards**14.6 Special precautions for user**

Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

| | |
|--|---|
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). | : Not applicable |
| REACH - List of substances subject to authorisation (Annex XIV) | : Not applicable |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer | : Not applicable |
| Regulation (EU) 2019/1021 on persistent organic pollutants (recast) | : Not applicable |
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : Banned and/or restricted (aluminium powder (stabilised)) (2-butoxyethanol) (N-(3-(trimethoxysilyl)propyl)ethylenediamine) |

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA BG HYDROLAN 2192 55900/G Aluminium Paste

Version 3.0

Revision Date 01.12.2023

Print Date 02.12.2023

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Full text of H-Statements**

| | |
|------|--|
| H227 | : Combustible liquid. |
| H228 | : Flammable solid. |
| H302 | : Harmful if swallowed. |
| H303 | : May be harmful if swallowed. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage. |
| H319 | : Causes serious eye irritation. |
| H331 | : Toxic if inhaled. |
| H332 | : Harmful if inhaled. |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.