according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version | Revision Date: | SDS Number: | Print Date: 28.02.2023 |
|---------|----------------|--------------|---------------------------------|
| 6.0 | 27.02.2023 | 102000031721 | Date of first issue: 12.07.2019 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

| 1.1 Product identifier | | |
|------------------------|---|--------------------------------------|
| Trade name | : | METALSTAR 03 0104 Black Label Silver |
| Product code | : | 050157RC0 |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Use of the | : | Colorant; Printing ink related material; Printing ink, Colouring |
|-------------------|---|--|
| Substance/Mixture | | agents, dyes |

1.3 Details of the supplier of the safety data sheet

| Company | : | ECKART GmbH Guentersthal 4 91235 Hartenstein |
|--|---|--|
| Telephone | : | +499152770 |
| Telefax | : | +499152777008 |
| E-mail address of person responsible for the SDS | : | msds.eckart@altana.com |

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

| Classification (REGULATION (EC) No 1272/2008) | |
|---|--|
|---|--|

Eye irritation, Category 2 H319: Causes serious eye irritation.

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects. Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | - | SDS Number: 02000031721 | Print Date: 28.02.2023 Date of first issue: 12.07.2019 |
|----------------|---------------------------|---|---|--|
| Haza | rd pictograms | : | | |
| Signa | al word | : | Warning | |
| Haza | rd statements | : | H319 H411 | Causes serious eye irritation. Toxic to aquatic life with long lasting effects. |
| Preca | autionary statements | : | Prevention: P264 P273 P280 Response: P337 + P313 P391 Disposal: P501 | Wash skin thoroughly after handling. Avoid release to the environment. Wear eye protection/ face protection. If eye irritation persists: Get medical advice/ attention. Collect spillage. Dispose of contents/ container to an approved waste disposal plant. |

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

| Components | | | |
|--|--|---|--------------------------|
| Chemical name | CAS-No. EC-No. Index-No. Registration number | ClassificationREGUL ATION (EC) No 1272/2008 | Concentration (% w/w) |
| Petroleum resins | 64742-16-1 265-116-8 | Aquatic Chronic 4; H413 | >= 20 - < 25 |
| Distillates (petroleum), hydrotreated middle; Gasoil — unspecified | 64742-46-7 265-148-2 649-221-00-X | Asp. Tox. 1; H304 EUH066 | >= 10 - < 20 |
| aluminium powder (stabilised) | 7429-90-5 231-072-3 013-002-00-1 01-2119529243-45 | Flam. Sol. 1; H228 | >= 10 - < 20 |

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | | Number: 000031721 | | Date: 28.02.2023 of first issue: 12.07.2019 |) |
|----------------|--|---------|--|------|---|--------------|
| hydro | tha (petroleum), treated heavy; Low bo ydrogen treated napht | | 64742-48-9 918-481-9 01-2119457273 | 8-39 | Asp. Tox. 1; H304 | >= 1 - < 10 |
| | propyl-2,2- hyltrimethylene diisob | utyrate | 6846-50-0 229-934-9 01-2119451093 | 8-47 | Repr. 2; H361d Aquatic Chronic 3; H412 | >= 1 - < 2.5 |
| octad | lecylamine | | 124-30-1 204-695-3 612-282-00-8 01-2119473804 | -32 | Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373 (Liver, Gastrointestinal tract, Immune system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10 | >= 1 - < 2.5 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

| General advice | Move the victim to fresh air. | |
|-------------------------|--|---------------------|
| | Move out of dangerous area. Show this safety data sheet to the Do not leave the victim unattende | |
| If inhaled | Remove to fresh air. If unconscious, place in recovery advice. If symptoms persist, call a physici | • |
| In case of skin contact | Wash off immediately with soap a | nd plenty of water. |
| | If skin irritation persists, call a phy If on clothes, remove clothes. | rsician. |
| In case of eye contact | Immediately flush eye(s) with pler | nty of water. |
| | Immediately flush eye(s) with pler Remove contact lenses. | nty of water. |



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Number: 102000031721 | Print Date: 28.02.2023 Date of first issue: 12.07.2019 |
|----------------|---------------------------|----------------------------------|---|
| | | | open while rinsing. persists, consult a specialist. |
| lf swa | llowed | Never give any If symptoms pe | ry tract clear. k or alcoholic beverages. thing by mouth to an unconscious person. ersist, call a physician. mediately to hospital. |
| | | | |

4.2 Most important symptoms and effects, both acute and delayed

| Risks | : Causes serious eye irritation. |
|-------|----------------------------------|
|-------|----------------------------------|

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

| 5.1 Extinguishing media | | |
|---|-----|---|
| Suitable extinguishing media | : | Dry sand ABC powder Foam |
| Unsuitable extinguishing media | : | High volume water jet Carbon dioxide (CO2) |
| | | High volume water jet |
| 5.2 Special hazards arising from | the | e substance or mixture |
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| 5.3 Advice for firefighters | | |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Num 10200003 | | Print Date: 28.02.2023 Date of first issue: 12.07.2019 | | | |
|---|---------------------------|---------------------|---|--|--|--|--|
| Personal precautions | | | Evacuate personnel to safe areas. Use personal protective equipment. | | | | |
| 6.2 Environmental precautions Environmental precautions | | | The product should not be allowed to enter drains, water courses or the soil. | | | | |
| | | Prever If the p | nt further le | rom entering drains. akage or spillage if safe to do so. taminates rivers and lakes or drains inform ities. | | | |
| 6.3 Method | ls and material for co | ntainment a | and cleani | ng up | | | |
| Metho | ds for cleaning up | Soak u | ip with inei | nandling equipment. t absorbent material (e.g. sand, silica gel, ersal binder, sawdust). | | | |
| | | acid bi | nder, unive | t absorbent material (e.g. sand, silica gel, ersal binder, sawdust). closed containers for disposal. | | | |

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Advice on safe handling | : | Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. |
|---|---|--|
| Advice on protection against fire and explosion | : | Normal measures for preventive fire protection. |
| Hygiene measures | : | When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. |

7.2 Conditions for safe storage, including any incompatibilities

| Requirements for storage | : | Earthing of containers and apparatuses is essential. Reaction |
|--------------------------|---|---|
| areas and containers | | with water liberates extremely flammable gas (hydrogen) Take |
| | | measures to prevent the build up of electrostatic charge. Use |
| | | explosion-proof equipment. Store in original container. Keep |

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Num 10200003 | | Print Date: 28.02.2023 Date of first issue: 12.07.2019 |
|----------------|---|-------------------------|---|---|
| | | away | | closed in a cool, well-ventilated place. Keep es of ignition - No smoking. Keep container in use. |
| | | place resea preca | . Containers led and kep utions. Elec | ghtly closed in a dry and well-ventilated which are opened must be carefully t upright to prevent leakage. Observe label trical installations / working materials must echnological safety standards. |
| | Further information on storage conditions | | ct from hum | idity and water. |
| Ac | Advice on common storage | | Do not store near acids. Do not store together with oxidizing and self-igniting Never allow product to get in contact with water due storage. Keep away from oxidizing agents, strongly alkaline strongly acid materials in order to avoid exothermic | |
| | rther information on prage stability | : No de | compositio | n if stored and applied as directed. |

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|----------------------------------|--|---|---|---|
| aluminium powder (stabilised) | 7429-90-5 | TWA (Inhalable) | 10 mg/m3 | GB EH40 |
| | | TWA (Respirable fraction) | 4 mg/m3 | GB EH40 |
| | | TWA (inhalable dust) | 10 mg/m3 | GB EH40 |
| | inhalable dust when samplin MDHS14/4 Ge respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply | are those fractions g is undertaken in a eneral methods for s pracic and inhalable zardous to health inc in air equal to or gre or 4 mg.m-3 8-hour be subject to COSHF dusts have been as with the appropriate | ses of these limits, respirable of airborne dust which will be ccordance with the methods ampling and gravimetric ana aerosols., The COSHH defin cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du igned specific WELs and ex limits., Most industrial dusts The behaviour, deposition a | e collected described in lysis or ition of a present at a TWA of s means that st above these posure to these contain |

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Number: 102000031721 | Print Date: 28 Date of first i | 8.02.2023 ssue: 12.07.2019 | |
|----------------|---|---|--|---|---|
| | respo distin and 'r mater availa to the defini conta shoul | ular particle after entry nse that it elicits, depe guishes two size fraction espirable'., Inhalable d tial that enters the nose uble for deposition in the fraction that penetrate tions and explanatory of in components that have d be complied with., W re three times the long TWA (Respire | nd on the nature ons for limit-settin lust approximate e and mouth duri e respiratory traces to the gas exc material are give ve their own ass 'here no specific -term exposure | and size of the pa ng purposes terme is to the fraction of ing breathing and i ct. Respirable dust hange region of the n in MDHS14/4., V igned WEL, all the short-term exposu limit should be use | article. HSE d 'inhalable' airborne s therefore approximates e lung. Fuller Vhere dusts relevant limits are limit is listed, |
| | dust) Further information: For the inhalable dust are those frawhen sampling is undertake MDHS14/4 General methor respirable, thoracic and infisubstance hazardous to be concentration in air equal to inhalable dust or 4 mg.m-3 any dust will be subject to levels. Some dusts have be must comply with the appring particles of a wide range of particular particle after enter response that it elicits, dep distinguishes two size fract and 'respirable'., Inhalable material that enters the not available for deposition in to the fraction that penetrate definitions and explanatory contain components that he should be complied with., we after the transmitted of the fraction that penetrate the transmitted of the should be complied with. | | tions of airborne n in accordance s for sampling an alable aerosols., alth includes dust or greater than 3-hour TWA of re OSHH if people en assigned spe priate limits., Mos sizes. The behave into the human and on the nature ons for limit-settin lust approximate e and mouth duri e respiratory traces to the gas exc material are give ve their own ass here no specific | e dust which will be with the methods and gravimetric ana The COSHH defin t of any kind when 10 mg.m-3 8-hour espirable dust. This are exposed to du cific WELs and exp st industrial dusts of viour, deposition ar respiratory system and size of the pa ng purposes terme to the fraction of ing breathing and i ct. Respirable dust hange region of the n in MDHS14/4., V igned WEL, all the short-term exposu | collected described in lysis or ition of a present at a TWA of a means that st above these posure to these contain nd fate of any , and the body urticle. HSE d 'inhalable' airborne s therefore approximates e lung. Fuller /here dusts relevant limits ure limit is listed, |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value | | | |
|--|-----------|-----------------|-------------------------------|------------|--|--|--|
| aluminium powder (stabilised) | Workers | Inhalation | Long-term systemic effects | 3.72 mg/m3 | | | |
| | Workers | Inhalation | Long-term local effects | 3.72 mg/m3 | | | |
| | Consumers | Oral | Long-term systemic effects | 3.95 mg/kg | | | |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha | Workers | Inhalation | Acute systemic effects | 1500 mg/m3 | | | |
| | Workers | Skin contact | Long-term systemic | 300 mg/kg | | | |

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version Revision Date: 6.0 27.02.2023 | | te: SDS Nu 1020000 | | Print Date: 28.02.2023 Date of first issue: 12.07.2019 | | | |
|--|---|-----------------------|--------------|---|-------------|--|--|
| | | | | effects | | | |
| | | Consumers | Ingestion | Long-term systemic effects | 300 mg/kg | | |
| | | Consumers | Skin contact | Long-term systemic effects | 300 mg/kg | | |
| | | Consumers | Inhalation | Long-term systemic effects | 900 mg/m3 | | |
| | 1-isopropyl-2,2- dimethyltrimethylene diisobutyrate | Workers | Skin contact | Long-term systemic effects | 5.00 mg/kg | | |
| | | Workers | Inhalation | Long-term systemic effects | 17.62 mg/m3 | | |
| | | Consumers | Ingestion | Long-term systemic effects | 5.00 mg/kg | | |
| | | Consumers | Skin contact | Long-term systemic effects | 5.00 mg/kg | | |
| | | Consumers | Inhalation | Long-term systemic effects | 4.35 mg/m3 | | |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|---|----------------------------|-------------|
| aluminium powder (stabilised) | Fresh water | 0.0749 mg/l |
| | clarification plant | 20 mg/l |
| 1-isopropyl-2,2- dimethyltrimethylene diisobutyrate | Fresh water | 0.014 mg/l |
| | Marine water | 0.0014 mg/l |
| | Fresh water sediment | 5.29 mg/kg |
| | Soil | 1.05 mg/kg |
| | STP | 3 mg/l |
| | Marine sediment | 0.529 mg/kg |
| | oral (secondary poisoning) | 83.3 mg/kg |

8.2 Exposure controls

Personal protective equipment

| Eye/face protection | : | Goggles | | |
|-----------------------------|---|--|--|--|
| | | Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems. | | |
| Hand protection Material | : | Solvent-resistant gloves (butyl-rubber) | | |
| Remarks | : | Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and | | |

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Versi 6.0 | ion | Revision Date: 27.02.2023 | | DS Number: 2000031721 | Print Date: 28.02.2023 Date of first issue: 12.07.2019 |
|--------------|---------|---------------------------|---|--|--|
| | | | | gloves. Also take conditions under danger of cuts, at Recommended p washed after con | e which are provided by the supplier of the into consideration the specific local which the product is used, such as the orasion, and the contact time. reventive skin protection Skin should be tact. The suitability for a specific workplace sed with the producers of the protective |
| ę | Skin ar | nd body protection | : | | ng tection according to the amount and he dangerous substance at the work place. |
| I | Respira | atory protection | : | Use suitable brea requires. | thing protection if workplace concentration |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Physical state | : | liquid |
|---|---|-------------------|
| Colour | : | silver |
| Odour | : | characteristic |
| Odour Threshold | : | No data available |
| Freezing point | : | No data available |
| Boiling point/boiling range | : | 240 °C |
| Flammability | : | No data available |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Flash point | : | > 100 °C |
| Auto-ignition temperature | : | Not relevant |
| Decomposition temperature | : | No data available |



METALSTAR 03 0104 Black Label Silver

| Vers 6.0 | sion | Revision Date: 27.02.2023 | | S Number: 2000031721 | Print Date: 28.02.2023 Date of first issue: 12.07.2019 |
|-------------|--------------------|------------------------------|---|-------------------------|---|
| | рН | | : | substance/mixtur | e is non-soluble (in water) |
| | Viscosi Visc | ity cosity, kinematic | : | > 21 mm2/s (40 ° | °C) |
| | Wat | ter solubility | : | No data available | 2 |
| | Solu | ubility in other solvents | : | No data available | 9 |
| | Partitio octano | n coefficient: n- I/water | : | No data available |) |
| | Vapou | rpressure | : | No data available |) |
| | Relativ | e density | : | No data available | 9 |
| | Density | / | : | No data available | 9 |
| | Relativ | e vapour density | : | No data available | 9 |
| | Par | ticle Size Distribution | : | No data available | 9 |

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

| Hazardous reactions | : Contact with acids and alkalis may release hydrog | |
|-----------------------------|---|---|
| | | No decomposition if stored and applied as directed. |
| 10.4 Conditions to avoid | | |
| Conditions to avoid | : | Do not allow evaporation to dryness. |
| | | No data available |
| 10.5 Incompatible materials | | |
| Materials to avoid | : | Acids Bases Oxidizing agents |

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version | Revision Date: | SDS Number: | Print Date: 28.02.2023 |
|---------|----------------|--------------|---------------------------------|
| 6.0 | 27.02.2023 | 102000031721 | Date of first issue: 12.07.2019 |

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

| Acute inhalation toxicity | : | LC50 (Rat): > 5 mg/l |
|---------------------------|---|----------------------------|
| | | Exposure time: 4 h |
| | | Test atmosphere: dust/mist |

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

| Acute oral toxicity | : | LD50 (Rat): > 5,000 mg/kg |
|---------------------------|---|--|
| Acute inhalation toxicity | : | LC50 (Rat): Test atmosphere: vapour Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration. |
| Acute dermal toxicity | : | LD50 (Rabbit): > 5,000 mg/kg |

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

| Acute dermal toxicity | : | LD50 Dermal (Rabbit): > 2,000 mg/kg |
|-----------------------|---|-------------------------------------|
| | | Method: OECD Test Guideline 402 |

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

| Rabbit |
|-------------------------|
| 4 h |
| OECD Test Guideline 404 |
| No skin irritation |
| |

octadecylamine:

Assessment : Irritating to skin.

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| ersion 0 | Revision Date: 27.02.2023 | SDS Number: 102000031721 | Print Date: 28.02.2023 Date of first issue: 12.07.2019 |
|--|---|-----------------------------|---|
| Serio | ous eye damage/eye | irritation | |
| Cause | es serious eye irritatio | n. | |
| Prod | uct: | | |
| Rema | arks | : May cause irrev | versible eye damage. |
| <u>Com</u> | ponents: | | |
| 1-iso | propyl-2,2-dimethylt | rimethylene diisobuty | vrate: |
| Speci | | : Rabbit | |
| | sure time | : 72 h | |
| Metho | | : OECD Test Gu | |
| Resu | I | : No eye irritatior | I |
| octac | lecylamine: | | |
| Asses | ssment | : Corrosive | |
| Resp | iratory or skin sensi | tisation | |
| Skin | sensitisation | | |
| Not c | lassified based on ava | ailable information. | |
| Resp | iratory sensitisation | | |
| Not c | lassified based on ava | ailable information. | |
| Germ cell mutagenicity Not classified based on available information. | | | |
| | | | |
| Naph | tha (petroleum), hyd | rotreated heavy; Low | v boiling point ydrogen treated naphtha: |
| | cell mutagenicity- ssment | | d on benzene content < 0.1% (Regulation (EC nex VI, Part 3, Note P) |
| | i nogenicity lassified based on ava | ailable information. | |
| <u>Com</u> | ponents: | | |
| Distil | lates (petroleum), hy | drotreated middle; G | asoil — unspecified: |
| | nogenicity - ssment | | d on the conditions cited in Nota N (Regulation 3, Annex VI, Part 3, Note N) |
| Naph | tha (petroleum), hyd | rotreated heavy; Low | v boiling point ydrogen treated naphtha: |
| | nogenicity - ssment | | d on benzene content < 0.1% (Regulation (EC nex VI, Part 3, Note P) |
| Repro | oductive toxicity | | |
| Not c | lassified based on ava | ailable information. | |

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version | Revision Date: | SDS Number: | Print Date: 28.02.2023 |
|---------|----------------|--------------|---------------------------------|
| 6.0 | 27.02.2023 | 102000031721 | Date of first issue: 12.07.2019 |

Components:

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Reproductive toxicity -
Assessment:Some evidence of adverse effects on development, based on
animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

octadecylamine:

| Exposure routes | : | Ingestion |
|-----------------|---|--|
| Target Organs | : | Liver, digestive system, Immune system |
| Assessment | : | May cause damage to organs through prolonged or repeated |
| | | exposure. |

Aspiration toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha: May be fatal if swallowed and enters airways.

octadecylamine:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Further information

Product:

Remarks

: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Petroleum resins:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Number: 102000031721 | Print Date: 28.02.2023 Date of first issue: 12.07.2019 | | | | |
|----------------|---|-----------------------------|--|--|--|--|--|
| 1-i | 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate: | | | | | | |
| | xicity to daphnia and other uatic invertebrates | : (Daphnia (wat | er flea)): 2.46 mg/l | | | | |
| | otoxicology Assessment ronic aquatic toxicity | | atic life with long lasting effects. | | | | |
| ос | tadecylamine: | | | | | | |
| | Factor (Short-term (acute) uatic hazard) | : 10 | | | | | |
| | Factor (Long-term nronic) aquatic hazard) | : 10 | | | | | |
| Ec | otoxicology Assessment | | | | | | |
| Ac | ute aquatic toxicity | : Very toxic to ac | quatic life. | | | | |
| Ch | ronic aquatic toxicity | : Very toxic to ac | quatic life with long lasting effects. | | | | |
| | 12.2 Persistence and degradability No data available | | | | | | |
| | oaccumulative potential data available | | | | | | |
| | obility in soil data available | | | | | | |
| 12.5 Re | esults of PBT and vPvB as | ssessment | | | | | |
| - | oduct: sessment | to be either per | e/mixture contains no components considered rsistent, bioaccumulative and toxic (PBT), or and very bioaccumulative (vPvB) at levels of | | | | |
| | docrine disrupting prope | erties | | | | | |
| | her adverse effects | | | | | | |
| Ad | oduct: ditional ecological ormation | unprofessional | ital hazard cannot be excluded in the event of handling or disposal. c life with long lasting effects. | | | | |
| <u>Cc</u> | mponents: | | | | | | |
| Na | Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha: | | | | | | |
| | | | | | | | |

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Versi 6.0 | ion | Revision Date: SDS Number: 27.02.2023 102000031721 | | ••••••••••••••••••••••••••••••••••••••• | Print Date: 28.02.2023 Date of first issue: 12.07.2019 | |
|--------------|--------------------|--|------|---|---|--|
| | Additio informa | nal ecological ation | : | No data available | | |
| SEC | TION | 13: Disposal consid | dera | ations | | |
| | | an Waste Catalogue an Waste Catalogue | : | | rrous metal dust and particles particulates and dust (including ball-mill dust) lous substances | |
| 13.1 | Waste | treatment methods | | | | |
| | Product | | : | courses or the so Do not contamina chemical or used | te ponds, waterways or ditches with | |
| | Contan | ninated packaging | : | Empty remaining Dispose of as unu Do not re-use em | used product. | |

SECTION 14: Transport information

| 14.1 UN number or ID number | | | |
|---------------------------------|---|---|--------------------------------------|
| ADR | : | UN 3082 | |
| IMDG | : | UN 3082 | |
| ΙΑΤΑ | : | UN 3082 | |
| 14.2 UN proper shipping name | | | |
| ADR | : | ENVIRONMENTALL N.O.S. (paint related materia | Y HAZARDOUS SUBSTANCE, LIQUID, I) |
| IMDG | : | ENVIRONMENTALL' N.O.S. (paint related materia | Y HAZARDOUS SUBSTANCE, LIQUID, I) |
| ΙΑΤΑ | : | Environmentally hazardous substance, liquid, n.o.s. (paint related material) | |
| 14.3 Transport hazard class(es) | | | |
| | | Class | Subsidiary risks |
| ADR | : | 9 | |
| IMDG | : | 9 | |
| ΙΑΤΑ | : | 9 | |

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | | DS Number: 02000031721 | Print Date: 28.02.2023 Date of first issue: 12.07.2019 |
|-----------------------|---|---|-----------------------------|---|
| 14.4 Pac | king group | | | |
| Clas Haza Labe | king group sification Code ard Identification Number | | III M6 90 9 (-) | |
| Labe | king group | : | III 9 F-A, S-F | |
| Pack aircr Pack | king instruction (LQ) | | 964 Y964 III 9 | |
| Pacł (pas Pacł | A (Passenger) king instruction senger aircraft) king instruction (LQ) king group els | | 964 Y964 III 9 | |
| 14.5 Env | ironmental hazards | | | |
| ADR Envi | t ronmentally hazardous | : | yes | |
| IMD Mari | G ne pollutant | : | yes | |
| 14.6 Spe | cial precautions for use | r | | |
| Rem | arks | : | packagings conta | gings <=5L / 5 kg, or combination aining inner packagings <= 5L / 5 kg net per SV375 ADR, 2.10.2.7 IMDG-Code, A197 be applied. |
| T L . | | | | |

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006



METALSTAR 03 0104 Black Label Silver

| Version | Revision Date: | SDS Number: | Print Date: 28.02.2023 |
|---------|----------------|--------------|---------------------------------|
| 6.0 | 27.02.2023 | 102000031721 | Date of first issue: 12.07.2019 |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : | Conditions of restriction for the following entries should be considered: Number on list 3 Distillates (petroleum), hydrotreated middle; Gasoil — unspecified (Number on list 3) aluminium powder (stabilised) (Number on list 40) Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha (Number on list 3) 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (Number on list 3) Distillates (petroleum), hydro- treated light; Kerosine — unspecified (Number on list 3) |
|--|---|---|
| UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation | : | Not applicable |
| The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) | : | Not applicable |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer | : | Not applicable |
| UK REACH List of substances subject to authorisation (Annex XIV) | : | Not applicable |

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

| Full | text of | H-Statements |
|------|---------|--------------|
|------|---------|--------------|

| H228 | : Flammable solid. |
|-------|---|
| H304 | : May be fatal if swallowed and enters airways. |
| H315 | : Causes skin irritation. |
| H318 | : Causes serious eye damage. |
| H361d | : Suspected of damaging the unborn child. |
| | |



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | | S Number: 2000031721 | Print Date: 28.02.2023 Date of first issue: 12.07.2019 | |
|---|---------------------------|------|---|---|--|
| H373 | | | exposure. | ge to organs through prolonged or repeated | |
| H400 H410 H412 H413 EUH0 | 66 | : | Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life. Repeated exposure may cause skin dryness or cracking. | | |
| Full te | ext of other abbreviat | ions | | | |
| Aquati Asp. T Eye D Flam. Repr. Skin Ir STOT GB E I | am. Sol. rit. RE | | Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Aspiration hazard Serious eye damage Flammable solids Reproductive toxicity Skin irritation Specific target organ toxicity - repeated exposure UK. EH40 WEL - Workplace Exposure Limits Long-term exposure limit (8-hour TWA reference periode) | | |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System: GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative



METALSTAR 03 0104 Black Label Silver

| Version 6.0 | Revision Date: 27.02.2023 | SDS Number: 102000031721 | Print Date: 28.02.2023 Date of first issue: 12.07.2019 |
|----------------|---|-----------------------------|---|
| | er information sification of the mix | ure: | Classification procedure: |
| Eye li | rrit. 2 | H319 | Calculation method |
| Aqua | tic Chronic 2 | H411 | Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN