

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : METALURE UV FPG 42001  
Material number : 027455N20

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Skin corrosion/irritation, Category 3, H316  
Serious eye damage/eye irritation, Category 1, H318  
Skin sensitisation, Category 1, H317

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

Long-term (chronic) aquatic hazard, Category 3, H412

**GHS-Labelling**

Symbol(s)

:



Signal word

: Danger

Hazard statements

: H316: Causes mild skin irritation.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H412: Harmful to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
P261 Avoid breathing mist or vapours.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P305 + P354 + P338 + P317 IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.  
P333 + P317 If skin irritation or rash occurs: Get medical help.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.**Hazardous components which must be listed on the label**

Identification

CAS-No.

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-  
.omega.-[(1-oxo-2-propenyl)oxy]-, ether

28961-43-5

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

with 2-ethyl-2-(hydroxymethyl)-1,3-  
propanediol (3:1)  
Glycerol, propoxylated, esters with acrylic acid 52408-84-1  
acid  
hexadecyl dihydrogen phosphate 3539-43-3

**Other hazards which do not result in classification**

Combustible Solids

**SECTION 3: Composition/information on ingredients**

Substance No. :

**Hazardous components**

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)	28961-43-5	;2A;H319 Skin Sens.;1;H317 Aquatic Chronic;3;H412	50 - 100
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	10 - 20
Glycerol, propoxylated, esters with acrylic acid	52408-84-1	;2A;H319 Skin Sens.;1;H317	1 - 10
hexadecyl dihydrogen phosphate	3539-43-3 911-302-5	;2;H315 ;1;H318	3 - 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- |                         |   |  |
|-------------------------|---|--|
| General advice          | : | Move the victim to fresh air.<br>Move out of dangerous area.<br>Consult a physician.<br>Show this safety data sheet to the doctor in attendance.<br>Do not leave the victim unattended.  |
| If inhaled              | : | Remove to fresh air.<br>If unconscious, place in recovery position and seek medical advice.<br>If symptoms persist, call a physician.  |
| In case of skin contact | : | Wash off immediately with soap and plenty of water.<br>If skin irritation persists, call a physician.<br>If on clothes, remove clothes.  |
| In case of eye contact  | : | Immediately flush eye(s) with plenty of water.<br>Small amounts splashed into eyes can cause irreversible tissue damage and blindness.<br>In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.<br>Continue rinsing eyes during transport to hospital.<br>Remove contact lenses.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist. |
| If swallowed            | : | Keep respiratory tract clear.<br>Do NOT induce vomiting.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.<br>Take victim immediately to hospital.   |

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : Water, Foam, ABC powder, Carbon dioxide (CO<sub>2</sub>)

High volume water jet

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

Remove all sources of ignition.  
Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.

**6.2 Environmental precautions**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

This information is not available.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation.

Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

This information is not available.

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

**8.2 Exposure controls****Personal protective equipment**

- Eye protection : Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
The exact break through time can be obtained from the



**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

- protective glove producer and this has to be observed.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Recommended preventive skin protection  
Skin should be washed after contact.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- : Long sleeved clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- : Use suitable breathing protection if workplace concentration requires.
- Environmental exposure controls**
- General advice : The product should not be allowed to enter drains, water courses or the soil.
- : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance : Pasty solid

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

Colour	: silver
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: 391 °C
Flash point	: No data available
Bulk density	: No data available
Flammability (solid, gas)	: Combustible Solids
Auto-flammability	: not auto-flammable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 1,107 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive Not explosive

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.  
Mixture reacts slowly with water resulting in evolution of hydrogen.  
Vapour/air-mixtures are explosive at intense warming.

No decomposition if stored and applied as directed.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow to dry.  
No data available

**10.5 Incompatible materials**

Materials to avoid : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

**10.6 Hazardous decomposition products**

Other information : No data available

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

No data available

**Skin corrosion/irritation****Product**

Extremely corrosive and destructive to tissue.

**Serious eye damage/eye irritation****Product**

May cause irreversible eye damage.

**Respiratory or skin sensitisation****Product**

Causes sensitisation.

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

No data available

---

**SECTION 12: Ecological information****12.1 Toxicity****Components:**

**Poly(oxy-1,2-ethanediyl), .alpha.-hydro.-omega.-[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) (28961-43-5) :**

**Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No data available

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

---

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**Additional ecological : No data available  
information

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

---

**SECTION 14: Transport information****14.1 UN number****ADR**

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

**14.2 Proper shipping name****ADR**

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

**14.3 Transport hazard class****ADR**

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

**14.4 Packing group****ADR**

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

**14.5 Environmental hazards****14.6 Special precautions for user**

Not classified as dangerous in the meaning of transport regulations.



**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Banned and/or restricted (Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)) (aluminium powder (stabilised)) (Glycerol, propoxylated, esters with acrylic acid)

**15.2 Chemical safety assessment**

No data available

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**METALURE UV FPG 42001**

Version 3.0

Revision Date 31.01.2024

Print Date 01.02.2024

---

**SECTION 16: Other information****Full text of H-Statements**

H228	: Flammable solid.
H315	: Causes skin irritation.
H316	: Causes mild skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H412	: Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.