according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version	Revision Date:	SDS Number:	Print Date: 02.03.2024
3.1	29.02.2024	102000030880	Date of first issue: 21.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Trade name	: ROTOVARIO 501 020 Silver IF
Product code	: 024281G60

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1 Eye irritation, Category 2 Specific target organ toxicity - single exposure, Category 3, Central nervous system H228: Flammable solid.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version 3.1	Revision Date: 29.02.2024		Number: 00030880	Print Date: 02.03.2024 Date of first issue: 21.11.2018
Haz	ard pictograms	:		
Sig	nal word	: Da	anger	•
Haz	ard statements	H	228 319 336	Flammable solid. Causes serious eye irritation. May cause drowsiness or dizziness.
	plemental Hazard tements	: El	JH066	Repeated exposure may cause skin dryness or cracking.
Pre	cautionary statements	• • •	revention: 210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
			261 280	Avoid breathing dust. Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
			esponse:	
		P	304 + P340 + P3	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
		P	370 + P378	In case of fire: Use for extinction: Special powder for metal fires.
		P	370 + P378	In case of fire: Use for extinction: Dry sand.

Hazardous components which must be listed on the label:

ethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000030880	Print Date: 02.03.2024 Date of first issue: 21.11.2018	
ethyl a	acetate	01-211952924 141-78-6 205-500-4 607-022-00-5 01-211947510	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous	>= 25 - < 50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measured	res		
General advice	: Move the victim to fresh air.		
	Move out of dangerous area. Show this safety data sheet to the doctor in attendance.		
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.		
In case of skin contact	: Wash off immediately with soap and plenty of water.		
	If on skin, rinse well with water. If on clothes, remove clothes.		
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. 		
If swallowed	 Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. 		
4.2 Most important symptoms and effects, both acute and delayed			
Risks	: Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.		

4.3 Indication of any immediate medical attention and special treatment needed This information is not available.

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version	Revision Date:	SDS Number:	Print Date: 02.03.2024
3.1	29.02.2024	102000030880	Date of first issue: 21.11.2018

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	Carbon dioxide (CO2) ABC powder Water Foam
5.2 Special hazards arising from the substance or mixture		

Specific hazards during firefighting	:	Contact with water liberates extremely flammable gas (hydrogen).
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Use personal protective equipment.
		Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective	equipment and emergency procedures
Personal precautions :	Evacuate personnel to safe areas. Use personal protective equipment. Use personal protective equipment. Avoid dust formation. Remove all sources of ignition.
6.2 Environmental precautions	
General advice :	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contain	nment and cleaning up
Mothode for cloaning up	Lise mechanical handling equipment

Methods for cleaning up	:	Use mechanical handling equipment.
		Soak up with inert absorbent material (e.g. sand, silica gel,

Version

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Revision Date:

acid binder, universal binder, sawdust). Do not flush with water. Keep in suitable, closed containers for disposal. 6.4 Reference to other sections For personal protection see section 8. SECTION 7: Handling and storage 7.1 Precautions for safe handling Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. Avoid of ormation of respirable particles. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in t application area. Provide sufficient air exchange and/or exhaust in work Dispose of rinse water in accordance with local and na regulations. Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. T measures to prevent the build up of electrostatic charge explosion-proof equipment. Avoid dust formation. Keep away from open flames, h surfaces and sources of ignition.	
6.4 Reference to other sections For personal protection see section 8. SECTION 7: Handling and storage 7.1 Precautions for safe handling Advice on safe handling Section 8. Colspan="2">Keep away from heat and sources of ignition. Avoid dust formation. Avoid dust formation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in t application area. Provide sufficient air exchange and/or exhaust in work Dispose of rinse water in accordance with local and na regulations. Advice on protection against fire and explosion Earthing of containers and apparatuses is essential. T measures to prevent the build up of electrostatic charge explosion-proof equipment.	
For personal protection see section 8. SECTION 7: Handling and storage Advice on safe handling Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in t application area. Provide sufficient air exchange and/or exhaust in work Dispose of rinse water in accordance with local and na regulations. Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. T measures to prevent the build up of electrostatic charge explosion-proof equipment. Avoid dust formation. Keep away from open flames, h	
SECTION 7: Handling and storage 7.1 Precautions for safe handling Advice on safe handling Advice on safe handling Section 2 Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in t application area. Provide sufficient air exchange and/or exhaust in work Dispose of rinse water in accordance with local and na regulations. Advice on protection against fire and explosion Earthing of containers and apparatuses is essential. T measures to prevent the build up of electrostatic charge explosion-proof equipment.	
7.1 Precautions for safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in t application area. Provide sufficient air exchange and/or exhaust in work Dispose of rinse water in accordance with local and na regulations. Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. T measures to prevent the build up of electrostatic charge explosion-proof equipment.	
 Advice on safe handling Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in t application area. Provide sufficient air exchange and/or exhaust in work Dispose of rinse water in accordance with local and na regulations. Earthing of containers and apparatuses is essential. T measures to prevent the build up of electrostatic charge explosion-proof equipment. Avoid dust formation. Keep away from open flames, h 	
 Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in t application area. Provide sufficient air exchange and/or exhaust in work Dispose of rinse water in accordance with local and na regulations. Earthing of containers and apparatuses is essential. T measures to prevent the build up of electrostatic charg explosion-proof equipment. Avoid dust formation. Keep away from open flames, h 	
Advice on protection against fire and explosion:Earthing of containers and apparatuses is essential. T measures to prevent the build up of electrostatic charge explosion-proof equipment.Avoid dust formation. Keep away from open flames, h	ne rooms.
^o	le. Use
Hygiene measures : When using do not eat or drink. When using do not sm Wash hands before breaks and at the end of workday	
7.2 Conditions for safe storage, including any incompatibilities	
Requirements for storage : Store in original container. Keep containers tightly clo cool, well-ventilated place. Keep container closed whe use. Keep away from sources of ignition - No smoking	n not in
No smoking. Keep container tightly closed in a dry and ventilated place. Electrical installations / working mate must comply with the technological safety standards.	
Further information on : Protect from humidity and water. Do not allow to dry. storage conditions	
Advice on common storage : Do not store together with oxidizing and self-igniting p Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and	

SDS Number: Print Date: 02.03.2024

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000030880	Print Date: 02.03.2024 Date of first issue: 21.11.2018
		strongly acid ma	terials in order to avoid exothermic reactions.
Further information on storage stability		: No decomposition	on if stored and applied as directed.
7.3 Specifi	ic end use(s)		

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	inhalable dust when samplin MDHS14/4 Ge respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirable material that e available for o to the fraction definitions and contain comp should be cor a figure three Further inform inhalable dust when samplin MDHS14/4 Ge respirable, the	are those fractions ig is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or great or 4 mg.m-3 8-hour be subject to COSHH dusts have been ass with the appropriate wide range of sizes. icle after entry into the it elicits, depend on two size fractions for e'., Inhalable dust appendent to size fractions for e'., Inhalable dust appendent that penetrates to the dexplanatory material onents that have the nplied with., Where re times the long-term TWA (Respirable dust) nation: For the purpor are those fractions g is undertaken in are pracic and inhalable	ses of these limits, respirable of airborne dust which will be ccordance with the methods ampling and gravimetric ana aerosols., The COSHH defir cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This l if people are exposed to du signed specific WELs and exp limits., Most industrial dusts The behaviour, deposition a ne human respiratory system the nature and size of the part r limit-setting purposes terme oproximates to the fraction of mouth during breathing and in itratory tract. Respirable dust in given in MDHS14/4., W in own assigned WEL, all the no specific short-term expose exposure limit should be use 4 mg/m3 ses of these limits, respirable ccordance with the methods anapling and gravimetric ana aerosols., The COSHH defir	e collected described in lysis or ition of a present at a TWA of a means that ast above these contain and fate of any and the body article. HSE ed 'inhalable' airborne s therefore approximates e lung. Fuller Where dusts relevant limits ure limit is listed, ad. GB EH40 e dust and e collected described in lysis or ition of a
	substance ha	zardous to health inc	ludes dust of any kind when	present at a

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000030880	Print Date: 02.03.2024 Date of first issue: 21.11.2	2018	
	inha any leve mus part part resp dist and mat ava to th defi con sho	lable dust or 4 mg.m dust will be subject to dust will be subject to st. Some dusts have t comply with the app icles of a wide range icular particle after en onse that it elicits, de inguishes two size fra 'respirable'., Inhalable erial that enters the n lable for deposition in the fraction that penetra nitions and explanato tain components that uld be complied with.	to or greater than 10 mg.m-3 8- 3 8-hour TWA of respirable dus o COSHH if people are exposed been assigned specific WELs and propriate limits., Most industrial of of sizes. The behaviour, depositive try into the human respiratory sy epend on the nature and size of ctions for limit-setting purposes a dust approximates to the fractions on the respiratory tract. Respirable ates to the gas exchange region ry material are given in MDHS14 have their own assigned WEL, a , Where no specific short-term e ong-term exposure limit should b	t. This means that to dust above these d exposure to these usts contain tion and fate of any ystem, and the body the particle. HSE termed 'inhalable' on of airborne and is therefore e dust approximates of the lung. Fuller 4/4., Where dusts all the relevant limits xposure limit is listed,	
ethyla	acetate 141	-78-6 TWA	200 ppm 734 mg/m3	GB EH40	
		STEL	400 ppm 1,468 mg/m3	GB EH40	
		STEL	400 ppm 1,468 mg/m3	2017/164/EU	
	Furt	Further information: Indicative			
		TWA	200 ppm 734 mg/m3	2017/164/EU	
	Furt	her information: Indic	ative		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Inhalation	Long-term local effects	734 mg/m3
	Workers	Inhalation	Acute systemic effects	1468 mg/m3
	Workers	Dermal	Long-term systemic effects	63 mg/kg
	Workers	Inhalation	Acute local effects	1468 mg/m3
	Consumers	Inhalation	Long-term systemic effects	367 mg/m3
	Consumers	Inhalation	Long-term local effects	367 mg/m3
	Consumers	Inhalation	Acute systemic	734 mg/m3

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Vers 3.1	sion Revision Date: 29.02.2024	SDS Numb 102000030		 ate: 02.03.2024 first issue: 21.11.2018	
				effects	
		Consumers	Inhalation	Acute local effects	734 mg/m3
		Consumers	Dermal	Long-term systemic effects	37 mg/kg
		Workers	Dermal	Long-term local effects	63 mg/kg
		Consumers	Oral	Long-term systemic effects	4.5 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
ethyl acetate	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	STP	650 mg/l
	Fresh water sediment	1.15 mg/kg
	Marine sediment	0.115 mg/kg
	Soil	0.148 mg/kg
	periodical release	1.65 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection		Wear face-shield and protective suit for abnormal processing problems.
Hand protection Material	:	Solvent-resistant gloves (butyl-rubber)
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Long sleeved clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use suitable breathing protection if workplace concentration requires.

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version	Revision Date:	SDS Number:	Print Date: 02.03.2024
3.1	29.02.2024	102000030880	Date of first issue: 21.11.2018

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	:	Pasty solid
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Freezing point	:	No data available
Boiling point/boiling range	:	77 °C
Flammability	:	The substance or mixture is a flammable solid with the category 1.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	substance/mixture is non-soluble (in water)
Viscosity, kinematic	:	No data available
Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	No data available
Relative density	:	No data available
Density	:	1.3 - 2.0 g/cm3
Relative vapour density	:	No data available
Particle characteristics Particle Size Distribution	:	No data available

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000030880	Print Date: 02.03.2024 Date of first issue: 21.11.2018	
	information osives	: Not explosive Vapours may	form explosive mixture with air.	
Self-	ignition	: not auto-flam	mable	
Misc	ibility with water	: immiscible		

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapours may form explosive mixture with air. Stable under recommended storage conditions.
10.4 Conditions to avoid Conditions to avoid	:	Do not allow to dry.
10.5 Incompatible materials Materials to avoid	:	Heat, flames and sparks. Acids Bases Oxidizing agents Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Vers 3.1	sion	Revision Date: 29.02.2024		OS Number: 2000030880	Print Date: 02.03.2024 Date of first issue: 21.11.2018	
	<u>Com</u> p	oonents:				
	alumi	inium powder (stabili	sed):			
		inhalation toxicity	:	LC50 (Rat): > 5 n Exposure time: 4 Test atmosphere:	h	
	ethyl	acetate:				
	Acute	oral toxicity	:	(Rat): 5,620 mg/	kg	
	Acute	inhalation toxicity	:	LC50 (Rat): 56 m Exposure time: 4 Test atmosphere:	h	
	Acute	dermal toxicity	:	LD50 (Rabbit): >	18,000 mg/kg	
		corrosion/irritation ated exposure may ca	use s	kin dryness or crac	king.	
	<u>Produ</u>	uct:				
	Rema		:	May cause skin ir	rritation in susceptible persons.	
		us eye damage/eye i es serious eye irritation		on		
	<u>Produ</u>	uct:				
	Rema	rks	:	Eye irritation		
	<u>Com</u> p	oonents:				
	ethyl	acetate:				
	Resul	t	:	Eye irritation		
	Respi	ratory or skin sensiti	isatio	n		
	•••••	sensitisation assified based on ava	ilable	information.		
	-	ratory sensitisation assified based on ava	ilable	information.		
		cell mutagenicity assified based on ava	ilable	information.		
	Carcinogenicity Not classified based on available information.					
	Repro	oductive toxicity				
	-	assified based on ava	ilable	information.		

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000030880	Print Date: 02.03.2024 Date of first issue: 21.11.2018			
	OT - single exposure ay cause drowsiness or diz	ziness.				
<u>Co</u>	mponents:					
	nyl acetate: sessment	: May cause dro	owsiness or dizziness.			
	OT - repeated exposure t classified based on availa	able information.				
	Aspiration toxicity Not classified based on available information.					
11.2 In	formation on other hazar	ds				
Fu	rther information					
	<u>oduct:</u> marks	tiredness, nau Concentration narcotic effect	overexposure may be headache, dizziness, sea and vomiting. s substantially above the TLV value may cause s. degrease the skin.			
SECT	ON 12: Ecological info	rmation				
12.1 To	oxicity					
<u>Co</u>	mponents:					
То	nyl acetate: xicity to daphnia and other uatic invertebrates	: (Daphnia (wa	ter flea)): 717 mg/l			
	ersistence and degradabi	lity				
	oaccumulative potential data available					
	obility in soil data available					
12.5 Re	esults of PBT and vPvB a	ssessment				
	<u>oduct:</u> sessment	to be either pe	e/mixture contains no components considered ersistent, bioaccumulative and toxic (PBT), or t and very bioaccumulative (vPvB) at levels of r.			

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Vers 3.1	ion	Revision Date: 29.02.2024		9S Number: 2000030880	Print Date: 02.03.2024 Date of first issue: 21.11.2018
		rine disrupting prope a available	rtie	S	
12.7	Other a	adverse effects			
	Produc Additio informa	nal ecological	:	No data available	
SEC	CTION	13: Disposal consid	lera	ations	
	•	an Waste Catalogue an Waste Catalogue	:		rous metal dust and particles articulates and dust (including ball-mill dust) ous substances
13.1	Waste	treatment methods			
	Produc	t	:	chemical or used Send to a licensed	te ponds, waterways or ditches with
	Contarr	ninated packaging	:		ised product.

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	:	UN 1325
IMDG	:	UN 1325
ΙΑΤΑ	:	UN 1325
14.2 UN proper shipping name		
ADR	:	FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste)
IMDG	:	FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste)
ΙΑΤΑ	:	Flammable solid, organic, n.o.s. (Aluminium pigment paste)
14.3 Transport hazard class(es)		

Subsidiary risks

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version 3.1	Revision Date: 29.02.2024		DS Number: 2000030880	Print Date: 02.03.2024 Date of first issue: 21.11.2018
		:	4.1 4.1	
IATA	-	:	4.1	
14.4 Pack	king group			
Class Haza Labe	ing group sification Code rd Identification Number	:	II F1 40 4.1 (E)	
Labe	ing group Is Code	::	ll 4.1 F-G, S-G IMDG Code segre	egation group 15 - Powdered metals
Pack aircra Pack	ing instruction (LQ) ing group	:	448 Y441 II 4.1	
Pack (pass Pack	(Passenger) ing instruction senger aircraft) ing instruction (LQ) ing group Is	:	445 Y441 II 4.1	
14.5 Envi	ronmental hazards			
IMDO	onmentally hazardous	:	no	

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version	Revision Date:	SDS Number:	Print Date: 02.03.2024
3.1	29.02.2024	102000030880	Date of first issue: 21.11.2018

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) ethyl acetate (Number on list 3) Poly(oxy-1,2-ethanediyl), alphaisotridecyl-omega-hydroxy-, phosphate (Number on list 3)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

EUH066

SECTION 16: Other information

Full text of H-Statements		
H225	:	Highly flammable liquid and vapour.
H228	:	Flammable solid.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Flam. Sol.	:	Flammable solids
STOT SE	:	Specific target organ toxicity - single exposure
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

: Repeated exposure may cause skin dryness or cracking.

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the

according to Regulation (EC) No. 1907/2006



ROTOVARIO 501 020 Silver IF

Version	Revision Date:	SDS Number:	Print Date: 02.03.2024
3.1	29.02.2024	102000030880	Date of first issue: 21.11.2018

Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Flam. Sol. 1	H228	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN