

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STANDART PCA 214 Aluminium Powder
Material number : 049146EVO

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guntersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Flammable solids, Category 1, H228
Skin corrosion/irritation, Category 3, H316

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

Information concerning particular hazards for human and environment:

Please refer to our website for further important safety instructions for handling aluminium powder:
http://www.eckart.net/fileadmin/eckart/Service/GDA_Alupulver_Safety_engl.pdf

GHS-Labeling

Symbol(s)

:



Signal word

:

Danger

Hazard statements

:

H228: Flammable solid.
 H316: Causes mild skin irritation.

Precautionary statements

:

Prevention:
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
 P332 + P317 If skin irritation occurs: Get medical help.
 P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.
 P370 + P378 In case of fire: Use for extinction: Dry sand.

Hazardous components which must be listed on the label

SECTION 3: Composition/information on ingredients

Substance No.

:

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100
3-trimethoxysilylpropyl methacrylate	2530-85-0 219-785-8	Acute Tox.;5;H303 ;2;H315 ;2A;H319 STOT SE;3;H335	1 - 10
Fatty acids, C14-18 and C16-18- unsatd.	67701-06-8 266-930-6	Acute Tox.;5;H313	1 - 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

General advice	: Move the victim to fresh air. Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : ABC powder, Carbon dioxide (CO₂), Water, Foam

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.
Evacuate personnel to safe areas.
Avoid dust formation.
Avoid breathing dust.
Remove all sources of ignition.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

This information is not available.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Do not use a vacuum cleaner.
Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid creating dust. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

Store away from heat.

Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Use explosion-proof equipment. During processing, dust may form explosive mixture in air. Take measures to prevent the build up of electrostatic charge. When transferring from one container to another apply earthing measures and use conductive hose material.

Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : Keep in a dry place. No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
------------	---------	----------------------------------	--------------------	--------	-------

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

aluminium	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	TWA (Respirable)	5 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (total dust)	15 mg/m ³	2012-07-01	
aluminium	7429-90-5	TWA (total)	10 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m ³	2012-07-01	
aluminium	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	PEL (Total dust)	10 mg/m ³	2014-11-26	
aluminium	7429-90-5	PEL (respirable dust fraction)	5 mg/m ³	2014-11-26	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m ³	2008-01-01	
aluminium	7429-90-5	TWA	5 mg/m ³	2005-09-01	
aluminium	7429-90-5	TWA (Total)	15 mg/m ³	1989-01-19	
aluminium	7429-90-5	TWA (Respirable fraction)	5 mg/m ³	1989-01-19	
aluminium	7429-90-5	TWA (total dust)	15 mg/m ³	2011-07-01	
aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m ³	2011-07-01	
aluminium	7429-90-5	TWA (Total dust)	15 mg/m ³	1989-01-19	
aluminium	7429-90-5	TWA (respirable dust fraction)	5 mg/m ³	1989-01-19	
aluminium	7429-90-5	TWA (welding fumes)	5 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (pyro powders)	5 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m ³	2013-03-01	
aluminium	7429-90-5	TWA (Fumes)	5 mg/m ³	1989-01-19	
aluminium	7429-90-5	PEL (Welding fumes)	5 mg/m ³	2017-10-02	
aluminium	7429-90-5	PEL (Pyro)	5 mg/m ³	2017-10-02	

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

		powders)			
aluminium	7429-90-5	TWA (powder)	5 mg/m3	1989-01-19	

8.2 Exposure controls
Personal protective equipment

- Eye protection : Face-shield
: Tightly fitting safety goggles
- Hand protection
Material : Leather
Glove length : Long sleeve gloves
Remarks : Leather gloves
The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Anti-static and fire resistant protective clothing. DIN EN 11612; EN 533; EN 1149-1. Anti-static safety shoes.
: Dust impervious protective suit
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
Breathing apparatus with filter.
P1 filter

Environmental exposure controls

- General advice : The product should not be allowed to enter drains, water courses or the soil.
: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: powder
Colour	: silver
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Melting point/range	: > 600 °C
Boiling point/boiling range	: No data available
Flash point	: No data available
Bulk density	: No data available
Flammability (solid, gas)	: The substance or mixture is a flammable solid with the category 1.
Smoldering temperature	: > 230 °C
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: 30 g/m ³
Vapour pressure	: No data available
Density	: 2,5 g/cm ³ (ca.)
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: 340 °C
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materialsMaterials to avoid : Acids
Bases
Oxidizing agents
Water

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

10.6 Hazardous decomposition products

Other information : No data available

SECTION 11: Toxicological information
11.1 Information on toxicological effects
Acute toxicity
Components:
3-trimethoxysilylpropyl methacrylate :

Acute oral toxicity : LD50 Rat: > 2 000 mg/kg

Acute dermal toxicity : Rat: > 2 000 mg/kg

Fatty acids, C14-18 and C16-18-unsatd. :

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg


Acute inhalation toxicity : LC50 Rat: > 46 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

Skin corrosion/irritation
Product

Page 12 / 18	102000000285	A member of 
--------------	--------------	---

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product

Product dust may be irritating to eyes, skin and respiratory system.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

Further information**Product**No data available

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : No data available

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	: Empty remaining contents. Send to a licensed waste management company. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**14.1 UN number**

ADR	: 1309
TDG	: 1309
CFR	: 1309
IMDG	: 1309
IATA	: 1309

14.2 Proper shipping name

ADR	: ALUMINIUM POWDER, COATED
TDG	: ALUMINUM POWDER, COATED
CFR	: ALUMINUM POWDER, COATED
IMDG	: ALUMINIUM POWDER, COATED
IATA	: ALUMINIUM POWDER, COATED

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

14.3 Transport hazard class

ADR	: 4.1
TDG	: 4.1
CFR	: 4.1
IMDG	: 4.1
IATA	: 4.1

14.4 Packing group**ADR**

Packaging group	: II
Classification Code	: F3
Hazard Identification Number	: 40
Labels	: 4.1
Tunnel restriction code	: (E)

TDG

Packaging group	: II
Labels	: 4.1

CFR

Packaging group	: II
Labels	: 4.1

IMDG

Packaging group	: II
Labels	: 4.1
EmS Code	: F-G, S-G

IATA

Packing instruction (cargo aircraft)	: 448
Packing instruction	: 445

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

(passenger aircraft)

Packing instruction (LQ) : Y441

Packaging group : II

Labels : 4.1

14.5 Environmental hazards

14.6 Special precautions for user

IMDG Code- segregation group:

: IMDG Code segregation group 15 - Powdered metals

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) :

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Banned and/or restricted (aluminium powder (stabilised)) (monoalkyl or monoaryl or

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART PCA 214 Aluminium Powder

Version 3.1

Revision Date 07.05.2024

Print Date 08.05.2024

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : monoalkyaryl esters of methacrylic acid)
: Listed
(aluminium powder (stabilised))

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid.
H303 : May be harmful if swallowed.
H313 : May be harmful in contact with skin.
H315 : Causes skin irritation.
H316 : Causes mild skin irritation.
H319 : Causes serious eye irritation.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.