according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version	Revision Date:	SDS Number:	Print Date: 15.04.2024
3.1	29.02.2024	102000024075	Date of first issue: 09.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

agents, pigments

1.1 Product identifier		
Trade name	:	ROTOVARIO TVO 531 073 Silver
Product code	:	022010G70

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring
Substance/Mixture		-

1.3 Details of the supplier of the safety data sheet

Company	: ECKART Suisse SA Route de la Brasserie 2 1963 Vétroz	
Telephone	: +410273454800	
Telefax	: +410273454859	
E-mail address of person responsible for the SDS	: msds.eckart@altana.cor	<u>n</u>

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1 Eye irritation, Category 2 Specific target organ toxicity - single exposure, Category 3, Central nervous system H228: Flammable solid.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version 3.1	Revision Date: 29.02.2024		DS Number: 02000024075	Print Date: 15.04.2024 Date of first issue: 09.11.2015
Hazaro	d pictograms	:		!
Signal	l word	:	Danger	•
Hazaro	d statements	:	H228 H319 H336	Flammable solid. Causes serious eye irritation. May cause drowsiness or dizziness.
Suppl Stater	emental Hazard nents	:	EUH066	Repeated exposure may cause skin dryness or cracking.
Preca	utionary statements	:	Prevention: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
			P261 P280	Avoid breathing dust. Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
			Response: P304 + P340 + P3	
			P370 + P378	In case of fire: Use for extinction: Special powder for metal fires.
			P370 + P378	In case of fire: Use for extinction: Dry sand.

Hazardous components which must be listed on the label:

ethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components			
Chemical name	CAS-No. EC-No. Index-No.	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
	Registration number		
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1	Flam. Sol. 1; H228	>= 50 - <= 100

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000024075	Print Date: 15.04.2024 Date of first issue: 09.11.20	15
ethyl a	acetate	01-21195292 141-78-6 205-500-4 607-022-00-5 01-21194751	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous	>= 25 - < 50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures					
General advice :	Move the victim to fresh air.				
	Move out of dangerous area. Show this safety data sheet to the doctor in attendance.				
If inhaled :	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.				
In case of skin contact :	Wash off immediately with soap and plenty of water.				
	If on skin, rinse well with water. If on clothes, remove clothes.				
In case of eye contact :	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing.				
If swallowed :	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.				
4.2 Most important symptoms and effects, both acute and delayed					
Risks :	Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.				

4.3 Indication of any immediate medical attention and special treatment needed This information is not available.

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

according to Regulation (EC) No. 1907/2006

ROTOVARIO TVO 531 073 Silver



Ver 3.1		Revision Date: 29.02.2024		9S Number: 2000024075	Print Date: 15.04.2024 Date of first issue: 09.11.2015	
	Suitable	extinguishing media	:	Dry sand Special powder aç	gainst metal fire	
	Unsuitable extinguishing : media		:	Carbon dioxide (CO2) ABC powder Water Foam		
5.2	Special I	hazards arising from	the	substance or mix	kture	
	Specific hazards during : firefighting		Contact with wate (hydrogen).	r liberates extremely flammable gas		
5.3	Advice f	or firefighters				
	Special protective equipment : for firefighters		:	Use personal prot	ective equipment.	
				Wear self-contain necessary.	ed breathing apparatus for firefighting if	
	Further	information	:	Use extinguishing	re for chemical fires. measures that are appropriate to local d the surrounding environment.	

SECTION 6: Accidental release measures

6.1 Personal precautions, Personal precautions	-	equipment and emergency procedures Evacuate personnel to safe areas. Use personal protective equipment. Use personal protective equipment. Avoid dust formation. Remove all sources of ignition.
6.2 Environmental precaut	tions	
General advice	:	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material	for contair	ment and cleaning up
Methods for cleaning u	ip :	Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
		Do not flush with water. Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version	Revisi
3.1	29.02.

sion Date: 2.2024 SDS Number: 102000024075 Print Date: 15.04.2024 Date of first issue: 09.11.2015

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Advice on protection against Earthing of containers and apparatuses is essential. Take : measures to prevent the build up of electrostatic charge. Use fire and explosion explosion-proof equipment. Avoid dust formation. Keep away from open flames, hot surfaces and sources of ignition. Hygiene measures When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage Store in original container. Keep containers tightly closed in a • areas and containers cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking. No smoking. Keep container tightly closed in a dry and wellventilated place. Electrical installations / working materials must comply with the technological safety standards. Further information on Protect from humidity and water. Do not allow to dry. storage conditions Do not store together with oxidizing and self-igniting products. Advice on common storage Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Further information on No decomposition if stored and applied as directed. : storage stability

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version	Revision Date:	SDS Number:
3.1	29.02.2024	102000024075

Print Date: 15.04.2024

Date of first issue: 09.11.2015

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40		
		TWA (Respirable fraction)	4 mg/m3	GB EH40		
		TWA (inhalable dust)	10 mg/m3	GB EH40		
	inhalable dust when samplin MDHS14/4 Ge respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that e available for o to the fraction definitions and contain comp should be cor a figure three	t are those fractions of is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or great tor 4 mg.m-3 8-hour be subject to COSHH dusts have been ass with the appropriate wide range of sizes. ticle after entry into the it elicits, depend on two size fractions for e'., Inhalable dust appendent that penetrates to the deposition in the response that penetrates to the decipal antory material onents that have the mplied with., Where re times the long-term TWA (Respirable dust)	ses of these limits, respirable of airborne dust which will be ccordance with the methods sampling and gravimetric ana aerosols., The COSHH defir cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du signed specific WELs and ex limits., Most industrial dusts The behaviour, deposition a he human respiratory system the nature and size of the part r limit-setting purposes termo oproximates to the fraction of mouth during breathing and diratory tract. Respirable dus he gas exchange region of the al are given in MDHS14/4., V ir own assigned WEL, all the ho specific short-term expos exposure limit should be use 4 mg/m3	e collected described in lysis or nition of a present at a TWA of s means that ust above these posure to these contain nd fate of any n, and the body article. HSE ed 'inhalable' airborne is therefore t approximates he lung. Fuller Where dusts a relevant limits ure limit is listed, ed. GB EH40		
	inhalable dust when samplin MDHS14/4 G respirable, the substance has concentration inhalable dust any dust will b levels. Some	her information: For the purposes of these limits, respirable dust and able dust are those fractions of airborne dust which will be collected a sampling is undertaken in accordance with the methods described IS14/4 General methods for sampling and gravimetric analysis or irable, thoracic and inhalable aerosols., The COSHH definition of a trance hazardous to health includes dust of any kind when present at centration in air equal to or greater than 10 mg.m-3 8-hour TWA of able dust or 4 mg.m-3 8-hour TWA of respirable dust. This means the dust will be subject to COSHH if people are exposed to dust above t s. Some dusts have been assigned specific WELs and exposure to t comply with the appropriate limits., Most industrial dusts contain				

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000024075	Print Date: 15.04.2024 Date of first issue: 09.11.2	2015			
	partia resp distin and mate avail to the defin conta shou	cular particle after ent onse that it elicits, dep nguishes two size frace respirable'., Inhalable rial that enters the no able for deposition in e fraction that penetra itions and explanator ain components that h Id be complied with.,	of sizes. The behaviour, deposit ry into the human respiratory sy bend on the nature and size of ctions for limit-setting purposes dust approximates to the fraction se and mouth during breathing the respiratory tract. Respirable tes to the gas exchange region y material are given in MDHS14 have their own assigned WEL, a Where no specific short-term en og-term exposure limit should b	ystem, and the body the particle. HSE termed 'inhalable' on of airborne and is therefore e dust approximates of the lung. Fuller k/4., Where dusts all the relevant limits xposure limit is listed, e used.			
ethyl	acetate 141-	78-6 TWA	200 ppm 734 mg/m3	GB EH40			
		STEL	400 ppm 1,468 mg/m3	GB EH40			
		STEL	400 ppm 1,468 mg/m3	2017/164/EU			
	Furth	Further information: Indicative					
		TWA	200 ppm 734 mg/m3	2017/164/EU			
	Furth	er information: Indica	ative				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Inhalation	Long-term local effects	734 mg/m3
	Workers	Inhalation	Acute systemic effects	1468 mg/m3
	Workers	Dermal	Long-term systemic effects	63 mg/kg
	Workers	Inhalation	Acute local effects	1468 mg/m3
	Consumers	Inhalation	Long-term systemic effects	367 mg/m3
	Consumers	Inhalation	Long-term local effects	367 mg/m3
	Consumers	Inhalation	Acute systemic effects	734 mg/m3
	Consumers	Inhalation	Acute local effects	734 mg/m3
	Consumers	Dermal	Long-term systemic effects	37 mg/kg
	Workers	Dermal	Long-term local	63 mg/kg

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version 3.1	Revision Date: 29.02.2024	SDS Numb 102000024		 ate: 15.04.2024 f first issue: 09.11.2015	
				effects	
		Consumers	Oral	Long-term systemic effects	4.5 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value		
aluminium powder (stabilised)	Fresh water	0.0749 mg/l	
	clarification plant	20 mg/l	
ethyl acetate	Fresh water	0.24 mg/l	
	Marine water 0.024 mg		
	STP	650 mg/l	
	Fresh water sediment 1.15 mg/		
	Marine sediment 0.115 mg		
	Soil 0.148 mg/l		
	periodical release	1.65 mg/l	

8.2 Exposure controls

Personal protective equipmentEye/face protection:Hand protection Material:	t Wear face-shield and protective suit for abnormal processing problems. Solvent-resistant gloves (butyl-rubber)
Remarks :	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection :	Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection :	Use suitable breathing protection if workplace concentration requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

	 -
Form	: Pasty solid

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version 3.1	Revision Date: 29.02.2024		S Number: 000024075	Print Date: 15.04.2024 Date of first issue: 09.11.2015
Oslava			- 11	
Colour		•	silver	
Odour		:	characteristic	
Odour	Threshold	:	No data available	9
Freezin	g point	:	No data available	9
Boiling	point/boiling range	:	77 °C	
Flamma	ability	:	The substance o category 1.	r mixture is a flammable solid with the
	explosion limit / Upper bility limit	:	No data available)
	explosion limit / Lower bility limit	:	No data available	2
Flash p	oint	:	-4 °C	
Auto-ig	nition temperature	:	No data available	2
Decom	position temperature	:	No data available)
рН		:	substance/mixtu	re is non-soluble (in water)
Viscosi	ity, kinematic	:	No data available)
	ity(ies) solubility ity in other solvents	:	insoluble No data available	9
	n coefficient: n-	:	No data available	9
octanol Vapour	pressure	:	No data available	9
	Pressure for Componer acetate	nts: :	98.4 hPa (20 °C)
Relative	e density	:	No data available	2
Density	,	:	1.3 - 2.0 g/cm3	
Relative	e vapour density	:	No data available	2
	characteristics icle Size Distribution	:	No data available	9
9.2 Other ir	nformation			

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version 3.1	Revision Date: 29.02.2024	SDS Num 102000024		Print Date: 15.04.2024 Date of first issue: 09.11.2015
Explos	ives	Vapo Not e	xplosive	m explosive mixture with air. m explosive mixture with air.
Burninç	able solids g number	: 5	uto-flammal	
Self-igi Miscibi	ility with water		uto-flammal	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapours may form explosive mixture with air. Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

Heat, flames and sparks.

10.5 Incompatible materials Materials to avoid

: Acids Bases Oxidizing agents Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version	Revision Date:	SDS Number:	Print Date: 15.04.2024
3.1	29.02.2024	102000024075	Date of first issue: 09.11.2015

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not classified based on available information.

Components:

aluminium powder (stabilis Acute inhalation toxicity	ed): :	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist			
ethyl acetate:					
Acute oral toxicity	:	(Rat): 5,620 mg/kg			
Acute inhalation toxicity	:	LC50 (Rat): 56 mg/l Exposure time: 4 h Test atmosphere: vapour			
Acute dermal toxicity	:	LD50 (Rabbit): > 18,000 mg/kg			
Skin corrosion/irritation Repeated exposure may cau	se s	kin dryness or cracking.			
Product:					
Remarks	:	May cause skin irritation in susceptible persons.			
Serious eye damage/eye irr Causes serious eye irritation.		on			
Product:					
Remarks	:	Eye irritation			
Components:					
ethyl acetate:					
Result	:	Eye irritation			
Respiratory or skin sensitisation					
Skin sensitisation					

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

ROTOVARIO TVO 531 073 Silver



Vers 3.1	sion	Revision Date: 29.02.2024	SDS Number: 102000024075	Print Date: 15.04.2024 Date of first issue: 09.11.2015				
	Germ cell mutagenicity Not classified based on available information.							
	Carcinogenicity Not classified based on available information.							
	Reproductive toxicity Not classified based on available information.							
	STOT - single exposure May cause drowsiness or dizziness.							
	<u>Comp</u>	onents:						
	ethyl a Asses	acetate: sment	: May cause drow	siness or dizziness.				
	STOT - repeated exposure Not classified based on available information.							
	Aspiration toxicity Not classified based on available information.							
11.2	2 Inforn	nation on other hazar	ds					
	Furthe	er information						
	<u>Produ</u> Remar		tiredness, nause	substantially above the TLV value may cause				
SECTION 12: Ecological information								
12.1	12.1 Toxicity							
	Components:							
	Toxicit	acetate: y to daphnia and other c invertebrates	: (Daphnia (water	flea)): 717 mg/l				

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000024075		Print Date: 15.04.2024 Date of first issue: 09.11.2015		
12.5 Resu	Ilts of PBT and vPvB a	sse	ssment			
Prod	uct:					
Asse	Assessment		This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.			
	ocrine disrupting prope ata available	ertie	S			
12.7 Othe	r adverse effects					
	uct: tional ecological mation	:	No data available			
SECTIO	N 13: Disposal consi	dera	ations			
	pean Waste Catalogue pean Waste Catalogue	:		errous metal dust and particles particulates and dust (including ball-mill dust) dous substances		
13.1 Wast	te treatment methods					
Prod	uct	:	Do not contamina chemical or used Send to a license	f waste into sewer. ate ponds, waterways or ditches with container. ed waste management company. th local and national regulations.		
Conta	aminated packaging	:		used product.		

SECTION 14: Transport information

14.1 UN number or ID number				
ADR	:	UN 1325		
IMDG	:	UN 1325		
ΙΑΤΑ	:	UN 1325		
14.2 UN proper shipping name				
ADR	:	FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste)		

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version 3.1	Revision Date: 29.02.2024		0S Number: 2000024075	Print Date: 15.04.2024 Date of first issue: 09.11.2015	
IMC	G	:	FLAMMABLE SC (Aluminium pigm	DLID, ORGANIC, N.O.S. ent paste)	
IAT	A	:	Flammable solid, organic, n.o.s. (Aluminium pigment paste)		
14.3 Tra	nsport hazard class(es)				
			Class	Subsidiary risks	
AD	R	:	4.1		
IMC	G	:	4.1		
IAT	A	:	4.1		
14.4 Pac	king group				
ADF Pac Clas Haz Lab	R king group ssification Code ard Identification Number	: : : : : : : : : : : : : : : : : : : :	II F1 40 4.1 (E)		
IMDG Packing group Labels EmS Code Remarks		:	,	egation group 15 - Powdered metals	
Pac airc Pac	A (Cargo) king instruction (cargo raft) king instruction (LQ) king group els	:	448 Y441 II 4.1		
IATA (Passenger) Packing instruction (passenger aircraft) Packing instruction (LQ) Packing group Labels		:	445 Y441 II 4.1		
14.5 Env	vironmental hazards				
IMC	ironmentally hazardous	:	no		
14.6 Spe	ecial precautions for use	r			

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version	Revision Date:	SDS Number:	Print Date: 15.04.2024
3.1	29.02.2024	102000024075	Date of first issue: 09.11.2015

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) ethyl acetate (Number on list 3)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements						
H225	:	Highly flammable liquid and vapour.				
H228	:	Flammable solid.				
H319	:	Causes serious eye irritation.				
H336	:	May cause drowsiness or dizziness.				
EUH066	:	Repeated exposure may cause skin dryness or cracking.				
Full text of other abbreviations						
Eye Irrit.	:	Eye irritation				
Flam. Liq.	:	Flammable liquids				
Flam. Sol.	:	Flammable solids				
STOT SE	:	Specific target organ toxicity - single exposure				
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a				
		fourth list of indicative occupational exposure limit values				
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits				
2017/164/EU / STEL	:	Short term exposure limit				
2017/164/EU / TWA	:	Limit Value - eight hours				
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)				
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)				

according to Regulation (EC) No. 1907/2006



ROTOVARIO TVO 531 073 Silver

Version	Revision Date:	SDS Number:	Print Date: 15.04.2024
3.1	29.02.2024	102000024075	Date of first issue: 09.11.2015

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the	e mixture:	Classification procedure:
Flam. Sol. 1	H228	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN