

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TOPSTAR UV/LED FPG 726 100 LITHO INK
Product code : 027465N20

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)
Call and response in your language is possible.
Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification


2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

| | | |
|--------------------------|---|--|
| Hazard statements | : H317 H319 | May cause an allergic skin reaction. Causes serious eye irritation. |
| Precautionary statements | : Prevention: P261 P280 Response: P333 + P313 P337 + P313 P362 + P364 Disposal: P501 | Avoid breathing mist or vapours. Wear protective gloves/ eye protection/ face protection. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse. Dispose of contents/ container to an approved waste disposal plant. |

Hazardous components which must be listed on the label:

Glycerol, propoxylated, esters with acrylic acid
Propylidynetrimethanol, ethoxylated, esters with acrylic acid
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | ClassificationREGUL ATION (EC) No 1272/2008 | Concentration (% w/w) |
|---|---|---|--------------------------|
| Glycerol, propoxylated, esters with acrylic acid | 52408-84-1 500-114-5 01-2119487948-12 | Eye Irrit. 2; H319 Skin Sens. 1; H317 | >= 25 - < 50 |
| Propylidynetrimethanol, ethoxylated, esters with acrylic acid | 28961-43-5 500-066-5 01-2119489900-30 | Eye Irrit. 2; H319 Skin Sens. 1; H317 | >= 20 - < 25 |
| aluminium powder (stabilised) | 7429-90-5 231-072-3 013-002-00-1 | Flam. Sol. 1; H228 | >= 1 - < 10 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

| | | | |
|--|--|--|--------------|
| phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide | 01-2119529243-45 162881-26-7 423-340-5 015-189-00-5 01-2119489401-38 | Skin Sens. 1; H317 Aquatic Chronic 4; H413 | >= 1 - < 2.5 |
|--|--|--|--------------|

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Dry sand
ABC powder

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 13.07.2023 |
| 3.0 | 11.07.2023 | 102000036057 | Date of first issue: 30.11.2022 |

Foam

Unsuitable extinguishing media : High volume water jet
Carbon dioxide (CO₂)

High volume water jet

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 13.07.2023 |
| 3.0 | 11.07.2023 | 102000036057 | Date of first issue: 30.11.2022 |

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.
- Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Do not store near acids.
Do not store together with oxidizing and self-igniting products.
Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Further information on storage stability : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-------------------------------|--|-------------------------------|----------------------|---------|
| aluminium powder (stabilised) | 7429-90-5 | TWA (Inhalable) | 10 mg/m ³ | GB EH40 |
| | | TWA (Respirable fraction) | 4 mg/m ³ | GB EH40 |
| | | TWA (inhalable dust) | 10 mg/m ³ | GB EH40 |
| | Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | | |
| | | TWA (Respirable dust) | 4 mg/m ³ | GB EH40 |
| | Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version
3.0

Revision Date:
11.07.2023

SDS Number:
102000036057

Print Date: 13.07.2023
Date of first issue: 30.11.2022

particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|---|-----------|-----------------|----------------------------|-------------------------|
| Glycerol, propoxylated, esters with acrylic acid | Workers | Inhalation | Long-term systemic effects | 16.22 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 1.92 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 4.87 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 1.15 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 1.39 mg/kg |
| Propylidynetrimethanol, ethoxylated, esters with acrylic acid | Workers | Inhalation | Long-term systemic effects | 16.2 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 0.8 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 4.9 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 0.48 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 1.39 mg/kg |
| aluminium powder (stabilised) | Workers | Inhalation | Long-term systemic effects | 3.72 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 3.72 mg/m ³ |
| | Consumers | Oral | Long-term systemic effects | 3.95 mg/kg |
| phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide | Workers | Inhalation | Long-term systemic effects | 7.84 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 3.0 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 1.93 mg/m ³ |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version
3.0

Revision Date:
11.07.2023

SDS Number:
102000036057

Print Date: 13.07.2023
Date of first issue: 30.11.2022

| | | | | |
|--|-----------|------------|----------------------------|-------------|
| | Consumers | Dermal | Long-term systemic effects | 1.5 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 1.5 mg/kg |
| | Workers | Inhalation | Acute systemic effects | 7.84 mg/m3 |
| | Workers | Dermal | Acute systemic effects | 3.3 mg/kg |
| | Consumers | Inhalation | Acute systemic effects | 1.93 mg/m3 |
| | Consumers | Dermal | Acute systemic effects | 1.67 mg/kg |
| | Consumers | Oral | Acute systemic effects | 0.00167 ppm |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|--|---|---------------|
| Glycerol, propoxylated, esters with acrylic acid | Fresh water | 0.0057 mg/l |
| | Marine water | 0.0005 mg/l |
| | Fresh water sediment | 0.0169 mg/kg |
| | Marine sediment | 0.0017 mg/kg |
| | STP | 10 mg/l |
| | Soil | 0.0011 mg/kg |
| | Propylidynetrimethanol, ethoxylated, esters with acrylic acid | Soil |
| Fresh water | | 0.00195 mg/l |
| Fresh water sediment | | 0.038 mg/kg |
| STP | | 10 mg/l |
| Marine water | | 0.000195 mg/l |
| Marine sediment | | 0.0038 mg/kg |
| Intermittent Release | | 0.00195 mg/l |
| aluminium powder (stabilised) | Intermittent water release | 0.0195 mg/l |
| | Fresh water | 0.0749 mg/l |
| | clarification plant | 20 mg/l |
| phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide | Fresh water | 0.8 µg/l |
| | Marine water | 0.8 µg/l |
| | STP | 1 mg/l |
| | Fresh water sediment | 0.712 mg/kg |
| | Marine sediment | 0.712 mg/kg |
| | Soil | 20 mg/kg |
| | Intermittent water release | 0.8 µg/l |

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Goggles
Tightly fitting safety goggles

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

| | |
|--------------------------|---|
| Hand protection | Wear face-shield and protective suit for abnormal processing problems. |
| Material | : Solvent-resistant gloves (butyl-rubber) |
| Remarks | : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves. |
| Skin and body protection | : Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place. |
| Respiratory protection | : Use suitable breathing protection if workplace concentration requires. |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---------------------|
| Physical state | : liquid |
| Colour | : silver |
| Odour | : No data available |
| Odour Threshold | : No data available |
| Freezing point | : No data available |
| Boiling point/boiling range | : > 100 °C |
| Flammability | : No data available |
| Upper explosion limit / Upper flammability limit | : No data available |
| Lower explosion limit / Lower flammability limit | : No data available |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

Flash point : 100 °C

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Relative density : No data available

Density : No data available

Relative vapour density : No data available

Particle Size Distribution : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

10.5 Incompatible materials

Materials to avoid : Acids

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

Bases
Oxidizing agents

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

Glycerol, propoxylated, esters with acrylic acid:

Result : Eye irritation

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Result : Irritating to eyes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version
3.0

Revision Date:
11.07.2023

SDS Number:
102000036057

Print Date: 13.07.2023
Date of first issue: 30.11.2022

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Components:

Glycerol, propoxylated, esters with acrylic acid:

Result : May cause sensitisation by skin contact.

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Result : May cause sensitisation by skin contact.

Remarks : Causes sensitisation.

May cause sensitisation of susceptible persons by skin contact.

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

SECTION 12: Ecological information

12.1 Toxicity

Components:

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Glycerol, propoxylated, esters with acrylic acid:

Partition coefficient: n-octanol/water : log Pow: 2.52 (23 °C)
Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : No data available

Components:

Glycerol, propoxylated, esters with acrylic acid:

Additional ecological information : No data available

SECTION 13: Disposal considerations

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 13.07.2023 |
| 3.0 | 11.07.2023 | 102000036057 | Date of first issue: 30.11.2022 |

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

| | | |
|--|---|---|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : | Conditions of restriction for the following entries should be considered: Number on list 3 Glycerol, propoxylated, esters with acrylic acid (Number on list 3) Propylidynetrimethanol, ethoxylated, esters with acrylic acid (Number on list 3) aluminium powder (stabilised) (Number on list 40) |
| UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation | : | Not applicable |
| The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) | : | Not applicable |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer | : | Not applicable |
| UK REACH List of substances subject to authorisation (Annex XIV) | : | Not applicable |

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

| | | |
|------|---|---|
| H228 | : | Flammable solid. |
| H317 | : | May cause an allergic skin reaction. |
| H319 | : | Causes serious eye irritation. |
| H413 | : | May cause long lasting harmful effects to aquatic life. |

Full text of other abbreviations

| | | |
|-----------------|---|--|
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard |
| Eye Irrit. | : | Eye irritation |
| Flam. Sol. | : | Flammable solids |
| Skin Sens. | : | Skin sensitisation |
| GB EH40 | : | UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 / TWA | : | Long-term exposure limit (8-hour TWA reference period) |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TOPSTAR UV/LED FPG 726 100 LITHO INK

Version 3.0 Revision Date: 11.07.2023 SDS Number: 102000036057 Print Date: 13.07.2023
Date of first issue: 30.11.2022

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Eye Irrit. 2 H319
Skin Sens. 1 H317

Classification procedure:

Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN