

	Date of impression page/of	09.04.2024/14:11:37 1/1		
	edition	09.01.2024		
STAPA IL HYDROLAN 9157 55900/G Aluminium Paste 005416HV0 Pigmentpaste of flaky aluminiumpowder produced of pure				

aluminium min. 99,5 % EN 576, with an inorganic coating Specific gravity app. 1,4 kg/l

The solvent contained is isopropanol (IL) including lubricant and additives. Pigmentcomposition: aluminium app. 53% coating app. 7%

## material specification

material denomination

material description

material-no.

specification	unit
58,0 - 62,0	%
38,0 - 42,0	%
99,9 - 100,0	%
pass	
8,0 - 12,0	μm
20,0 - 26,0	μm
35,0 - 43,0	μm
	58,0 - 62,0 38,0 - 42,0 99,9 - 100,0 pass 8,0 - 12,0 20,0 - 26,0

total shelf life in month: 24

EC-safety data sheet-no. 005416HV0

The Data on this technical information sheet correspond with the current status of our knowledge and experience.

The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.

We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

Draft	Approval	Release
Technical services	Production	Quality control
09.01.2024	09.01.2024	09.01.2024

This document has been printed automatically and will not be signed.