according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAPA NDF 150 Aluminium Paste

Product code : 052177AR0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Colouring agents, pigments

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person

responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, H412: Harmful to aquatic life with long lasting

Category 3 effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting

effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Disposal:

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

P501 Dispose of contents/ container to an

approved waste disposal plant.

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	004 070 0		
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Distillates (petroleum), hydro- treated light; Kerosine — unspecified	64742-47-8	Asp. Tox. 1; H304	>= 20 - < 25
Solvent naphtha (petroleum), light	64742-95-6	Flam. Liq. 3; H226	>= 2.5 - < 10
arom.		STOT SE 3; H336	
	918-668-5	(Central nervous	
		system)	
		STOT SE 3; H335	
		(Respiratory system)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	
1,2,4-trimethylbenzene	95-63-6	Flam. Liq. 3; H226	>= 1 - < 2.5
		Acute Tox. 4; H332	
	202-436-9	Skin Irrit. 2; H315	
	601-043-00-3	Eye Irrit. 2; H319	
		STOT SE 3; H335	
		(Respiratory system)	
		Aquatic Chronic 2;	
		H411	

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Wash off immediately with soap and plenty of water.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand

Special powder against metal fire

Unsuitable extinguishing

media

Water Foam

ABC powder

Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

102000023958 Date of first issue: 05.04.2016 5.0 04.05.2023

5.3 Advice for firefighters

for firefighters

Special protective equipment: Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas.

> Use personal protective equipment. Remove all sources of ignition. Use personal protective equipment.

Avoid dust formation.

Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Use mechanical handling equipment. Methods for cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Do not flush with water.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.

Avoid dust formation.

Ensure adequate ventilation.

Avoid formation of respirable particles.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Keep away from open flames, hot surfaces and sources of

ignition. Earthing of containers and apparatuses is essential.

Avoid dust formation. Keep away from open flames, hot

surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in

use. Keep away from sources of ignition - No smoking.

No smoking. Keep container tightly closed in a dry and wellventilated place. Observe label precautions. Electrical installations / working materials must comply with the

technological safety standards.

Further information on storage conditions

Protect from humidity and water. Do not allow to dry.

Advice on common storage :

Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on

storage stability

: No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40	
,		TWA (Respirable fraction)	4 mg/m3	GB EH40	
		TWA (inhalable dust)	10 mg/m3	GB EH40	
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.				
		TWA (Respirable dust)	4 mg/m3	GB EH40	
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain				

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle, HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. 95-63-6 2000/39/EC 1,2,4-TWA 20 ppm trimethylbenzene 100 mg/m3 Further information: Indicative TWA 25 ppm GB EH40 125 mg/m3 Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	, ,		• •	
Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection Hand protection

Safety glasses

Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Pasty solid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : 140 - 200 °C

Flammability : Combustible Solids

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : No data available

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : No data available

Relative density : No data available

Density : 1.3 - 2.0 g/cm3

Relative vapour density : No data available

Particle Size Distribution :

9.2 Other information

Explosives : Not explosive

Vapours may form explosive mixture with air.

Not explosive

Self-ignition : not auto-flammable

not auto-flammable

Miscibility with water : immiscible

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

Heat, flames and sparks.

10.5 Incompatible materials

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

Materials to avoid : Acids

Bases

Oxidizing agents

Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

1,2,4-trimethylbenzene:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

short term inhalation.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

Distillates (petroleum), hydro- treated light; Kerosine — unspecified:

Result : Mild skin irritation

1,2,4-trimethylbenzene:

Result : Skin irritation

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Product dust may be irritating to eyes, skin and respiratory

system.

Components:

Distillates (petroleum), hydro- treated light; Kerosine — unspecified:

Result : No eye irritation

1,2,4-trimethylbenzene:

Result : Mild eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.:

Germ cell mutagenicity- : Classified based on benzene content < 0.1% (Regulation (EC)

Assessment 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.:

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)

Assessment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

Components:

Solvent naphtha (petroleum), light arom.:

Assessment : May cause respiratory irritation., May cause drowsiness or

dizziness.

1,2,4-trimethylbenzene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydro- treated light; Kerosine — unspecified:

May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum), light arom.:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

Components:

Solvent naphtha (petroleum), light arom.:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1,2,4-trimethylbenzene:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust)

containing hazardous substances

13.1 Waste treatment methods

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum. In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport

regulations.

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

102000023958 Date of first issue: 05.04.2016 5.0 04.05.2023

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be

considered:

aluminium powder (stabilised)

(Number on list 40)

Distillates (petroleum), hydrotreated light; Kerosine unspecified (Number on list 3) Solvent naphtha (petroleum), light arom. (Number on list 40, 3)

1,2,4-trimethylbenzene (Number on

list 40, 3)

Not applicable

Not applicable

: Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Regulation (EC) No 1005/2009 on substances that

UK REACH List of substances subject to authorisation

deplete the ozone layer

Not applicable

(Annex XIV)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

Flammable liquid and vapour. H226

Flammable solid. H228

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

Causes serious eye irritation. H319

H332 Harmful if inhaled.

H335 May cause respiratory irritation. May cause drowsiness or dizziness. H336

H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids
Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States): UN - United Nations: vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Aquatic Chronic 3 H412 Based on product data or assessment

according to Regulation (EC) No. 1907/2006



STAPA NDF 150 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 05.05.2023

5.0 04.05.2023 102000023958 Date of first issue: 05.04.2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN