according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ROTOVARIO FPG 550 913 SILVER

Product code : 027552G60

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Colouring agents, pigments

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person

responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1 H228: Flammable solid.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single H336: May cause drowsiness or dizziness.

exposure, Category 3, Central nervous

system

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

Hazard pictograms :

Signal word : Danger

Hazard statements : H228 Flammable solid.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Supplemental Hazard

Statements

EUH066 Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection/ hearing

protection.

Response:

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel

unwell.

P370 + P378 In case of fire: Use for extinction: Special

powder for metal fires.

P370 + P378 In case of fire: Use for extinction: Dry sand.

Hazardous components which must be listed on the label:

ethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1	Flam. Sol. 1; H228	>= 25 - < 50

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

	01-2119529243-45		
ethyl acetate	141-78-6	Flam. Liq. 2; H225	>= 25 - < 50
	205-500-4	Eye Irrit. 2; H319	
	607-022-00-5	STOT SE 3; H336	
		(Central nervous	
	01-2119475103-46	system)	
		EUH066	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Remove to fresh air.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Wash off immediately with soap and plenty of water.

If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand

Special powder against metal fire

Unsuitable extinguishing

media

Carbon dioxide (CO2)

ABC powder

Water Foam

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Contact with water liberates extremely flammable gas

(hydrogen).

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Use personal protective equipment. Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Remove all sources of ignition.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.

Avoid dust formation.

Ensure adequate ventilation.

Avoid formation of respirable particles.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use

explosion-proof equipment.

Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from open flames,

hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in

use. Keep away from sources of ignition - No smoking.

No smoking. Keep container tightly closed in a dry and wellventilated place. Observe label precautions. Electrical

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

installations / working materials must comply with the

technological safety standards.

Further information on storage conditions

: Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability

No decomposition if stored and applied as directed.

Value type (Form | Control parameters

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

CAS-No.

8.1 Control parameters

Components

Occupational Exposure Limits

		of exposure)		
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	inhalable dus when samplir MDHS14/4 G respirable, the substance has concentration inhalable dus any dust will be levels. Some must comply particles of a particular par response that distinguishes and 'respirable material that available for to the fraction definitions and	t are those fractions ag is undertaken in an eneral methods for so pracic and inhalable azardous to health incomin air equal to or great or 4 mg.m-3 8-hour one subject to COSH-dusts have been asswith the appropriate wide range of sizes. It elicits, depend on two size fractions for e'., Inhalable dust appendent the respondent of the penetrates to the dexplanatory material	ses of these limits, respirable of airborne dust which will be coordance with the methods ampling and gravimetric ana aerosols., The COSHH definitudes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to dustigned specific WELs and explimits., Most industrial dusts. The behaviour, deposition and human respiratory system the nature and size of the partimit-setting purposes terms are proximates to the fraction of mouth during breathing and i iratory tract. Respirable dust he gas exchange region of the lare given in MDHS14/4., Viriown assigned WEL, all the	e collected described in lysis or aition of a present at a TWA of a means that ast above these contain and fate of any and the body article. HSE ed 'inhalable' airborne a therefore a approximates e lung. Fuller Where dusts

Basis

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

	should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m3	GB EH40
	inhalable dust when samplin MDHS14/4 Grespirable, the substance has concentration inhalable dust any dust will be levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that e available for to the fraction definitions and contain comply should be corresponded.	t are those fractions ag is undertaken in a seneral methods for so cracic and inhalable zardous to health incide in air equal to or great or 4 mg.m-3 8-hour or 5 mg.m-3 8-hour or 5 mg.m-3 8-hour or 5 mg.m-3 8-hour or 6 mg.	ses of these limits, respirable of airborne dust which will be coordance with the methods campling and gravimetric anapaerosols., The COSHH definitudes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to dustigned specific WELs and explimits., Most industrial dusts. The behaviour, deposition at the human respiratory system the nature and size of the partimit-setting purposes termes approximates to the fraction of mouth during breathing and intratory tract. Respirable dust the gas exchange region of the all are given in MDHS14/4., Wir own assigned WEL, all the no specific short-term expositions are supposure limit should be use	e collected described in lysis or ition of a present at a TWA of means that est above these contain and fate of any and the body article. HSE ed 'inhalable' airborne s therefore approximates e lung. Fuller Where dusts relevant limits ure limit is listed, d.
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m3	GB EH40
		STEL	400 ppm 1,468 mg/m3	GB EH40
		STEL	400 ppm 1,468 mg/m3	2017/164/EU
	Further inform	nation: Indicative	· · · · · · · · · · · · · · · · · · ·	•
		TWA	200 ppm 734 mg/m3	2017/164/EU
	Further information: Indicative			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Inhalation	Long-term local effects	734 mg/m3

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

Work	ers Inha	alation	Acute systemic effects	1468 mg/m3
Work	ers Der	mal	Long-term systemic effects	63 mg/kg
Work	ers Inha	alation	Acute local effects	1468 mg/m3
Cons	umers Inha	alation	Long-term systemic effects	367 mg/m3
Cons	umers Inha	alation	Long-term local effects	367 mg/m3
Cons	umers Inha	alation	Acute systemic effects	734 mg/m3
Cons	umers Inha	alation	Acute local effects	734 mg/m3
Cons	umers Der	mal	Long-term systemic effects	37 mg/kg
Work	ers Der	mal	Long-term local effects	63 mg/kg
Cons	umers Ora	I	Long-term systemic effects	4.5 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value	
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
ethyl acetate	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	STP	650 mg/l
	Fresh water sediment	1.15 mg/kg
	Marine sediment	0.115 mg/kg
	Soil	0.148 mg/kg
	periodical release	1.65 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form : Pasty solid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Melting point/range : Not applicable

Boiling point/boiling range : 77 °C (1013.0 hPa)

Flammability : The substance or mixture is a flammable solid with the

category 1.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : -4 °C

Auto-ignition temperature : 425 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : No data available

Relative density : No data available

Density : 1.3 - 2.0 g/cm3

Relative vapour density : No data available

Particle characteristics

Particle Size Distribution : No data available

9.2 Other information

Explosives : Not explosive

Vapours may form explosive mixture with air.

Self-ignition : not auto-flammable

Miscibility with water : partly miscible

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

Highly halogenated compounds

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

ethyl acetate:

Acute oral toxicity : (Rat): 5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 56 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Remarks : May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

ethyl acetate:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

ethyl acetate:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

ethyl acetate:

Toxicity to daphnia and other :

(Daphnia (water flea)): 717 mg/l

aquatic invertebrates

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust)

containing hazardous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1325 IMDG : UN 1325 IATA : UN 1325

14.2 UN proper shipping name

ADR : FLAMMABLE SOLID, ORGANIC, N.O.S.

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

(Aluminium pigment paste)

IMDG : FLAMMABLE SOLID, ORGANIC, N.O.S.

(Aluminium pigment paste)

IATA : Flammable solid, organic, n.o.s.

(Aluminium pigment paste)

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 4.1

 IMDG
 : 4.1

 IATA
 : 4.1

14.4 Packing group

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 40
Labels : 4.1
Tunnel restriction code : (E)

IMDG

Packing group : II Labels : 4.1 EmS Code : F-G, S-G

Remarks : IMDG Code segregation group 15 - Powdered metals

IATA (Cargo)

Packing instruction (cargo : 448

aircraft)

Packing instruction (LQ) : Y441
Packing group : II
Labels : 4.1

IATA (Passenger)

Packing instruction : 445

(passenger aircraft)

Packing instruction (LQ) : Y441
Packing group : II
Labels : 4.1

14.5 Environmental hazards

adr

Environmentally hazardous : no

IMDG

Marine pollutant : no

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be

considered:

aluminium powder (stabilised)

(Number on list 40)

ethyl acetate (Number on list 3)

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

Not applicable

: Not applicable

Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.

H228 : Flammable solid.

H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids

STOT SE : Specific target organ toxicity - single exposure

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2017/164/EU / STEL : Short term exposure limit 2017/164/EU / TWA : Limit Value - eight hours

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AllC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Sol. 1 H228 Based on product data or assessment

Eye Irrit. 2 H319 Calculation method STOT SE 3 H336 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

according to Regulation (EC) No. 1907/2006



ROTOVARIO FPG 550 913 SILVER

Version Revision Date: SDS Number: Print Date: 02.03.2024

1.2 29.02.2024 102000036198 Date of first issue: 27.01.2023

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN