

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : HYDROSHINE WS 3070  
Material number : 022453AN0

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Flammable liquids, Category 2, H225  
Acute toxicity, Category 5, Oral, H303  
Acute toxicity, Category 5, Dermal, H313

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

Serious eye damage/eye irritation, Category 2A, H319  
Specific target organ toxicity - single exposure, Category 3,  
Central nervous system, H336

**GHS-Labelling**

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.  
H303 + H313: May be harmful if swallowed or in contact with skin.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing mist or vapours.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
P301 + P337 + P317 IF SWALLOWED or if eye irritation persists: Get medical help.  
P303 + P361 + P353 + P317 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Get medical help.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Hazardous components which must be listed on the label**

Identification  
propan-2-ol

CAS-No.  
67-63-0

**SECTION 3: Composition/information on ingredients**

Substance No. :

**Hazardous components**

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
propan-2-ol	67-63-0 200-661-7	Flam. Liq.;2;H225 Acute Tox.;5;H303 Acute Tox.;5;H313 ;2A;H319 STOT SE;3;H336	50 - 100

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	10 - 20
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3 217-164-6	;1;H318 Skin Sens.;1B;H317 STOT SE;3;H335	0,1 - 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, ABC powder, Foam

Unsuitable extinguishing media : High volume water jet, Carbon dioxide (CO<sub>2</sub>)**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive  
concentrations. Vapours can accumulate in low areas.

**6.2 Environmental precautions**

General advice : The product should not be allowed to enter drains, water  
courses or the soil.  
Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

This information is not available.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel,  
acid binder, universal binder, sawdust).  
Contain spillage, and then collect with non-combustible  
absorbent material, (e.g. sand, earth, diatomaceous earth,  
vermiculite) and place in container for disposal according to  
local / national regulations (see section 13).  
Do not flush with water.

**6.4 Reference to other sections**

For personal protection see section 8.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use. Avoid  
contact with skin and eyes. For personal protection see  
section 8. Smoking, eating and drinking should be prohibited  
in the application area. Take precautionary measures against  
static discharges. Provide sufficient air exchange and/or  
exhaust in work rooms. Open drum carefully as content may  
be under pressure. Dispose of rinse water in accordance with

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

local and national regulations.

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.


No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage conditions : Protect from humidity and water.

- Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

- Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

Page 7 / 20	102000028187	A member of  <b>ALTANA</b>
-------------	--------------	---

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

This information is not available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
propan-2-ol	67-63-0	AGW	200 ppm 500 mg/m <sup>3</sup>	2006-01-01	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
silicon dioxide	7631-86-9	AGW (Inhalable fraction)	4 mg/m <sup>3</sup>	2013-09-19	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). Colloidal amorphous silica, including pyrogenic silica and in wet processes				



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## HYDROSHINE WS 3070

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

manufactured silica (precipitated silica, silicagel). When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child

### United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
propan-2-ol	67-63-0	TWA	200 ppm	2013-03-01	
propan-2-ol	67-63-0	STEL	400 ppm	2013-03-01	
propan-2-ol	67-63-0	TWA	400 ppm 980 mg/m <sup>3</sup>	2013-10-08	
propan-2-ol	67-63-0	ST	500 ppm 1 225 mg/m <sup>3</sup>	2013-10-08	
propan-2-ol	67-63-0	TWA	400 ppm 980 mg/m <sup>3</sup>	1997-08-04	
propan-2-ol	67-63-0	TWA	400 ppm 980 mg/m <sup>3</sup>	1989-01-19	
propan-2-ol	67-63-0	STEL	500 ppm 1 225 mg/m <sup>3</sup>	1989-01-19	
propan-2-ol	67-63-0	PEL	400 ppm 980 mg/m <sup>3</sup>	2014-11-26	
propan-2-ol	67-63-0	STEL	500 ppm 1 225 mg/m <sup>3</sup>	2014-11-26	
aluminium	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	TWA (Respirable)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2012-07-01	
aluminium	7429-90-5	TWA (total)	10 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2012-07-01	
aluminium	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	PEL (Total dust)	10 mg/m <sup>3</sup>	2014-11-26	
aluminium	7429-90-5	PEL (respirable dust fraction)	5 mg/m <sup>3</sup>	2014-11-26	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m <sup>3</sup>	2008-01-01	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## HYDROSHINE WS 3070

Version 3.0


Revision Date 16.01.2024

Print Date 18.01.2024

aluminium	7429-90-5	TWA	5 mg/m <sup>3</sup>	2005-09-01	
aluminium	7429-90-5	TWA (Total)	15 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (Respirable fraction)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2011-07-01	
aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2011-07-01	
aluminium	7429-90-5	TWA (Total dust)	15 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (welding fumes)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (pyro powders)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m <sup>3</sup>	2013-03-01	
aluminium	7429-90-5	TWA (Fumes)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	PEL (Welding fumes)	5 mg/m <sup>3</sup>	2017-10-02	
aluminium	7429-90-5	PEL (Pyro powders)	5 mg/m <sup>3</sup>	2017-10-02	
aluminium	7429-90-5	TWA (powder)	5 mg/m <sup>3</sup>	1989-01-19	
silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot	2012-07-01	
silicon dioxide	7631-86-9	TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub>	2012-07-01	
silicon dioxide	7631-86-9	TWA	6 mg/m <sup>3</sup>	2013-10-08	
silicon dioxide	7631-86-9	PEL	6 mg/m <sup>3</sup>	2014-11-26	

### 8.2 Exposure controls

#### Personal protective equipment

Page 10 / 20	102000028187	A member of  ALTANA
--------------	--------------	--

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

- Eye protection : Goggles  
: Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
The exact break through time can be obtained from the protective glove producer and this has to be observed.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
Recommended preventive skin protection  
Skin should be washed after contact.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- : In the case of vapour formation use a respirator with an approved filter.

**Environmental exposure controls**

- General advice : The product should not be allowed to enter drains, water courses or the soil.  
: Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

respective authorities.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: silver
Odour	: characteristic
pH	: 6 - 8, 100 %
Melting point/range	: Not applicable
Boiling point/boiling range	: 82 °C
Flash point	: 12 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 0,9 - 1,1 g/cm3
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: partly miscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**Conditions to avoid : Do not allow evaporation to dryness.  
Heat, flames and sparks.**10.5 Incompatible materials**Materials to avoid : Acids  
Bases  
Oxidizing agents**10.6 Hazardous decomposition products**

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

Other information : No data available

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****propan-2-ol :**

Acute oral toxicity : LD50 Rat: > 2 000 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

**Skin corrosion/irritation****Product**

May cause skin irritation in susceptible persons.

**Serious eye damage/eye irritation****Product**

Eye irritation

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,  
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may  
degrease the skin.

---

**SECTION 12: Ecological information****12.1 Toxicity**

No data available

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**Additional ecological : No data available  
information

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.



**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

**SECTION 14: Transport information****14.1 UN number**

ADR : 1263  
TDG : 1263  
CFR : 1263  
IMDG : 1263  
IATA : 1263

**14.2 Proper shipping name**

ADR : PAINT  
TDG : PAINT  
CFR : PAINT  
IMDG : PAINT Classified according to 2.3.2.2 IMDG-Code  
IATA : PAINT classified according to 3.3.3.1 IATA-DGR

**14.3 Transport hazard class**

ADR : 3  
TDG : 3  
CFR : 3  
IMDG : 3  
IATA : 3

**14.4 Packing group**

ADR  
Packaging group : III  
Classification Code : F1

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

Hazard Identification Number : 30

Labels : 3

Tunnel restriction code : (E)

**TDG**

Packaging group : III

Labels : 3

**CFR**

Packaging group : III

Labels : 3

**IMDG**

Packaging group : III

Labels : 3

EmS Code : F-E, S-E**IATA**Packing instruction (cargo  
aircraft) : 366Packing instruction  
(passenger aircraft) : 355

Packing instruction (LQ) : Y344

Packaging group : III

Labels : 3

**14.5 Environmental hazards****14.6 Special precautions for user****14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

No data available

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Banned and/or restricted (propan-2-ol) (aluminium powder (stabilised)) (N-(3-(trimethoxysilyl)propyl)ethylenediamine)

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H228	: Flammable solid.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**HYDROSHINE WS 3070**

Version 3.0

Revision Date 16.01.2024

Print Date 18.01.2024

H303	: May be harmful if swallowed.
H303 + H313	: May be harmful if swallowed or in contact with skin.
H313	: May be harmful in contact with skin.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.