

# METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
9.0	30.04.2024	102000027897	Date of first issue: 27.06.2017

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	:	METALSTAR PANTONE 874 Supergloss 07 4874
Product code	:	070352RN0
<b>1.2 Relevant identified uses of t</b> Use of the Substance/Mixture	he s :	substance or mixture and uses advised against Colorant; Printing ink related material; Printing ink, Colouring agents, dyes
1.3 Details of the supplier of the	e saf	ety data sheet
Company	:	ECKART GmbH

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person	: msds.eckart@altana.com

#### 1.4 Emergency telephone number

responsible for the SDS

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Short-term (acute) aquatic hazard,	H400: Very toxic to aquatic life.
Category 1	
Long-term (chronic) aquatic hazard,	H410: Very toxic to aquatic life with long lasting
Category 1	effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
9.0	30.04.2024	102000027897	Date of first issue: 27.06.2017

#### 2.2 Label elements

<b>Labelling (REGULATION (I</b> Hazard pictograms	EC) N :	No 1272/2008)	¥2
Signal word	:	Warning	•
Hazard statements	:	H302 H319 H410	Harmful if swallowed. Causes serious eye irritation. Very toxic to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b> P264 P273 P280 <b>Response:</b> P337 + P313	Wash skin thoroughly after handling. Avoid release to the environment. Wear eye protection/ face protection. If eye irritation persists: Get medical advice/ attention.
		P391 Disposal: P501	Collect spillage. Dispose of contents/ container to an approved waste disposal plant.

#### Hazardous components which must be listed on the label:

Copper

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components			
Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
Copper	7440-50-8	Acute Tox. 4; H302	>= 25 - < 50
	231-159-6	Eye Irrit. 2; H319	
		Aquatic Acute 1;	
	01-2119480154-42	H400	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

rsion )			nt Date: 03.05.2024 e of first issue: 27.06.2017	7
			Aquatic Chronic 1; H410	
			M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	
	ates (petroleum), solvent- d middle; Gasoil — cified	64741-91-9 919-029-3	Asp. Tox. 1; H304	>= 10 - < 2
zinc p (stabil	owder — zinc dust lised)	7440-66-6 231-175-3 030-001-01-9 01-2119467174-37	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2.5 - <
			M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
Petrol	eum resins	64742-16-1 265-116-8	Aquatic Chronic 4; H413	>= 2.5 - <
	propyl-2,2- hyltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47	Repr. 2; H361d Aquatic Chronic 3; H412	>= 1 - < 2
octad	ecylamine	124-30-1 204-695-3 612-282-00-8 01-2119473804-32	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373 (Liver, Gastrointestinal tract, Immune system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.25 - <
			M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	
amine	s, hydrogenated tallow alkyl	61788-45-2(90640- 32-7)	Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 0.0025 0.025

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024	
9.0	30.04.2024	102000027897	Date of first issue: 27.06.2017	
		262-976-6 612-284-00-9	STOT RE 2; H373 (Liver, Gastrointestinal tract, Immune system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Move the victim to fresh air.
Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
Wash off immediately with soap and plenty of water.
Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

Risks	: Harmful if swallowed.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
9.0	30.04.2024	102000027897	Date of first issue: 27.06.2017

Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

#### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media Suitable extinguishing media Special powder against metal fire Dry sand ABC powder Unsuitable extinguishing media Water High volume water jet Carbon dioxide (CO2)

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during	:	Do not allow run-off from fire fighting to enter drains or water
firefighting		COURSES.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Standard procedure for chemical fires.
		Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protecti	ve equipment and emergency procedures
Personal precautions	<ul> <li>Evacuate personnel to safe areas.</li> <li>Ensure adequate ventilation.</li> <li>Use personal protective equipment.</li> </ul>
6.2 Environmental precautions	
General advice	The product should not be allowed to enter drains, water courses or the soil.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Version 9.0	Revision Date: 30.04.2024	SDS Number: 102000027897	Print Date: 03.05.2024 Date of first issue: 27.06.2017			
		Prevent further le	from entering drains. eakage or spillage if safe to do so. ntaminates rivers and lakes or drains inform rities.			
6.3 Method	Is and material for co	ntainment and cleani	ing up			
Metho	ds for cleaning up	: Use mechanical	Use mechanical handling equipment.			
inclucio for oldarnig ap		Do not flush with Contain spillage, absorbent materi vermiculite) and local / national re Soak up with iner acid binder, unive	sfer to properly labelled containers. water. and then collect with non-combustible ial, (e.g. sand, earth, diatomaceous earth, place in container for disposal according to egulations (see section 13). rt absorbent material (e.g. sand, silica gel, ersal binder, sawdust). closed containers for disposal.			

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

7.1 Precautions for safe handling				
Advice on safe handling :	Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.			
Advice on protection against : fire and explosion	Keep away from heat and sources of ignition. No smoking.			
	Normal measures for preventive fire protection.			
Hygiene measures :	General industrial hygiene practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.			
7.2 Conditions for safe storage, including any incompatibilities				
Requirements for storage : areas and containers	Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.			

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Versio 9.0	on	Revision Date: 30.04.2024		DS Number: 2000027897	Print Date: 03.05.2024 Date of first issue: 27.06.2017
				place. Containers resealed and kep precautions. Elec	ghtly closed in a dry and well-ventilated which are opened must be carefully t upright to prevent leakage. Observe label trical installations / working materials must echnological safety standards.
-		information on e conditions	:	Protect from hum	idity and water.
Þ	Advice	on common storage	:	strongly acid mat	oxidizing agents, strongly alkaline and erials in order to avoid exothermic reactions. ther with oxidizing and self-igniting products.
C	Dampr	ness	:	Keep in a dry, co	ol and well-ventilated place.
		r information on e stability	:	No decompositio	n if stored and applied as directed.
7.3 Sp	pecific	c end use(s)			

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Copper	7440-50-8	TWA (Fumes)	0.2 mg/m3 (Copper)	GB EH40
		TWA (Dusts and mists)	1 mg/m3 (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m3 (Copper)	GB EH40
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Copper	Workers	Dermal	Long-term systemic effects	137 mg/kg
	Workers	Dermal	Acute systemic effects	273 mg/kg
	Workers	Inhalation	Long-term systemic effects	20 mg/m3
	Consumers	Inhalation	Long-term local	1 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

rsion	Revision Date: 30.04.2024	SDS Nu 1020000		Print Date: 03.05.2024 Date of first issue: 27.06.2017	
1		I	1	effects	1
		Consumers	Inhalation	Acute local effects	1 mg/m3
		Consumers	Dermal	Long-term systemic effects	137 mg/kg
		Consumers	Dermal	Acute systemic effects	273 mg/kg
		Consumers	Oral	Long-term systemic effects	0.041 mg/l
	owder — zinc stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m3
		Workers	Dermal	Long-term systemic effects	83 mg/kg
		Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
		Consumers	Dermal	Long-term systemic effects	83 mg/kg
		Consumers	Oral	Long-term systemic effects	0.83 mg/kg
dimet	propyl-2,2- hyltrimethylene putyrate	Workers	Dermal	Long-term systemic effects	5.00 mg/kg
		Workers	Inhalation	Long-term systemic effects	17.62 mg/ı
		Consumers	Oral	Long-term systemic effects	5.00 mg/kg
		Consumers	Dermal	Long-term systemic effects	5.00 mg/kg
		Consumers	Inhalation	Long-term systemic effects	4.35 mg/m
amine tallow	es, hydrogenated v alkyl	Workers	Inhalation	Long-term systemic effects	0.38 mg/m
		Workers	Inhalation	Long-term local effects	1 mg/m3
		Workers	Inhalation	Acute local effects	1 mg/m3
		Consumers	Inhalation	Long-term systemic effects	0.035 mg/i
		Consumers	Oral	Long-term systemic effects	0.04 mg/k

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value	
Copper	Fresh water	0.0078 mg/l
	Marine water	0.0052 mg/l
	STP	0.230 mg/l
	Fresh water sediment	87 mg/kg
	Marine sediment	676 mg/kg
	Soil	65 mg/kg
zinc powder — zinc dust Fresh water 0.0206		0.0206 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

ersion 0	Revision Date: 30.04.2024	SDS Number: 102000027897	Print Date: 03.05.2024 Date of first issue: 27.06.2017	
-				
(stabi	ilised)		Í	
		Marine water	0.0061 mg/l	
		STP	0.100 mg/l	
		Fresh water s		
		Marine sedim	ient 121 mg/kg	
		Soil	35.6 mg/kg	
dimet	oropyl-2,2- hyltrimethylene outyrate	Fresh water	0.014 mg/l	
	•	Marine water	0.0014 mg/l	
		Fresh water s	sediment 5.29 mg/kg	
		Soil	1.05 mg/kg	
		STP	3 mg/l	
		Marine sedim	ent 0.529 mg/kg	
		oral (seconda	ary poisoning) 83.3 mg/kg	
amine alkyl	es, hydrogenated tallov	v Fresh water	0.00026 mg/	I
		Marine water	0.000026 mg	j/l
		Sewage treat		
		Fresh water s	sediment 3.76 mg/kg	
		Marine sedim	ent 376 mg/kg	
		Soil	10 mg/kg	
		Intermittent R	elease 0.0016 mg/l	

#### 8.2 Exposure controls

<b>Personal protective equipment</b> Eye/face protection :	Safety glasses Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing
Hand protection Material :	problems. Solvent-resistant gloves (butyl-rubber)
Remarks :	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.



# METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
9.0	30.04.2024	102000027897	Date of first issue: 27.06.2017
	and body protection	concentration of Use suitable breat requires.	ing otection according to the amount and the dangerous substance at the work place. athing protection if workplace concentration d conform to EN 14387

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Form	:	liquid
Colour	:	gold
Odour	:	characteristic
Odour Threshold	:	No data available
Freezing point	:	No data available
Boiling point/boiling range	:	> 100 °C
Flammability	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 100 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	substance/mixture is non-soluble (in water)
Viscosity Viscosity, kinematic	:	> 21 mm2/s (40 °C)
Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
Partition coefficient: n- octanol/water	:	No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Versior 9.0	Revision Date: 30.04.2024	SDS Numb 102000027		Print Date: 03.05.2024 Date of first issue: 27.06.2017
Vapour pressure		: No dat	ta available	
Va	Vapor Pressure for Compone			
	Distillates (petroleum), hydrotreated middle; Gasoil — unspecified		(40 °C)	
	1-isopropyl-2,2- dimethyltrimethylene diisobutyrate		a (25 °C)	
	amines, hydrogenated tallow alkyl		Pa (20 °C)	
	Relative density		ta available	
De	ensity	: 1.4 g/c	cm3	
Re	Relative vapour density		ta available	9
Pa	Particle characteristics Particle Size Distribution		ta available	9
	er information			

No data available

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
		No decomposition if stored and applied as directed.
10.4 Conditions to avoid		
Conditions to avoid	:	Do not allow evaporation to dryness.
		No data available
10.5 Incompatible materials		

#### 10.6 Hazardous decomposition products

Thermal decomposition	:	Carbon monoxide, carbon dioxide and unburned
		hydrocarbons (smoke).

Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
9.0	30.04.2024	102000027897	Date of first issue: 27.06.2017

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed.		
Product:		
Acute oral toxicity	:	Acute toxicity estimate: 1,528 mg/kg Method: Calculation method
Components:		
Copper:		
Acute oral toxicity	:	Assessment: The component/mixture is moderately toxic after single ingestion.
Distillates (petroleum), so	lvent-	refined middle; Gasoil — unspecified:
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg
zinc powder — zinc dust (	stabil	ised):
Acute oral toxicity	:	(Rat): > 2,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 5.41 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist
1-isopropyl-2,2-dimethyltri	methy	ylene diisobutyrate:
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2,000 mg/kg
		Method: OECD Test Guideline 402
amines, hydrogenated tall	ow al	kyl:
Acute oral toxicity		LD50 (Rat): > 2,000 - 5,000 mg/kg
		Method: OECD Test Guideline 401
Skin corrosion/irritation		
Not classified based on avail	ilable	information.
Product:		
Remarks	:	May cause skin irritation in susceptible persons.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

	Revision Date: 30.04.2024	SDS Number: 102000027897	Print Date: 03.05.2024 Date of first issue: 27.06.2017
<u>Com</u> r	oonents:		
Сорр	er:		
Rema		: May cause	skin irritation in susceptible persons.
1-isop	propyl-2,2-dimethylt	rimethylene diiso	butyrate:
Speci	es	: Rabbit	
	sure time	: 4 h	
Metho			t Guideline 404
Resul	t	: No skin irrit	ation
octad	ecylamine:		
Asses	ssment	: Irritating to	skin.
amine	es, hydrogenated ta	llow alkyl:	
Resul		: Skin irritatio	วท
Rema	rks	: May cause	skin irritation in susceptible persons.
		on.	irreversible eye damage.
_			
Comr	oonents:		
-	oonents: er:		
Comp Copp Resul	er:	: Eye irritatio	n
<b>Copp</b> Resul	<b>er:</b> t	,	
Copp Result	er: t propyl-2,2-dimethylt	,	
Copp Result 1-isop Speci	er: t propyl-2,2-dimethylt	rimethylene diiso	
Copp Result 1-isop Speci	<b>er:</b> t propyl-2,2-dimethylt es sure time	r <b>imethylene diiso</b> : Rabbit : 72 h	
Copp Result 1-isop Speci Expos	er: t propyl-2,2-dimethylt es sure time od	r <b>imethylene diiso</b> : Rabbit : 72 h	<b>butyrate:</b> t Guideline 405
Copp Result 1-isop Speci Expos Metho Result	er: t propyl-2,2-dimethylt es sure time od	r <b>imethylene diiso</b> : Rabbit : 72 h : OECD Test	<b>butyrate:</b> t Guideline 405
Copp Result 1-isop Speci Expos Metho Result octad	<b>er:</b> t <b>propyl-2,2-dimethylt</b> es sure time od t	r <b>imethylene diiso</b> : Rabbit : 72 h : OECD Test	<b>butyrate:</b> t Guideline 405
Copp Result 1-isop Speci Expos Metho Result octad Asses	er: t propyl-2,2-dimethylt es sure time od t t	rimethylene diiso : Rabbit : 72 h : OECD Tes : No eye irrit : Corrosive	<b>butyrate:</b> t Guideline 405
Copp Result 1-isop Speci Expos Metho Result octad Asses	er: t propyl-2,2-dimethyltr es sure time od t f ecylamine: ssment es, hydrogenated ta	rimethylene diiso : Rabbit : 72 h : OECD Tesi : No eye irrit : Corrosive	<b>butyrate:</b> t Guideline 405



### METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
9.0	30.04.2024	102000027897	Date of first issue: 27.06.2017

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### **Components:**

#### Distillates (petroleum), solvent-refined middle; Gasoil - unspecified:

Carcinogenicity -	:	Classified based on the conditions cited in Nota N (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note N)

#### **Reproductive toxicity**

Not classified based on available information.

#### Components:

#### 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Reproductive toxicity -:Some evidence of adverse effects on development, based on<br/>animal experiments.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Components:

#### octadecylamine:

Exposure routes	:	Ingestion
Target Organs	:	Liver, digestive system, Immune system
Assessment	:	May cause damage to organs through prolonged or repeated
		exposure.

#### amines, hydrogenated tallow alkyl:

Target Organs	:	Liver, Gastrointestinal tract, Immune system
Assessment	:	The substance or mixture is classified as specific target organ
		toxicant, repeated exposure, category 2.



### METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
9.0	30.04.2024	102000027897	Date of first issue: 27.06.2017

#### Aspiration toxicity

Not classified based on available information.

#### Components:

#### Distillates (petroleum), solvent-refined middle; Gasoil - unspecified:

May be fatal if swallowed and enters airways.

#### octadecylamine:

May be fatal if swallowed and enters airways.

#### amines, hydrogenated tallow alkyl:

May be fatal if swallowed and enters airways.

#### 11.2 Information on other hazards

#### **Further information**

#### Product:

Remarks	:	No data available

#### Components:

# Copper:

Remarks : No data available

#### zinc powder — zinc dust (stabilised):

Remarks : No data available

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

<b>Copper:</b> M-Factor (Short-term (acute)	:	10
aquatic hazard) M-Factor (Long-term		10
(chronic) aquatic hazard) Ecotoxicology Assessment		
Acute aquatic toxicity	:	Very toxic to aquatic life.
Chronic aquatic toxicity	:	Very toxic to aquatic life with long lasting effects.



# METALSTAR PANTONE 874 Supergloss 07 4874

Vers 9.0	sion	Revision Date: 30.04.2024	-	9S Number: 2000027897	Print Date: 03.05.2024 Date of first issue: 27.06.2017
	zinc po	owder — zinc dust (sta	abil	ised):	
	M-Fact	or (Short-term (acute)		•	
	M-Fact	: hazard) or (Long-term c) aquatic hazard)	:	1	
	Ecotox	cicology Assessment			
	Acute a	aquatic toxicity	:	Very toxic to aqua	tic life.
	Chronic	c aquatic toxicity	:	Very toxic to aqua	tic life with long lasting effects.
	Petrole	eum resins:			
		cicology Assessment			
	Chronic	c aquatic toxicity	:	May cause long la	sting harmful effects to aquatic life.
	1-isopr	ropyl-2,2-dimethyltrim	eth	vlene diisobutvra	te:
	Toxicity	y to daphnia and other invertebrates		•	
	Ecotox	cicology Assessment			
	Chronic	c aquatic toxicity	:	Harmful to aquation	c life with long lasting effects.
	octado	cylamine:			
	M-Fact	or (Short-term (acute) hazard)	:	10	
	M-Fact	or (Long-term c) aquatic hazard)	:	10	
	Ecotox	cicology Assessment			
	Acute a	aquatic toxicity	:	Very toxic to aqua	tic life.
	Chronic	c aquatic toxicity	:	Very toxic to aqua	tic life with long lasting effects.
	amines	s, hydrogenated tallov	v al	kyl:	
		or (Short-term (acute)	:	10	
		: hazard) or (Long-term	:	10	
		c) aquatic hazard)	-	-	
		cicology Assessment			
	Acute a	aquatic toxicity	:	Very toxic to aqua	tic life.
	Chronic	c aquatic toxicity	:	Very toxic to aqua	tic life with long lasting effects.

Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Version 9.0	Revision Date: 30.04.2024	SDS Number: 102000027897	Print Date: 03.05.2024 Date of first issue: 27.06.2017	

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

#### Product:

Additional ecological	:	An environmental hazard cannot be excluded in the event of
information		unprofessional handling or disposal.
		Very toxic to aquatic life with long lasting effects.

#### Components:

Copper:

Additional ecological	:	An environmental hazard cannot be excluded in the event of
information		unprofessional handling or disposal.
		Very toxic to aquatic life with long lasting effects.

#### zinc powder — zinc dust (stabilised):

Additional ecological	:	An environmental hazard cannot be excluded in the event of
information		unprofessional handling or disposal.
		Very toxic to aquatic life with long lasting effects.

#### amines, hydrogenated tallow alkyl:

Additional ecological	:	An environmental hazard cannot be excluded in the event of
information		unprofessional handling or disposal.
		Very toxic to aquatic life with long lasting effects.

#### **SECTION 13: Disposal considerations**



# METALSTAR PANTONE 874 Supergloss 07 4874

Version 9.0	Revision Date: 30.04.2024	SDS Number: 102000027897	Print Date: 03.05.2024 Date of first issue: 27.06.2017
Europ	ean Waste Catalogue	: 08 03 12* - wa	ste ink containing dangerous substances
13.1 Waste	e treatment methods		
Product		courses or the Do not contam chemical or us	inate ponds, waterways or ditches with
Contaminated packaging		•	ng contents. unused product. empty containers.

### **SECTION 14: Transport information**

14.1 UN number or ID number		
ADR	:	UN 3082
IMDG	:	UN 3082
ΙΑΤΑ	:	UN 3082
14.2 UN proper shipping name		
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Copper metal powder)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Copper metal powder)
ΙΑΤΑ	:	Environmentally hazardous substance, liquid, n.o.s. (Copper metal powder)
14.3 Transport hazard class(es)		
		Class Subsidiary risks
ADR	:	9
IMDG	:	9
ΙΑΤΑ	:	9
14.4 Packing group		
ADR		
Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Versio 9.0	on	Revision Date: 30.04.2024		DS Number: 2000027897	Print Date: 03.05.2024 Date of first issue: 27.06.2017
т	Funnel	restriction code	:	(-)	
P	<b>MDG</b> Packing Labels EmS C	g group ode	:	III 9 F-A, S-F	
P a P P	aircraft) Packing	g instruction (cargo	:	964 Y964 III 9	
P (f P P	Packing passer Packing	Passenger) g instruction nger aircraft) g instruction (LQ) g group	: : : :	964 Y964 III 9	
14.5 Environmental hazards					
E	MDG	mentally hazardous pollutant	:	yes yes	
14.6 \$	Specia	I precautions for use	er	-	
R	Remark	S	:	packagings conta	gings <=5L / 5 kg, or combination aining inner packagings <= 5L / 5 kg net per SV375 ADR, 2.10.2.7 IMDG-Code, A197 be applied.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on	:	Conditions of restriction for the
the market and use of certain dangerous substances,		following entries should be

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Version 9.0	Revision Date: 30.04.2024	SDS Number: 102000027897		ate: 03.05.2024 f first issue: 27.06.2017
mixtures and articles (Annex XVII)			considered: Number on list 3 Distillates (petroleum), hydrotreated middle; Gasoil — unspecified (Number on list 3) 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (Number on list 3)	
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation			h :	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)			ned :	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer			:	Not applicable
UK	REACH List of substance nex XIV)	es subject to authorisati	on :	Not applicable

#### 15.2 Chemical safety assessment

No data available

#### **SECTION 16: Other information**

#### Full text of H-Statements

H302 H304 H315 H318 H319 H361d	:	Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. Causes serious eye irritation. Suspected of damaging the unborn child.	
H373	:	May cause damage to organs through prolonged or repeated	
H400 H410 H412 H413		exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.	
Full text of other abbreviations			
Acute Tox. Aquatic Acute Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Repr. Skin Irrit. STOT RE GB EH40	:	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Aspiration hazard Serious eye damage Eye irritation Reproductive toxicity Skin irritation Specific target organ toxicity - repeated exposure UK. EH40 WEL - Workplace Exposure Limits	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date: 30.04.2024	SDS Number:	Print Date: 03.05.2024	
9.0		102000027897	Date of first issue: 27.06.2017	
			sure limit (8-hour TWA reference period) sure limit (15-minute reference period)	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

Classification of th	ne mixture:	Classification procedure:
Acute Tox. 4	H302	Calculation method
Eye Irrit. 2	H319	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is



## METALSTAR PANTONE 874 Supergloss 07 4874

Version	Revision Date:	SDS Number:	Print Date: 03.05.2024
9.0	30.04.2024	102000027897	Date of first issue: 27.06.2017

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN