

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Agent Zincflake G 500 200 kgs
Product code : 088132VA0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guntersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)
Call and response in your language is possible.
Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006




Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapours.
P273 Avoid release to the environment.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Hazardous components which must be listed on the label:

Solvent naphtha (petroleum), light arom.
xylene
acetone
naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha

Additional Labelling

EUH208 Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3 030-001-01-9 01-2119467174-37	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 10 - < 20
Solvent naphtha (petroleum), light arom.	64742-95-6 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 10 - < 20
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Central nervous system) Asp. Tox. 1; H304	>= 10 - < 20
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version
7.1

Revision Date:
03.04.2024

SDS Number:
102000005103

Print Date: 16.04.2024
Date of first issue: 07.11.2014

		EUH066	
naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha	64742-82-1 265-185-4 649-330-00-2 01-2119458049-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	$\geq 2.5 - < 10$
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	$\geq 1 - < 10$
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	$\geq 0.25 - < 1$
zinc 5-nitroisophthalate	60580-61-2 262-309-9	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	$\geq 0.25 - < 1$
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3 217-164-6 01-2119970215-39	Eye Dam. 1; H318 Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	$\geq 0.1 - < 1$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Remove to fresh air.
Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

- advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If skin irritation persists, call a physician.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Dry sand
ABC powder
Foam
- Unsuitable extinguishing media : High volume water jet
Carbon dioxide (CO₂)

High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
7.1	03.04.2024	102000005103	Date of first issue: 07.11.2014

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Do not store near acids.
Do not store together with oxidizing and self-igniting products.
Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Further information on : No decomposition if stored and applied as directed.
-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

storage stability

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Limestone	1317-65-3	TWA (inhalable dust)	10 mg/m ³	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m ³	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
 Date of first issue: 07.11.2014

		response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 220 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
acetone	67-64-1	TWA	500 ppm 1,210 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	500 ppm 1,210 mg/m3	GB EH40
		STEL	1,500 ppm 3,620 mg/m3	GB EH40
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

	substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (Respirable dust)	4 mg/m ³	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version
7.1

Revision Date:
03.04.2024

SDS Number:
102000005103

Print Date: 16.04.2024
Date of first issue: 07.11.2014

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value	
zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m ³	
	Workers	Dermal	Long-term systemic effects	83 mg/kg	
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m ³	
	Consumers	Dermal	Long-term systemic effects	83 mg/kg	
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg	
	Solvent naphtha (petroleum), light arom.	Workers	Inhalation	Long-term systemic effects	151 mg/m ³
Workers		Inhalation	Acute systemic effects	1286.4 mg/m ³	
Workers		Inhalation	Long-term local effects	837.5 mg/m ³	
Workers		Inhalation	Acute local effects	1066.67 mg/m ³	
Workers		Dermal	Long-term systemic effects	12.5 mg/kg	
Consumers		Inhalation	Long-term systemic effects	32 mg/m ³	
Consumers		Inhalation	Acute systemic effects	1152 mg/m ³	
Consumers		Inhalation	Long-term local effects	178.57 mg/m ³	
Consumers		Inhalation	Acute local effects	640 mg/m ³	
Consumers		Dermal	Long-term systemic effects	7.5 mg/kg	
Consumers		Oral	Long-term systemic effects	7.5 mg/kg	
xylene		Workers	Inhalation	Long-term systemic effects	77 mg/m ³
		Workers	Inhalation	Acute systemic effects	289 mg/m ³
		Workers	Inhalation	Acute local effects	442 mg/m ³
		Workers	Inhalation	Long-term local effects	221 mg/m ³
	Workers	Dermal	Long-term systemic effects	180 mg/kg	
	Consumers	Inhalation	Long-term systemic effects	14.8 mg/m ³	
	Consumers	Inhalation	Long-term local effects	65.3 mg/m ³	
	Consumers	Inhalation	Acute systemic effects	260 mg/m ³	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version
7.1

Revision Date:
03.04.2024

SDS Number:
102000005103

Print Date: 16.04.2024
Date of first issue: 07.11.2014

	Consumers	Inhalation	Acute local effects	260 mg/m ³
	Consumers	Dermal	Long-term systemic effects	108 mg/kg
	Consumers	Oral	Long-term systemic effects	1.5 mg/kg
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m ³
	Workers	Inhalation	Acute local effects	2420 mg/m ³
	Workers	Inhalation	Acute systemic effects	1210 mg/m ³
	Workers	Dermal	Long-term systemic effects	186 mg/kg
	Consumers	Inhalation	Long-term systemic effects	200 mg/m ³
	Consumers	Dermal	Long-term systemic effects	62 mg/kg
	Consumers	Oral	Long-term systemic effects	62 mg/kg
naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha	Workers	Inhalation	Long-term systemic effects	330 mg/m ³
	Workers	Inhalation	Acute systemic effects	1300 mg/m ³
	Workers	Inhalation	Long-term local effects	840 mg/m ³
	Workers	Dermal	Long-term systemic effects	44 mg/kg
	Consumers	Inhalation	Acute systemic effects	1200 mg/m ³
	Consumers	Inhalation	Long-term local effects	180 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	1200 mg/m ³
	Consumers	Dermal	Long-term systemic effects	26 mg/kg
	Consumers	Oral	Long-term systemic effects	26 mg/kg
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m ³
	Workers	Inhalation	Long-term local effects	3.72 mg/m ³
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m ³
	Workers	Inhalation	Long-term local effects	0.5 mg/m ³
	Workers	Dermal	Long-term systemic effects	83 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version
7.1

Revision Date:
03.04.2024

SDS Number:
102000005103

Print Date: 16.04.2024
Date of first issue: 07.11.2014

	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
	Consumers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Workers	Inhalation	Long-term systemic effects	35.3 mg/m3
	Workers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Acute local effects	5.36 mg/m3
	Workers	Dermal	Long-term systemic effects	5 mg/kg
	Workers	Dermal	Acute systemic effects	5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	8.7 mg/m3
	Consumers	Inhalation	Long-term local effects	0.1 mg/m3
	Consumers	Inhalation	Acute systemic effects	50 mg/m3
	Consumers	Inhalation	Acute local effects	4 mg/m3
	Consumers	Dermal	Long-term systemic effects	2.5 mg/kg
	Consumers	Dermal	Acute systemic effects	17 mg/kg
	Consumers	Oral	Long-term systemic effects	2.5 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
zinc powder — zinc dust (stabilised)	Fresh water	0.0206 mg/l
	Marine water	0.0061 mg/l
	STP	0.100 mg/l
	Fresh water sediment	235.6 mg/kg
	Marine sediment	121 mg/kg
xylene	Soil	35.6 mg/kg
	Fresh water	0.044 mg/l
	Marine water	0.0044 mg/l
	Fresh water sediment	12.46 mg/kg
	Marine sediment	12.46 mg/kg
acetone	Soil	2.31 mg/kg
	STP	1.6 mg/l
	Intermittent Release	0.01 mg/l
	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l
	Fresh water sediment	30.4 mg/kg
	Marine sediment	3.04 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version
7.1

Revision Date:
03.04.2024

SDS Number:
102000005103

Print Date: 16.04.2024
Date of first issue: 07.11.2014

	STP	100 mg/l
	Soil	29.5 mg/kg
	periodical release	21 mg/l
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
zinc oxide	Fresh water	0.0206 mg/l
	Marine water	0.0061 mg/l
	Fresh water sediment	117.8 mg/kg
	Marine sediment	56.5 mg/kg
	Soil	35.6 mg/kg
	STP	0.1 mg/l
N-(3-(trimethoxysilyl)propyl)ethylenedi amine	Fresh water	0.062 mg/l
	Marine water	0.0062 mg/l
	STP	25 mg/l
	Fresh water sediment	0.048 mg/kg
	Marine sediment	0.0048 mg/kg
	Soil	0.0075 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Goggles
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	:	liquid
Colour	:	No data available
Odour	:	characteristic
Odour Threshold	:	No data available
Freezing point	:	No data available
Boiling point/boiling range	:	55 °C
Flammability	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	-19 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Viscosity	:	
Viscosity, kinematic	:	No data available
Flow time	:	14 - 16 s at 20 °C Cross section: 4 mm Method: DIN 53211
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	No data available
Vapor Pressure for Components:	:	
Solvent naphtha (petroleum), light arom.	:	2 hPa (20 °C)
xylene	:	8.2 hPa (20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

acetone : 240 hPa (20 °C)

naphtha (petroleum),
hydrodesulphurized heavy;
Low boiling point hydrogen
treated naphtha
N-(3-
(trimethoxysilyl)propyl)ethy
lenediamine : 240 kPa (37.8 °C)

Relative density : 1.5 hPa (20 °C)

Density : No data available

Density : ca. 1.35 g/cm³

Relative vapour density : No data available

Particle characteristics
Particle Size Distribution : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

zinc powder — zinc dust (stabilised):

Acute oral toxicity : (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

xylene:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

acetone:

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg

(Mouse): 3,000 mg/kg

(Rat): 9,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

N-(3-(trimethoxysilyl)propyl)ethylenediamine :

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

Solvent naphtha (petroleum), light arom.:

Result : Repeated exposure may cause skin dryness or cracking.

xylene:

Result : Skin irritation

acetone:

Remarks : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

xylene:

Result : Eye irritation

acetone:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

Result : Eye irritation

N-(3-(trimethoxysilyl)propyl)ethylenediamine :

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

N-(3-(trimethoxysilyl)propyl)ethylenediamine :

Result : The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.:

Germ cell mutagenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:

Germ cell mutagenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:

Solvent naphtha (petroleum), light arom.:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

xylene:

Assessment : May cause respiratory irritation.

acetone:

Assessment : May cause drowsiness or dizziness.

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:

Assessment : May cause drowsiness or dizziness.

N-(3-(trimethoxysilyl)propyl)ethylenediamine:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

xylene:

Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:

Assessment : Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Solvent naphtha (petroleum), light arom.:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

xylene:

May be fatal if swallowed and enters airways.

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

Components:

zinc powder — zinc dust (stabilised):

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

zinc powder — zinc dust (stabilised):

M-Factor (Short-term (acute) aquatic hazard) : 1
M-Factor (Long-term (chronic) aquatic hazard) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.
Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Solvent naphtha (petroleum), light arom.:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

acetone:

Toxicity to daphnia and other : (Daphnia magna (Water flea)): 21,600 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

aquatic invertebrates

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

zinc oxide:

M-Factor (Short-term (acute) aquatic hazard) : 1

M-Factor (Long-term (chronic) aquatic hazard) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

zinc 5-nitroisophthalate:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

Toxic to aquatic life with long lasting effects.

Components:

zinc powder — zinc dust (stabilised):

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

zinc oxide:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT
IMDG : PAINT
(Zinc powder, stabilized)
IATA : Paint

14.3 Transport hazard class(es)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADR	
Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
Tunnel restriction code	: (D/E)
IMDG	
Packing group	: II
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 364
Packing instruction (LQ)	: Y341
Packing group	: II
Labels	: 3
IATA (Passenger)	
Packing instruction (passenger aircraft)	: 353
Packing instruction (LQ)	: Y341
Packing group	: II
Labels	: 3

14.5 Environmental hazards

ADR	
Environmentally hazardous	: yes
IMDG	
Marine pollutant	: yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3
Solvent naphtha (petroleum), light arom. (Number on list 3)
xylene (Number on list 3)
acetone (Number on list 3)
naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha (Number on list 3)
aluminium powder (stabilised) (Number on list 40)
n-butyl acetate (Number on list 3)
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha (Number on list 3)
butan-1-ol (Number on list 3)
N-(3-(trimethoxysilyl)propyl)ethylenediamine (Number on list 3)
ethylbenzene (Number on list 40, 3)

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : acetone

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. acetone (ANNEX II)

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: 44.38 %, 599.15 g/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H228 : Flammable solid.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H372 : Causes damage to organs through prolonged or repeated exposure.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version 7.1 Revision Date: 03.04.2024 SDS Number: 102000005103 Print Date: 16.04.2024
Date of first issue: 07.11.2014

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Agent Zincflake G 500 200 kgs

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
7.1	03.04.2024	102000005103	Date of first issue: 07.11.2014

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN