

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version 5.0      Revision Date: 25.11.2019      SDS Number: 102000000006      Print Date: 07.08.2020  
Date of first issue: 13.01.2014

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : 9302 UNIPAK 500 SILVER LITHO  
Product code : 014244RC0M1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company :  
  
E-mail address of person responsible for the SDS : msds.eckart@altana.com

#### 1.4 Emergency telephone number

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3      H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412      Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066      Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P273      Avoid release to the environment.  
**Disposal:**  
P501      Dispose of contents/ container to an approved waste disposal plant.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version 5.0      Revision Date: 25.11.2019      SDS Number: 102000000006      Print Date: 07.08.2020  
Date of first issue: 13.01.2014

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5 231-072-3  01-2119529243-45	Flam. Sol. 1; H228	>= 20 - < 25
Distillates (petroleum), solvent-refined middle; Gasoil - unspecified	64741-91-9 265-093-4 01-2119457735-29	Asp. Tox. 1; H304	>= 10 - < 20
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47	Repr. 2; H361d Aquatic Chronic 3; H412	>= 1 - < 2.5
amines, hydrogenated tallow alkyl	61788-45-2 (90640-32-7) 262-976-6	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.25 - < 1

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.  
Do not leave the victim unattended.
- No hazards which require special first aid measures.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version	Revision Date:	SDS Number:	Print Date:
5.0	25.11.2019	102000000006	07.08.2020
			Date of first issue: 13.01.2014

---

Remove contact lenses.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
ABC powder  
Foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version	Revision Date:	SDS Number:	Print Date: 07.08.2020
5.0	25.11.2019	102000000006	Date of first issue: 13.01.2014

---

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Wipe up with absorbent material (e.g. cloth, fleece).  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids.  
Do not store together with oxidizing and self-igniting products.  
Never allow product to get in contact with water during storage.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version  
5.0

Revision Date:  
25.11.2019

SDS Number:  
102000000006

Print Date: 07.08.2020  
Date of first issue: 13.01.2014

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable)	4 mg/m <sup>3</sup>	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version  
5.0

Revision Date:  
25.11.2019

SDS Number:  
102000000006

Print Date: 07.08.2020  
Date of first issue: 13.01.2014

	<p>particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
	<table border="1"><tr><td>TWA (Respirable dust)</td><td>4 mg/m<sup>3</sup></td><td>GB EH40</td></tr></table>	TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40		
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	Workers	Skin contact	Long-term systemic effects	5.00 mg/kg
	Workers	Inhalation	Long-term systemic effects	17.62 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic	5.00 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version  
5.0

Revision Date:  
25.11.2019

SDS Number:  
102000000006

Print Date: 07.08.2020  
Date of first issue: 13.01.2014

			effects	
	Consumers	Skin contact	Long-term systemic effects	5.00 mg/kg
	Consumers	Inhalation	Long-term systemic effects	4.35 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	Fresh water	0.014 mg/l
	Marine water	0.0014 mg/l
	Fresh water sediment	5.29 mg/kg
	Soil	1.05 mg/kg
	STP	3 mg/l
	Marine sediment	0.529 mg/kg
	oral (secondary poisoning)	83.3 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Goggles

Safety glasses

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Respiratory protection

: Use suitable breathing protection if workplace concentration requires.

No personal respiratory protective equipment normally required.

### Environmental exposure controls

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version  
5.0

Revision Date:  
25.11.2019

SDS Number:  
102000000006

Print Date: 07.08.2020  
Date of first issue: 13.01.2014

Water : The product should not be allowed to enter drains, water courses or the soil.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : No data available

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Freezing point : No data available

Boiling point/boiling range : 260 °C

Flash point : 101 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Auto-ignition temperature : No data available

Smoldering temperature : No data available

Decomposition temperature : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version	Revision Date:	SDS Number:	Print Date: 07.08.2020
5.0	25.11.2019	102000000006	Date of first issue: 13.01.2014

---

Density	: No data available
Bulk density	: No data available
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 21 mm <sup>2</sup> /s (40 °C)
Flow time	: No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents

### 10.6 Hazardous decomposition products

Contact with water or humid : This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version 5.0      Revision Date: 25.11.2019      SDS Number: 102000000006      Print Date: 07.08.2020  
Date of first issue: 13.01.2014

---

air

Thermal decomposition : This information is not available.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Components:

##### **aluminium powder (stabilised):**

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **Distillates (petroleum), solvent-refined middle; Gasoil -unspecified:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

##### **1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:**

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402

##### **amines, hydrogenated tallow alkyl:**

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg  
Method: OECD Test Guideline 401

##### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

##### Components:

##### **1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:**

Species: Rabbit  
Exposure time: 4 h  
Method: OECD Test Guideline 404  
Result: No skin irritation

##### **amines, hydrogenated tallow alkyl:**

Result: Skin irritation

Remarks: May cause skin irritation in susceptible persons.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version  
5.0

Revision Date:  
25.11.2019

SDS Number:  
102000000006

Print Date: 07.08.2020  
Date of first issue: 13.01.2014

---

### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Components:**

##### **1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:**

Species: Rabbit  
Exposure time: 72 h  
Method: OECD Test Guideline 405  
Result: No eye irritation

##### **amines, hydrogenated tallow alkyl:**

Result: Irreversible effects on the eye

Remarks: May cause irreversible eye damage.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Components:**

##### **amines, hydrogenated tallow alkyl:**

Target Organs: Liver, Gastrointestinal tract, Immune system  
Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Components:**

##### **amines, hydrogenated tallow alkyl:**

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version  
5.0

Revision Date:  
25.11.2019

SDS Number:  
102000000006

Print Date: 07.08.2020  
Date of first issue: 13.01.2014

---

### Further information

#### Product:

Remarks: No data available

#### Components:

##### **amines, hydrogenated tallow alkyl:**

Remarks: Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

##### **Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

#### Components:

##### **1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 2.46 mg/l

##### **Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

##### **amines, hydrogenated tallow alkyl:**

M-Factor (Short-term (acute) aquatic hazard) : 10

M-Factor (Long-term (chronic) aquatic hazard) : 10

##### **Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version 5.0      Revision Date: 25.11.2019      SDS Number: 102000000006      Print Date: 07.08.2020  
Date of first issue: 13.01.2014

---

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

#### Components:

#### **amines, hydrogenated tallow alkyl:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
In accordance with local and national regulations.

Contaminated packaging : In accordance with local and national regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version	Revision Date:	SDS Number:	Print Date: 07.08.2020
5.0	25.11.2019	102000000006	Date of first issue: 13.01.2014

---

### SECTION 14: Transport information

#### 14.1 UN number

#### 14.2 UN proper shipping name

#### 14.3 Transport hazard class(es)

#### 14.4 Packing group

#### 14.5 Environmental hazards

#### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

#### 15.2 Chemical safety assessment

---

### SECTION 16: Other information

#### Full text of H-Statements

H228	: Flammable solid.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H361d	: Suspected of damaging the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version	Revision Date:	SDS Number:	Print Date: 07.08.2020
5.0	25.11.2019	102000000006	Date of first issue: 13.01.2014

---

### Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Flam. Sol.	:	Flammable solids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## 9302 UNIPAK 500 SILVER LITHO

Version  
5.0

Revision Date:  
25.11.2019

SDS Number:  
102000000006

Print Date: 07.08.2020  
Date of first issue: 13.01.2014

---

GB / EN