

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : METALSTAR FPG 712 0872
Product code : 025408RN0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

Hazard statements : H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

Copper
Rosin, maleated, polymer with pentaerythritol
Resin acids and Rosin acids, maleated, esters with pentaerythritol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
Copper	7440-50-8 231-159-6 01-2119480154-42	Acute Tox. 4; H302 Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 25 - < 50
Rosin, maleated, polymer with pentaerythritol	68333-69-7	Skin Sens. 1B; H317 Eye Irrit. 2; H319 Aquatic Chronic 4; H413	>= 10 - < 20
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3	Aquatic Acute 1; H400	>= 10 - < 20

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

	01-2119467174-37	Aquatic Chronic 1; H410	
Resin acids and Rosin acids, maleated, esters with pentaerythritol	94581-17-6 305-516-2	Aquatic Chronic 4; H413 Eye Irrit. 2; H319 Skin Sens. 1B; H317	$\geq 2.5 - < 10$
octadecylamine	124-30-1 204-695-3 01-2119473804-32	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 0.25 - < 1$
2,6-di-tert-butyl-p-cresol	128-37-0 204-881-4	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 0.25 - < 1$
amines, hydrogenated tallow alkyl	61788-45-2 (90640-32-7) 262-976-6	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 0.025 - < 0.1$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If on skin, rinse well with water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version	Revision Date:	SDS Number:	Print Date: 06.08.2020
2.0	10.12.2019	102000031910	Date of first issue: 30.08.2019

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Special powder against metal fire
Dry sand
ABC powder

Unsuitable extinguishing media : Water
High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version	Revision Date:	SDS Number:	Print Date: 06.08.2020
2.0	10.12.2019	102000031910	Date of first issue: 30.08.2019

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Pick up and transfer to properly labelled containers.
Do not flush with water.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

Dampness : Keep in a dry, cool and well-ventilated place.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Copper	7440-50-8	TWA (Fumes)	0.2 mg/m ³ (Copper)	GB EH40
		TWA (Dusts and mists)	1 mg/m ³ (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m ³ (Copper)	GB EH40
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (Inhalable)	10 mg/m ³	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**METALSTAR FPG 712 0872**Version
2.0Revision Date:
10.12.2019SDS Number:
102000031910Print Date: 06.08.2020
Date of first issue: 30.08.2019

	mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable)	4 mg/m3	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
2,6-di-tert-butyl-p-cresol	128-37-0	TWA	10 mg/m3	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Copper	Workers	Skin contact	Acute systemic effects	273 mg/kg
	Workers	Inhalation	Acute systemic effects	20 mg/m3
	Workers	Skin contact	Long-term systemic effects	137 mg/kg
	Consumers	Skin contact	Acute systemic effects	273 mg/kg
zinc powder — zinc dust (stabilised)	Consumers	Inhalation	Acute systemic effects	20 mg/m3
	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Skin contact	Long-term systemic effects	83 mg/kg
	Consumers	Ingestion	Long-term systemic effects	0.83 mg/kg
	Consumers	Skin contact	Long-term systemic effects	83 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
2,6-di-tert-butyl-p-cresol	Workers	Inhalation	Long-term systemic effects	3.5 mg/m3
	Workers	Dermal	Long-term systemic effects	0.5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.86 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.25 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

	Consumers	Oral	Long-term systemic effects	0.25 mg/kg
--	-----------	------	----------------------------	------------

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Copper	Soil	65.5 mg/kg
	Fresh water	0.0078 mg/l
	Fresh water sediment	87 mg/kg
	Marine water	0.0052 mg/l
	Marine sediment	676 mg/kg
	STP	0.230 mg/l
zinc powder — zinc dust (stabilised)	Fresh water	0.0206 mg/l
	Fresh water sediment	117.8 mg/kg
	Marine water	0.0061 mg/l
	Soil	35.6 mg/kg
	Marine sediment	56.5 mg/kg
2,6-di-tert-butyl-p-cresol	Fresh water	0.199 µg/l
	Marine water	0.02 µg/l
	Fresh water sediment	0.0996 mg/kg
	Marine sediment	0.00996 mg/kg
	STP	0.17 mg/l
	Soil	0.04769 mg/kg
	Sporadic Release	1.99 µg/l
Secondary Poisoning	8.33 mg/kg	

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses

Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.
Equipment should conform to EN 14387

Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : gold

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Freezing point : No data available

Boiling point/boiling range : > 100 °C

Flash point : > 100 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Auto-ignition temperature : No data available

Smoldering temperature : No data available

Decomposition temperature : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Upper explosion limit / Upper flammability limit : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Bulk density : No data available

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Flow time : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

10.5 Incompatible materials

10.6 Hazardous decomposition products

Thermal decomposition : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,810 mg/kg
Method: Calculation method

Components:

Copper:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

zinc powder — zinc dust (stabilised):

Acute oral toxicity : (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

2,6-di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 402

amines, hydrogenated tallow alkyl:

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation and/or dermatitis.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version
2.0

Revision Date:
10.12.2019

SDS Number:
102000031910

Print Date: 06.08.2020
Date of first issue: 30.08.2019

Components:

Copper:

Remarks: May cause skin irritation in susceptible persons.

amines, hydrogenated tallow alkyl:

Result: Skin irritation

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Eye irritation

Components:

Copper:

Result: Eye irritation

amines, hydrogenated tallow alkyl:

Result: Irreversible effects on the eye

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks: Causes sensitisation.

May cause sensitisation of susceptible persons by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version
2.0

Revision Date:
10.12.2019

SDS Number:
102000031910

Print Date: 06.08.2020
Date of first issue: 30.08.2019

STOT - repeated exposure

Not classified based on available information.

Components:

amines, hydrogenated tallow alkyl:

Target Organs: Liver, Gastrointestinal tract, Immune system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

amines, hydrogenated tallow alkyl:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Components:

Copper:

Remarks: No data available

zinc powder — zinc dust (stabilised):

Remarks: No data available

amines, hydrogenated tallow alkyl:

Remarks: Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Copper:

M-Factor (Short-term (acute) : 10
aquatic hazard)

Ecotoxicology Assessment

Short-term (acute) aquatic : Very toxic to aquatic life.
hazard

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version
2.0

Revision Date:
10.12.2019

SDS Number:
102000031910

Print Date: 06.08.2020
Date of first issue: 30.08.2019

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

zinc powder — zinc dust (stabilised):

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

octadecylamine:

M-Factor (Short-term (acute) aquatic hazard) : 10

: 10

M-Factor (Long-term (chronic) aquatic hazard) : 10

10

2,6-di-tert-butyl-p-cresol:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

amines, hydrogenated tallow alkyl:

M-Factor (Short-term (acute) aquatic hazard) : 10

M-Factor (Long-term (chronic) aquatic hazard) : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

Components:

Copper:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

zinc powder — zinc dust (stabilised):

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

amines, hydrogenated tallow alkyl:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number

ADR : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
IATA : Environmentally hazardous substance, liquid, n.o.s.

14.3 Transport hazard class(es)

ADR : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADR
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
IMDG
Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Class 9 - Miscellaneous dangerous substances and articles

IATA (Passenger)

Packing instruction (passenger aircraft) : 964

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version	Revision Date:	SDS Number:	Print Date: 06.08.2020
2.0	10.12.2019	102000031910	Date of first issue: 30.08.2019

Packing instruction (LQ) : Y964
Packing group : III
Labels : Class 9 - Miscellaneous dangerous substances and articles

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H373 : May cause damage to organs through prolonged or repeated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version 2.0 Revision Date: 10.12.2019 SDS Number: 102000031910 Print Date: 06.08.2020
Date of first issue: 30.08.2019

H400 : exposure.
H410 : Very toxic to aquatic life.
H411 : Very toxic to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALSTAR FPG 712 0872

Version
2.0

Revision Date:
10.12.2019

SDS Number:
102000031910

Print Date: 06.08.2020
Date of first issue: 30.08.2019

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN