

## SHINEDECOR 9212

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SHINEDECOR 9212  
Product code : 052666HD0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company :  
  
E-mail address of person responsible for the SDS : msds.eckart@altana.com

#### 1.4 Emergency telephone number

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3      H226: Flammable liquid and vapour.  
Eye irritation, Category 2      H319: Causes serious eye irritation.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :  

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version  
3.2

Revision Date:  
24.03.2020

SDS Number:  
102000002358

Print Date: 07.08.2020  
Date of first issue: 09.01.2014

P280 Wear protective gloves/ protective clothing/  
eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off  
immediately all contaminated clothing.  
Rinse skin with water.

P337 + P313 If eye irritation persists: Get medical advice/  
attention.

P370 + P378 In case of fire: Use dry sand, dry chemical  
or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

### Additional Labelling

EUH208 Contains 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5 231-072-3  01-2119529243-45	Flam. Sol. 1; H228	>= 20 - < 25
propan-2-ol	67-63-0 200-661-7 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 1 - < 10
ethanol	64-17-5 200-578-6  01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 1 - < 10
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 01-2120764690-50	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.0015 - < 0.0025

## SHINEDECOR 9212

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

For explanation of abbreviations see section 16.

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.  
Do not leave the victim unattended.
- Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.

#### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Dry sand  
ABC powder  
Foam
- Unsuitable extinguishing : Water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

media

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Do not flush with water.

### 6.4 Reference to other sections

For personal protection see section 8.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version	Revision Date:	SDS Number:	Print Date: 07.08.2020
3.2	24.03.2020	102000002358	Date of first issue: 09.01.2014

---

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Advice on common storage : Do not store near acids.  
Do not store together with oxidizing and self-igniting products. Keep away from oxidizing agents and strongly acid or alkaline materials.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Further information on storage stability : No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version  
3.2

Revision Date:  
24.03.2020

SDS Number:  
102000002358

Print Date: 07.08.2020  
Date of first issue: 09.01.2014

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable)	4 mg/m <sup>3</sup>	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version  
3.2

Revision Date:  
24.03.2020

SDS Number:  
102000002358

Print Date: 07.08.2020  
Date of first issue: 09.01.2014

	exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m <sup>3</sup>	GB EH40
		STEL	500 ppm 1,250 mg/m <sup>3</sup>	GB EH40
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m <sup>3</sup>	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
silicon dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m <sup>3</sup> (Silica)	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes</p>			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version  
3.2

Revision Date:  
24.03.2020

SDS Number:  
102000002358

Print Date: 07.08.2020  
Date of first issue: 09.01.2014

	termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (Respirable dust)	2.4 mg/m <sup>3</sup> (Silica)	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
propan-2-ol	Workers	Skin contact	Long-term systemic effects	888 mg/kg
	Workers	Inhalation	Long-term systemic effects	500 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	26 mg/kg
	Consumers	Skin contact	Long-term systemic effects	319 mg/kg
	Consumers	Inhalation	Long-term systemic	89 mg/m <sup>3</sup>



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version  
3.2

Revision Date:  
24.03.2020

SDS Number:  
102000002358

Print Date: 07.08.2020  
Date of first issue: 09.01.2014

			effects	
ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	1900 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	343 mg/kg
	Consumers	Inhalation	Long-term systemic effects	114 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	206 mg/kg
	Consumers	Ingestion	Long-term systemic effects	87 mg/kg
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	Workers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Ingestion	Long-term systemic effects	300 mg/kg
	Consumers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Inhalation	Long-term systemic effects	900 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
propan-2-ol	Soil	28 mg/kg
	Fresh water	140.9 mg/l
	Fresh water sediment	552 mg/kg
	Marine water	140.9 mg/l
	Marine sediment	552 mg/kg
	STP	2251 mg/l
ethanol	Fresh water	0.96 mg/l
	Marine water	0.79 mg/l
	Intermittent water release	2.75 mg/l
	STP	580 mg/l
	Fresh water sediment	3.6 mg/kg
	Marine sediment	2.9 mg/kg
	Soil	0.63 mg/kg
	Secondary Poisoning	380 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Goggles

Wear face-shield and protective suit for abnormal processing problems.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

- Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- Environmental exposure controls**
- Water : The product should not be allowed to enter drains, water courses or the soil.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : No data available
- Odour : characteristic
- Odour Threshold : No data available
- pH : No data available
- Freezing point : No data available
- Boiling point/boiling range : 82 °C
- Flash point : 26 °C
- Evaporation rate : No data available

**SHINEDECOR 9212**

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

- Flammability (solid, gas) : No data available
- Self-ignition : No data available
- Auto-ignition temperature : No data available
- Smoldering temperature : No data available
- Decomposition temperature : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Relative density : No data available
- Density : No data available
- Bulk density : No data available
- Water solubility : No data available
- Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available
- Decomposition temperature : No data available
- Viscosity, dynamic : No data available
- Viscosity, kinematic : No data available
- Flow time : No data available

**9.2 Other information**

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.  
  
Stable under recommended storage conditions.  
  
Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.  
  
Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents

#### 10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.  
  
Thermal decomposition : This information is not available.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Components:

##### propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
  
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

##### ethanol:

Acute oral toxicity : LD50 (Mouse): 3,450 mg/kg

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

LD50 (Rat): 7,060 mg/kg

LD50 (Rabbit): 6,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 20,000 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

### **2-methylisothiazol-3(2H)-one:**

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.

### **Skin corrosion/irritation**

Not classified based on available information.

### **Product:**

Remarks: May cause skin irritation in susceptible persons.

### **Components:**

#### **ethanol:**

Result: No skin irritation

Remarks: Based on available data, the classification criteria are not met.

### **2-methylisothiazol-3(2H)-one:**

Result: Corrosive after 3 minutes to 1 hour of exposure

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Product:**

Remarks: Eye irritation

### **Components:**

#### **ethanol:**

Result: Eye irritation

Remarks: Based on available data, the classification criteria are not met.

### **2-methylisothiazol-3(2H)-one:**

Result: Irreversible effects on the eye

## SHINEDECOR 9212

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Product:**

Result: Does not cause skin sensitisation.

#### **Components:**

##### **2-methylisothiazol-3(2H)-one:**

Result: May cause sensitisation by skin contact.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Further information**

#### **Product:**

Remarks: Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

##### **2-methylisothiazol-3(2H)-one:**

M-Factor (Short-term (acute) : 10  
aquatic hazard)

: 1

M-Factor (Long-term : 1

## SHINEDECOR 9212

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

(chronic) aquatic hazard)

### Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles  
European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version  
3.2

Revision Date:  
24.03.2020

SDS Number:  
102000002358

Print Date: 07.08.2020  
Date of first issue: 09.01.2014

Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

### SECTION 14: Transport information

#### 14.1 UN number

**ADR** : Not regulated as a dangerous good  
**IMDG** : UN 1263  
**IATA** : UN 1263

#### 14.2 UN proper shipping name

**ADR** : Not regulated as a dangerous good  
**IMDG** : PAINT  
**IATA** : Paint

#### 14.3 Transport hazard class(es)

**ADR** : Not regulated as a dangerous good  
**IMDG** : 3  
**IATA** : 3

#### 14.4 Packing group

**ADR** : Not regulated as a dangerous good  
**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : Transport in accordance with 2.3.2.5 of the IMDG Code.

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Class 3 - Flammable liquids

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Class 3 - Flammable liquids

#### 14.5 Environmental hazards

**ADR** : Not regulated as a dangerous good



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version 3.2      Revision Date: 24.03.2020      SDS Number: 102000002358      Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

Remarks : IMDG: Classified in accordance with Chapter 2.3.2.5 IMDG-Code  
ADR: Classified in accordance with Chapter 2.2.3.1.5.1 and 2.2.3.1.5.2 ADR  
Due to the risk of hydrogen development we recommend to refrain from airfreighting this/these product(s).

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

### 15.2 Chemical safety assessment

---

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H228 : Flammable solid.  
H301 : Toxic if swallowed.  
H311 : Toxic in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H336 : May cause drowsiness or dizziness.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version	Revision Date:	SDS Number:	Print Date: 07.08.2020
3.2	24.03.2020	102000002358	Date of first issue: 09.01.2014

---

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Flam. Sol.	: Flammable solids
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SHINEDECOR 9212

Version  
3.2

Revision Date:  
24.03.2020

SDS Number:  
102000002358

Print Date: 07.08.2020  
Date of first issue: 09.01.2014

---

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN