

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STANDART Porenbeton RO 100 Aluminium Powder
Material number : 040352F80

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colouring agent

1.3 Details of the supplier of the safety data sheet

Company :

Telephone :
Telefax :
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Flammable solids, Category 1, H228

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART Porenbeton RO 100 Aluminium Powder


Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

Information concerning particular hazards for human and environment: : Please refer to our website for further important safety instructions for handling aluminium powder:
http://www.eckart.net/fileadmin/eckart/Service/GDA_Alupulver_Safety_engl.pdf

GHS-Labeling

Symbol(s) : 

Signal word : Danger

Hazard statements : H228: Flammable solid.

Precautionary statements : **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
 P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.
 P370 + P378 In case of fire: Use for extinction: Dry sand.

Hazardous components which must be listed on the label

SECTION 3: Composition/information on ingredients

Substance name : aluminium powder (stabilised)

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

Substance No. : EINECS-No. : 231-072-3

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Move out of dangerous area.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : ABC powder, Carbon dioxide (CO₂), Water, Foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

Evacuate personnel to safe areas.
Avoid dust formation.
Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Do not use a vacuum cleaner.

Do not flush with water.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid creating dust. Routine housekeeping should be
instituted to ensure that dusts do not accumulate on surfaces.
Store away from heat.

For personal protection see section 8. Smoking, eating and
drinking should be prohibited in the application area. Dispose
of rinse water in accordance with local and national
regulations.

Advice on protection against fire and explosion : Use explosion-proof equipment. During processing, dust may
form explosive mixture in air. Take measures to prevent the

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

build up of electrostatic charge. When transferring from one container to another apply earthing measures and use conductive hose material.

Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : Keep in a dry place. No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (total dust)	15 mg/m ³	2012-07-01	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

powder (stabilised)					
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m ³	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m ³	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m ³	2014-11-26	
aluminium powder (stabilised)	7429-90-5	PEL (respirable dust fraction)	5 mg/m ³	2014-11-26	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m ³	2008-01-01	
aluminium powder (stabilised)	7429-90-5	TWA	5 mg/m ³	2005-09-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m ³	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m ³	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m ³	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m ³	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m ³	1989-01-19	

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m3	2013-03-01	
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	PEL (Welding fumes)	5 mg/m3	2017-10-02	
aluminium powder (stabilised)	7429-90-5	PEL (Pyro powders)	5 mg/m3	2017-10-02	

8.2 Exposure controls

Personal protective equipment

- Eye protection : Face-shield
 : Safety glasses
- Hand protection
 Material : Leather
- Glove length : Long sleeve gloves

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

- Remarks : Leather gloves
 The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Anti-static and fire resistant protective clothing. DIN EN 11612; EN 533; EN 1149-1. Anti-static safety shoes.
- : Dust impervious protective suit
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
 Breathing apparatus with filter.
 P1 filter

Environmental exposure controls

- General advice :
- : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

- Water : The product should not be allowed to enter drains, water courses or the soil.
- :

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: powder
Colour	: silver
Odour	: odourless
pH	: No data available
Melting point/freezing point	: 660 °C
Boiling point/boiling range	: 2 467 °C
Flash point	: No data available
Bulk density	: No data available
Flammability (solid, gas)	: The substance or mixture is a flammable solid with the category 1.
Smoldering temperature	: > 230 °C
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: 30 g/m ³
Vapour pressure	: No data available
Density	: 2,5 g/cm ³ (ca.)
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: 340 °C
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

Water

10.6 Hazardous decomposition products

Other information : No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product

No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

SECTION 14: Transport information**14.1 UN number**

ADR	: 1309
TDG	: 1309
CFR	: 1309
IMDG	: 1309
IATA	: 1309

14.2 Proper shipping name

ADR	: ALUMINIUM POWDER, COATED
TDG	: ALUMINUM POWDER, COATED
CFR	: ALUMINUM POWDER, COATED
IMDG	: ALUMINIUM POWDER, COATED
IATA	: ALUMINIUM POWDER, COATED

14.3 Transport hazard class

ADR	: 4.1
TDG	: 4.1
CFR	: 4.1
IMDG	: 4.1
IATA	: 4.1

14.4 Packing group

ADR	
Packaging group	: II
Classification Code	: F3
Hazard Identification Number	: 40
Labels	: 4.1

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

Tunnel restriction code : (E)

TDG

Packaging group : II

Labels : 4.1

CFR

Packaging group : II

Labels : 4.1

IMDG

Packaging group : II

Labels : 4.1

EmS Number : F-G, S-G

IATAPacking instruction (cargo
aircraft) : 448Packing instruction
(passenger aircraft) : 445

Packing instruction (LQ) : Y441

Packaging group : II

Labels : 4.1

14.5 Environmental hazards**14.6 Special precautions for user****IMDG Code- segregation group:**

: IMDG Code segregation group 15 - Powdered metals

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Full text of H-Statements**

H228 : Flammable solid.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

STANDART Porenbeton RO 100 Aluminium Powder

Version 4.0

Revision Date 03.12.2019

Print Date 28.12.2020
