

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : ROTOSTAR UV/LED 366 873 FLEXO INK
Material number : 026429U10

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

Telephone :
Telefax :
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Acute toxicity, Category 5, Oral, H303
Skin corrosion/irritation, Category 2, H315
Serious eye damage/eye irritation, Category 2A, H319

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

Skin sensitisation, Category 1, H317
 Short-term (acute) aquatic hazard, Category 1, H400
 Long-term (chronic) aquatic hazard, Category 1, H410

GHS-Labeling

Symbol(s)



Signal word

: Warning

Hazard statements

: H303: May be harmful if swallowed.
 H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.
 H319: Causes serious eye irritation.
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P301 + P333 + P317 IF SWALLOWED or if skin irritation or rash occurs: Get medical help.
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P317 If eye irritation persists: Get medical help.
 P391 Collect spillage.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

Hazardous components which must be listed on the label

Identification	CAS-No.
copper	7440-50-8
3-methyl-1,5-pentanediy diacrylate	64194-22-5
2-Propenoic acid, reaction products with dipentaerythritol	1384855-91-7
Glycerol, propoxylated, esters with acrylic acid	52408-84-1

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1)	51728-26-8	Skin Irrit.;2;H315 Eye Irrit.;2;H319 Aquatic Chronic;2;H411	25 - 50
Copper	7440-50-8 231-159-6	Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	20 - 25
monoalkylor monoaryl or monoalkylaryl esters of acrylic acid	64194-22-5 264-727-7	Acute Tox.;4;H332 ;2;H315 ;2A;H319 Skin Sens.;1A;H317 STOT SE;3;H335	10 - 20

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

		Aquatic Chronic;3;H412	
2-Propenoic acid, reaction products with dipentaerythritol	1384855-91-7	Skin Sens.;1B;H317 Eye Irrit.;2A;H319 Aquatic Chronic;3;H412	2,5 - 10
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	2,5 - 10
Glycerol, propoxylated, esters with acrylic acid	52408-84-1	Eye Irrit.;2A;H319 Skin Sens.;1;H317	1 - 10
Epoxy acrylate	55818-57-0	Skin Sens.;1;H317	0,1 - 1
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	28961-43-5	;2A;H319 Skin Sens.;1;H317	0,1 - 1
amines, hydrogenated tallow alkyl	61788-45-2 (90640-32-7) 262-976-6	Acute Tox.;5;H303 ;2;H315 ;1;H318 STOT RE;2;H373 Asp. Tox.;1;H304 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	0,0025 - 0,025

For the full text of the H-Statements mentioned in this Section, see Section 16.

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media : Special powder against metal fire, Dry sand, ABC powder
- Unsuitable extinguishing media : Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Pick up and transfer to properly labelled containers.
Do not flush with water.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.


Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

Dampness : Keep in a dry, cool and well-ventilated place.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Page 8 / 22	102000033793	A member of  ALтана
-------------	--------------	---

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
Copper	7440-50-8	AGW (inhalable fraction)	1 mg/m ³		DE TRGS 900
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				
Epoxy acrylate	55818-57-0	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet				

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

		have information regarding unspecific action on the respiratory organs in excess of the normal values. Commission for dangerous substances Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Epoxy acrylate	55818-57-0	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values. Commission for dangerous substances Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses
- : Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
 The exact break through time can be obtained from the protective glove producer and this has to be observed.
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.
Equipment should conform to EN 14387

Environmental exposure controls

General advice :

: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Water : The product should not be allowed to enter drains, water courses or the soil.

:

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: gold
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: 100 °C
Flash point	: > 100 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

Viscosity, dynamic : No data available
Viscosity, kinematic : No data available
Flow time : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products :

Other information : Carbon monoxide, carbon dioxide and unburned

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

hydrocarbons (smoke).

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****Copper :**Acute oral toxicity : The component/mixture is moderately toxic after single
ingestion.**monoalkyl or monoaryl or monoalkylaryl esters of acrylic acid :**Acute inhalation toxicity : The component/mixture is moderately toxic after short term
inhalation.**zinc powder — zinc dust (stabilised) :**

Acute oral toxicity : Rat: > 2 000 mg/kg

amines, hydrogenated tallow alkyl :

Acute oral toxicity : LD50 Rat: > 2 000 - 5 000 mg/kg

Method: OECD Test Guideline 401

Skin corrosion/irritation**Product**

May cause skin irritation and/or dermatitis.

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

Serious eye damage/eye irritation

Product

Eye irritation

Respiratory or skin sensitisation

Product

Causes sensitisation.

May cause sensitisation of susceptible persons by skin contact.

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

Further information

Product

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

copper (7440-50-8) :

M-Factor : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

3-methyl-1,5-pentanediy diacrylate (64194-22-5) :

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

zinc (7440-66-6) :

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Propylidynetrimethanol, ethoxylated, esters with acrylic acid (28961-43-5) :

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 10 232,73 mg/l

Amines, hydrogenated tallow alkyl (61788-45-2) :

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

-
- Product** : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.
- Contaminated packaging** : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
In accordance with local and national regulations.

SECTION 14: Transport information**14.1 UN number****ADR** : 3082**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : 3082**IATA** : 3082**14.2 Proper shipping name****ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Copper metal powder)**TDG**

Not dangerous goods

CFR

Not dangerous goods

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(,Copper metal powder)

IATA : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Copper metal powder)

14.3 Transport hazard class**ADR** : 9**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : 9**IATA** : 9**14.4 Packing group****ADR**

Packaging group : III

Classification Code : M6

Hazard Identification Number : 90

Labels : 9

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Packaging group : III

Labels : 9

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

EmS Number : F-A, S-F

IATA

Packing instruction (cargo aircraft) : 964

Packing instruction (passenger aircraft) : 964

Packing instruction (LQ) : Y964

Packaging group : III

Labels : 9

14.5 Environmental hazards**ADR** : Environmentally hazardous**IMDG** : Marine pollutant**14.6 Special precautions for user**

For single packagings $\leq 5L / 5 \text{ kg}$, or combination packagings containing inner packagings $\leq 5L / 5 \text{ kg}$ net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Prohibition/Restriction**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

Prohibition/Restriction

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Prohibition/Restriction

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) :

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted (monoalkyl or monoaryl or monoalkylaryl esters of acrylic acid) (2-Propenoic acid, reaction products with dipentaerythritol) (Glycerol, propoxylated, esters with acrylic acid) (Epoxy acrylate) (2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one) (cyclohexane)

15.2 Chemical safety assessment

No data available

ROTOSTAR UV/LED 366 873 FLEXO INK

Version 1.0

Revision Date 15.12.2020

Print Date 28.12.2020

SECTION 16: Other information**Full text of H-Statements**

H302	: Harmful if swallowed.
H303	: May be harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.