

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Concentrate Goldeffect rpg 190 kgs  
Product code : 08070625V

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company :

E-mail address of person responsible for the SDS : msds.eckart@altana.com

#### 1.4 Emergency telephone number

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Solvent naphtha (petroleum), light arom.  
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha  
n-butyl acetate  
xylene

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No.	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version  
4.1

Revision Date:  
27.04.2020

SDS Number:  
102000000037

Print Date: 08.08.2020  
Date of first issue: 07.01.2014

	Registration number		
Solvent naphtha (petroleum), light arom.	64742-95-6 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 25 - < 50
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	64742-49-0 926-605-8	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	>= 25 - < 50
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 10
Copper	7440-50-8 231-159-6  01-2119480154-42	Acute Tox. 4; H302 Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2.5 - < 10
xylene	1330-20-7 215-535-7	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 10
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3  01-2119467174-37	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2.5
amines, hydrogenated tallow alkyl	61788-45-2 (90640-32-7) 262-976-6	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.0025 - < 0.025

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move the victim to fresh air.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version	Revision Date:	SDS Number:	Print Date: 08.08.2020
4.1	27.04.2020	102000000037	Date of first issue: 07.01.2014

---

- Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
  
If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Special powder against metal fire  
Dry sand  
ABC powder
- Unsuitable extinguishing media : Water  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version	Revision Date:	SDS Number:	Print Date: 08.08.2020
4.1	27.04.2020	102000000037	Date of first issue: 07.01.2014

---

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
  
Pick up and transfer to properly labelled containers.  
Do not flush with water.  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
  
Contain spillage, and then collect with non-combustible

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

Dampness : Keep in a dry, cool and well-ventilated place.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
Copper	7440-50-8	TWA (Fumes)	0.2 mg/m <sup>3</sup> (Copper)	GB EH40
		TWA (Dusts and mists)	1 mg/m <sup>3</sup> (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m <sup>3</sup> (Copper)	GB EH40
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version  
4.1

Revision Date:  
27.04.2020

SDS Number:  
102000000037

Print Date: 08.08.2020  
Date of first issue: 07.01.2014

	dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (Respirable)	4 mg/m <sup>3</sup>	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Solvent naphtha (petroleum), light arom.	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	25 mg/kg
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Skin contact	Acute systemic effects	11 mg/kg
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35.7 mg/m <sup>3</sup>
	Consumers	Skin contact	Acute systemic effects	6 mg/kg
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg
	Consumers	Ingestion	Acute systemic effects	2 mg/kg
Copper	Workers	Skin contact	Acute systemic	273 mg/kg



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version  
4.1

Revision Date:  
27.04.2020

SDS Number:  
102000000037

Print Date: 08.08.2020  
Date of first issue: 07.01.2014

			effects	
	Workers	Inhalation	Acute systemic effects	20 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	137 mg/kg
	Consumers	Skin contact	Acute systemic effects	273 mg/kg
	Consumers	Inhalation	Acute systemic effects	20 mg/m <sup>3</sup>
xylene	Consumers	Inhalation	Long-term local effects	65.3 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	65.3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg
	Consumers	Ingestion	Long-term systemic effects	12.5 mg/kg
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	212 mg/kg
zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	83 mg/kg
	Consumers	Ingestion	Long-term systemic effects	0.83 mg/kg
	Consumers	Skin contact	Long-term systemic effects	83 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	STP	35.6 mg/l
	Fresh water sediment	0.981 mg/kg
	Marine sediment	0.098 mg/kg
	Soil	0.090 mg/kg
Copper	Soil	65.5 mg/kg
	Fresh water	0.0078 mg/l
	Fresh water sediment	87 mg/kg
	Marine water	0.0052 mg/l
	Marine sediment	676 mg/kg
	STP	0.230 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

xylene	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Fresh water sediment	13.7 mg/l
	Marine sediment	1.37 mg/l
	Soil	2.68 mg/l
	Secondary Poisoning	20 mg/kg
zinc powder — zinc dust (stabilised)	STP	9.6 mg/l
	Fresh water	0.0206 mg/l
	Fresh water sediment	117.8 mg/kg
	Marine water	0.0061 mg/l
	Soil	35.6 mg/kg
	Marine sediment	56.5 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses

Safety glasses

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

Equipment should conform to EN 14387

In the case of vapour formation use a respirator with an approved filter.

#### Environmental exposure controls

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version  
4.1

Revision Date:  
27.04.2020

SDS Number:  
102000000037

Print Date: 08.08.2020  
Date of first issue: 07.01.2014

Water : The product should not be allowed to enter drains, water courses or the soil.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : No data available

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Freezing point : No data available

Boiling point/boiling range : 45 °C

Flash point : -18 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Auto-ignition temperature : No data available

Smoldering temperature : No data available

Decomposition temperature : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

Density : ca. 0.91 g/cm<sup>3</sup>

Bulk density : No data available

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity  
  Viscosity, dynamic : see user defined free text

Viscosity, kinematic : No data available

Flow time : 10 - 12 s at 20 °C  
  Cross section: 4 mm  
  Method: DIN 53211

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

### 10.5 Incompatible materials

### 10.6 Hazardous decomposition products

Thermal decomposition : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version  
4.1

Revision Date:  
27.04.2020

SDS Number:  
102000000037

Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

##### Components:

##### **Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

##### **Copper:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

##### **xylene:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

##### **zinc powder — zinc dust (stabilised):**

Acute oral toxicity : (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.41 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **amines, hydrogenated tallow alkyl:**

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg  
Method: OECD Test Guideline 401

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version  
4.1

Revision Date:  
27.04.2020

SDS Number:  
102000000037

Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

### **Skin corrosion/irritation**

Causes skin irritation.

#### **Product:**

Remarks: May cause skin irritation in susceptible persons.

#### **Components:**

##### **Copper:**

Remarks: May cause skin irritation in susceptible persons.

##### **xylene:**

Result: Skin irritation

##### **amines, hydrogenated tallow alkyl:**

Result: Skin irritation

Remarks: May cause skin irritation in susceptible persons.

### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

#### **Components:**

##### **Copper:**

Result: Eye irritation

##### **xylene:**

Result: Eye irritation

##### **amines, hydrogenated tallow alkyl:**

Result: Irreversible effects on the eye

Remarks: May cause irreversible eye damage.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version  
4.1

Revision Date:  
27.04.2020

SDS Number:  
102000000037

Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness.

### **Components:**

#### **Solvent naphtha (petroleum), light arom.:**

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

#### **n-butyl acetate:**

Assessment: May cause drowsiness or dizziness.

#### **xylene:**

Assessment: May cause respiratory irritation.

### **STOT - repeated exposure**

Not classified based on available information.

### **Components:**

#### **xylene:**

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

#### **amines, hydrogenated tallow alkyl:**

Target Organs: Liver, Gastrointestinal tract, Immune system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **Components:**

#### **Solvent naphtha (petroleum), light arom.:**

May be fatal if swallowed and enters airways.

#### **xylene:**

May be fatal if swallowed and enters airways.

#### **amines, hydrogenated tallow alkyl:**

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

### Further information

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

#### Components:

##### **Copper:**

Remarks: No data available

##### **zinc powder — zinc dust (stabilised):**

Remarks: No data available

##### **amines, hydrogenated tallow alkyl:**

Remarks: Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **Solvent naphtha (petroleum), light arom.:**

##### **Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

##### **Copper:**

M-Factor (Short-term (acute) aquatic hazard) : 10

##### **Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

##### **zinc powder — zinc dust (stabilised):**

##### **Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

hazard

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

### **amines, hydrogenated tallow alkyl:**

M-Factor (Short-term (acute) aquatic hazard) : 10

M-Factor (Long-term (chronic) aquatic hazard) : 10

### **Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

#### **Components:**

#### **n-butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### **12.6 Other adverse effects**

#### **Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

#### **Components:**

#### **Copper:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

### **zinc powder — zinc dust (stabilised):**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

### **amines, hydrogenated tallow alkyl:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

---

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

### 14.2 UN proper shipping name

ADR : PAINT  
(, Copper metal powder)  
IMDG : PAINT

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

(Copper metal powder)

**IATA** : Paint

### 14.3 Transport hazard class(es)

**ADR** : 3

**IMDG** : 3

**IATA** : 3

### 14.4 Packing group

#### **ADR**

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

#### **IMDG**

Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Class 3 - Flammable liquids

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Class 3 - Flammable liquids

### 14.5 Environmental hazards

#### **ADR**

Environmentally hazardous : yes

#### **IMDG**

Marine pollutant : yes

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version	Revision Date:	SDS Number:	Print Date: 08.08.2020
4.1	27.04.2020	102000000037	Date of first issue: 07.01.2014

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EC) No 850/2004 on persistent organic pollutants	:	Not applicable
Volatile organic compounds	:	Directive 2004/42/EC Volatile organic compounds (VOC) content: 64 %, 582.4 g/l

#### 15.2 Chemical safety assessment

### SECTION 16: Other information

#### Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version 4.1      Revision Date: 27.04.2020      SDS Number: 102000000037      Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---

list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 BAT : UK. Biological monitoring guidance values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Concentrate Goldeffect rpg 190 kgs

Version  
4.1

Revision Date:  
27.04.2020

SDS Number:  
102000000037

Print Date: 08.08.2020  
Date of first issue: 07.01.2014

---