

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : Konzentrat Alu DFW  
Material number : 08841225V

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company :  
  
Telephone :  
Telefax :  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Flammable liquids, Category 2, H225  
Acute toxicity, Category 5, Oral, H303  
Acute toxicity, Category 5, Dermal, H313

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

Skin corrosion/irritation, Category 3, H316  
 Serious eye damage/eye irritation, Category 2A, H319  
 Specific target organ toxicity - single exposure, Category 3,  
 Central nervous system, H336  
 Specific target organ toxicity - repeated exposure, Category 2,  
 H373  
 Aspiration hazard, Category 1, H304  
 Long-term (chronic) aquatic hazard, Category 3, H412

**GHS-Labeling**

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.  
 H303 + H313: May be harmful if swallowed or in contact with skin.  
 H304: May be fatal if swallowed and enters airways.  
 H316: Causes mild skin irritation.  
 H319: Causes serious eye irritation.  
 H336: May cause drowsiness or dizziness.  
 H373: May cause damage to organs through prolonged or repeated exposure.  
 H412: Harmful to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 Keep container tightly closed.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## Konzentrat Alu DFW

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

P312 Call a POISON CENTER/doctor if you feel unwell.  
 P331 Do NOT induce vomiting.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or  
 alcohol-resistant foam to extinguish.

### Hazardous components which must be listed on the label

Identification	CAS-No.
acetone	67-64-1
Solvent naphtha (petroleum), light arom.	64742-95-6
n-butyl acetate	123-86-4
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1
Naphtha (petroleum), hydrotreated heavy xylene	64742-48-9
dibutylamine	1330-20-7
	111-92-2

### SECTION 3: Composition/information on ingredients

Substance name : WS KONZENTRAT FÜR ALU DFW/W IT

Substance No. :

#### Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
acetone	67-64-1 200-662-2	Flam. Liq.;2;H225 Acute Tox.;5;H303 Acute Tox.;5;H313 Eye Irrit.;2A;H319 STOT SE;3;H336	25 - 50
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	1 - 10

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## Konzentrat Alu DFW

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

Solvent naphtha (petroleum), light arom.	64742-95-6	Flam. Liq.;3;H226 Acute Tox.;5;H303 Acute Tox.;5;H313 STOT SE;3;H335, H336 Asp. Tox.;1;H304 Aquatic Chronic;2;H411	2,5 - 10
n-butyl acetate	123-86-4 204-658-1	Flam. Liq.;3;H226 STOT SE;3;H336	1 - 10
Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha	64742-82-1 265-185-4	Flam. Liq.;3;H226 STOT SE;3;H336 STOT RE;1;H372 Asp. Tox.;1;H304 Aquatic Chronic;2;H411	2,5 - 10
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	Flam. Liq.;4;H227 Asp. Tox.;1;H304	1 - 10
xylene	1330-20-7 215-535-7	Flam. Liq.;3;H226 Acute Tox.;4;H332 Acute Tox.;4;H312 ;2;H315	1 - 10
di-n-butylamine	111-92-2 203-921-8	Flam. Liq.;3;H226 Acute Tox.;2;H330 Acute Tox.;4;H302 Acute Tox.;3;H311 Skin Corr.;1;H314 Eye Irrit.;1;H318	0,1 - 1

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

--	--	--	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.  
Do not leave the victim unattended.
- Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, ABC powder, Foam

Unsuitable extinguishing media : High volume water jet

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Do not flush with water.

**6.4 Reference to other sections**

For personal protection see section 8.

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.



**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

This information is not available.

**SECTION 8: Exposure controls/personal protection**
**8.1 Control parameters**
**Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
acetone	67-64-1	TWA	500 ppm 1 210 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information		Indicative			
acetone	67-64-1	AGW	500 ppm 1 200 mg/m <sup>3</sup>	2015-03-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(1)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a			

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

		limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				
Solvent naphtha (petroleum), light arom.	64742-95-6	AGW	100 mg/m <sup>3</sup>	2009-02-16	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9 of the TRGS 900				
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m <sup>3</sup>	2012-09-13	DE TRGS 900
Peak-limit: excursion factor (category)	2;(I)				
Further information	Commission for dangerous substancesWhen there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m <sup>3</sup>	2017-11-30	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9 of the TRGS 900				
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skinIndicative				
xylene	1330-20-7	STEL	100 ppm 442 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skinIndicative				
xylene	1330-20-7	AGW	100 ppm 440 mg/m <sup>3</sup>	2010-08-04	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)Skin absorption				
di-n-butylamine	111-92-2	AGW	5 ppm 29 mg/m <sup>3</sup>	2006-01-01	DE TRGS 900
Peak-limit: excursion factor (category)	1;(I)				

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

Further information

 Commission for dangerous substances  
 The reaction with nitrosating agents can lead to the formation of carcinogenic N-nitrosoamine.  
 Skin absorption

**8.2 Exposure controls**
**Personal protective equipment**

- Eye protection : Goggles
- : Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
 The exact break through time can be obtained from the protective glove producer and this has to be observed.  
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
 Recommended preventive skin protection  
 Skin should be washed after contact.  
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- : In the case of vapour formation use a respirator with an approved filter.

**Environmental exposure controls**

- General advice :
- : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Water : The product should not be allowed to enter drains, water courses or the soil.
- :

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

- Appearance : liquid
- Colour : No data available
- Odour : characteristic

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 55 °C
Flash point	: -19 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: ca. 0,88 g/cm <sup>3</sup>
Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: 11 - 14 s at 20 °C Cross section: 4 mm Method: DIN 53211

**9.2 Other information**

No data available

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

**10.5 Incompatible materials**

Materials to avoid : Acids  
Bases  
Oxidizing agents

**10.6 Hazardous decomposition products**

Hazardous decomposition products : No data available

Other information : No data available

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****acetone :**

Acute oral toxicity : LD50 Rabbit: 4 700 - 5 800 mg/kg

Mouse: 3 000 mg/kg

Rat: 9 800 mg/kg

Acute inhalation toxicity : LC50 Rat: 76 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: &gt; 2 000 mg/kg

**Solvent naphtha (petroleum), light arom. :**

Acute oral toxicity : LD50 Rat: 3 492 mg/kg

Acute dermal toxicity : LD50 Rabbit: &gt; 3 160 mg/kg



**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

**Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha :**  
Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

**Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha :**  
Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: Test atmosphere: vapour

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity : LD50 Rabbit: > 5 000 mg/kg

**xylene :**  
Acute oral toxicity : LD50 Rat: 8 700 mg/kg

Acute inhalation toxicity : LC50 Rat: 6 350 mg/l

Exposure time: 4 h

Test atmosphere: vapour

The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Acute toxicity estimate : 1 100 mg/kg

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

Method: Converted acute toxicity point estimate

The component/mixture is moderately toxic after single  
contact with skin.**Skin corrosion/irritation****Product**

May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation****Product**

Eye irritation

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,  
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may  
degrease the skin.

**SECTION 12: Ecological information****12.1 Toxicity****Components:****acetone (67-64-1) :**

Toxicity to daphnia and other : (Daphnia magna (Water flea)): 21 600 mg/l  
aquatic invertebrates

**Solvent naphtha (petroleum), light arom. (64742-95-6) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic : Toxic to aquatic life with long lasting effects.  
hazard

**Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic : Toxic to aquatic life with long lasting effects.

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

hazard

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**Additional ecological  
information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product

: The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

**SECTION 14: Transport information****14.1 UN number**

ADR : 1263  
TDG : 1263  
CFR : 1263  
IMDG : 1263  
IATA : 1263

**14.2 Proper shipping name**

ADR : PAINT  
TDG : PAINT  
CFR : PAINT  
IMDG : PAINT  
IATA : PAINT

**14.3 Transport hazard class**

ADR : 3  
TDG : 3  
CFR : 3  
IMDG : 3  
IATA : 3

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

**14.4 Packing group****ADR**

Packaging group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

**TDG**

Packaging group : II  
Labels : 3

**CFR**

Packaging group : II  
Labels : 3

**IMDG**

Packaging group : II  
Labels : 3  
EmS Number : F-E, S-E

**IATA**

Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packaging group : II  
Labels : 3

**14.5 Environmental hazards**

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## Konzentrat Alu DFW

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

### 14.6 Special precautions for user

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Prohibition/Restriction**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

**Prohibition/Restriction**

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

**Prohibition/Restriction**

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

### 15.2 Chemical safety assessment

No data available

**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

**SECTION 16: Other information****Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H227	: Combustible liquid.
H228	: Flammable solid.
H302	: Harmful if swallowed.
H303	: May be harmful if swallowed.
H303 + H313	: May be harmful if swallowed or in contact with skin.
H304	: May be fatal if swallowed and enters airways.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H313	: May be harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H316	: Causes mild skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



**Konzentrat Alu DFW**

Version 2.0

Revision Date 06.12.2019

Print Date 07.08.2020

---