

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version 2.0 Revision Date: 05.12.2019 SDS Number: 102000000654 Print Date: 08.08.2020
Date of first issue: 02.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : METALURE L-55350
Product code : 056252IA0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.
Eye irritation, Category 2 H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :  

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version 2.0 Revision Date: 05.12.2019 SDS Number: 102000000654 Print Date: 08.08.2020
Date of first issue: 02.01.2014

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

ethyl acetate
acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification REGULATION (EC) No 1272/2008 | Concentration (% w/w) |
|-------------------------------|---|---|--------------------------|
| ethyl acetate | 141-78-6 205-500-4 01-2119475103-46 | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 | >= 50 - <= 100 |
| aluminium powder (stabilised) | 7429-90-5 231-072-3 01-2119529243-45 | Flam. Sol. 1; H228 | >= 10 - < 20 |
| acetone | 67-64-1 200-662-2 01-2119471330-49 | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 | >= 1 - < 10 |

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version 2.0 Revision Date: 05.12.2019 SDS Number: 102000000654 Print Date: 08.08.2020
Date of first issue: 02.01.2014

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Dry sand
ABC powder
Foam
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 08.08.2020 |
| 2.0 | 05.12.2019 | 102000000654 | Date of first issue: 02.01.2014 |

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 08.08.2020 |
| 2.0 | 05.12.2019 | 102000000654 | Date of first issue: 02.01.2014 |

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Do not store near acids.
Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version
2.0

Revision Date:
05.12.2019

SDS Number:
102000000654

Print Date: 08.08.2020
Date of first issue: 02.01.2014

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-------------------------------|--|-------------------------------|------------------------------------|-------------|
| ethyl acetate | 141-78-6 | TWA | 200 ppm 734 mg/m ³ | GB EH40 |
| | | STEL | 400 ppm 1,468 mg/m ³ | GB EH40 |
| | | STEL | 400 ppm 1,468 mg/m ³ | 2017/164/EU |
| Further information | Indicative | | | |
| | | TWA | 200 ppm 734 mg/m ³ | 2017/164/EU |
| Further information | Indicative | | | |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Inhalable) | 10 mg/m ³ | GB EH40 |
| Further information | The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | | |
| | | TWA (Respirable) | 4 mg/m ³ | GB EH40 |
| Further information | The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | | |
| | | TWA (inhalable dust) | 10 mg/m ³ | GB EH40 |
| Further information | For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version
2.0

Revision Date:
05.12.2019

SDS Number:
102000000654

Print Date: 08.08.2020
Date of first issue: 02.01.2014

| | | | | |
|---------------------|---|-----------------------|--------------------------------------|------------|
| | <p>hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p> | | | |
| | | TWA (Respirable dust) | 4 mg/m ³ | GB EH40 |
| Further information | <p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p> | | | |
| acetone | 67-64-1 | TWA | 500 ppm 1,210 mg/m ³ | 2000/39/EC |
| Further information | Indicative | | | |
| | | TWA | 500 ppm 1,210 mg/m ³ | GB EH40 |
| | | STEL | 1,500 ppm 3,620 mg/m ³ | GB EH40 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version
2.0

Revision Date:
05.12.2019

SDS Number:
102000000654

Print Date: 08.08.2020
Date of first issue: 02.01.2014

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|----------------|-------------------------------|-----------------|----------------------------|-------------------------|
| ethyl acetate | Workers | Inhalation | Acute local effects | 1468 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects | 1468 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 734 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 63 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 734 mg/m ³ |
| | Consumers | Inhalation | Acute local effects | 734 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 734 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 367 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 37 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 367 mg/m ³ |
| | Consumers | Ingestion | Long-term systemic effects | 4.5 mg/kg |
| | aluminium powder (stabilised) | Workers | Inhalation | Long-term local effects |
| Consumers | | Oral | Long-term systemic effects | 3.95 mg/kg |
| Workers | | Inhalation | Long-term systemic effects | 3.72 mg/m ³ |
| acetone | Workers | Skin contact | Long-term systemic effects | 186 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 1210 mg/m ³ |
| | Consumers | Ingestion | Long-term systemic effects | 62 mg/kg |
| | Consumers | Skin contact | Long-term systemic effects | 62 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 200 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 2420 mg/m ³ |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|-------------------------------|---------------------------|-------------|
| ethyl acetate | Soil | 0.148 mg/kg |
| | STP | 650 mg/l |
| | Fresh water | 0.24 mg/l |
| | Marine water | 0.024 mg/l |
| | Fresh water sediment | 1.15 mg/kg |
| | Marine sediment | 0.115 mg/kg |
| aluminium powder (stabilised) | Fresh water | 0.0749 mg/l |
| | clarification plant | 20 mg/l |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version 2.0 Revision Date: 05.12.2019 SDS Number: 102000000654 Print Date: 08.08.2020
Date of first issue: 02.01.2014

| | | |
|---------|----------------------|------------|
| acetone | Soil | 29.5 mg/kg |
| | Fresh water | 10.6 mg/l |
| | Fresh water sediment | 30.4 mg/kg |
| | Marine water | 1.06 mg/l |
| | Marine sediment | 3.04 mg/kg |
| | STP | 100 mg/l |

8.2 Exposure controls

Personal protective equipment

Eye protection : Goggles

Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection

: Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection

: Use suitable breathing protection if workplace concentration requires.

In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

Water

: The product should not be allowed to enter drains, water courses or the soil.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version 2.0 Revision Date: 05.12.2019 SDS Number: 102000000654 Print Date: 08.08.2020
Date of first issue: 02.01.2014

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--------------------------------|
| Appearance | : liquid |
| Colour | : silver |
| Odour | : characteristic |
| Odour Threshold | : No data available |
| pH | : No data available |
| Freezing point | : No data available |
| Boiling point/boiling range | : 76 °C |
| Flash point | : -4 °C |
| Evaporation rate | : No data available |
| Flammability (solid, gas) | : No data available |
| Self-ignition | : No data available |
| Auto-ignition temperature | : No data available |
| Smoldering temperature | : No data available |
| Decomposition temperature | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Upper explosion limit / Upper flammability limit | : No data available |
| Lower explosion limit / Lower flammability limit | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density | : No data available |
| Relative density | : No data available |
| Density | : 0.95 - 1.0 g/cm ³ |
| Bulk density | : No data available |
| Water solubility | : No data available |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 2.0 | Revision Date: 05.12.2019 | SDS Number: 102000000654 | Print Date: 08.08.2020 Date of first issue: 02.01.2014 |
|----------------|------------------------------|-----------------------------|---|

| | |
|--|---------------------|
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : No data available |
| Flow time | : No data available |

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

| | |
|---------------------|--|
| Hazardous reactions | : Contact with acids and alkalis may release hydrogen. |
| | Stable under recommended storage conditions. |
| | Vapours may form explosive mixture with air. |

10.4 Conditions to avoid

| | |
|---------------------|--|
| Conditions to avoid | : Do not allow evaporation to dryness. |
| | Heat, flames and sparks. |

10.5 Incompatible materials

| | |
|--------------------|--------------------------------------|
| Materials to avoid | : Acids Bases Oxidizing agents |
|--------------------|--------------------------------------|

10.6 Hazardous decomposition products

| | |
|---------------------------------|--------------------------------------|
| Contact with water or humid air | : This information is not available. |
| Thermal decomposition | : This information is not available. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version 2.0 Revision Date: 05.12.2019 SDS Number: 102000000654 Print Date: 08.08.2020
Date of first issue: 02.01.2014

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

ethyl acetate:

Acute oral toxicity : (Rat): 5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 56 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

acetone:

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg
(Mouse): 3,000 mg/kg
(Rat): 9,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

acetone:

Remarks: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version
2.0

Revision Date:
05.12.2019

SDS Number:
102000000654

Print Date: 08.08.2020
Date of first issue: 02.01.2014

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Eye irritation

Components:

acetone:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

ethyl acetate:

Toxicity to daphnia and other : (Daphnia (water flea)): 717 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version 2.0 Revision Date: 05.12.2019 SDS Number: 102000000654 Print Date: 08.08.2020
Date of first issue: 02.01.2014

aquatic invertebrates

acetone:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21,600 mg/l

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version 2.0 Revision Date: 05.12.2019 SDS Number: 102000000654 Print Date: 08.08.2020
Date of first issue: 02.01.2014

SECTION 14: Transport information

14.1 UN number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT
IMDG : PAINT, CLASSIFIED ACCORDING TO 2.3.2.2 IMDG-CODE
IATA : Paint, classified according to 3.3.3.1 IATA-DGR

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Class 3 - Flammable liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Class 3 - Flammable liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

Version 2.0 Revision Date: 05.12.2019 SDS Number: 102000000654 Print Date: 08.08.2020
Date of first issue: 02.01.2014

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H228 : Flammable solid.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU : Commission Directive (EU) 2017/164 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA : Limit Value - eight hours
2017/164/EU / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE L-55350

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 08.08.2020 |
| 2.0 | 05.12.2019 | 102000000654 | Date of first issue: 02.01.2014 |

Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN